



707 W. GRANGE ST
 PHILADELPHIA, PA 19120
 800-523-0888 * 215-927-3388 fax
 www.mutualindustries.com

TRAFFIC CONES

INJECTION CONSTRUCTION FOR MAXIMUM
 STRUCTURAL INTEGRITY * SMOOTH GLOSSY FINISH OVER
 THE ENTIRE SURFACE KEEPS THE CONE CLEANER IN USE *
 STANDARD TAPER FOR EASIER STACKING * PREMIUM
 FLUORESCENT PIGMENTS ARE USED TO GIVE MAXIMUM
 DAYTIME VISIBILITY * INCREASED WALL THICKNESS HELPS
 RESIST SEPARATION OF THE TOP FROM THE BASE * 100%
 PVC CONSTRUCTION FOR DURABILITY * ENHANCED
 FLEXIBILITY FOR REDUCED IMPACT DAMAGE



MODEL	WEIGHT	HEIGHT	BASE DIMENSION	WALL THICKNESS TOP	WALL THICKNESS BOTTOM	CONICAL O.D. TOP	CONICAL O.D. BOTTOM
18" 3lb CONE	3	18	11	0.065	0.100	2	7.1
28" 7lb CONE	7	28	14	0.080	0.130	2.25	11.00
HEAT RESISTANCE	178 degrees F without slump or sag.						
COLD RESISTANCE	0 degrees F without cracking or splitting of base.						

PART#	DESCRIPTION	PALLET QUANTITY
17720-18-3	18" 3# CONE	600
17720-118-3	18" 3# CONE w/REFLECT	
17721-28-7	28" 7# CONE	360
17721-128-7	28" 7# CONE w/REFLECT	
17722-36-10	36" 10# CONE	360
17722-136-10	36" 10# CONE w/REFLECT	

Reflexite Brand Reflective Tape Used