

**Submit by uploading two pdf files** to the D2L Dropbox for this assignment (in “Week 2”). Generally your homework solutions in this class can be typewritten or handwritten, but must be converted to a pdf file to hand in. And, for all homework assignments that include computer problems, you must submit a separate (second) pdf file containing all your code. The code file must be computer readable (not a scan or a screenshot) – you can check for this by trying to select text in the pdf file.

This homework is written to be solved using Matlab or Python (your choice)\*.

\*About help with coding: generally you are expected to use your own resources for help with coding (this can include help files, books, internet help, and discussions with other students - on piazza or in person). If this isn't sufficient, then please feel free to consult either TA.

1. In this problem you will code a minimum-distance-to-class-means classifier, using Euclidean distance ( $L_2$  norm). You will then use the classifier on data we provide.

Note that you are to write the code for the classifier and error-rate computation yourself; using a toolbox's or library's function or module that implements this (or similar) classifier is not sufficient. If you use Python, this means that you can use built-in functions, numpy, and matplotlib. Use of other libraries or packages (e.g., pandas or scikit-learn) are not in the spirit of this homework problem and will result in points deducted.

Your code should take as input a set of data points (training dataset) that are labeled according to class, and should calculate a representation of the classifier (class means and a way to use them to classify data points). Once the classifier is “trained” (class means are calculated), your code should be able to calculate the error rate obtained when classifying training data, and calculate the error rate obtained when classifying test data. Error rate is defined as the number of misclassified data points divided by the total number of data points classified, usually expressed as percentage. In addition, with the aid of a supplied plotting function, you will plot the training data points, resulting class means, decision boundaries, and decision regions.

You will use your implemented minimum-distance-to-class-means classifier on 3 different datasets: two synthetic datasets, and one real dataset (“wine” from UCI machine learning repository).

To help you, the following files are available for download on the course web site, in “Week 2”, along with this HW assignment:

- (i) Dataset files (containing labeled data points).

**Matlab:** synthetic1.mat, synthetic2.mat, wine.mat.

For each dataset file, there are in total 4 variables: 'feature\_train', 'label\_train', 'feature\_test' and 'label\_test'. While feature\_XXX stores the data points (inputs  $\underline{x}_n, n=1,2,\dots,N$ ) for training (or testing, respectively), label\_XXX are the class labels for these data points ( $y_n, n=1,2,\dots,N$ ). Each row in feature\_XXX corresponds to a data point, and each column corresponds to a feature. Class labels are stored as a

column vector in label\_XXX, where the  $i^{\text{th}}$  entry corresponds to the  $i^{\text{th}}$  data point in the feature\_XXX file.

**Python:**

sythetic1\_train.csv, synthetic1\_test.csv, synthetic2\_train.csv, synthetic2\_test.csv, wine\_train.csv, wine\_test.csv.

Each csv file has one row for each data point, and one column for each feature; except the last column contains the class labels (each label is an integer from 1 to  $C$ , in which  $C$  is the number of classes).

- (ii) PlotDecBoundaries.m or PlotDecBoundaries.py function helps you plot the decision boundary and regions.

To use PlotDecBoundaries.m (or PlotDecBoundaries.py), you only need to pass in 3 variables, which are training data points of all classes, class labels of all training data points, and sample means for all classes.

For training data points, you need to be consistent with the format of feature\_train (or any of the csv files), where a row corresponds to a data point; it should contain no class labels. The class labels variable should also follow the format of label\_train (or in Python, one column of class labels, same order as rows of “training”). For sample mean, the  $i^{\text{th}}$  row needs to be set as the sample mean of  $i^{\text{th}}$  class.

Please answer the following parts.

- (a) For each of the two synthetic datasets, there are in total  $C=2$  classes and  $D=2$  features. For each synthetic dataset: (i) train the classifier, plot the (training-set) data points, the resulting class means, decision boundaries, and decision regions (using PlotDecBoundaries()); also run the trained classifier to classify the data points from their inputs; give the classification error rate on the training set, and separately give the classification error rate on the test set. The test-set data points should never be used for training. Turn in the plots and error rates.

**Hint:** You might want to check your code first, by trying it out with just two or three training data points in each class, for which you can check the results.

- (b) Is there much difference in error rate between the two synthetic datasets? Why or why not?

**Parts (c)-(e) below** use the “wine” dataset, which is for classifying the cultivar of the grape plant a wine was made from, given measured attributes of the wine. This dataset is briefly described at (in which “attribute” means “feature”):

<http://archive.ics.uci.edu/ml/datasets/Wine>

- (c) For the wine dataset, there are in total  $C=3$  classes (grape cultivars) and  $D=13$  features (measured attributes of the wine). In this problem you are to use only 2 features for classification. Pick the first two features ( $x_1$  = alcohol content, and  $x_2$  = malic acid content), and repeat the procedure of part (a) for this dataset.
- (d) Again for the “wine” dataset, find the 2 features among the 13 that achieve the minimum classification error on the training set. (We haven’t yet covered how to do

feature selection in class, but will later in the semester. For this problem, try coming up with your own method - one that you think will give good results - and see how well it works. **Hint:** 13 is not a lot of features, so computation time probably need not be a consideration.)

Plot the data points and decision boundaries in 2D for your best performing pair of features, and give its classification error on the training set.

Then give its classification error on the test set. The purpose of the test set is only to estimate the error of the final classifier on unknown (previously unseen) data. Describe the method you used to choose the best pair of features.

Turn in a description of your method for choosing the best pair of features, a plot of your chosen pair of features, state which features you chose, and give both error rates.

- (e) For the wine dataset, is there much difference in training-set error rate for different pairs of features? Justify your answer (e.g., by giving the error rate for a few different example pairs of features; or by giving the standard deviation of error rates over all possible pairs of features).

Also, answer the same question for the test-set error rate.