

Institut für Betriebssysteme und Rechnerverbund
Technische Universität Braunschweig

Masterarbeit

Computational Aspects of MaxMin Triangulations

Winfried Hellmann

2013-07-29 (DRAFT)

Betreuer: Prof. Dr. Sándor Fekete

for my daughter—in the hope that she will understand sometime

Erklärung

Ich versichere, die vorliegende Arbeit selbstständig und nur unter Benutzung der angegebenen Hilfsmittel angefertigt zu haben. Bei den Experimenten sind keine unbeteiligten Dreiecke zu Schaden gekommen.

Braunschweig, den 11. Juli 2013

Abstract

Maxmin length triangulations are just awesome.

Zusammenfassung

Maxmin Triangulationen sind einfach super.

Contents

1. Introduction	1
2. Integer Programming	3
2.1. SAT	4
2.2. Vertex Cover	6
2.3. Independent Set	9
3. Triangulations	13
3.1. Point Set Triangulations	15
3.2. Intersection Graph	19
3.3. Polygon Triangulations	20
3.4. Edge Flipping	21
3.5. Related Work	23
4. MaxMin Length Triangulation	25
4.1. Complexity	25
4.2. Geometric Approaches	27
4.3. Combinatorial Approach	27
4.4. Separators	30
4.5. Algorithm	35
5. Implementation	37
5.1. Geometry	37
5.1.1. CGAL	37
5.1.2. Kernel	37
5.1.3. Triangulation	38
5.1.4. Convex Hull	38
5.1.5. Intersection Algorithm	38
5.1.6. Intersection Graph	38
5.2. Optimization	38
5.2.1. SAT problem	38
5.2.2. SAT solution	39
5.2.3. SAT solver	39
5.2.4. CPLEX	39
5.3. Remains	39
5.3.1. Boost	39

5.3.2. Qt	40
5.3.3. JSON Parser	40
5.3.4. Logger	40
5.3.5. Point Generator	40
5.3.6. SVG Painter	40
6. Results	41
6.1. Technical Details	41
6.2. Segment Lengths	41
6.3. Execution Time	44
6.4. Aborted instances	47
7. Conclusion	49
A. Documentation	51
B. Result Data	93
Glossary	96

1. Introduction

1 pages

Triangulations, that is subdividing the plane (or a polygon) into triangles, are a popular topic in computational geometry — not only because of their connections to other problems but also due to their practical applications. They can be helpful as a preprocessing in other algorithms or as a tool in geometric proofs. One popular example is the artgallery problem. Another area where triangulations are widely used is mesh generation and approximation of complex geometric structures.

cite

For different use cases the objectives for a triangulation vary. For example, the widely known Delaunay triangulation [2, Section 9.2] tends to avoid “skinny” triangles and is therefore useful for meshes. One can image many different properties to be optimized: Edge lengths, triangle area, angle, and degree in a vertex are some of them. Many have already been looked into, but for some of them no application is known by now — so they remain theoretical problems. In chapter 3 we will have a brief overview of different kinds of triangulations.

cite

This thesis will focus on the MaxMin Length Triangulation (MMLT). Stated an open problem in 1991 [17], it has been proven to be NP-complete in 2012 [19]. However our assumption is that the hard instances are rare and that random instances can be solved in polynomial time on average. Therefore we provide an algorithmic idea in chapter 4 and its implementation in chapter 5.

Even though there seems to be no known application of MMLT yet, it is Greg’s [32] preferred kind of triangulation.

2. Integer Programming

This chapter focuses on some preliminaries around integer programming—which is a subarea of (mathematical) optimization. In that context we introduce three common optimization problems which can be solved using integer programming: SAT, Vertex Cover, and Independent Set. They will appear later on within this thesis (chapters 3 and 4) in association with the MaxMin Length Triangulation (MMLT) problem.

An integer program is basically a problem description as a system of (in-)equations involving only variables with integer values. As an addition there can be an objective function for modeling optimization problems. Throughout this thesis, we assume that all of the (in-)equations are linear which is referred to as a *linear integer program*.

Definition 2.1 ((Linear) Integer Program (IP))

An IP is a system of integer variables $x \in \mathbb{Z}^n$ with a set of constraints on them and optionally an objective function. We consider only the case where the constraints are linear with respect to x .

A natural standardized way of formulating (linear) IPs is the so called *canonical form*. It combines the variable coefficients for all (in-)equations in a matrix A , all constant terms are summed up to a vector b , and the objective function is represented as a multiplication of the variables x and a constant target vector c . For readability, we slightly modify the canonical form, e.g. by allowing sums.

Problem 2.2 (IP in canonical form [37])

$$\begin{array}{ll}
 \text{maximize } c^T x & \text{minimize } c^T x \\
 \text{subject to } Ax \leq b & \text{subject to } Ax \geq b \\
 x \geq 0 & x \leq 0 \\
 x \in \mathbb{Z} & x \in \mathbb{Z}
 \end{array}
 \quad \text{or}$$

Even though the structure of IPs looks very simple, it is a long known fact that solving them is not easy. Nevertheless they come in useful for various optimization problems—especially because there are many practical applications involving only integers. A common

strategy to simplify the problem is leaving out the integrity restriction for retrieving bounds of the optimal solution.

Theorem 2.3

Solving IPs is NP-hard.

Proof:

Even the special case where there is no objective function, only binary variables, and only equality constraints is NP-complete [28]. Therefore the more general problem is NP-hard.

2.1. SAT

The (boolean) satisfiability problem (SAT) asks for a variable assignment which fulfills a logical term. It was the first problem to be proven NP-complete [11] and has since been a common choice for NP-hardness proofs—many times even more restricted such as the 3-SAT problem which allows only for three variables in each “sub-term” (clause).

Problem 2.4 (3-SAT)

Given: Set of boolean literals $x_i \in X$, a formula in conjunctive normal form consisting of clauses $c \in C$ each involving exactly three literals (or their negations)

Sought: An assignment for X which lets all clauses in C evaluate to “true”

Shortly after the concept of NP-completeness was introduced by [11], Richard Karp applied the idea to several other well-known problems [28]. One of them was the 3-SAT problem which has more structure than the general boolean satisfiability problem and is therefore easier to embed into constructive NP-hardness or NP-completeness proofs.

Theorem 2.5 (NP-completeness of 3-SAT)

Problem 2.4 is NP-complete. [28, Satisfiability with at most 3 Literals per Clause]

As already mentioned earlier, the 3-SAT problem can be formulated as an IP. This easily confirms the NP-hardness of solving IPs. Additionally it allows for applying IP solvers (such as CPLEX, see also section 5.2.4) to 3-SAT problems. Usually however, SAT solvers are used which take advantage of the problem structure better and have therefore less overhead.

Problem 2.6 (IP formulation of 3-SAT)

$$\begin{aligned}
 & (\text{minimize} \quad 1) \\
 & \text{subject to} \quad \forall c \in C : \sum_{x_i \in c} x_i + \sum_{\neg x_i \in c} (1 - x_i) = 1 \\
 & \quad \forall x_i \in X : \quad \quad \quad x_i \in \{0, 1\}
 \end{aligned}$$

For geometric and graph problems an even more restricted class of 3-SAT problem has been established, the *Planar 3-SAT*. It asks for the connection graph of all clauses and their variables to be embeddable in the plane.

Problem 2.7 (Planar 3-SAT)

An instance of the 3-SAT problem with literals X and clauses C which can be represented by a planar graph $G = (V, E)$ such that

$$\begin{aligned}
 V &= \{v : v \in X \cup C\} \\
 E &= \{\{x, c\} : x \in X, c \in C, (x \in c) \vee (\neg x \in c)\}
 \end{aligned}$$

Figure 2.1 shows an example of a 3-SAT instance with a planar variable-clause-connection graph. There is a vertex for every clause (mint colored squares) and every variable (red circles) and edges in between if a variable (or its negation) is part of a clause.

It was shown that even this restricted class of satisfiability problems is NP-complete. That way problems can be proven to be NP-hard in the plane without having to deal




Figure 2.1.: Example of a Planar 3SAT instance which represents the term

$$\underbrace{(x_1 \vee x_2 \vee x_4)}_{c_1} \wedge \underbrace{(\neg x_2 \vee x_3 \vee \neg x_4)}_{c_2} \wedge \underbrace{(x_1 \vee \neg x_3 \vee \neg x_4)}_{c_3}$$

with intersections. This result can then be used for higher dimensions (usually, problems become harder to solve if they are elevated to higher dimensions).

Theorem 2.8 (NP-completeness of Planar 3-SAT)

Problem 2.7 is still NP-complete. [30]

2.2. Vertex Cover

Another problem in the collection of [28] is *Vertex Cover* which aims to cover (all) edges of a graph by their incident vertices. It is closely related to other graph problems such as Edge Cover, Clique, Independent Set (see section 2.3), Coloring, and the more general Set Cover.

Definition 2.9 (Vertex Cover)

Given an undirected graph $G = (V, E)$, a Vertex Cover $V_{\text{cover}} \subseteq V$ for G is a vertex set such that every edge $e \in E$ is incident to at least one vertex $v \in V_{\text{cover}}$:

$$\forall e \in E : \exists v \in V_{\text{cover}} : v \in e$$

A trivial Vertex Cover of any graph $G = (V, E)$ would be the complete vertex set V .

In general, such a Vertex Cover is not useful but one asks for the covering vertex set to be minimal (roughly speaking without unnecessary vertices).

Definition 2.10 (Minimal Vertex Cover)

A Vertex Cover V_{cover} for an undirected graph $G = (V, E)$ is minimal if there is no vertex $v \in V_{\text{cover}}$ such that $V_{\text{cover}} \setminus \{v\}$ remains a Vertex Cover.

Still, *any* Minimal Vertex Cover is not always wanted as it needs not be unique—hence there can be a much smaller covering vertex set. An extreme example is a star-shaped graph where one vertex can cover all edges but the set of all other vertices would also be minimal. Therefore we distinguish between a Minimal Vertex Cover and a *Minimum* Vertex Cover, i.e. a smallest possible one. Figure 2.2 shows the difference between Minimal and Minimum Vertex Cover by example.

Definition 2.11 (Minimum Vertex Cover)

A Vertex Cover V_{cover} for an undirected graph $G = (V, E)$ is minimum if there is no other Vertex Cover V'_{cover} for G which has fewer vertices:

$$\forall V'_{\text{cover}} \text{ Vertex Cover} : |V_{\text{cover}}| \leq |V'_{\text{cover}}|$$

The IP formulation of Minimum Vertex Cover can be directly deduced from the definition: We minimize the number of covering vertices such that for every edge at least one vertex is selected. The optimal vertex set V_{cover} can then be retrieved from the IP solution vector by just collecting all selected vertices: $V_{\text{cover}} = \{v \in V \wedge x_v = 1\}$

Problem 2.12 (IP Formulation of Minimum Vertex Cover)

$$\begin{aligned} & \text{minimize} && \sum_{v \in V} x_v \\ & \text{subject to} && \forall \{v, w\} \in E : x_v + x_w \geq 1 \\ & && \forall v \in V : x_v \in \{0, 1\} \end{aligned}$$

What follows is that the Minimum Vertex Cover is also NP-complete because it is a subset of the Set Cover problem [28] and clearly lies in NP as it can be (polynomially) reduced to solving IPs.




Figure 2.2.: Example of Minimal vs. Minimum Vertex Cover, covering vertices in red

Theorem 2.13 (NP-completeness of Minimum Vertex Cover)

Minimum Vertex Cover is NP-complete. [28]

We now introduce the class of *well-covered* graphs which we will need in chapter 3. They combine all graphs in which there is no difference between Minimal and Minimum Vertex Cover. Minimal Vertex Covers can be calculated with significant less effort (i.e. in polynomial time) than Minimum Vertex Covers (e.g. by just iteratively removing vertices from the set until it would destroy the covering property). This leads to Minimum Vertex Cover being solvable in polynomial time for *well-covered* graphs.

A subset of *well-covered* graphs are connected bipartite graphs $G = (A \cup B, E \subseteq A \times B)$ with both vertex sets having the same size: $|A| = |B|$. Either one of A and B is a Minimal and a Minimum Vertex Cover for G . Clearly this graph class is not empty which already implies that the class of *well-covered* graph is not empty either.

Definition 2.14 (Well-covered Graph)

An undirected graph $G = (V, E)$ is *well-covered* iff every Minimal Vertex Cover for G is also a Minimum Vertex Cover for G . [38]

As a logical consequence of definition 2.14, every two vertex sets which are a Minimal Vertex Cover for a *well-covered* graph G have the same size. If one of them had more vertices than the other one, it could not have been a Minimum Vertex Cover for G —which contradicts G being *well-covered*.

Theorem 2.15

In a *well-covered* graph, all Minimal Vertex Covers have the same cardinality. [38]

2.3. Independent Set

Another prominent graph problem is the *Independent Set* which asks for a vertex set that is “independent”, meaning that no two vertices are adjacent. It can be seen as the counter part of Vertex Cover (see section 2.2) because it requires *at most* one vertex for every edge while Vertex Cover demands *at least* one vertex for every edge. We consider this connection in theorem 2.19.

Definition 2.16 (Independent Set)

Given an undirected graph $G = (V, E)$, an independent set $V_{\text{IS}} \subseteq V$ is a vertex set such that no two vertices $v, w \in V_{\text{IS}}$ are incident to the same edge $\{v, w\} \in E$:

$$\forall v \in V_{\text{IS}} : \forall \{v, w\} \in E : w \notin V_{\text{IS}}$$

Again we can find a trivial Independent Set for every graph in constant time: the empty set. However, similar to Vertex Cover one usually asks for a “large” Independent Set as defined below:

Definition 2.17 (Maximal/Maximum Independent Set)

For an undirected graph $G = (V, E)$, an independent set $V_{\text{IS}} \subseteq V$ is maximal if there is no vertex $v \in V \setminus V_{\text{IS}}$ such that $V_{\text{IS}} \cup \{v\}$ remains an independent set. It is maximum if there is no independent set V_{IS}' with larger cardinality.

The IP for Maximum Independent Set maximizes the number of selected vertices such that for every edge only one of the incident vertices is selected. Analogous to the IP formulation of Minimum Vertex Cover, the optimal V_{IS} solution can directly be retrieved from the IP solution: $IP = \{v \in V : x_v = 1\}$

Problem 2.18 (IP Formulation of Maximum Independent Set)

$$\begin{aligned}
 & \text{maximize} && \sum_{v \in V} x_v \\
 & \text{subject to} && \forall \{v, w\} \in E : x_v + x_w \leq 1 \\
 & && \forall v \in V : x_v \in \{0, 1\}
 \end{aligned}$$

We already mentioned the close connection between Vertex Cover and Independent Set earlier. Note that in fig. 2.2 the Minimal Vertex Cover is a Maximum Independent Set and the Minimum Vertex Cover a Maximal Independent Set. From the IP formulations it can also be seen that the problems behave the opposite way:

Theorem 2.19 (Independent Set and Vertex Cover)

For an undirected graph $G = (V, E)$, $V_{\text{IS}} \subseteq V$ is a Maximum Independent Set iff $V_{\text{cover}} = V \setminus V_{\text{IS}}$ is a Minimum Vertex Cover.

Proof:

Let V_{cover} be a Vertex Cover for G .

$$\begin{aligned}
 \forall e \in E : \exists v \in V_{\text{cover}} : v \in e & \iff \forall \{v, w\} \in E : v \in V_{\text{cover}} \vee w \in V_{\text{cover}} \\
 & \iff \forall \{v, w\} \in E : \neg(v \notin V_{\text{cover}} \wedge w \notin V_{\text{cover}}) \\
 & \iff \forall \{v, w\} \in E : \neg(v \in (V \setminus V_{\text{cover}}) \wedge w \in (V \setminus V_{\text{cover}})) \\
 & \iff \forall v \in (V \setminus V_{\text{cover}}) : \forall \{v, w\} \in E : w \notin (V \setminus V_{\text{cover}}) \\
 & \iff (V \setminus V_{\text{cover}}) \text{ independent set}
 \end{aligned}$$

Assume V_{cover} is a Minimum Vertex Cover for G and the independent set $V_{\text{IS}} = V \setminus V_{\text{cover}}$ is not maximum. Then there is an independent $V'_{\text{IS}} \subseteq V$ with $|V_{\text{IS}}| < |V'_{\text{IS}}|$. But then for the Vertex Cover $V'_{\text{cover}} = V \setminus V'_{\text{IS}}$ the following holds: $|V'_{\text{cover}}| < |V_{\text{cover}}|$ —which is a contradiction to V_{cover} being minimum. The same argumentation applies in the other direction.

Now that the link between both problems is proven, we can apply properties of the Vertex Cover problem to Independent Sets. Firstly, it follows that the Maximum Independent

Set problem is NP-complete as well because every solution can be transformed into a Minimum Vertex Cover and vice versa in polynomial time.

Theorem 2.20 (NP-Completeness of Maximum Independent Set)

Theorems 2.13 and 2.19 imply that Maximum Independent Set is NP-complete.

Additionally, we can adapt the concept of *well-covered* graphs to Independent Sets. The following theorem implies that for *well-covered* graphs, the complexity of finding a Maximum Independent Set is reduced to polynomial time.

Theorem 2.21 (Independent Set in *Well-covered* Graphs)

For a *well-covered* graph $G = (V, E)$, every maximal independent set has the same size and is therefore maximum.

Proof:

Theorem 2.21 follows directly from definition 2.14 and theorems 2.15 and 2.19.

Now we show a straightforward approach for finding Maximal Independent Sets in any undirected graph. It is similar to a method for Minimum Vertex Cover mentioned earlier. The idea consists in iteratively adding vertices to the set as long as they do not violate the Independent Set property until all vertices have been considered. Such an approach is called “greedy” because it constantly extends the solution until this is no longer possible—without removing part of the solution at any time.

Algorithmus 2.1 : Greedy Algorithm for Independent Set

Input : Undirected graph $G = (V, E)$

Output : Maximal Independent Set $V_{IS} \subseteq V$ for G

```

1 Set  $V_{IS} = \emptyset$ 
2 foreach  $v \in V$  do
3   if  $\forall \{v, w\} \in E : (w \notin V_{IS})$  then
4      $\quad$  Set  $V_{IS} = V_{IS} \cup \{v\}$ 
5 return  $V_{IS}$ 
```

This simple algorithm performs surprisingly well—to be seen in the following theorem. The Independent Set property can not be ensured without taking all edges into account which implies that the running time of algorithm 2.1 is even asymptotically optimal.

Theorem 2.22 (Correctness and Complexity of Algorithm 2.1)

Algorithm 2.1 always finds a Maximal Independent Set in $O(|E|)$ time.

Proof:

Because the vertices are processed sequentially, for every edge $\{v, w\} \in E$ at most one of v and w is added to V_{IS} . Therefore V_{IS} is an independent set. Additionally every vertex $v \in V$ is processed and if there is no $w \in V_{\text{IS}}$ with $\{v, w\} \in E$ then $v \in V_{\text{IS}}$. So V_{IS} is maximal.

The for-loop runs $|V|$ times but the if-statement is only executed twice for every edge $e \in E$. Every other statement runs in $O(1)$ time. Thus algorithm 2.1 needs $O(|E|)$ time.

Finally, we can take advantage of *well-covered* graphs when running algorithm 2.1 on them. It implicitly returns a Maximum Independent Set for *well-covered* graphs—without even comparing it to other Maximal Independent Sets.

Theorem 2.23 (Algorithm 2.1 in *well-covered* Graphs)

For a *well-covered* graph algorithm 2.1 always finds a Maximum Independent Set in $O(|E|)$ time.

Proof:

Theorem 2.23 follows directly from theorems 2.21 and 2.22.

3. Triangulations

4 pages: |||

glue text

Definition 3.1 (Complete Graph)

Given a vertex set V , the complete graph $K_V = (V, E)$ for V contains all possible undirected edges between two vertices of V :

$$E = \{e = \{v, w\} : v, w \in V \wedge v \neq w\}$$

glue text

Definition 3.2 (Conflict Graph)

The conflict graph $G_{\text{conf}}(E, X) = (E, X)$ for a set of edges E and a set of edge conflicts

$$X \subseteq \{\{e_i, e_j\} : e_i, e_j \in E \wedge e_i \neq e_j\}$$

is an undirected graph with E as vertices and X as edges.

glue text

Definition 3.3 (Triangulation)

Given the complete graph $K_V = (V, E)$ for a vertex set V and a set of edge conflicts

$$X \subseteq \{\{e_i, e_j\} : e_i, e_j \in E \wedge e_i \neq e_j\}$$

such that the conflict graph $G_{\text{conf}}(E, X)$ is *well-covered*. A *triangulation* $T(V, X) \subseteq E$ of V with respect to X is a maximum set of non-conflicting edges:

$$e_i \in T(V, X) \iff e_i \in E \wedge \forall e_j \in T(V, X) : \{e_i, e_j\} \notin X$$

glue text




Figure 3.1.: Example of the conflict graph for a given set of segments and the conflicts being all intersections

glue text

Theorem 3.4 (Equality of Triangulation and Maximum Independent Set)
 Every triangulation $T(V, X)$ of a vertex set V with respect to conflicts X is a maximum independent set for the conflict graph $G_{\text{conf}}(E, X)$ and vice versa. Hereby E are the edges of the complete graph K_V .

Proof:

Theorem 3.4 follows directly from definition 2.17 and theorem 2.21.

Theorem 3.5

From theorems 2.23 and 3.4 follows that finding the triangulation $T(V, X)$ of a vertex set V with respect to conflicts X can be calculated in $O(|X|)$ time.

glue text

Definition 3.6 (Triangulation with Forbidden Edges)

A *triangulation with forbidden edges* $T(V, X, F)$ is a triangulation of the vertex set V with respect to conflicts X which does not contain any of the edges in F :

$$\forall e \in F : e \notin T(V, X, F)$$

glue text

Theorem 3.7 (NP-completeness of Triangulation with Forbidden Edges)

The decision problem whether a triangulation with forbidden edges $T(V, X, F)$ exists is NP-complete. [31, triangulation existence problem]

glue text

Definition 3.8 (Constrained Triangulation)

A *constrained triangulation* $T(V, X, C)$ is a triangulation of the vertex set V with respect to conflicts X which contains the edge constraints C :

$$\forall e \in C : e \in T(V, X, C)$$

3.1. Point Set Triangulations

glue text

Definition 3.9 (Planar Points)

A *planar set of points* or *set of points in the plane* P is a set of points with two coordinates:

$$P \subseteq \{p = (p_x, p_y) : p_x, p_y \in F\}$$

We do not make any assumptions on the coordinates besides F being a field, e.g. the real numbers \mathbb{R} . Furthermore, because P is a set, no duplicate points $p = (p_x, p_y) \in P$ and $p' = (p'_x, p'_y) \in P$ with $p_x = p'_x$ and $p_y = p'_y$ are allowed. Note however that we do not require the points in P to be in general position as that would forbid some interesting instances.

do we need this definition at all?

glue text

Definition 3.10 (Line Segments)

A *line segment* $s = (p, q)$ is determined by its endpoints $p, q \in P$ with P being a point set. For compatibility with other definitions, s is directed from p to q , i.e. $(p, q) \neq (q, p)$ and contains all points “between” p and q :

$$m \in s \iff \exists a \in [0, 1] : m = p + a \cdot (q - p)$$

glue text

Definition 3.11 (Crossing)

Two line segments $s_i = (p_i, q_i)$ and $s_j = (p_j, q_j)$ with different slope are *crossing*, if their intersection is not empty and not an endpoint, i.e.

$$s_i, s_j \text{ crossing} \iff (p \in s_i \cap s_j) \wedge (|s_i \cap s_j| = 1) \wedge (p \notin \{p_i, q_i, p_j, q_j\})$$

Two segments s_i and s_j are *non-crossing* if they are not *crossing*. A set S of segments is *crossing* if at least two segments $s_i, s_j \in S$ are *crossing*. It is *non-crossing* if each pair $s_i, s_j \in S$ is *non-crossing*.

glue text

Definition 3.12 (Overlapping Segments)

Given a point set P and a line segment $s = (p, q)$ with $p, q \in P$. s is *overlapping* in P iff there is a point $p' \in P$ which lies in its interior:

$$s \text{ overlapping} \iff \exists p' \in P : (p' \in s) \wedge (p' \notin \{p, q\})$$

s is *non-overlapping* if it is not *overlapping*.




Figure 3.2.: Examples of overlapping segments $(\{a, b\}, \{c, e\}, \{d, f\}, \{g, h\})$

glue text

Definition 3.13 (Topological Representation)

A vertex set $V(P)$ represents a point set P iff there is exactly one vertex $v_p \in V(P)$ for each point $p \in P$ and v_p can be identified by p and vice versa.

remove comment

Definition 3.14 (Point Set Triangulation)

The triangulation $T(P)$ of a point set P is a triangulation $T(P) = T(V, X)$ where the vertex set $V = V(P)$ represents P , the conflicts X are all *crossing* segments, and which contains no *overlapping* segments:

$$\begin{aligned} (p, q), (p', q') \text{ crossing} &\iff \{\{v_p, v_q\}, \{v_{p'}, v_{q'}\}\} \in X \\ (p, q) \text{ overlapping} &\implies \{v_p, v_q\} \notin T(P) \end{aligned}$$

For convenience we define $s = (p, q) \equiv e = \{v_p, v_q\}$ such that $s \in T(P) \iff e \in T(P)$. For a slightly different yet equivalent definition of a point set triangulation see also [2, Section 9.1].

glue text

Theorem 3.15 (Time for Planar Point Set Triangulation)

A point set $P \subseteq \mathbb{R}^2$ can be triangulated in $O(n \log n)$ time with $n = |P|$. [2, Theorem 9.12]

glue text

Definition 3.16 (Constrained Point Set Triangulation)

Analogous to the Constrained Triangulation (definition 3.8), a *constrained point set triangulation* $T(P, C)$ of a point set P with line segment constraints C is a point set triangulation $T(P, C) = T(P)$ such that $C \subseteq T(P, C)$.

glue text

Theorem 3.17

A constrained point set triangulation $T(P, C)$ for a point set $P \subseteq \mathbb{R}^2$ and line segment constraints $C \subseteq P^2$ can be calculated in $O(n \log n)$ time. [6]

3.2. Intersection Graph

glue text

Definition 3.18 (Intersection Graph)

For a set of line segments S the *intersection graph* $G_{\text{cross}}(S) = (V_S, X)$ consists of a vertex $v_s \in V_S$ for every line segment $s \in S$ and an edge $\{v_{s_i}, v_{s_j}\} \in X$ for every pair of *crossing* segments $s_i, s_j \in S$. It is the geometric equivalent of the conflict graph (definition 3.2).

glue text

Theorem 3.19 (Computational Complexity of Intersection Graph)

Given a set of line segments S the intersection graph $G_{\text{cross}}(S) = (V_S, X)$ can be calculated in $O(m \log m + i \log m)$ time where $m = |V_S| = |S|$ and $i = |X|$ is the number of intersections in S . [2, Lemma 2.3]

glue text

Theorem 3.20 (Complexity of Point Set Intersections)

For a point set P with n points the set of all line segments S with endpoints in P has $\Theta(n^4)$ intersections. [34] Thus calculating the intersection graph for S takes $\Omega(n^4)$ time.

glue text

Theorem 3.21 (Non-Optimality of Sweep Algorithm for Point Sets)

The sweep algorithm presented in [2, Section 2.1] with the time complexity of theorem 3.19 is not optimal for calculating the intersections of all line segments with endpoints in a given point set P as it takes $O(n^4 \log n)$ time.

Algorithmus 3.1 : Naive Intersection Algorithm

Input : Set of segments S

Output : Intersection graph $G_{\text{cross}}(S) = (V_S, X)$

```
1 Set  $V_S = \{v_s : s \in S\}$ 
2 Set  $X = \emptyset$ 
3 foreach  $s \in S$  do
4   foreach  $s_{\times} \in S$  with  $|s| \leq |s_{\times}|$  do
5     if  $s$  and  $s_{\times}$  are crossing then
6       └ Add  $\{v_s, v_{s_{\times}}\}$  to  $X$ 
7 return  $G_{\text{cross}}(S) = (V_S, X)$ 
```

glue text

glue text

Theorem 3.22 (Complexity and Correctness of Algorithm 3.1)

Algorithm 3.1 finds all intersecting line segments in $O(m^2)$ time with $m = |S|$.

glue text

Theorem 3.23 (Optimality of Algorithm 3.1 for Point Set)

Algorithm 3.1 is asymptotically optimal for finding the intersections of all line segments with endpoints in a given point set P as it takes $O(n^4)$ time for $n = |P|$.

3.3. Polygon Triangulations

glue text

Definition 3.24 (Polygon Triangulation)

A triangulation $T(P)$ of a polygon P bounded by line segments are all boundary and interior edges of P in a constrained point set triangulation of the polygon vertices with the polygon boundary as constraints.

glue text

Theorem 3.25 (Generalization of Point Set Triangulation)

Given a point set P , a triangulation $T(\text{conv}(P) \cup P)$ of the polygon bounded by the convex hull $\text{conv}(P)$ of P and containing all inner points of P is a triangulation of P .

3.4. Edge Flipping

glue text

Definition 3.26 (Edge Flip)

Given a triangulation $T(V, X)$ for a vertex set V with respect to a set of conflicts X , (e, f) with $e \in T(V, X)$ and $f \notin T(V, X)$ is an *edge flip* iff $T(V, X) \setminus \{e\} \cup \{f\}$ is a triangulation for V with respect to X .

glue text

Theorem 3.27 (Edge Flips are Conflicts)

Given a triangulation $T(V, X)$ for a vertex set V with respect to a set of conflicts X , every edge flip (e, f) is a conflict: $\{e, f\} \in X$.

Proof:

Assume $\{e, f\} \notin X$. Further assume that

$$\neg \exists e' \in T(V, X) \setminus \{e\} : \{e', f\} \in X.$$

Then f can be added to $T(V, X)$ (without removing e) and therefore $T(V, X)$ is no triangulation—which is a contradiction. Now let $e' \in T(V, X) \setminus \{e\}$ such that $\{e', f\} \in X$. Then $e' \in T(V, X) \setminus \{e\} \cup f$ —which contradicts that $T(V, X) \setminus \{e\} \cup f$ is a triangulation. Therefore every edge flip (e, f) is a conflict.

glue text

Definition 3.28 (Flip Graph)

The flip graph $G_{\text{flip}}(V, X) = (V_T, E_{\text{flip}})$ for a vertex set V and edge conflicts X contains a vertex $v \in V_T$ for every triangulation of V with respect to X and edges $e \in E_{\text{flip}}$ for every possible edge flip.

glue text




Figure 3.3.: Example triangulations and their flip graph

glue text

Theorem 3.29 (Connectivity of the Flip Graph)

The flip graph $G_{\text{flip}}(V, X)$ is connected in two dimensions [46, Behauptung 4] and has a diameter of at most $6n - 30$ for $n = |V|$. [4] Therefore every triangulation $T(V, X)$ of a vertex set V with respect to edge conflicts X can be transformed into any other triangulation of V with respect to X in $O(n)$ time.

For three dimensions, it is still an open problem whether the flip graph is connected. [14]

- local vs. global optimal
- hint to edge flipping paper

notes

3.5. Related Work

After class was over, Greg asked Mrs. Minerva if there are different kinds of triangulations. She replied that the problem of triangulating has kept researchers busy for over 100 years already [23] and that people have found different aspects in that a triangulation can be optimal.

The most famous class is the Delaunay triangulation [2, Section 9.2]. It forces every circumcircle of a triangle to be empty of other points and therefore maximizes the minimum angle [2, Theorem 9.9]. There is an edge flipping algorithm which calculates it in $O(n \log n)$ expected time using $O(n)$ space [2, Theorem 9.12].

There are several other triangulations which can be computed in polynomial time. Minimizing the maximum edge length in $O(n^2)$ times was one of the first results [17]. The counterpart of a Delaunay triangulation, minimizing the maximum angle, takes $O(n^2 \log n)$ time and $O(n)$ space [3]. The same approach can also produce triangulations which maximize the minimum height of a triangle. Finally, the same reference shows also that minimizing the maximum slope and minimizing the maximum eccentricity can both be done in $O(n^3)$ time and $O(n^2)$ space. A triangulation which minimizes or maximizes the area of triangles can be computed in $O(n^2 \log n)$ time with $O(n^2)$ space. [45]

Other triangulations have been proven NP-hard or NP-complete. One of them is to minimize the edge length sum (also known as the minimum weight triangulation) which is NP-hard [36]. Maximizing the minimum edge length was stated an open problem [17] but 20 years later it has been shown that it is NP-complete [19]. The latter one remains NP-hard for polygons with holes and interior points [7] but can be solved in $O(n^3)$ time for simple polygons and even in linear time for convex polygons [24].

4. MaxMin Length Triangulation

...

2 pages

glue text

Problem 4.1 (MaxMin Length Triangulation (MMLT))

Given: Set of points P , length function $|s|$ for each line segment s with endpoints in P (e.g. Euclidean distance of the endpoints)

Sought: Point Set Triangulation $T_{\text{opt}} = T(P)$ of P which maximizes $\min_{s \in T_{\text{opt}}} |s|$

glue text




Figure 4.1.: Example of different optimal solutions for the same point set

4.1. Complexity

glue text [19]

Problem 4.2 (Covering by Disjoint Segments (CDS))

Given: Set of line segments S , set of target points $T \subseteq \{s_i \cap s_j : s_i, s_j \in S\}$

Sought: Set of non-intersecting line segments $S_{\text{opt}} \subseteq S$ such that T is covered:

$$\forall p \in T : \exists s \in S_{\text{opt}} : p \in s$$

glue text

Theorem 4.3

Problem 4.2 is NP-complete.

Proof:

CDS can be reduced to Planar 3-SAT (problem 2.7) and vice-versa. For further details of the proof refer to [19].

glue text

Theorem 4.4 (NP-hardness of Problem 4.1)

Problem 4.1 (MMLT) is NP-hard—even for the case where P is planar.

Proof:

...

proof

4.2. Geometric Approaches

- sweep line does not work (non-local segments)
- flip does not work (locally non-optimal flip necessary)

notes




Figure 4.2.: Example of necessary locally non-optimal flips: The shortest edge needs to be flipped in before the optimal solution can be achieved.

4.3. Combinatorial Approach

glue text

Definition 4.5 (Edge Length Order)

Given a set of edges E representing a set of line segments S and two edges $e_{s_i}, e_{s_j} \in E$ representing two line segments $s_i, s_j \in S$, respectively. Let $|s|$ for $s \in S$ be the segment length and $s_i < s_j$ the lexicographical order of $s_i, s_j \in S$. The edge length order is defined as

$$e_{s_i} < e_{s_j} \iff |s_i| < |s_j| \vee ((|s_i| = |s_j|) \wedge (s_i < s_j)).$$

glue text

Definition 4.6 (Edge Length Index)

Given a set of edges E representing a set of line segments S and an edge $e \in E$. The *edge length index* $\text{idx}(e)$ is the index of e in E sorted by edge length order.

glue text

Theorem 4.7 (Uniqueness of Edge Length Index)

For a set of edges E representing line segments S , there can be no two edges $e, e' \in E$ with the same edge length index.

Proof:

For two two segments $s, s' \in S$ the lexicographical order is unique—i.e. either $s < s'$ or $s > s'$ but not both. The same holds for the edge length order.

glue text

Problem 4.8 (MaxMin Edge Length Index Triangulation (MELT))

Given: Set of points P

Sought: Point Set Triangulation $T_{\text{opt}} = T(P)$ of P which maximizes the minimum edge length index $\min_{e \in T_{\text{opt}}} \text{idx}(e)$.

glue text

Theorem 4.9 (Uniqueness of Optimal MELT Solution)

From Theorem 4.7 follows directly that problem 4.8 has a unique optimal solution.

glue text

Theorem 4.10 (Equality of MELT and MMLT)

Every optimal MELT solution is an optimal MMLT solution.

Proof:

Let T_{opt} be the optimal MELT solution for a point set P and assume that there is a MMLT solution T with $\min_{s \in T} |s| < \min_{s \in T_{\text{opt}}} |s|$. By definitions 4.5 and 4.6 $\text{idx}(\arg \min_{s \in T} |s|) < \text{idx}(\arg \min_{s \in T_{\text{opt}}} |s|)$ —which contradicts T_{opt} being optimal.

glue text

Theorem 4.11 (NP-hardness of MELT)

From theorem 4.10 follows that MELT is NP-hard.

glue text

Problem 4.12 (Integer Program (IP) Formulation of MELT)

E : *non-overlapping* line segments with endpoints in P

X : pairs of *crossing* line segments

T : MELT solution

$$\begin{aligned} & \text{maximize} \quad \min_{e \in T} x_e \cdot \text{idx}(e) \\ & \text{subject to} \quad \forall \{e_i, e_j\} \in X : \quad x_{e_i} + x_{e_j} \leq 1 \\ & \quad \quad \quad \forall e_i \in E : x_{e_i} + \sum_{\{e_i, e_j\} \in X} x_{e_j} \geq 1 \\ & \quad \quad \quad \forall e \in E : \quad x_e \in \{0, 1\} \end{aligned}$$

IP:

- maximize min. edge index
- no conflicting edges
- for every edge: either edge or crossing edge picked
- n^2 variables, $O(n^4)$ restrictions

notes

4.4. Separators

glue text

Definition 4.13 (Short Edges)

Short edges within a set of edges E are all edges with an edge length index smaller than a certain threshold:

$$E_{\text{short}}(E, \ell) := \{e \in E : \text{idx}(e) < \ell\}$$

glue text

Definition 4.14 (Separators)

Given a set of edges E and edge conflicts $X \subseteq E^2$. The set of separators $E_{\text{sep}}(E, X, e)$ for an edge $e \in E$ are all edges that improve the MELT solution, i.e. all e_{sep} with $\{e, e_{\text{sep}}\} \in X$ which have a higher edge length index:

$$E_{\text{sep}}(E, X, e) := \{e_{\text{sep}} \in E : \text{idx}(e) < \text{idx}(e_{\text{sep}}) \wedge \{e, e_{\text{sep}}\} \in X\}$$

glue text

Theorem 4.15 (upper bound)

Given the optimal MELT solution T_{opt} for a point set P , let the edge set E represent all *non-overlapping* line segments S with endpoints in P and X be all pairs of *crossing* line segment in S . Every edge $e \in E$ without separators is an upper bound for T_{opt} :

$$\forall e \in E, E_{\text{sep}}(E, X, e) = \emptyset : \min_{e_{\text{min}} \in T_{\text{opt}}} \text{idx}(e_{\text{min}}) \leq \text{idx}(e)$$

which is equivalent to

$$\begin{aligned} \forall e \in E : \neg \exists e_{\text{sep}} \in E : \text{idx}(e) < \text{idx}(e_{\text{sep}}) \wedge \{e, e_{\text{sep}}\} \in X \\ \implies \min_{e_{\text{min}} \in T_{\text{opt}}} \text{idx}(e_{\text{min}}) \leq \text{idx}(e) \end{aligned}$$

Proof:

Assume

$$\exists e \in E, E_{\text{sep}}(E, X, e) = \emptyset : \min_{e_{\text{min}} \in T_{\text{opt}}} \text{idx}(e_{\text{min}}) > \text{idx}(e)$$

This implies $e \notin T_{\text{opt}}$ and

$$\forall e' \in E : \text{idx}(e') < \text{idx}(e) \implies e' \notin T_{\text{opt}}.$$

With $E_{\text{sep}}(E, X, e) = \emptyset$ it follows that $\forall \{e, e_x\} \in X : e_x \notin T_{\text{opt}}$. This means that for T_{opt} to be a triangulation e has to be in T_{opt} —which is a contradiction.

glue text

Definition 4.16 (Shortest Non-separable Edge)

Given a set of edges E and edge conflicts $X \subseteq E^2$. The *shortest non-separable edge* e_{nose} is the edge with the smallest edge length index which has no separators:

$$e_{\text{nose}} := \arg \min_{e \in E : E_{\text{sep}}(E, X, e) = \emptyset} \text{idx}(e)$$

glue text

glue text




Figure 4.3.: Example where the upper bound from theorem 4.15 is not tight. One of the short segments (red) is part of an optimal MELT solution because their separators (green) cross. Thus the shortest segment in the solution is shorter than the shortest one of all segments without separators (blue).

Problem 4.17 (Non-Conflicting Separators (NOCS))

Given: Set of short edges E and their separators E_{sep} , edge conflicts $X \subseteq (E \cup E_{\text{sep}})^2$

Sought: Set of non-conflicting edges

$$E_{\text{opt}} \subseteq E \cup \bigcup_{e \in E} E_{\text{sep}}(e)$$

which contains for every edge $e \in E$ either e itself or at least one separator $e_{\text{sep}} \in E_{\text{sep}}(e)$ and maximizes the smallest edge length index $\min_{e \in E_{\text{opt}}} \text{idx}(e)$

glue text

Theorem 4.18 (Equality of MELT and NOCS)

Given a point set P , edges E representing all *non-overlapping* line segments S with endpoints in P , and all pairs of *crossing* line segments X in S , let e_{nose} be the shortest non-separable edge in E . The optimal MELT solution T_{opt} for P and the optimal NOCS solution S_{opt} for $E_{\text{short}}(E, \text{idx}(e_{\text{nose}}))$ have the same value:

$$\min_{e \in T_{\text{opt}}} \text{idx}(e) = \min_{e \in S_{\text{opt}}} \text{idx}(e)$$

Proof:

...

proof

glue text

Theorem 4.19 (NP-hardness of NOCS)

For $E_{\text{short}}(E, \text{idx}(e_{\text{nose}})) \cup e_{\text{nose}} = E$, NOCS and MELT are the same problem. Therefore NOCS is also NP-hard.

glue text

Problem 4.20 (IP Formulation of NOCS)

E : short edges

E_{sep} : separators

X : edge conflicts

S : NOCS solution

$$\begin{aligned}
 & \text{maximize} && \min_{e \in S} x_e \cdot \text{idx}(e) \\
 & \text{subject to} && \forall \{e_i, e_j\} \in X : && x_{e_i} + x_{e_j} \leq 1 \\
 & && \forall e_i \in E : x_{e_i} + \sum_{e_j \in E_{\text{sep}}(e_i)} x_{e_j} \geq 1 \\
 & && \forall e \in E \cup \bigcup_{e \in E} E_{\text{sep}}(e) : && x_e \in \{0, 1\}
 \end{aligned}$$

IP:

- maximize min. edge index
- no conflicting edges
- for every short edge: either edge or separator picked
- worst case: n^2 variables, $O(n^4)$ restrictions
- random points: $O(n)$ variables, $< O(n^3)$ restrictions?

notes

glue text

Definition 4.21 (Completion of NOCS)

Given an optimal NOCS solution T_{opt} for a set of short edges E , their separators E_{sep} , and conflicts X , the completion of T_{opt} is

$$T := T_{\text{opt}} \cup \left\{ e_{\text{sep}} \in \bigcup_{e \in E} E_{\text{sep}}(e) : \neg \exists e \in T : \{e, e_{\text{sep}}\} \in X \right\}.$$

If $T = T_{\text{opt}}$, T_{opt} is *complete*.

glue text

Theorem 4.22 (Optimality of NOCS Completion)

Given an optimal NOCS solution T_{opt} the completion T of T_{opt} is also an optimal NOCS solution.

Proof:

...

proof

Theorem 4.23 (Connection of NOCS and Independent Set)

Every complete optimal NOCS solution T_{opt} for a set of short edges E , their separators E_{sep} , and conflicts $X \subseteq (E \cup E_{\text{sep}})^2$ is a maximal independent set (definition 2.17) for the undirected graph $G = (E \cup E_{\text{sep}}, X)$.

Proof:

...

proof

4.5. Algorithm

...

glue text

key feature: enose is short!

update notation in algorithm

use subroutines?

Algorithmus 4.1 : MMLT algorithm

Input : Planar point set P

Output : An optimal MMLT solution for P

- 1 Generate the induced segments S_P for P
 - 2 Find the shortest non-separable segment e_{nose} and calculate intersections for $E_{\text{short}}(|e_{\text{nose}}|)$ and their separators
 - 3 Set the lower bound $\text{lb} = 0$
 - 4 Set the upper bound ub such that $S_P[\text{ub}] = e_{\text{nose}}$
 - 5 Set $\text{last} = \emptyset$
 - 6 **while** $\text{lb} < \text{ub}$ **do**
 - 7 Set $\text{mid} = \lceil \frac{\text{lb} + \text{ub}}{2} \rceil$
 - 8 Find optimal NOCS solution S_{opt} for $E_{\text{short}}(P, |S_P[\text{ub}]|)$ without using any segment from $E_{\text{short}}(P, |S_P[\text{mid}]|)$
 - 9 **if** *there is a solution* S_{opt} **then**
 - 10 Set $\text{last} = S_{\text{opt}}$
 - 11 Maximize lb such that $|S_P[\text{lb}]| = \min_{s \in S_{\text{opt}}} |s|$
 - 12 **if** $\text{lb} > \text{ub}$ **then**
 - 13 $\text{lb} = \text{ub}$
 - 14 **else**
 - 15 **if** $\text{lb} < \text{mid}$ **then**
 - 16 Set $\text{ub} = \text{mid} - 1$
 - 17 **else**
 - 18 Set $\text{ub} = \text{lb}$
 - 19 **return** *constrained triangulation* T_{opt} *with last as constraints*
-

5. Implementation

In this chapter, we will briefly describe the program components—roughly split into the geometry and the optimization part. To let the program run close to the hardware layer (which usually leads to fast execution times), the code was written in C++. First attempts to use Python instead (for the sake of clarity and better readability) stumbled over the non-readiness of the CGAL bindings and the lack of good alternatives. For the technical documentation, please refer to appendix A.

5.1. Geometry

The geometry part consists of number, point, and segment types, data structures for triangulation, convex hull, and bounding box, and it also handles the segment intersection. For most of it Winfried made extensive use of CGAL, which will be introduced in section 5.1.1.

5.1.1. CGAL

CGAL [5] is an Open Source library (mainly) for computational geometry written in C++. It includes most of the common algorithms in the field and also offers efficient data structures. Through the use of C++ templates it is flexible and extendable: For example it is common to adjust the underlying number types to the application.

5.1.2. Kernel

A kernel in CGAL is something like a computational geometry operating system: It holds the basic type definitions like numbers, points, lines, and line segments. Basic operations such as intersection, angle calculations, or comparisons are also part of it.

In our application we use the built-in `Exact_predicates_inexact_constructions_kernel`¹ [18], which uses double as a number type and is not capable of constructing new geometric objects from existing ones accurately. Both properties lead to faster execution time yet do not produce wrong results in our case.

On top of the CGAL kernel there are two modifications: One is for printing points and segments without the need to use streams, the other one to output them to SVG (see also sections 5.3.2 and 5.3.6). Additionally segments are indexed by length and have the information whether they overlap with other segments attached to them.

¹Thanks to Michael Hemmer for making me aware that I should use it!

5.1.3. Triangulation

CGAL brings along a constrained triangulation already [9] which triangulates a point set with respect to a given mandatory set of (non-crossing) edges. For this application the class was extended to be drawable to SVG and to find the shortest edge which is part of the triangulation.

5.1.4. Convex Hull

This class directly calls the `convex_hull_2` function of CGAL [10] which itself defaults to the algorithm of Akl & Toussaint [1]. The only extension is that the class serves as container which holds the output points and contains a function to find the shortest segment within.

For the algorithm this class is not necessary as its bound is worse than the one of the SAT solution. It is left in the implementation though as a measure of quality for the other bound.

5.1.5. Intersection Algorithm

To find all pairs of intersecting segments we use algorithm 3.1. For the intersection check itself we make use of the CGAL function `do_intersect` [15]. In contrast to the `intersection` function [26], it does not actually compute the intersection and therefore performs much better.²

5.1.6. Intersection Graph

The intersection graph (as defined in definition 3.18) stores for every segment the indices of all intersecting segments. This graph data structure (adjacency list) performs well for few edges (in this case intersections) per vertex (in this case line segment)—which we assume here. It may however in future versions of the implementation be replaced by a sparse adjacency matrix from the section 5.3.1 library.

5.2. Optimization

The optimization part itself consists mainly of data structures for SAT problems and solutions, an interface for SAT solvers and the solvers themselves (currently only CPLEX).

Only segment indices and intersections are passed to the SAT problem. This is because geometry does not influence the problem, but only topology. Also it is easier that way to keep track of which segments take part in the restrictions.

5.2.1. SAT problem

This class serves two purposes: To grant an interface to the relevant data for the SAT (i.e. segments and intersections) and to set the short segment range.

²Thanks again to Michael Hemmer!

5.2.2. SAT solution

The SAT solution class mainly just stores the segment indices derived from solving the SAT problem — which can be none if no feasible solution is found. Additionally it offers methods for drawing short segments and separators and for finding the shortest segment of the solution.

5.2.3. SAT solver

To unify the way solving the SAT problem is done, there are three interfaces: The base SAT solver and two derived interfaces for decision and optimization problems. They all share methods for adding forbidden segments, intersection and separation restrictions and for running the actual solving. Furthermore there is a method for binding short segments to the objective function for optimization problems.

5.2.4. CPLEX

IBM ILOG CPLEX [25] is a commercial optimization suite written in C. It contains a standalone tool for solving optimization problems and also includes libraries for being used in other programs or even other programming languages. According to [35] CPLEX is one of the two fastest MILP solvers.

In our application we use the Concert API for C++ [8] to access CPLEX. It allows for adding variables and restrictions to a model, extracting them to more efficient data structures and then running several solving algorithms on it.

5.3. Remains

And then there is the rest: A controller class for the whole algorithm which combines all the other components and utility classes for reading input files, debug output and assertions, test case generation, and drawing certain states of the algorithm to SVG.

5.3.1. Boost

Boost [13] is a collection of free (as in freedom) C++ libraries containing tools for various tasks. It makes extensive use of the C++ pre-processor (mostly templates) and aims to extend the C++ standard library (STL).

In our implementation, we use the Spirit [22] library for parsing the JSON input files (see section 5.3.3), and the Program Options library [39] for parsing command line arguments and configuration files. Later versions of the implementation may as well use the Boost Graph Library [44] for the intersection graph, and the Geometry library [20] for creating SVG images (see section 5.3.6).

5.3.2. Qt

Qt [42] is a framework for cross-platform application development written in C++. It features some enhancements to the C++ standard library including an own string class `QString` [41] which supports a different formatting syntax than the `std::string`, offers a UI description format with integration into a even processing framework, and also comes with a simplified build system `qmake` which wraps platform dependent tools such as GNU `make`.

We make use of `QString` for our logger class (section 5.3.4), generate SVG images through the `QPainter` class, and build our applications using `qmake` (which also allows for integration in the C++ IDE Qtcreator).

5.3.3. JSON Parser

JSON Spirit [47] uses the Boost Spirit library [22] for parsing the input point files in JSON (JavaScript Object Notation) [27] format. As of writing, the built-in JSON support of Qt unfortunately has a bug [33] such that it is not compatible with the C++ standard library (and therefore also neither with CGAL nor with Boost). After parsing the input file, all points are stored in a sorted set to allow for fast lookup.

5.3.4. Logger

Our logger class supports different levels of verbosity (debug, info, error, print) and adds the current timestamp to each of them. Additionally, there are shortcut methods for output of measured times, and the current status of the algorithm. Debug output is only included in the programs if they are compiled in debug mode. For convenience, all methods accept `QString`.

5.3.5. Point Generator

For testing and analyzing the algorithm, we generated different instances of point sets and stored them for repeated runs. We hereby rely on the `Random_points_in_square_2` class [43] in combination with the `Creator_uniform_2` class [12]—both part of CGAL (section 5.1.1).

5.3.6. SVG Painter

Mainly for debugging purposes and to visualize different steps of the algorithm, we included the possibility to draw certain data structures to SVG using the `QPainter` class [40].

6. Results

3 pages

This chapter covers the results from running our implementation on a fine grid. Random sample points are uniformly selected within a square of side length $100\sqrt{n}$ where n is the number of points. This guarantees the same point density for all sample sizes and seemed to be a sufficient accuracy for real world instances. All coordinates are integer and transformed back to the unit square for analysis. For calculations (i.e. within the implementation itself) we use `double` however.

6.1. Technical Details

All experiments are run on a Intel[®] Core[™] 2 Duo CPU E6850 with 2 GB RAM. For everything but the IP-solving with CPLEX only one core is used. We compile with the GCC and following options: `-frounding-math -std=c++11 -O3`. The libraries we compile against are Qt 5.0.0, CGAL 4.0.2, Boost 1.49, and JSON Spirit 4.06.

6.2. Segment Lengths

Figures 6.1 and 6.2 show the trend of the shortest non-separable segment in comparison with the shortest segment overall and the shortest segment of the MaxMin Edge Length Index Triangulation (MELT) solution. For each data point 100 instances were run—though some of them have been aborted after 30 minutes (refer to section 6.4 and tables B.2 and B.3).

Even though the specific progression of the shortest non-separable segment index is not clear from fig. 6.2, it can be assumed that it is sub-linear. From fig. 6.1, we can also see that the shortest segment length significantly drops below the shortest non-separable segment length—which results in more segments being in between for a uniform distribution.




Figure 6.1.: Comparison of segment lengths




Figure 6.2.: Comparison of segment indices

6.3. Execution Time

We made different experimental analyses on the running time of our implementation. Again we let 100 instances run for each data point. The resulting times are real time (in contrast to user or system time)—i.e. execution time of non-related background processes is not excluded. This decision was made because it is usually impossible to guarantee that no other (system) tasks are running, so real time is more meaningful (yet less accurate).

Figure 6.3 shows which part of our algorithm takes what amount of time in comparison to the full execution execution time. As can table B.1






Figure 6.3.: Composition of execution times




(a) Improved method




(b) Complete SAT

Figure 6.4.: Total execution time




(a) 70 points




(b) 80 points

Figure 6.5.: Histogram of execution times

6.4. Aborted instances



(a) Complete SAT



(b) Improved method

Figure 6.6.: Instances with running time < 23:20min

7. Conclusion

2 pages

With the MaxMin Length Triangulation (MMLT) algorithm at hand Greg made his way to world domination.

be conclusive

- other distributions
 - * larger grids / true uniform
 - * gaussian
 - * cluster
- find patterns / graph classes
 - * longest edge of each clique?
- polygons
- greedy independent set as lower bound

notes

A. Documentation

The following is the technical documentation of the program, including class structure and interfaces. It was generated using Doxygen [16]. For an overview of the program components see chapter 5. The source code itself is hosted at: <https://bitbucket.org/winniehell/mmlt>

Contents

1	Class Documentation	1
1.1	Kernel_base< K_, Base_Kernel_ >::Base< Kernel2 > Struct Template Reference	2
1.2	BoundingBox Class Reference	2
1.2.1	Constructor & Destructor Documentation	2
1.2.2	Member Function Documentation	2
1.3	Controller Class Reference	3
1.3.1	Constructor & Destructor Documentation	4
1.3.2	Member Function Documentation	4
1.3.3	Member Data Documentation	5
1.4	ConvexHull Class Reference	5
1.4.1	Constructor & Destructor Documentation	6
1.4.2	Member Function Documentation	6
1.5	CPLEX Class Reference	6
1.5.1	Detailed Description	6
1.5.2	Constructor & Destructor Documentation	6
1.6	CplexSATSolver Class Reference	6
1.6.1	Detailed Description	9
1.6.2	Member Function Documentation	9
1.7	IntersectionAlgorithm Class Reference	10
1.7.1	Constructor & Destructor Documentation	11
1.7.2	Member Function Documentation	11
1.7.3	Member Data Documentation	11
1.8	IntersectionGraph Class Reference	11
1.8.1	Constructor & Destructor Documentation	12
1.8.2	Member Function Documentation	12
1.8.3	Member Data Documentation	13
1.9	Intersections Class Reference	13
1.9.1	Detailed Description	13
1.9.2	Constructor & Destructor Documentation	13
1.9.3	Member Function Documentation	13
1.10	JSON Class Reference	14
1.10.1	Member Function Documentation	15
1.11	Kernel Struct Reference	15
1.11.1	Detailed Description	16
1.12	Kernel_base< K_, Base_Kernel_ > Class Template Reference	16
1.12.1	Detailed Description	16
1.13	Logger Class Reference	16
1.13.1	Constructor & Destructor Documentation	17


1.13.2	Member Function Documentation	17
1.14	Messages Class Reference	17
1.14.1	Detailed Description	18
1.14.2	Member Function Documentation	18
1.15	OptimizationSATSolver Class Reference	18
1.15.1	Detailed Description	20
1.15.2	Member Function Documentation	20
1.16	PointC2< Kernel_ > Class Template Reference	21
1.16.1	Detailed Description	21
1.16.2	Member Typedef Documentation	22
1.16.3	Constructor & Destructor Documentation	22
1.16.4	Member Function Documentation	22
1.17	PointGenerator Class Reference	22
1.17.1	Member Function Documentation	23
1.17.2	Member Data Documentation	23
1.18	PointSet Class Reference	23
1.18.1	Detailed Description	24
1.18.2	Constructor & Destructor Documentation	24
1.18.3	Member Function Documentation	24
1.19	SATProblem Class Reference	24
1.19.1	Constructor & Destructor Documentation	25
1.19.2	Member Function Documentation	26
1.19.3	Member Data Documentation	26
1.20	SATSolution Class Reference	26
1.20.1	Constructor & Destructor Documentation	27
1.20.2	Member Function Documentation	27
1.21	SATSolver Class Reference	27
1.21.1	Detailed Description	29
1.21.2	Member Function Documentation	29
1.22	SegmentC2< Kernel_ > Class Template Reference	30
1.22.1	Detailed Description	31
1.22.2	Constructor & Destructor Documentation	31
1.22.3	Member Function Documentation	31
1.22.4	Member Data Documentation	32
1.23	SegmentContainer Class Reference	32
1.23.1	Detailed Description	32
1.23.2	Constructor & Destructor Documentation	32
1.23.3	Member Function Documentation	33
1.24	SegmentData Struct Reference	33
1.24.1	Detailed Description	33

1.24.2	Member Data Documentation	33
1.25	SegmentIndexOrder Struct Reference	34
1.25.1	Detailed Description	34
1.25.2	Member Function Documentation	34
1.26	SegmentLengthOrder Struct Reference	34
1.26.1	Detailed Description	35
1.26.2	Member Function Documentation	35
1.27	Stats Class Reference	35
1.27.1	Constructor & Destructor Documentation	36
1.27.2	Member Function Documentation	36
1.27.3	Member Data Documentation	36
1.28	SVGPainter Class Reference	36
1.28.1	Constructor & Destructor Documentation	37
1.28.2	Member Function Documentation	37
1.28.3	Member Data Documentation	38
1.29	Triangulation Class Reference	38
1.29.1	Constructor & Destructor Documentation	38
1.29.2	Member Function Documentation	38

1 Class Documentation

1.1 Kernel_base< K_, Base_Kernel_ >::Base< Kernel2 > Struct Template Reference


Collaboration diagram for Kernel_base< K_, Base_Kernel_ >::Base< Kernel2 >:



1.2 BoundingBox Class Reference

```
#include <bounding_box.h>
```

Collaboration diagram for BoundingBox:



Public Member Functions

- `BoundingBox (const PointSet &points)`
- `Number height () const`
- `Number width () const`

1.2.1 Constructor & Destructor Documentation

1.2.1.1 `BoundingBox::BoundingBox (const PointSet & points)` `[inline]`

1.2.2 Member Function Documentation


1.2.2.1 `Number BoundingBox::height () const` `[inline]`

1.2.2.2 `Number BoundingBox::width () const` `[inline]`

1.3 Controller Class Reference

```
#include <controller.h>
```

Collaboration diagram for Controller:



Public Member Functions

- Controller (const QString &file_prefix, QFile &input_file, const QSettings &settings)
- void done ()
- bool iteration ()
- bool start ()

Private Member Functions

- void draw_bounds () const
- void draw_intersections () const
- void draw_points (SVGPainter &painter) const
- void draw_sat_solution () const
- void draw_segments (SVGPainter &painter) const
- void draw_separators () const
- void draw_triangulation () const
- void output_status () const
- void pre_solving ()

Private Attributes

independent members

- CplexSATSolver cplex_solver_
- IntersectionAlgorithm intersection_algorithm_
- SATSolution sat_solution_
- Stats stats_

input parameters

- const QString &file_prefix_
- QFile &input_file_
- const QSettings &settings_

dependent on input parameter

- `const PointSet points_`

dependent on input points

- `const BoundingBox bounding_box_`
- `const ConvexHull convex_hull_`
- `SegmentContainer segments_`
- `Triangulation triangulation_`

dependent on segments

- `IntersectionGraph intersection_graph_`

1.3.1 Constructor & Destructor Documentation

1.3.1.1 `Controller::Controller (const QString & file_prefix, QFile & input_file, const QSettings & settings)`

1.3.2 Member Function Documentation

1.3.2.1 `void Controller::done ()`

called after the algorithm finished

1.3.2.2 `void Controller::draw_bounds () const [private]`

1.3.2.3 `void Controller::draw_intersections () const [private]`

1.3.2.4 `void Controller::draw_points (SVGPainter & painter) const [private]`

1.3.2.5 `void Controller::draw_sat_solution () const [private]`

1.3.2.6 `void Controller::draw_segments (SVGPainter & painter) const [private]`

1.3.2.7 `void Controller::draw_separators () const [private]`

1.3.2.8 `void Controller::draw_triangulation () const [private]`

1.3.2.9 `bool Controller::iteration ()`

run next iteration

Returns

true if next iteration should be triggered

1.3.2.10 `void Controller::output_status () const [private]`

dumps the current algorithm status

1.3.2.11 `void Controller::pre_solving () [private]`

does some pre-processing

1.3.2.12 `bool Controller::start ()`

start the algorithm

Returns

true if iteration should be triggered


1.3.3 Member Data Documentation

- 1.3.3.1 `const BoundingBox Controller::bounding_box_` [private]
- 1.3.3.2 `const ConvexHull Controller::convex_hull_` [private]
- 1.3.3.3 `CplexSATSolver Controller::cplex_solver_` [private]
- 1.3.3.4 `const QString& Controller::file_prefix_` [private]
- 1.3.3.5 `QFile& Controller::input_file_` [private]
- 1.3.3.6 `IntersectionAlgorithm Controller::intersection_algorithm_` [private]
- 1.3.3.7 `IntersectionGraph Controller::intersection_graph_` [private]
- 1.3.3.8 `const PointSet Controller::points_` [private]
- 1.3.3.9 `SATSolution Controller::sat_solution_` [private]
- 1.3.3.10 `SegmentContainer Controller::segments_` [private]
- 1.3.3.11 `const QSettings& Controller::settings_` [private]
- 1.3.3.12 `Stats Controller::stats_` [private]
- 1.3.3.13 `Triangulation Controller::triangulation_` [private]

1.4 ConvexHull Class Reference

```
#include <convex_hull.h>
```

Collaboration diagram for ConvexHull:



Public Member Functions

- ConvexHull (const PointSet &points)
- const SegmentIndex & shortest_segment (const SegmentContainer &segments) const

1.4.1 Constructor & Destructor Documentation

1.4.1.1 ConvexHull::ConvexHull (const PointSet & points)

compute convex hull of given point set

1.4.2 Member Function Documentation


1.4.2.1 `const SegmentIndex & ConvexHull::shortest_segment (const SegmentContainer & segments) const`

find the convex hull segment with minimum length

1.5 CPLEX Class Reference

```
#include <concert.h>
```

Collaboration diagram for CPLEX:



Public Member Functions

- `CPLEX ()`

1.5.1 Detailed Description

ugly CPLEX code is not our fault helper class for CPLEX concert API


1.5.2 Constructor & Destructor Documentation

1.5.2.1 `CPLEX::CPLEX() [inline]`


1.6 CplexSATSolver Class Reference

```
#include <cplex_sat_solver.h>
```

Inheritance diagram for CplexSATSolver:



Collaboration diagram for CplexSATSolver:




Classes

- struct ProblemData

Public Member Functions

- CplexSATSolver ()

Collaboration diagram for DecisionSATSolver:



Public Member Functions

- `void solve_decision_problem (const QSettings &settings, const QString &file_prefix, const SATProblem &problem, SATSolution &solution)`

Protected Member Functions

- `virtual void init_decision_problem (const SATProblem *problem)=0`

1.6.1 Detailed Description

interface for decision SAT solvers

1.6.2 Member Function Documentation

- 1.6.2.1** `virtual void DecisionSATSolver::init_decision_problem (const SATProblem * problem) [protected], [pure virtual]`


Implemented in CplexSATSolver.

- 1.6.2.2** `void DecisionSATSolver::solve_decision_problem (const QSettings & settings, const QString & file_prefix, const SATProblem & problem, SATSolution & solution)`

1.7 IntersectionAlgorithm Class Reference

```
#include <intersection_algorithm.h>
```

Collaboration diagram for IntersectionAlgorithm:



Public Member Functions

- IntersectionAlgorithm ()
- void run (IntersectionGraph &igraph, SegmentContainer &segments)

Public Attributes

- SegmentIndex shortest_noncrossing_segment_

Private Member Functions

- void handle_crossing (IntersectionGraph &igraph, const Segment &s1, const Segment &s2)
- void handle_overlap (IntersectionGraph &igraph, const Segment &s1, const Segment &s2)
- void handle_same_endpoint (const Segment &s1, const Segment &s2) const
- bool have_same_endpoint (const Segment &s1, const Segment &s2) const
- bool do_overlap (Segment &s1, Segment &s2) const

1.7.1 Constructor & Destructor Documentation

1.7.1.1 IntersectionAlgorithm::IntersectionAlgorithm ()

1.7.2 Member Function Documentation

1.7.2.1 bool IntersectionAlgorithm::do_overlap (Segment & s1, Segment & s2) const [private]

checks if two segments overlap

Returns

the outer segment

1.7.2.2 void IntersectionAlgorithm::handle_crossing (IntersectionGraph & igrph, const Segment & s1, const Segment & s2) [private]

segments cross

1.7.2.3 void IntersectionAlgorithm::handle_overlap (IntersectionGraph & igrph, const Segment & s1, const Segment & s2) [private]

segments intersect but do not cross

1.7.2.4 void IntersectionAlgorithm::handle_same_endpoint (const Segment & s1, const Segment & s2) const [private]

segments have the same end point

1.7.2.5 bool IntersectionAlgorithm::have_same_endpoint (const Segment & s1, const Segment & s2) const [private]

checks if two segments share an endpoint

Returns

the endpoint

1.7.2.6 void IntersectionAlgorithm::run (IntersectionGraph & igrph, SegmentContainer & segments)


1.7.3 Member Data Documentation

1.7.3.1 SegmentIndex IntersectionAlgorithm::shortest_noncrossing_segment_

1.8 IntersectionGraph Class Reference

```
#include <intersection_graph.h>
```


Collaboration diagram for IntersectionGraph:



Public Member Functions

- IntersectionGraph (const SegmentIndex &size)
- const Intersections & operator[] (const SegmentIndex &index) const
- void add_intersection (const Segment &s1, const Segment &s2)
- IntersectionsVector::const_iterator begin () const
- IntersectionsVector::const_iterator end () const
- const SegmentIndex & longest_intersecting_segment (const SegmentIndex &index) const

Private Attributes

- IntersectionsVector intersections_

1.8.1 Constructor & Destructor Documentation

1.8.1.1 IntersectionGraph::IntersectionGraph (const SegmentIndex & size)

default constructor

1.8.2 Member Function Documentation

1.8.2.1 void IntersectionGraph::add_intersection (const Segment & s1, const Segment & s2)

add two intersecting segments to the graph

1.8.2.2 IntersectionsVector::const_iterator IntersectionGraph::begin () const [inline]

1.8.2.3 IntersectionsVector::const_iterator IntersectionGraph::end () const [inline]

1.8.2.4 const SegmentIndex & IntersectionGraph::longest_intersecting_segment (const SegmentIndex & index) const

1.8.2.5 const Intersections& IntersectionGraph::operator[] (const SegmentIndex & index) const [inline]


Returns

all intersecting segments for a segment

1.8.3 Member Data Documentation**1.8.3.1 IntersectionsVector IntersectionGraph::intersections_ [private]****1.9 Intersections Class Reference**

```
#include <intersections.h>
```

Collaboration diagram for Intersections:

**Public Member Functions**

- Intersections ()
- void draw (QPainter &painter, const SegmentContainer &segments) const
- void find_separators (const SegmentIndex &segment_index, const SegmentContainer &segments, std::vector< SegmentIndex > &separators) const
- QString to_string (const SegmentContainer &segments) const

1.9.1 Detailed Description

sorted set of intersecting segments

1.9.2 Constructor & Destructor Documentation**1.9.2.1 Intersections::Intersections () [inline]**

default constructor

1.9.3 Member Function Documentation**1.9.3.1 void Intersections::draw (QPainter & *painter*, const SegmentContainer & *segments*) const**

draws intersections using QPainter

1.9.3.2 void Intersections::find_separators (const SegmentIndex & *segment_index*, const SegmentContainer & *segments*, std::vector< SegmentIndex > & *separators*) const

finds all separators for a given segment and stores them in the passed container


1.9.3.3 QString Intersections::to_string (const SegmentContainer & *segments*) const

output intersections to QString

1.10 JSON Class Reference

```
#include <json.h>
```

Collaboration diagram for JSON:



Static Public Member Functions

- `template<typename OutputIterator >`
`static bool read_points (QFile &file, OutputIterator output)`
- `template<typename Container >`
`static bool write_points (const std::string &file_name, Container points)`

helper functions

- `static JSONValue fromNumber (const Number &value)`
- `static JSONArray fromPoint (const Point &point)`
- `static bool isArray (const JSONValue &value)`
- `static bool isInt (const JSONValue &value)`
- `static bool isNumber (const JSONValue &value)`
- `static bool isReal (const JSONValue &value)`
- `static const JSONArray & toArray (const JSONValue &value)`
- `static int toInt (const JSONValue &value)`
- `static Number toNumber (const JSONValue &value)`
- `static Point toPoint (const JSONValue &value)`
- `static double toReal (const JSONValue &value)`
- `static const std::string & toString (const JSONValue &value)`

1.10.1 Member Function Documentation

1.10.1.1 `JSON::JSONValue JSON::fromNumber (const Number & value) [static]`

1.10.1.2 `JSON::JSONArray JSON::fromPoint (const Point & point) [static]`

1.10.1.3 `bool JSON::isArray (const JSONValue & value) [static]`

1.10.1.4 `bool JSON::isInt (const JSONValue & value) [static]`

1.10.1.5 `bool JSON::isNumber (const JSONValue & value) [static]`

1.10.1.6 `bool JSON::isReal (const JSONValue & value) [static]`

1.10.1.7 `template<typename OutputIterator > static bool JSON::read_points (QFile & file, OutputIterator output) [inline], [static]`

1.10.1.8 `const JSON::JSONArray & JSON::toArray (const JSONValue & value) [static]`

1.10.1.9 `int JSON::toInt (const JSONValue & value) [static]`

1.10.1.10 `Number JSON::toNumber (const JSONValue & value) [static]`

1.10.1.11 `Point JSON::toPoint (const JSONValue & value) [static]`

1.10.1.12 `double JSON::toReal (const JSONValue & value) [static]`


1.10.1.13 `const std::string & JSON::toString (const JSONValue & value) [static]`

1.10.1.14 `template<typename Container > static bool JSON::write_points (const std::string & file_name, Container points) [inline], [static]`

1.11 Kernel Struct Reference

```
#include <kernel.h>
```

Collaboration diagram for Kernel:




1.11.1 Detailed Description

customized kernel

1.12 Kernel_base< K_, Base_Kernel_ > Class Template Reference

```
#include <kernel.h>
```

Collaboration diagram for Kernel_base< K_, Base_Kernel_ >:



Classes

- struct Base

1.12.1 Detailed Description


```
template<typename K_, typename Base_Kernel_>class Kernel_base< K_, Base_Kernel_ >
```

kernel base with customized PointC2 and SegmentC2

1.13 Logger Class Reference

```
#include <logger.h>
```

Collaboration diagram for Logger:



Public Member Functions

- `Logger ()`
- `void debug (const QString &message) const`
- `void info (const QString &message) const`
- `void warn (const QString &message) const`
- `void error (const QString &message) const`
- `void print (const QString &message) const`
- `void stats (const Stats &stats) const`
- `void time (const QString &identifier, int milliseconds) const`

1.13.1 Constructor & Destructor Documentation

1.13.1.1 `Logger::Logger ()`

1.13.2 Member Function Documentation

1.13.2.1 `void Logger::debug (const QString & message) const`

1.13.2.2 `void Logger::error (const QString & message) const`

1.13.2.3 `void Logger::info (const QString & message) const`

1.13.2.4 `void Logger::print (const QString & message) const`

1.13.2.5 `void Logger::stats (const Stats & stats) const`


1.13.2.6 `void Logger::time (const QString & identifier, int milliseconds) const`

1.13.2.7 `void Logger::warn (const QString & message) const`

1.14 Messages Class Reference

```
#include <logger.h>
```

Collaboration diagram for Messages:



Public Member Functions

- QString operator() (const char *text)

1.14.1 Detailed Description

helper class for string literals


1.14.2 Member Function Documentation

1.14.2.1 QString Messages::operator() (const char * *text*) [inline]


1.15 OptimizationSATSolver Class Reference

```
#include <sat_solver.h>
```

Inheritance diagram for OptimizationSATSolver:



Collaboration diagram for OptimizationSATSolver:



Public Member Functions

- `void solve_optimization_problem (const QSettings &settings, const QString &file_prefix, const SATProblem &problem, SATSolution &solution)`

Protected Member Functions

- `virtual void add_short_segment_restriction (const SATProblem *problem, const SegmentIndex &index)=0`
- `virtual void init_optimization_problem (const SATProblem *problem)=0`

1.15.1 Detailed Description

interface for optimization SAT solvers

1.15.2 Member Function Documentation

- 1.15.2.1 `virtual void OptimizationSATSolver::add_short_segment_restriction (const SATProblem * problem, const SegmentIndex & index)` [protected],[pure virtual]

Implemented in CplexSATSolver.

1.15.2.2 `virtual void OptimizationSATSolver::init_optimization_problem (const SATProblem * problem)`
`[protected], [pure virtual]`


Implemented in CplexSATSolver.

1.15.2.3 `void OptimizationSATSolver::solve_optimization_problem (const QSettings & settings, const QString & file_prefix,
const SATProblem & problem, SATSolution & solution)`

1.16 PointC2< Kernel_ > Class Template Reference

`#include <point.h>`

Collaboration diagram for PointC2< Kernel_ >:



Public Member Functions

- `PointC2 ()`
- `PointC2 (const CGAL::Origin &origin)`
- `PointC2 (const FT &x, const FT &y)`
- `PointC2 (const FT &hx, const FT &hy, const FT &hw)`
- `void draw (QPainter &painter) const`
- `QString to_string () const`

Private Types

- `typedef Kernel_::FT FT`
- `typedef CGAL::PointC2< Kernel_ > PointBase`

1.16.1 Detailed Description

`template<class Kernel_>class PointC2< Kernel_ >`

customized point type

1.16.2 Member Typedef Documentation

1.16.2.1 `template<class Kernel_> typedef Kernel_::FT PointC2< Kernel_>::FT` [private]

1.16.2.2 `template<class Kernel_> typedef CGAL::PointC2<Kernel_> PointC2< Kernel_>::PointBase` [private]

1.16.3 Constructor & Destructor Documentation

1.16.3.1 `template<class Kernel_> PointC2< Kernel_>::PointC2 ()` [inline]

empty constructor

1.16.3.2 `template<class Kernel_> PointC2< Kernel_>::PointC2 (const CGAL::Origin & origin)` [inline]

origin constructor

1.16.3.3 `template<class Kernel_> PointC2< Kernel_>::PointC2 (const FT & x, const FT & y)` [inline]

Cartesian constructor

1.16.3.4 `template<class Kernel_> PointC2< Kernel_>::PointC2 (const FT & hx, const FT & hy, const FT & hw)`
[inline]

homogeneous constructor

1.16.4 Member Function Documentation

1.16.4.1 `template<class Kernel_> void PointC2< Kernel_>::draw (QPainter & painter) const`

draw segment using given QPainter


1.16.4.2 `template<class Kernel_> QString PointC2< Kernel_>::to_string () const`

dump point to QString

1.17 PointGenerator Class Reference

`#include <point_generator.h>`

Collaboration diagram for PointGenerator:



Static Public Member Functions

- static void run (const QSettings &settings)

Static Public Attributes

- static const double BASE_RANGE = 100.0

Static Private Member Functions

- template<typename GeneratorType >
static void generate (const QString &base_name, std::size_t num_points, std::size_t num_iterations)

1.17.1 Member Function Documentation

1.17.1.1 `template<typename GeneratorType > static void PointGenerator::generate (const QString & base_name, std::size_t num_points, std::size_t num_iterations) [inline],[static],[private]`

1.17.1.2 `static void PointGenerator::run (const QSettings & settings) [inline],[static]`


1.17.2 Member Data Documentation

1.17.2.1 `const double PointGenerator::BASE_RANGE = 100.0 [static]`

1.18 PointSet Class Reference

```
#include <point_set.h>
```

Collaboration diagram for PointSet:

**Public Member Functions**

- PointSet ()
- PointSet (QFile &input_file)
- bool contains (const Point &point) const
- void draw (QPainter &painter) const

1.18.1 Detailed Description

(sorted) set of points

1.18.2 Constructor & Destructor Documentation

1.18.2.1 PointSet::PointSet ()

empty set

1.18.2.2 PointSet::PointSet (QFile & *input_file*)

read points from file

1.18.3 Member Function Documentation

1.18.3.1 bool PointSet::contains (const Point & *point*) const [inline]

shortcut for STL count()

Returns

true if point is in set


1.18.3.2 void PointSet::draw (QPainter & *painter*) const

output point set using QPainter

1.19 SATProblem Class Reference

```
#include <sat_problem.h>
```

Collaboration diagram for SATProblem:



Public Member Functions

- `SATProblem (const IntersectionGraph &igrph, const SegmentContainer &segments)`
- `const Intersections & intersections (const SegmentIndex &index) const`
- `const SegmentIndex & lower_bound () const`
- `const SegmentContainer & segments () const`
- `void set_short_segment_range (const SegmentIndex &lower_bound, const SegmentIndex &upper_bound)`
- `SegmentIndex size () const`
- `const SegmentIndex & upper_bound () const`

Protected Attributes

- `const IntersectionGraph & igrph_`
- `const SegmentContainer & segments_`
- `SegmentIndex lower_bound_`
- `SegmentIndex upper_bound_`

1.19.1 Constructor & Destructor Documentation

1.19.1.1 SATProblem::SATProblem (const IntersectionGraph & igrph, const SegmentContainer & segments)

default constructor

1.19.2 Member Function Documentation

1.19.2.1 `const Intersections& SATProblem::intersections (const SegmentIndex & index) const` `[inline]`

1.19.2.2 `const SegmentIndex& SATProblem::lower_bound () const` `[inline]`

1.19.2.3 `const SegmentContainer& SATProblem::segments () const` `[inline]`

1.19.2.4 `void SATProblem::set_short_segment_range (const SegmentIndex & lower_bound, const SegmentIndex & upper_bound)`

set range of segments to consider

1.19.2.5 `SegmentIndex SATProblem::size () const` `[inline]`

1.19.2.6 `const SegmentIndex& SATProblem::upper_bound () const` `[inline]`

1.19.3 Member Data Documentation

1.19.3.1 `const IntersectionGraph& SATProblem::igraph_` `[protected]`

1.19.3.2 `SegmentIndex SATProblem::lower_bound_` `[protected]`


1.19.3.3 `const SegmentContainer& SATProblem::segments_` `[protected]`

1.19.3.4 `SegmentIndex SATProblem::upper_bound_` `[protected]`

1.20 SATSolution Class Reference

`#include <sat_solution.h>`

Collaboration diagram for SATSolution:



Public Member Functions

- `SATSolution ()`
- `void draw_short_segments (QPainter &painter, const SegmentIndex &num_short_segments, const SegmentContainer &segments) const`
- `void draw_separators (QPainter &painter, const SegmentIndex &num_short_segments, const SegmentContainer &segments) const`
- `const SegmentIndex & shortest_segment () const`

1.20.1 Constructor & Destructor Documentation

1.20.1.1 SATSolution::SATSolution () [inline]

1.20.2 Member Function Documentation

1.20.2.1 void SATSolution::draw_separators (QPainter & *painter*, const SegmentIndex & *num_short_segments*, const SegmentContainer & *segments*) const


1.20.2.2 void SATSolution::draw_short_segments (QPainter & *painter*, const SegmentIndex & *num_short_segments*, const SegmentContainer & *segments*) const

1.20.2.3 const SegmentIndex & SATSolution::shortest_segment () const


1.21 SATSolver Class Reference

```
#include <sat_solver.h>
```


Inheritance diagram for SATSolver:



Collaboration diagram for SATSolver:



Protected Member Functions

- virtual void add_forbidden_segment (const SATProblem *problem, const SegmentIndex &index)=0
- virtual void add_intersection_restrictions (const SATProblem *problem, const SegmentIndex &index, const Intersections &igroup)=0
- virtual void add_separation_restriction (const SATProblem *problem, const SegmentIndex &index, const std::vector< SegmentIndex > &separators)=0
- virtual void dump_problem (const QString &file_prefix, const SATProblem *problem)=0
- void prepare_problem (const SATProblem &problem)
- virtual void solve_problem (const SATProblem *problem, SATSolution &solution)=0

1.21.1 Detailed Description

interface for SAT solvers

1.21.2 Member Function Documentation

1.21.2.1 virtual void SATSolver::add_forbidden_segment (const SATProblem * *problem*, const SegmentIndex & *index*)
[protected],[pure virtual]

Implemented in CplexSATSolver.

1.21.2.2 virtual void SATSolver::add_intersection_restrictions (const SATProblem * *problem*, const SegmentIndex & *index*, const Intersections & *igroup*) [protected],[pure virtual]

Implemented in CplexSATSolver.

1.21.2.3 virtual void SATSolver::add_separation_restriction (const SATProblem * *problem*, const SegmentIndex & *index*, const std::vector< SegmentIndex > & *separators*) [protected],[pure virtual]

Implemented in CplexSATSolver.

1.21.2.4 virtual void SATSolver::dump_problem (const QString & *file_prefix*, const SATProblem * *problem*)
[protected],[pure virtual]

Implemented in CplexSATSolver.

1.21.2.5 void SATSolver::prepare_problem (const SATProblem & *problem*) [protected]


1.21.2.6 virtual void SATSolver::solve_problem (const SATProblem * *problem*, SATSolution & *solution*)
[protected],[pure virtual]

Implemented in CplexSATSolver.

1.22 SegmentC2< Kernel_ > Class Template Reference

```
#include <segment.h>
```

Collaboration diagram for SegmentC2< Kernel_ >:



Public Member Functions

- SegmentC2 ()
- SegmentC2 (const Point_2 &source, const Point_2 &target)

- SegmentC2 (const SegmentC2 &other)
- SegmentC2 & operator= (const SegmentC2 &other)
- SegmentData & data ()
- const SegmentData & data () const
- void draw (QPainter &painter) const
- QString to_string () const

Private Attributes

- SegmentData data_

1.22.1 Detailed Description

template<class Kernel_>class SegmentC2< Kernel_ >

customized segment type

1.22.2 Constructor & Destructor Documentation

1.22.2.1 template<class Kernel_> SegmentC2< Kernel_ >::SegmentC2 () [inline]

empty constructor

1.22.2.2 template<class Kernel_> SegmentC2< Kernel_ >::SegmentC2 (const Point_2 & source, const Point_2 & target) [inline]

base constructor

1.22.2.3 template<class Kernel_> SegmentC2< Kernel_ >::SegmentC2 (const SegmentC2< Kernel_ > & other) [inline]

copy constructor

1.22.3 Member Function Documentation

1.22.3.1 template<class Kernel_> SegmentData& SegmentC2< Kernel_ >::data () [inline]

getter for attached data

1.22.3.2 template<class Kernel_> const SegmentData& SegmentC2< Kernel_ >::data () const [inline]

constant getter for attached data

1.22.3.3 template<class Kernel_> void SegmentC2< Kernel_ >::draw (QPainter & painter) const

draw segment using given QPainter

1.22.3.4 template<class Kernel_> SegmentC2& SegmentC2< Kernel_ >::operator= (const SegmentC2< Kernel_ > & other) [inline]

assignment operator

1.22.3.5 template<class Kernel_> QString SegmentC2< Kernel_ >::to_string () const

dump segment to QString


1.22.4 Member Data Documentation

1.22.4.1 `template<class Kernel_> SegmentData SegmentC2< Kernel_>::data_ [private]`

1.23 SegmentContainer Class Reference

```
#include <segment_container.h>
```

Collaboration diagram for SegmentContainer:



Public Member Functions

- `SegmentContainer (const PointSet &points)`
- `void draw (QPainter &painter) const`
- `void draw_range (QPainter &painter, const SegmentIndex &lower_bound, const SegmentIndex &upper_bound) const`

access i-th shortest segment

these operators assume that the segment set is not changed after construction

- `Segment & operator[] (const SegmentIndex &index)`
- `const Segment & operator[] (const SegmentIndex &index) const`

1.23.1 Detailed Description

container of segments sorted by length

1.23.2 Constructor & Destructor Documentation

1.23.2.1 `SegmentContainer::SegmentContainer (const PointSet & points)`

construct segments for all point pairs from set

1.23.3 Member Function Documentation

1.23.3.1 void SegmentContainer::draw (QPainter & *painter*) const

draws all segments

1.23.3.2 void SegmentContainer::draw_range (QPainter & *painter*, const SegmentIndex & *lower_bound*, const SegmentIndex & *upper_bound*) const


draw a range of segments

1.23.3.3 Segment & SegmentContainer::operator[] (const SegmentIndex & *index*)1.23.3.4 const Segment & SegmentContainer::operator[] (const SegmentIndex & *index*) const

1.24 SegmentData Struct Reference

```
#include <segment.h>
```

Collaboration diagram for SegmentData:



Public Attributes

- SegmentIndex index
- bool is_outer

1.24.1 Detailed Description

data attached to a segment

1.24.2 Member Data Documentation

1.24.2.1 SegmentIndex SegmentData::index


1.24.2.2 bool SegmentData::is_outer

true if the segment includes another

1.25 SegmentIndexOrder Struct Reference

```
#include <orders.h>
```

Collaboration diagram for SegmentIndexOrder:



Public Member Functions

- CGAL::Comparison_result operator() (const Segment &s, const Segment &t) const

1.25.1 Detailed Description

CGAL order for Segment by index


1.25.2 Member Function Documentation

1.25.2.1 CGAL::Comparison_result SegmentIndexOrder::operator() (const Segment & *s*, const Segment & *t*) const

1.26 SegmentLengthOrder Struct Reference

```
#include <orders.h>
```

Collaboration diagram for SegmentLengthOrder:



Public Member Functions

- `CGAL::Comparison_result operator() (const Segment &s, const Segment &t) const`

1.26.1 Detailed Description

CGAL order for Segment by length


1.26.2 Member Function Documentation

1.26.2.1 `CGAL::Comparison_result SegmentLengthOrder::operator() (const Segment & s, const Segment & t) const`

1.27 Stats Class Reference

```
#include <stats.h>
```

Collaboration diagram for Stats:



Public Member Functions

- `Stats ()`
- `void add_lower_bound (const SegmentIndex &bound)`

- void add_upper_bound (const SegmentIndex &bound)
- SegmentIndex gap () const
- const SegmentIndex & lower_bound () const
- const SegmentIndex & upper_bound () const
- QString to_string () const

Public Attributes

- size_t iteration
- quint64 sat_solving_time

Private Attributes

- SegmentIndex lower_bound_
- SegmentIndex upper_bound_

1.27.1 Constructor & Destructor Documentation

1.27.1.1 Stats::Stats () [inline]

1.27.2 Member Function Documentation

1.27.2.1 void Stats::add_lower_bound (const SegmentIndex & bound) [inline]

1.27.2.2 void Stats::add_upper_bound (const SegmentIndex & bound) [inline]

1.27.2.3 SegmentIndex Stats::gap () const [inline]

1.27.2.4 const SegmentIndex& Stats::lower_bound () const [inline]

1.27.2.5 QString Stats::to_string () const [inline]

1.27.2.6 const SegmentIndex& Stats::upper_bound () const [inline]

1.27.3 Member Data Documentation

1.27.3.1 size_t Stats::iteration

1.27.3.2 SegmentIndex Stats::lower_bound_ [private]


1.27.3.3 quint64 Stats::sat_solving_time

1.27.3.4 SegmentIndex Stats::upper_bound_ [private]

1.28 SVGPainter Class Reference

```
#include <svgPainter.h>
```

Collaboration diagram for SVGPainter:



Public Member Functions

- SVGPainter (const QString &file_prefix, const QString &file_name, const BoundingBox &bbox)
- void setPenColor (const QColor &color)
- void setPenWidth (int width)
- ~SVGPainter ()

Private Attributes

- QSvgGenerator generator_
- QPen pen_

Static Private Attributes

- static const int SVG_PADDING = 10
- static const double SVG_SCALE = 4.0

1.28.1 Constructor & Destructor Documentation

1.28.1.1 SVGPainter::SVGPainter (const QString &file_prefix, const QString &file_name, const BoundingBox &bbox)

1.28.1.2 SVGPainter::~~SVGPainter ()

1.28.2 Member Function Documentation

1.28.2.1 void SVGPainter::setPenColor (const QColor & *color*)

1.28.2.2 void SVGPainter::setPenWidth (int *width*)

1.28.3 Member Data Documentation

1.28.3.1 QSvgGenerator SVGPainter::generator_ [private]

1.28.3.2 QPen SVGPainter::pen_ [private]

1.28.3.3 const int SVGPainter::SVG_PADDING = 10 [static], [private]

padding for SVG images


1.28.3.4 const double SVGPainter::SVG_SCALE = 4.0 [static], [private]

scale for SVG images

1.29 Triangulation Class Reference

```
#include <triangulation.h>
```

Collaboration diagram for Triangulation:



Public Member Functions

- Triangulation (const PointSet &points)
- void draw (QPainter &painter) const
- const SegmentIndex & shortest_segment (const SegmentContainer &segments) const

1.29.1 Constructor & Destructor Documentation

1.29.1.1 Triangulation::Triangulation (const PointSet & *points*)

default constructor

1.29.2 Member Function Documentation

1.29.2.1 void Triangulation::draw (QPainter & *painter*) const

draw triangulation segments using given QPainter

1.29.2.2 `const SegmentIndex & Triangulation::shortest_segment (const SegmentContainer & segments) const`

B. Result Data

replace

Table B.1.: Composition of execution times

replace

Table B.2.

replace

Table B.3.

a

Glossary

Glossary

e_{nose}	shortest non-separable edge
e_{sep}	separating edge
s_{\times}	crossing segment
CDS	Covering by Disjoint Segments
IP	Integer Program
MELT	MaxMin Edge Length Index Triangulation
MMLT	MaxMin Length Triangulation
NOCS	Non-Conflicting Separators

Properties

crossing	see definition 3.11
non-crossing	see definition 3.11
non-overlapping	see definition 3.12
overlapping	see definition 3.12
well-covered	see definition 2.14

Sets

E_{flip}	set of edge flips (see definition 3.26)
E_{sep}	set of separators (see definition 4.14)
E_{short}	set of short edges (see definition 4.13)

G_{conf}	conflict graph (see definition 3.2)
G_{cross}	intersection graph (see definition 3.18)
G_{flip}	flip graph (see definition 3.28)
S_{opt}	an optimal set of segments
T_{opt}	an optimal triangulation
V_{IS}	independent set (see definition 2.16)
V_{cover}	vertex cover (see definition 2.9)

Bibliography

- [1] Selim G. Akl and Godfried T. Toussaint. „A Fast Convex Hull Algorithm“. In: *Information Processing Letters* 7.5 (1978), pp. 219–222.
- [2] Mark de Berg et al. *Computational Geometry: Algorithms and Applications*. Third. Springer-Verlag, 2008, p. 386. URL: <http://www.cs.uu.nl/geobook/>.
- [3] Marshall W. Bern et al. „Edge Insertion for Optimal Triangulations.“ In: *Discrete & Computational Geometry* 10 (1993), pp. 47–65. DOI: 10.1007/BF02573962.
- [4] Prosenjit Bose and Ferran Hurtado. „Flips in planar graphs“. In: *Computational Geometry: Theory and Applications* 42 (1 2009), pp. 60–80. DOI: 10.1016/j.comgeo.2008.04.001.
- [5] *CGAL - Computational Geometry Algorithms Library*. CGAL Open Source Project. 2013. URL: <https://www.cgal.org/> (visited on 2013-06-19).
- [6] L. P. Chew. „Constrained Delaunay triangulations“. In: *Proceedings of the third annual symposium on Computational geometry*. SCG '87. ACM, 1987, pp. 215–222. ISBN: 0-89791-231-4. DOI: 10.1145/41958.41981. URL: <http://doi.acm.org/10.1145/41958.41981>.
- [7] Christiane Schmidt. „Maxmin Length Triangulation in Polygons“. In: *Proceedings of the 28th European Workshop on Computational Geometry*. 2012, pp. 121–124.
- [8] *Concert Technology for C++ users*. Version 12.2. IBM Corporation. URL: http://pic.dhe.ibm.com/infocenter/cosinfoc/v12r2/topic/ilog.odms.cplex.help/Content/Optimization/Documentation/CPLEX/_pubskel/CPLEX197.html (visited on 2013-06-25).
- [9] *Constrained_triangulation_2<Traits,Tds,Itag>*. Version 4.2. CGAL Open Source Project. 2013-04-09. URL: https://www.cgal.org/Manual/4.2/doc_html/cgal_manual/Triangulation_2_ref/Class_Constrained_triangulation_2.html (visited on 2013-06-19).
- [10] *convex_hull_2*. Version 4.2. CGAL Open Source Project. 2013-04-09. URL: https://www.cgal.org/Manual/4.2/doc_html/cgal_manual/Convex_hull_2_ref/Function_convex_hull_2.html (visited on 2013-06-19).
- [11] Stephen A. Cook. „The complexity of theorem-proving procedures“. In: *Proceedings of the third annual ACM symposium on Theory of computing*. STOC '71. ACM, 1971, pp. 151–158. DOI: 10.1145/800157.805047.

- [12] *Creator_uniform_2*<Arg, Result>. Version 4.2. CGAL Open Source Project. 2013-04-09. URL: http://www.cgal.org/Manual/4.2/doc_html/cgal_manual/STL_Extension_ref/FunctionObjectClass_Creator_uniform_2.html (visited on 2013-07-22).
- [13] Beman Dawes, David Abrahams, and Rene Rivera. *Boost C++ Libraries*. URL: <https://www.boost.org/> (visited on 2013-07-21).
- [14] E. Demaine et al. *Problem 28: Flip Graph Connectivity in 3D*. 2008-12-22. URL: <http://cs.smith.edu/~orourke/TOPP/P28.html> (visited on 2013-07-17).
- [15] *do_intersect*. Version 4.2. CGAL Open Source Project. 2013-04-09. URL: https://www.cgal.org/Manual/4.2/doc_html/cgal_manual/Kernel_23_ref/Function_do_intersect.html (visited on 2013-07-21).
- [16] *Doxygen*. 2013-05-20. URL: <http://doxygen.org/> (visited on 2013-07-25).
- [17] Herbert Edelsbrunner and Tiow Seng Tan. „A Quadratic Time Algorithm for the MinMax Length Triangulation“. In: *SIAM J. Comput* 22 (1991), pp. 414–423.
- [18] *Exact_predicates_inexact_constructions_kernel*. Version 4.2. CGAL Open Source Project. 2013-04-09. URL: https://www.cgal.org/Manual/4.2/doc_html/cgal_manual/Kernel_23_ref/Class_Exact_predicates_inexact_constructions_kernel.html (visited on 2013-06-19).
- [19] Sándor P. Fekete. „The Complexity of MaxMin Length Triangulation“. In: *CoRR* abs/1208.0202 (2012).
- [20] Barend Gehrels et al. *Geometry*. 2013-06-25. URL: https://www.boost.org/doc/libs/1_54_0/libs/graph/ (visited on 2013-07-21).
- [21] Peter Greenberg. „Piecewise $SL_2\mathbb{Z}$ Geometry“. In: *Transactions of the American Mathematical Society* 335.2 (1993), pp. 705–720. DOI: 10.2307/215440.
- [22] Joel de Guzman and Hartmut Kaiser. *Spirit*. Version 2.5.2. 2013-06-25. URL: https://www.boost.org/doc/libs/1_54_0/libs/spirit/ (visited on 2013-07-21).
- [23] David Hilbert. *Grundlagen der Geometrie*. 2nd ed. B. G. Teubner, 1903, p. 39.
- [24] Shiyang Hu. „A linear time algorithm for max-min length triangulation of a convex polygon“. In: *Inf. Process. Lett.* 101.5 (2007-03), pp. 203–208. ISSN: 0020-0190. DOI: 10.1016/j.ipl.2006.09.014. URL: <http://dx.doi.org/10.1016/j.ipl.2006.09.014>.
- [25] *IBM CPLEX Optimizer - United States*. Version 17. IBM Corporation. 2013-05-09. URL: <https://www.ibm.com/software/commerce/optimization/cplex-optimizer/> (visited on 2013-06-25).
- [26] *intersection*. Version 4.2. CGAL Open Source Project. 2013-04-09. URL: https://www.cgal.org/Manual/4.2/doc_html/cgal_manual/Kernel_23_ref/Function_intersection.html (visited on 2013-07-21).
- [27] *JSON*. 2013-07-02. URL: <http://www.json.org/> (visited on 2013-07-21).

- [28] Richard M. Karp. „Reducibility Among Combinatorial Problems“. In: *Complexity of Computer Computations*. Ed. by Raymond E. Miller and James W. Thatcher. The IBM Research Symposia Series. Plenum Press, New York, 1972, p. 94. ISBN: 0-306-30707-3.
- [29] Bernhard Korte and Jens Vygen. *Combinatorial Optimization: Theory and Algorithms*. 5th ed. Springer Publishing Company, Incorporated, 2012, p. 414. ISBN: 9783642244872.
- [30] David Lichtenstein. „Planar Formulae and Their Uses“. In: *SIAM Journal on Computing* 11.2 (1982), pp. 329–343. DOI: 10.1137/0211025.
- [31] Errol Lynn Lloyd. „On triangulations of a set of points in the plane“. In: *18th Annual Symposium on Foundations of Computer Science*. 1977, pp. 228–240. DOI: 10.1109/SFCS.1977.21. URL: <http://ieeexplore.ieee.org/xpl/articleDetails.jsp?arnumber=4567947>.
- [32] Sue Wheeler Lloyd. *Greg Likes Triangles for Lunch*. Authorhouse, 2011. ISBN: 978-1452098838.
- [33] David Lonie. *QJson iterators broken – missing operator->*. 2013-02-08. URL: <https://bugreports.qt-project.org/browse/QTBUG-29573> (visited on 2013-07-21).
- [34] László Lovász et al. „Convex quadrilaterals and k-sets“. In: *Contemporary Mathematics Series, 342, AMS 2004*. 2004, pp. 139–148.
- [35] H. Mittelmann. *Mixed Integer Linear Programming Benchmark (MILPLIB2010)*. 2013-05-25. URL: <http://plato.asu.edu/ftp/milpc.html> (visited on 2013-06-25).
- [36] Wolfgang Mulzer and Günter Rote. „Minimum-weight triangulation is NP-hard“. In: *CoRR* abs/cs/0601002 (2006).
- [37] Christos H. Papadimitriou and Kenneth Steiglitz. *Combinatorial Optimization: Algorithms and Complexity*. Dover Publications Inc., 2000. ISBN: 978-0486402581.
- [38] Michael D. Plummer. „Some covering concepts in graphs“. In: *Journal of Combinatorial Theory* 8.1 (1970), pp. 91–98. ISSN: 0021-9800. DOI: 10.1016/S0021-9800(70)80011-4. URL: <http://www.sciencedirect.com/science/article/pii/S0021980070800114>.
- [39] Vladimir Prus. *Boost.Program_options*. 2007-11-25. URL: https://www.boost.org/doc/libs/1_54_0/libs/program_options/ (visited on 2013-07-21).
- [40] *QPainter Class*. Version 5.1. URL: <https://qt-project.org/doc/qt-5.1/qtgui/qpainter.html> (visited on 2013-07-22).
- [41] *QString Class*. Version 5.1. URL: <https://qt-project.org/doc/qt-5.1/qtcore/qstring.html> (visited on 2013-07-22).
- [42] *Qt Project*. URL: <https://qt-project.org/> (visited on 2013-07-21).

- [43] *Random_points_in_square_2*<Point_2, Creator>. Version 4.2. CGAL Open Source Project. 2013-04-09. URL: http://www.cgal.org/Manual/4.2/doc_html/cgal_manual/Generator_ref/Class_Random_points_in_square_2.html (visited on 2013-07-22).
- [44] Jeremy Siek, Lie-Quan Lee, and Andrew Lumsdaine. *The Boost Graph Library*. 2012-09-30. URL: https://www.boost.org/doc/libs/1_54_0/libs/graph/ (visited on 2013-07-21).
- [45] Tzvetalin Simeonov Vassilev. „Optimal Area Triangulation“. PhD thesis. University of Saskatchewan, Saskatoon, 2005. URL: <http://ecommons.usask.ca/bitstream/handle/10388/etd-08232005-111957/thesisFF.pdf>.
- [46] Klaus Wagner. „Bemerkungen zum Vierfarbenproblem“. In: *Jahresbericht der Deutschen Mathematiker-Vereinigung* 46 (1936), pp. 26–32.
- [47] John W. Wilkinson. *JSON Spirit: A C++ JSON Parser/Generator Implemented with Boost Spirit*. 2013-05-23. URL: <http://www.codeproject.com/Articles/20027/JSON-Spirit-A-C-JSON-Parser-Generator-Implemented> (visited on 2013-07-21).

Liste der noch zu erledigenden Punkte

1 pages	1
cite	1
cite	1
4 pages: 	13
glue text	13
glue text	13
glue text	13
glue text	14
glue text	14
glue text	14
glue text	15
glue text	15
glue text	15
do we need this definition at all?	16
glue text	16
glue text	16
glue text	16
glue text	17
remove comment	17
glue text	18
glue text	18
glue text	18
glue text	19
glue text	19
glue text	19
glue text	19
glue text	20
glue text	20
glue text	20
glue text	20
glue text	21
glue text	21
glue text	21
glue text	22
glue text	22
glue text	22

notes	23
2 pages	25
glue text	25
glue text	25
glue text [19]	25
glue text	26
glue text	26
proof	26
notes	27
glue text	27
glue text	27
glue text	28
glue text	28
glue text	28
glue text	29
glue text	29
glue text	29
notes	30
glue text	30
glue text	30
glue text	30
glue text	31
glue text	31
glue text	31
glue text	32
proof	33
glue text	33
glue text	33
notes	34
glue text	34
glue text	34
proof	35
proof	35
glue text	35
update notation in algorithm	35
use subroutines?	35
3 pages	41
2 pages	49
be conclusive	49
notes	49
replace	94
replace	94
replace	94