

H12-211 HCNA-HNTD Mock Exam

1.True or False

One of the significant features of the PPP protocol is the authentication function. With this function, the two ends of a link can negotiate with each other to use which authentication protocol and then perform authentication. A PPP connection is established only when the authentication is successful.

☐☐

2.True or False

Root bridges provide root ports and designated ports.

☐☐

3.True or False

A static route can be either configured manually by a network administrator or generated automatically.

☐☐

4.True or False

A Trunk port always sends tagged frames to the peer equipment.

☐☐

Correct answer :

×

5.True or False

The PPP protocol provides a standard method of transmitting datagrams of different protocols on a point-to-point link. It is a point-to-point communication protocol widely used at the present time.

☐☐

6.True or False

Each router forwards only the packets received by the local station through the optimal path. The packet is forwarded by different routers on the path in a relay mode.

☐☐

7.True or False

In OSPF protocol, most of the packets are sent by using reserved multicast address and this can reduce the impact on non-OSPF speaking devices.

☐☐

8.True or False

RTA connects with RTB through interface Serial0. The configuration on RTA is as follow:

```
[RTA]aaa
[RTA-aaa]local-user huawei password cipher hello
[RTA-aaa]local-user huawei service-type ppp
[RTA]interface Serial 0
[RTA-Serial0]link-protocol ppp
[RTA-Serial0]ppp authentication-mode chap
[RTA-Serial0]ip address 10.1.1.1 30
```

The configuration on RTB is as follow:

```
[RTB]interface Serial 0
[RTB-Serial0]link-protocol ppp
[RTB-Serial0]ppp chap user huawei
[RTB-Serial0]ppp chap password cipher hello
[RTB-Serial0]ip address 10.1.1.2 30
```

With the configuration above, RTA and RTB are able to communicate with each other.

☐☐

9.True or False

After a fault occurs in a network, a static route can be rectified automatically and the network administrator does not need to reconfigure it.

☐☐

10.True or False

After receiving a data frame from any port, a hub forwards it to any other port.

☐☐

11.True or False

The ICMP protocol (RFC792) is not applied to Application Layer but Network Layer.

☐☐

12.True or False

On a port running frame relay, an MAP table corresponds to a logical port. Different logical ports have different MAP tables.

☐☐

13.True or False

Frame relay point-to-multipoint sub-port can connect “multiple” remote nodes together through a PVC.

☐☐

14.True or False

The 10.1.1.2 IP address in the returned result of the frame relay command represents the IP address of the local device.

```
[RTA]dis fr map-info
```

```
Map Statistics for interface Serial0 (DTE)
```

```
DLCI = 100, IP INARP 10.1.1.2, Serial0
```

```
create time = 2007/06/04 17:34:59. status = ACTIVE
```

encapsulation = ietf, vlink = 20, broadcast

☐☐

15.True or False

Routing Information Protocol (RIP) is available in the RIPv1, RIPv2, and RIPv3 versions.

☐☐

16.True or False

When you configure Frame Relay on Quidway routers, you can configure Inverse ARP instead of static address mapping because the function of Inverse ARP is to provide dynamic address mapping.

☐☐

17.True or False

In broadcast network of OSPF protocol, any two DR Others will neither exchange routing information nor send Hello packet to each other due to the existence of DR.

☐☐

18.True or False

If the optimal path to the destination IP address is unavailable after a change occurs in a network topology, the dynamic routing protocol can make adaptation to this change and determine another optimal path to the destination IP address.

☐☐

19.True or False

RTA connects with RTB through interface Serial0. The configuration on RTA is as follow:

```
[RTA]aaa
```

```
[RTA-aaa]local-user huawei password simple quidway
```

```
[RTA-aaa]local-user huawei service-type ppp
```

```
[RTA]interface Serial 0
```

```
[RTA-Serial0]link-protocol ppp
```

```
[RTA-Serial0]ppp authentication-mode pap
```

```
[RTA-Serial0]ip address 10.1.1.1 30
```

The configuration on RTB is as follow:

```
[RTB]interface Serial 0
```

```
[RTB-Serial0]link-protocol ppp
```

```
[RTB-Serial0]ppp pap local-user huawei password simple hello
```

```
[RTB-Serial0]ip address 10.1.1.2 30
```

With the configuration above, RTA and RTB are able to communicate with each other.

☐☐

20.True or False

The operation deleting the configuration files saved in the storage devices will become effective after rebooting the router.

☐☐

21.Single

According to OSI reference model, which layer defines mechanical, electrical, functional and procedural functions to realize data transmission?

☐

a.Transport layer

☐

b.Data link layer

☐

c.Network layer

☐

d.Physical layer

22.Single

Assume an internal network has only one route to the external networks, which of the following configurations is better?

- ☐ a.Default route
- ☐ b.Host route
- ☐ c.Dynamic route
- ☐ d.Direct route

23.Single

Which of the following is reserved for loopback address?

- ☐ a.127.0.0.0
- ☐ b.130.0.0.0
- ☐ c.164.0.0.0
- ☐ d.200.0.0.0

24.Single

Direct interconnection of traffic with different VLANs is not allowed. Such traffic must be transmitted based on ().

- ☐ a.Port isolation
- ☐ b.MAC addresses
- ☐ c.VLAN routing
- ☐ d.VLAN switching

25.Single

Which of the following multicast address represents all routers of the subnet?

- ☐ a.224.0.0.1

☐ b.224.0.0.2

☐ c.224.0.0.3

☐ d.224.0.0.9

26.Single

For a traditional class C network without sub-netting, how many hosts are available at most?

☐ a.1024

☐ b.65025

☐ c.254

☐ d.48

27.Single

A PC is connected to router's Ethernet port through its network interface card. What type of cable should be used to connect these two interfaces?

☐ a.Cross cable

☐ b.Straight cable

☐ c.Console cable

☐ d.Backup cable

28.Single

The TTL field in an IP header specifies the number of routers that a datagram is allowed to traverse. After the datagram traverses a router, the TTL value is deducted by 1. When the TTL reaches a certain value, the datagram is discarded. Which of the following represents this value?

☐ a.0

☐ b.1

☐ c.-1

☐ d.2

29.Single

According to OSI reference model, router operates at ()

☐ a.Physical layer

☐ b.Data link layer

☐ c.Network layer

☐ d.Application layer

30.Single

Which of the following protocols is a transport-level protocol based on TCP, translates a domain name into an IP address, and manages domain names in a distributed manner?

☐ a.TCP

☐ b.UDP

☐ c.DNS

☐ d.HTTP

31.Single

In a destination MAC address, which bit of the address determines whether a frame is sent to a “single” station or a group of stations?

☐ a.7

☐ b.8

32.Single

In Ethernet standard, which of the following mechanisms is used to avoid collision when different nodes transmit packets simultaneously?

- ☐ a.CSMA/CA
- ☐ b.CSMA/DA
- ☐ c.CSMA/CD
- ☐ d.CSMA/AC

33.Single

Which of the following is the broadcast MAC address?

- ☐ a.FF-FF-FF-FF
- ☐ b.FF-FF-FF-FF-FF-FF
- ☐ c.00-00-00-00-00-00
- ☐ d.00-00-00-FF-FF-FF

34.Single

In Window XP system, which of the following commands is used to release the IP address assigned by the DHCP Server?

- ☐ a.ipconfig /all
- ☐ b.ipconfig /renew
- ☐ c.ipconfig /release
- ☐ d.ipconfig

35.Single

How to eliminate the collision in Ethernet?

- ☐ a.Increase the length of cable
- ☐ b.Decrease the number of transmitted packets
- ☐ c.Decrease the number of users on each network segment
- ☐ d.Replace the hub and repeater with switch or bridge

36.Single

What's the broadcast address for network segment 201.1.0.0/21?

- ☐ a.201.1.7.255
- ☐ b.201.1.0.255
- ☐ c.201.1.1.255
- ☐ d.201.0.0.255

37.Single

Which port number does Telnet uses for protocol transmission?

- ☐ a.23
- ☐ b.24

38.Single

STP calculates the overall cost of each path between a non-root bridge and a root bridge. What is a port on the non-root bridge called on the path that has the minimum overall cost?

- ☐ a.Designated port
- ☐ b.Root port

☐ c.Common port

☐ d.Queue port

39.Single

In an OSPF area, routers exchange information about (). This type of information forms an information library.

☐ a.Link status

☐ b.Distance vector

☐ c.Route cost

☐ d.Route priority

40.Single

OSPF is an application layer protocol and it runs on ()

☐ a.UDP, port number 520

☐ b.TCP, port number 179

☐ c.IP, Protocol Number 89

41.Single

Which of the following descriptions about function of VRRP is true?

☐ a.VRRP improves the reliability of the default gateway in the network

☐ b.VRRP makes the routing protocols converge faster

☐ c.VRRP is mainly used for load balancing

☐ d.VRRP provides the same default gateway for different network segments, thus simplifies gateway configuration of PCs in the network

42.Single

What does the distance vector routing protocol focus on according to the discovered routes and calculated routes?

- ☐ a.The number of hops on between the router and the destination
- ☐ b.The address of the next hop specified manually
- ☐ c.Whether the egress port on the route belongs to a port aggregation group
- ☐ d.Link bandwidth resource information

43.Single

The network address of the IP 190.233.27.13/16 is ()

- ☐ a.190.0.0.0
- ☐ b.190.233.0.0
- ☐ c.190.233.27.0
- ☐ d.190.233.27.1

44.Single

Which of the following operations can be used to verify the failure of installation or running of TCP/IP protocol?

- ☐ a.Ping 10.1.1.1
- ☐ b.Ping 127.0.0.1

☐ c.Ping 169.254.1.1

☐ d.Ping 192.168.1.1

45.Single

In STP calculation, a port identifier consists of two parts: one-byte () and one-byte port number.

☐ a.Port priority

☐ b.Link priority

☐ c.Bridge MAC address

☐ d.Port MAC address

46.Multiple Choice,

According to the algorithms, routing protocols fall into two categories. They are ()

☐ a.IGP

☐ b.EGP

☐ c.Distance Vector

☐ d.Link-state

47.Multiple Choice,

Which of the following statements about RIP protocol priorities are true?

☐ a.With routing protocol priorities, a route obtained by a certain routing protocol can be selected as the optimal route according to the specified routing policy.

☐ b.A greater value of the RIP routing protocol priority means a higher priority.

☐ c.The RIP protocol priority can be set manually on a router.

- ☐ d.By default, the RIP protocol priority of Huawei router is 100.

48.Multiple Choice,

Which of the following packets belong to CHAP authentication protocol?

- ☐ a.Challenge
- ☐ b.Request
- ☐ c.Response
- ☐ d.Success
- ☐ e.Failure

49.Multiple Choice,

Packet filtering firewall filters packet based on quintuplet. Which of the following are the components of quintuplet?

- ☐ a.IP address
- ☐ b.Protocol number
- ☐ c.Port number
- ☐ d.Application program
- ☐ e.MAC address

50.Multiple Choice,

Which of the following statements regarding OSPF are correct?

- ☐ a.Support CIDR (Classless Inter-Domain Routing)
- ☐ b.Use the distance vector algorithm

☐ c. Use the triggered updates to immediately notify the neighbors about the topology changes so that the changes are synchronized in the AS.

☐ d. Use the reserved multicast addresses to transmit protocol packets.

51. Multiple Choice,

The evolution of firewall technology goes through the following three stages, and these stages include ()

☐ a. Packet filtering firewall

☐ b. Proxy firewall

☐ c. Stateful firewall

☐ d. Link-layer firewall

52. Multiple Choice,

In STP, the bridge ID consists of two parts. They are () and ().

☐ a. Switch priority

☐ b. Switch Port ID

☐ c. Switch MAC address

☐ d. Switch IP address

53. Multiple Choice,

Which of the protocols are commonly used at the Data Link Layer of a WAN?

☐ a. 802.2

☐ b. 802.4

☐ c. HDLC

☐ d.PPP

54. Multiple Choice,

Which of the following functions does LCP provide?

☐ a. Negotiates to establish links.

☐ b. Negotiates to use which Layer 3 protocols.

☐ c. Disconnects a link when the idle timer of the link expires.

☐ d. Tests a link to check the link quality and thus to determine whether a link can be established.

55. Multiple Choice,

Which of the following devices operate at data link layer?

☐ a. Hub

☐ b. Bridge

☐ c. Switch

☐ d. Router

☐ e. Firewall