

SE 3XA3: Module Internal Specification MAC Schedule Importer

Team 12, 0C
Cassandra Nicolak, nicolace
Michelle Leung, leungm16
Winnie Liang, liangw15

November 10, 2018

Contents

1	Introduction	1
2	Module Hierarchy	1
3	MIS of ParseMosaic	2
3.1	Uses	2
3.2	Interface Syntax	2
3.2.1	Exported Access Programs	2
3.3	Interface Semantics	2
3.3.1	State Variables	2
3.3.2	Environmental Variables	2
3.3.3	State Invariant	2
3.3.4	Assumptions	2
3.3.5	Access Program Semantics	2
4	MIS of Converter	3
4.1	Uses	3
4.2	Interface Syntax	3
4.2.1	Exported Access Programs	3
4.3	Interface Semantics	3
4.3.1	State Variables	3
4.3.2	Environmental Variables	3
4.3.3	State Invariant	3
4.3.4	Assumptions	3
4.3.5	Access Program Semantics	3
5	MIS of Connector	4
5.0.1	Uses	4
5.1	Interface Syntax	4
5.1.1	Exported Access Programs	4
5.2	Interface Semantics	5
5.2.1	State Variables	5
5.2.2	Environmental Variables	5
5.2.3	Assumptions	5
5.2.4	Access Program Semantics	5
6	MIS of guiClient	6
6.0.1	Uses	6
6.1	Interface Syntax	7
6.1.1	Exported Access Programs	7
6.2	Interface Semantics	7
6.2.1	State Variables	7

6.2.2 Environmental Variables 7

6.2.3 State Invariant 7

6.2.4 Assumptions 7

6.2.5 Access Program Semantics 7

List of Tables

1 Revision History ii

2 Module Hierarchy 1

List of Figures

Table 1: Revision History

Date	Version	Notes
2018-11-07	1.0	Rough Draft
Date 2	1.1	Notes

1 Introduction

The purpose of this module internal specification document is to provide a complete description of the specifications to design the MAC Schedule Importer. The project is a redesign of the open-source Chrome extension, UMD Google Calendar Schedule Importer, which imports the class schedule for students at the University of Maryland into Google Calendar. The reimplementation will be modified to allow students from McMaster University to import their schedules from Mosaic through a Desktop application.

2 Module Hierarchy

This section provides an overview of the module design. Modules are summarized in a hierarchy decomposed by secrets in Table 2. The modules listed below, which are leaves in the hierarchy tree, are the modules that will actually be implemented.

Level 1	Level 2
Hardware-Hiding Module	
Behaviour-Hiding Module	converter connector guiClient
Software Decision Module	parseMosaic

Table 2: Module Hierarchy

3 MIS of ParseMosaic

3.1 Uses

scrapy, subprocess

3.2 Interface Syntax

3.2.1 Exported Access Programs

Name	In	Out	Exceptions
parse	response: TextResponse	dataList: list of string tuples	-
runMe	passed_url: url (str)	GUI	-

*Note: Exceptions are still in development.

3.3 Interface Semantics

3.3.1 State Variables

dataList : list of string tuples

3.3.2 Environmental Variables

process : CrawlerSpiderProcess() from the Scrapy Library

3.3.3 State Invariant

$0 \leq |\text{dataList}|$

3.3.4 Assumptions

parse() is called before runMe().

3.3.5 Access Program Semantics

parse(response)

- transition: dataList := modify dataList so that it uses the Scrapy library to parse data from *response* and stores a list of string tuples with the tuple containing (course name, component, schedule, location, dates) of each course.

- exception : None

runMe()

- output := dataList
- exception: None

4 MIS of Converter

4.1 Uses

parseMosaic

4.2 Interface Syntax

4.2.1 Exported Access Programs

Name	In	Out	Exceptions
extract_date	input: str	start: str, end: str	-
to_military	input: str	mil: str	-
extract_weekdays	input: str	weekdays: str	-
rfc_output	date_str, time_str: str	start_date_time, end_date_time: str	-
convert	input: list of string tuples	output: list of dictionaries	-

*Note: Exceptions are still in development.

4.3 Interface Semantics

4.3.1 State Variables

None

4.3.2 Environmental Variables

None

4.3.3 State Invariant

None

4.3.4 Assumptions

None, unless stated in the access program.

4.3.5 Access Program Semantics

extract_date(input)

- output: start := $(\exists i | i \in \text{input} \wedge \text{input}[i] = \text{'-'} : \text{start} = \text{input}[0..i - 1])$
- output: end := $(\exists i | i \in \text{input} \wedge \text{input}[i] = \text{'-'} : \text{end} = \text{input}[i + 1..|\text{input}|])$
- exception: None

to_military(input)

- output: `mil :=` returns a string of the military time given a 12-hour time input string.
- exception: None

`extract_weekdays(input)`

- output: `weekdays :=` given a string containing weekdays, ex. "MoTWeThFr", it returns a string with capitalized string with commas between the weekdays, ex."MO,TU,WE,TH,FR"
- exception: None

`rfc_output(date_str, time_str)`

- output: a start and end date`Time` in RFC 2232 format, and a `rrule` in Rfc 5545 format
- exception: None

`convert(input)`

- output: a list of dictionaries containing calendar event parameters
- exception: None

5 MIS of Connector

5.0.1 Uses

`sys`, `os`, `googleapiclient`, `socket`, `oauth2client`, `httplib2`

5.1 Interface Syntax

5.1.1 Exported Access Programs

Name	In	Out	Exceptions
<code>login</code>	-	GUI	<code>ServerNotFoundError</code>
<code>logout</code>	-	GUI	-
<code>check_perms</code>	-	bool	-
<code>create_cal</code>	<code>name: str</code>	Google Calendars	<code>AccessTokenRefreshError</code> , <code>ServerNotFound Error</code> , <code>ga</code>
<code>insert_events</code>	-	True, None	<code>AccessTokenRefreshError</code> , <code>ServerNotFound Error</code> , <code>ga</code>
<code>get_num_events</code>	-	<code> event_list : int</code>	<code>AccessTokenRefreshError</code> , <code>ServerNotFound Error</code> , <code>ga</code>
<code>check_insertion</code>	-	bool	-
<code>remove_new_cal</code>	-	bool	<code>AccessTokenRefreshError</code> , <code>ServerNotFound Error</code> , <code>ga</code>
<code>push_to_schedule</code>	-	bool	-

5.2 Interface Semantics

5.2.1 State Variables

service: Object
cal_id: string
bodies: dictionary

5.2.2 Environmental Variables

None

5.2.3 Assumptions

None, unless noted in the access programs

5.2.4 Access Program Semantics

login

- transition: service := Object
- exception: None

logout

- transition: service := None
- exception: None

check_perms

- output: Bool, true if permissions were granted, False otherwise.
- exception: None

create_cal

- transition: cal_id := new calendar id
- exception: client.AccessTokenRefreshError, when access token fails to refresh.
- exception: gaierror, internet fails
- exception: ConnectionResetError, internet fails
- exception: ServerNotFoundError, internet fails

insert_events

- output: inserts event into google calendar
- exception: client.AccessTokenRefreshError, when access token fails to refresh.
- exception: gaierror, internet fails
- exception: ConnectionResetError, internet fails
- exception: ServerNotFoundError, internet fails

get_num_events

- output: number of events in calendar: cal_id
- exception: client.AccessTokenRefreshError, when access token fails to refresh.
- exception: gaierror, internet fails
- exception: ConnectionResetError, internet fails
- exception: ServerNotFoundError, internet fails

check_insertion

- output: True if number of events in Google calendars matches the number of event parameters sent to Google. False otherwise

remove_new_cal

- output: removal of calendar: cal_id
- exception: client.AccessTokenRefreshError, when access token fails to refresh.
- exception: gaierror, internet fails
- exception: ConnectionResetError, internet fails
- exception: ServerNotFoundError, internet fails

push_to_schedule

- output: Pushes events to Google calendars. Returns True if successful. False otherwise.

6 MIS of guiClient

6.0.1 Uses

PySimpleGUI, parseMosaic, connector, converter, urllib, webbrowser

6.1 Interface Syntax

6.1.1 Exported Access Programs

Name	In	Out	Exceptions
convertURL	str	str	-
parseMosaic	str	fetchedList: list of tuple of str	-
printSched	fetchedList: list of tuple of str	str	-
fetch	str	str	-
conn	-	Object	-
login	-	bool	-
logout	-	-	-
pushSchedule	-	bool	-

6.2 Interface Semantics

6.2.1 State Variables

fetchFLG: bool

fetchedList: list of string tuples

googleConn: None

6.2.2 Environmental Variables

layout: list of lists of type GUI

window: GUI

menu_def: list of lists of str

6.2.3 State Invariant

$|\text{fetchedList}| \geq 0$

6.2.4 Assumptions

None, unless stated by the access programs.

6.2.5 Access Program Semantics

convertURL(userInput)

- output: $\text{userURL} :=$ given a url from a path name (str), it returns the absolute file path (str).
- exception: None

parseMosaic(url)

- output: url:= Parses the html document from *url* and displays the *url* on the GUI.
- exception: None

printSched(fetchList)

- output: out:= Converts fetchList into the following format of str: "Course, Type, When, Location, Start/End Dates"

fetch(url)

- output: out:= Parses url using parseMosaic() function and returns the schedule using printSched().
- exception: None

conn()

- transition: Converts the output of parseMosaic to Google API inputs.
- exception: None

login()

- output: out:= Creates a link to google's api service when the user logs into their Google account. Returns true if there is a service, otherwise false.
- exception: None

logout()

- transition: deletes access key to user's account.
- exception: None

pushSchedule()

- output: out:= Uploads event items to a Google Calendar. Returns true if the import is successful and false otherwise.