TIR

SOTA: How to explain a classifier?

Mastrorillo Noé, Tortosa Matthias, Pigeon Axel, Sinatti Antoine

Abstract

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Introduction

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

1 Explanation methods based on Shapley values

Some of the most widely used methods for single decision features importance explanation are based on the Shapley values from game theory. These methods are so popular because they give a contribution score for each feature in the decision that is easily understood by the user. This contribution score has a sign, so that a positive score means that the features contributes positively to the decision and the opposite for a negative score, and it has a magnitude, so that a higher absolute score means a higher contribution towards the respective class.

While these methods are amongst the most popular, that doesn't mean that they are superior, as we will see the several shortcomings later.

1.1 Game theory preliminaries

In game theory, Shapley values provide a mathematically fair and unique method to attribute the payoff of a cooperative game to the players. Formally, a coalitional game $(\mathcal{F}, v)$ is represented by a set of n players $\mathcal{F} = \{1, \dots, n\}$, and a characteristic function $v : \mathcal{P}(\mathcal{F}) \to \mathbb{R}$ that represents the payoff for a subset of players $\mathcal{S} \subset \mathcal{F}$ (a coalition). Then, the Shapley value for a single player $i \in \mathcal{F}$, noted $\varphi_i(v)$ is defined as follows in [1]:

Definition 1.1 *Shapley value*

$$\varphi_i(v) = \frac{1}{n} \sum_{\mathcal{S} \in \mathcal{F} \setminus \{i\}} \binom{n-1}{|\mathcal{S}|}^{-1} \big(v(\mathcal{S} \cup \{i\}) - v(\mathcal{S})\big)$$

Therefore, the Shapley value for a player i is computed by going through all the coalitions of players not containing i and looking at the payoff difference with and without the player i (with a normalization factor).

The Shapley value of a coalitional game $(\mathcal{F}, v)$ is the only solution that respects the four following powerful axioms, as described in [2]:

- *Efficiency*: The worth of the coalition containing all players is distributed losslessly among the players :
$$\sum_{i \in \mathcal{F}} \varphi_i(v) = v(\mathcal{F}) - v(\emptyset)$$
- *Null Player*: If a player contributes nothing to each coalition, then its Shapley value is zero :
$$\forall i \in \mathcal{F} \quad \big[\forall \mathcal{S} \subset \mathcal{F} \quad v(\mathcal{S} \cup \{i\}) = v(\mathcal{S})\big] \Longrightarrow \varphi_i(v) = 0$$
- *Symmetry*: Any two players that play equal roles amongst all coalition receive the same Shapley value :
$$\forall i, j \in \mathcal{F} \quad \big[\forall \mathcal{S} \subset \mathcal{F} \setminus \{i, j\} \quad v(\mathcal{S} \cup \{i\}) = v(\mathcal{S} \cup \{j\})\big] \Longrightarrow \varphi_i(v) = \varphi_j(v)$$
- *Additivity*: Let v_1 and v_2 be two characteristic funtions, the Shapley value respects the additivity of functions :
$$\varphi(v_1 + v_2) = \varphi(v_1) + \varphi(v_2)$$

1.2 Shapley values for feature explanation

In ML, Shapley values allocates the predicted value of a specific instance fairly amongst all the features. Thus, the Shapley values represent the contribution (positive or negative) of each feature in the decision to explain.

Formally, let $x \in \mathbb{F}$ be the input where $\mathbb{F} = \mathbb{F}_1 \times \cdots \times \mathbb{F}_2$ is the input space of our model (each $\mathbb{F}_i$ is the space of the feature i), and $f(x)$ is the predicted value of our model for a specific class ($f : \mathbb{F} \longrightarrow [-1, +1]$). We consider the coalitional game represented by $\mathcal{F} = \{1, \ldots, n\}$ the set of numbered features that will be our players, and the characteristic function $v : \mathcal{P}(\mathcal{F}) \longrightarrow \mathbb{R}$ defined as follows:

$$\forall \mathcal{S} \subset \mathcal{F} \quad v(\mathcal{S}) = \mathbb{E}[f(X) | X_{\mathcal{S}} = x_{\mathcal{S}}] \tag{1}$$

where $X_{\mathcal{S}} = x_{\mathcal{S}}$ means that instances X and x share the same values for the features in $\mathcal{S}$.

The characteristic function is the mean value of the predictions on inputs that share the same values for the features in $\mathcal{S}$.

Finally, we can define the Shapley value of a feature i in the wish of explaining the prediction of an input x as follows:

$$\varphi_i = \frac{1}{n} \sum_{\mathcal{S} \in \mathcal{F} \setminus \{i\}} \binom{n-1}{|\mathcal{S}|}^{-1} \big(\mathbb{E}[f(X) | X_{\mathcal{S} \setminus \{i\}} = x_{\mathcal{S} \setminus \{i\}}] - \mathbb{E}[f(X) | X_{\mathcal{S}} = x_{\mathcal{S}}]\big) \tag{2}$$

Remark. Every Shapley value computed will be based on the choice of the distribution of the reference instances X, and we will see later how it matters. Moreover, we can deduce from the above definitions and the efficiency axiom the following property:

$$\sum_{i \in \mathcal{F}} \varphi_i(v) = \mathbb{E}[f(X) | X_{\mathcal{F}} = x_{\mathcal{F}}] - \mathbb{E}[f(X) | X_{\emptyset} = x_{\emptyset}] = f(x) - \mathbb{E}[f(X)] \tag{3}$$

Therefore, the sum of the Shapley values of all features equals to the predicted value minus a reference contribution that is the mean of all predictions (for inputs based on a specific distribution).

1.3 Approximation

As you may have noticed, computing exact Shapley values has an exponential complexity in terms of the number of features. Indeed, it requires exploring all the subcoalitions $\mathcal{S}$ of $\mathcal{F}\backslash\{i\}$. In practice, this problem becomes intractable when playing with hundreds of features [3]. Moreover, the calculation of the characteristic function $v(\mathcal{S})$ is also intractable as it requires exploring all the input space $\mathbb{F}$.

Both issues are solved notably in [1] by using sampling methods. For the former, subcoalitions $\mathcal{S} \subset \mathcal{F}\backslash\{i\}$ are sampled by taking all the features preceding i in random orderings O_j of $\mathcal{F}$: we define $\mathcal{S}_j = Pre_i(O_j)$. For the latter, ehe reference instances X are sampled following the chosen distribution.

Remark. These two approximation solutions allow us to build confidence intervals over the computed Shapley values. Each feature contribution can now be represented as an interval. This is particularly interesting because this gives us more information whether an approximation of the contribution is relevant or not. If a Shapley value is approximated to be close to zero, its confidence interval may take values from negatives to positives values, meaning that we cannot deduce any valuable information about whether this feature contributes positively or negatively in the decision. Remember that if we could compute the exact Shapley value, this case would not exist.

1.4 Different methods

Several explanation methods based on Shapley values have been proposed through the past years. What is described above is the original SHAP (SHapley Additive exPlanations) framework, that serves as the groundwork for newer methods. Various papers pinpointed the shortcomings of SHAP ([4][2]), and mainly the fact that it can attribute more importance to features having less influence (or even no influence at all) in the decision.

On the one hand, [4] claims that this issue can be solely attributed to the characteristic function used, and the authors propose new characteristic functions based on abductive and contrastive explanations (AXps and CXps). They introduce a similarity predicate σ defined below and one example of characteristic function v_a associated :

$$\sigma(y) = \begin{cases} 1 & \text{if } f(y) \approx f(x) \\ 0 & \text{else} \end{cases} \qquad v_a(\mathcal{S}) = \begin{cases} 1 & \text{if } \mathbb{E}[\sigma(X)|X_{\mathcal{S}} = x_{\mathcal{S}}] = 1 \\ 0 & \text{else} \end{cases} \tag{4}$$

Concretely, $v_a(\mathcal{S}) = 1$ if all the instances sharing the same values as x on the features in $\mathcal{S}$ get predicted a similar value (same class in the case of classification). Therefore, $v_a(\mathcal{S})$ is equivalent as knowing if $\mathcal{S}$ is a weak abductive explanation (wAXp) of x. v_a and the other proposed characteristic functions respects two important property: *strong value independance* (mapping the input space into another one by a surjection doesn't change the value of the characteristic function) and *feature irrelevancy* (a feature that doesn't influence the prediction gets attributed a Shapley value of 0). These properties are desirable to get around the previously mentionned issues.

On the other hand, [1] pinpoint the importance of the choice of the reference distribution, noted $\mathcal{D}^{ref}$, used in the characteristic function while computing $\mathbb{E}[f(X)|X_{\mathcal{S}} = x_{\mathcal{S}}]$. Indeed, we could decide that X follows the input distribution (distribution of the dataset) $\mathcal{D}^{inp}$ (used in SHAP and KernelSHAP), the joint-marginal distribution of features $\mathcal{D}^{J.M.}$ (used in QII), or even a uniform distribution over the input space $\mathcal{D}^{unif}$. While chosing $\mathcal{D}^{inp}$ take into account only instances present in the dataset and can suffer from the proeminance of some feature values that is directly reflected in the SHAP-scores, chosing $\mathcal{D}^{J.M.}$ assumes independance between all the features, and like $\mathcal{D}^{unif}$, can sample unrealistic instances that will have an impact in the computed attributions. Therefore, the paper proposes the Formulate-Approximate-Explain framework when facing this choice, saying that we should firstly formulate a contrastive question related to the classification task to pin down the desired reference distribution. The choice in distribution lies in the question of "Why does this instance received this score *in contrast of* these other references".

Finally, there exists model-specific SHAP-based methods for explaining decisions of classifiers with known designs. For instance, [5] presents Eject, intended to give more model-related explanations while solving shortcomings of previous TreeSHAP method that computes SHAP scores on Tree-based models (classification trees and trees ensembles models like random forests). Eject computes the utility of a coalition of features for a specific instance by going down the decision branch and "ejecting" (returning the predicted value of the previously visited node) when the branch uses a feature not present in the coalition. This notably ensures the *local dummy player* property: a feature not used in the prediction gets a score of 0. On the other hand, CNN SHAP proposed in [6] aims to compute SHAP scores on convolutive neural networks (more precisely CNN text classification models), and thus on non-structured data. CNN SHAP firstly let the convolutive layers of the model extract the semantic features, and compute the SHAP scores on these extracted features, while keeping in memory the part of the input corresponding to each feature. Then, there's a deduplication step for features having similar semantic meanings and a merging step for features whose corresponding input parts overlap. Finally, the computed SHAP scores can directly be attributed to the input areas.

2 Perturbation model-agnostic methods

In this section, we present a set of perturbation method used in black-box models explanation. A perturbation method can be defined by the generation of perturbed samples (ex: noised features in model representation or perturbed input tensor) at the input of the black-box model. The objective is to compare the model behavior (the prediction) between a set of different perturbed inputs and the original one. Then, we can determine which one is more important for the prediction. It allows the explanation model to detail why the model took a specific decision and why. The following methods register in this type. The first one, LIME (Local Interpretable Model-Agnostic Explanation) focus on a linear approximation of local model behavior. Secondly, the Anchors method provides an amelioration of LIME by introducing the concept of IF-THEN rules to provide a better user-experience. Finally, we will briefly talk about add-ons of those methods in specific cases.

Remark (Notation). Let's introduce some notations to identify which objects we will talk about. We denote with f a black-box model we want to explain, then $f : X \longrightarrow Y$ where X is the set of instances $x \in X$ and Y the different possible predictions $f(x)$. In this section, we will talk about linear explanation model, denoted g. To identify which input representation we use, we denote by x' the interpretable representation of an input x in the black-box model f. Then, if we construct a set of perturbed interpreted samples $\mathcal{Z}$ from x', this set contains perturbed version of x' called z'. Finally, $\Omega(g)$ express the complexity of the model g, generally defined by the number of non-zeros weights in g.

2.1 LIME (Local Interpretable Model-Agnostic Explainer)

LIME founded the principe of perturbation method for classifiers explanation [7]. It provides a local explanation of a black-box model behavior $f : \mathbb{R}^d \longrightarrow \mathbb{R}$ by training a simple explanation model g over perturbed samples. This method is *model-agnostic* because it doesn't depend on the black-box model architecture. f is considered as an oracle used to train g.

Formally, for an original interpretable representation $x' \in \{0,1\}^{d'}$ of a sample $x \in \mathbb{R}^d$, it generates a set of perturbed samples z' which are drawn by selecting uniformly some x' non-zero components. This random sampling is weighted by π_x which defines a locality around x' denoted $\mathcal{Z}$. In practical, π_x is an exponential kernel applied to a distance D. To find the optimal model g, we can define a loss function $\mathcal{L}(f, g, \pi_x)$ telling how unfaithful g is in approximating f on $\mathcal{Z}$. The objective is then to minimize $\mathcal{L}$ and having $\Omega(g)$ low enough for human comprehension. The LIME explanation is then produced by:

$$\xi(x) = \arg\min_{g \in G} \mathcal{L}(f, g, \pi_x) + \Omega(g) \tag{5}$$

with G the set of available explanation models [7]. Using $\mathcal{L}$ and $\Omega(g)$ to find the best model g ensures *interpretability* and *local fidelity* on the black-box model explanation. Finally, the local explanation of the model is provided by the weights w_g trained with $g(z') = w_g \cdot z'$.

As stated at beginning, LIME provides a *local* explanation of f. To ensure a global explanation, the paper proposes a Sub-modular Picks LIME (SP-LIME) which selects a set local and non-redundant LIME explanations to be given to the user [7]. To choose those explanations, the paper introduces the concept of coverage of a set of instances which defines the importance of those instances.

Definition 2.1 *Coverage*

Let g be an explanation model and $g_i = \xi(x_i)$ the explanation of the instance x_i, we construct the $|X| \times d'$ explanation matrix $\mathcal{W}$ with $\mathcal{W}_{i,j} = |w_{g_{i,j}}|$. Then, I_j is the j-column of W and denotes the global importance of that component in the explanation space. Then, the coverage of a set of instances V is defined as the total importance of the features that appear at least one instance in V:

$$c(V, \mathcal{W}, I) := \sum_{j=1}^{d'} \mathbb{1}_{\{\exists i \in V, \mathcal{W}_{i,j} > 0\}} I_j \tag{6}$$

Finally, from a maximum number of global explanations B set by the user, the pick problem is defined by:

$$Pick(\mathcal{W}, I) = \underset{V, |V| \leqslant B}{\arg\max}\ c(V, \mathcal{W}, I) \tag{7}$$

We want to select the highest coverage and non-redundant explanations to provide a global one.

Unfortunately, this system has limits. First, in practice, the pick problem is intractable, so a greedy algorithm is used to compute it. Secondly, LIME algorithm doesn't define clear boundaries of the explanation instances. Indeed, all black-box models cannot be locally approximated by a linear one [8]. Finally, the explanation results depend on the LIME parameters such as B, the distance metric D and the kernel π_x. Changing one of them can change the interpretation and undermining the reliability of this method [9].

2.2 Anchors

Anchors is also a model-agnostic explanation method based on LIME system but enhanced in order to provide local sufficient conditions for prediction. Anchors are defined by short and disjoint rules which are preferred by users for explanation [10]. It can be applied on different set of domains (tabular, text, images, etc...) for different tasks (classification, prediction, text generation, etc...).

Definition 2.2 *Anchors*

Formally, Anchors are built on a set of predicates a called a "rules". We can also see it as a function of instances $x \in X$:

$$A : \begin{cases} X \longrightarrow \{0, 1\} \\ x \longmapsto \begin{cases} 1 \text{ if all rules are true for } x \\ 0 \text{ otherwise} \end{cases} \end{cases}$$

to link a set of rules A on a prediction $f(x)$ (where $f : X \longrightarrow Y$ is the black-box model). Finally, A is an Anchor of x if $A(x) = 1$ and A is a sufficient condition for the prediction $y = f(x)$:

$$\mathbb{E}_{\mathcal{D}(z|A)}[1_{f(x)=f(z)}] \geqslant \tau \tag{8}$$

with τ the desired level of precision of the Anchor on x [10]. Here, $\mathcal{D}(x \mid A)$ represents

> the distribution of neighbors of x which satisfy the Anchor A.

Computing Anchors is the difficult part of the process. This is a combinatorial optimization problem if we decide to choose anchors which satisfy a precision constraint with high probability:

$$\mathbb{P}(prec(A) \geqslant \tau) \geqslant 1 - \delta$$

with $prec(A) = \mathbb{E}_{\mathcal{D}(z|A)}(1_{f(x)=f(z)})$ called the Anchors "precision". Among those anchors, we choose the largest coverage ones, where coverage is :

$$cov(A) = \mathbb{E}_{\mathcal{D}(z)}(A(z)) \tag{9}$$

Finally, the optimization problem can be described by :

$$\max_{\mathbb{P}(prec(A)\geqslant\tau)\geqslant 1-\delta} cov(A) \tag{10}$$

Because the number of all possible Anchor is exponential, we can perform an exhaustive search. That's why the article introduced the Bottom-Up approach:

1. *Initialization*: The anchor A is initialized as an empty rule (applying to all instances).
2. *Candidate Generation*: In each iteration, a set of candidate rules $\mathcal{A}$ is generated by extending A with one additional feature predicate $\{a_i\}$: $\mathcal{A} = \{A \wedge a_i, A \wedge a_{i+1}, A \wedge a_{i+2}, ...\}$
3. *Selection via Multi-Armed Bandit (MAB)*: To identify the best candidate without an exhaustive number of calls to f, the problem is formulated as a pure-exploration multi-armed bandit problem. The *KL-LUCB* algorithm is used to find the rule with the highest precision using a minimal set of samples [10].
4. *Termination*: The process terminates when a rule meets the statistical precision constraint: $\mathbb{P}(prec(A) \geqslant \tau) \geqslant 1 - \delta$.

To address the limitations of a purely greedy search, the algorithm extends the construction to a *Beam Search* of size B. It maintains a set of B current candidates instead of a single one. Among the multiple anchors identified that satisfy the precision threshold τ, the algorithm outputs the one with the highest coverage $cov(A)$, effectively optimizing the original problem.

To provide a global understanding of the model, the article adapts a *Submodular Pick* (SP) procedure. The goal is to select a set of K anchors that are non-redundant and cover as many instances in the validation set similar to the approach used in LIME [7, 10].

References

[1] Luke Merrick and Ankur Taly. "The Explanation Game: Explaining Machine Learning Models Using Shapley Values". en. In: *Machine Learning and Knowledge Extraction.* Ed. by Andreas Holzinger et al. Cham: Springer International Publishing, 2020, pp. 17–38. ISBN: 978-3-030-57321-8. DOI: 10.1007/978-3-030-57321-8_2.

[2] Daniel Fryer, Inga Strümke, and Hien Nguyen. "Shapley Values for Feature Selection: The Good, the Bad, and the Axioms". In: *IEEE Access* 9 (2021), pp. 144352–144360. ISSN: 2169-3536. DOI: 10.1109/ACCESS.2021.3119110. URL: https://ieeexplore.ieee.org/abstract/document/9565902 (visited on 02/16/2026).

[3] Erik Strumbelj and Igor Kononenko. "An Efficient Explanation of Individual Classifications using Game Theory". In: *J. Mach. Learn. Res.* 11 (Mar. 2010), pp. 1–18. ISSN: 1532-4435. URL: https://dl.acm.org/doi/10.5555/1756006.1756007 (visited on 02/21/2026).

[4] Olivier Létoffé, Xuanxiang Huang, and Joao Marques-Silva. "Towards trustable SHAP scores". In: *Proceedings of the AAAI Conference on Artificial Intelligence*. Vol. 39. 17. 2025, pp. 18198–18208. URL: https://ojs.aaai.org/index.php/AAAI/article/view/34002 (visited on 02/05/2026).

[5] Thomas W. Campbell et al. "Exact Shapley values for local and model-true explanations of decision tree ensembles". In: *Machine Learning with Applications* 9 (Sept. 2022), p. 100345. ISSN: 2666-8270. DOI: 10.1016/j.mlwa.2022.100345. URL: https://www.sciencedirect.com/science/article/pii/S2666827022000500 (visited on 02/21/2026).

[6] Wei Zhao et al. *SHAP values for Explaining CNN-based Text Classification Models*. July 2021. DOI: 10.48550/arXiv.2008.11825. URL: http://arxiv.org/abs/2008.11825 (visited on 02/21/2026).

[7] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. ""Why Should I Trust You?": Explaining the Predictions of Any Classifier". en. In: *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. San Francisco California USA: ACM, Aug. 2016, pp. 1135–1144. ISBN: 978-1-4503-4232-2. DOI: 10.1145/2939672.2939778. URL: https://dl.acm.org/doi/10.1145/2939672.2939778 (visited on 02/05/2026).

[8] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. *Nothing Else Matters: Model-Agnostic Explanations By Identifying Prediction Invariance*. Nov. 2016. DOI: 10.48550/arXiv.1611.05817. URL: http://arxiv.org/abs/1611.05817 (visited on 02/21/2026).

[9] Rahel Wilking, Matthias Jakobs, and Katharina Morik. "Fooling Perturbation-Based Explainability Methods". In: *Workshop on Trustworthy Artificial Intelligence as a part of the ECML/PKDD 22 program*. Grenoble, France, France: IRT SystemX [IRT SystemX], Sept. 2022. URL: https://hal.science/hal-03773429 (visited on 02/21/2026).

[10] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "Anchors: High-precision model-agnostic explanations". In: *Proceedings of the AAAI conference on artificial intelligence*. Vol. 32. 1. 2018. URL: https://ojs.aaai.org/index.php/aaai/article/view/11491 (visited on 02/05/2026).