

TRANSLATION WITH A SEQUENCE TO SEQUENCE NETWORK AND ATTENTION

- Translate from French to English
- Sequence to sequence network
 - : two RNN work together to transform one sequence to another.
 - Encoder: condenses an input sequence into a vector
 - Decoder: unfolds the vector into a new sequence

Requievements

```
from __future__ import unicode_literals, print_function, division
```

```
from io import open
```

```
import unicodedata
```

```
import string
```

```
import re
```

```
import random
```

```
import torch
```

```
from torch.nn import nn
```

```
from torch import optim
```


```
import torch.nn.functional as F
```

```
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
```

Loading data files

- English to French pairs
- unique index per word & one-hot vector

| | | | | | | |
|-----|-----|-----|----|----|-----|--------|
| SOS | EOS | the | a | is | and | or |
| | | | | | | |
| 01 | 02 | 03 | 04 | 05 | 06 | 07 ... |



and = $\langle 0 \ 0 \ 0 \ 0 \ 0 \ 1 \ 0 \dots \rangle$

- class Lang: helper class
 - word \rightarrow index (word2index)
 - index \rightarrow word (index2word)
 - Count of each word (word2count)

SOS_token = 0

EOS_token = 1

class Lang:

def __init__(self, name):

self.name = name

self.word2index = {}

self.word2count = {}

self.index2word = {0: "SOS", 1: "EOS"}

self.n_words = 2 # Count SOS and EOS

def addSentence(self, sentence):

for word in sentence.split(' '):

self.addWord(word)

def addWord(self, word):

if word not in self.word2index:

self.word2index[word] = self.n_words

self.word2count[word] = 1

self.index2word[self.n_words] = word

self.n_words += 1

else:

self.word2count[word] += 1

To simplify:

- turn Unicode characters to ASCII
- make everything lowercase
- trim most punctuation

```
def unicodeToAscii(s):  
    return "".join(  
        c for c in unicodedata.normalize('NFD', s)  
        if unicodedata.category(c) != 'Mn'  
    )
```

Lowercase, trim, and remove non-letter characters

```
def normalizeString(s):  
    s = unicodeToAscii(s.lower().strip())  
    s = re.sub(r"([!?!])", r"\1", s)  
    s = re.sub(r"^[^a-zA-Z.!?!]+", r" ", s)  
    return s
```

To read the data file :

- split the file into lines

↓

- split lines into pairs

To translate from other language → English : reverse flag

```
def readLangs (lang1, lang2, reverse = False) :
```

```
    print ("Reading lines...")
```

```
    # Read the file and split into lines
```

```
    lines = open('data/%S-%S.txt' % (lang1, lang2), encoding = 'utf-8'). \
        read().strip().split('\n')
```

```
    # split every line into pairs and normalize
```

```
    pairs = [[normalizeString(s) for s in l.split('\t')] for l in lines]
```

```
    # Reverse pairs, make Lang instances
```

```
    if reverse :
```

```
        pairs = [list(reversed(p)) for p in pairs]
```

```
        input_lang = Lang(lang2)
```

```
        output_lang = Lang(lang1)
```

```
    else :
```

```
        input_lang = Lang(lang1)
```

```
        output_lang = Lang(lang2)
```

```
    return input_lang, output_lang, pairs
```

To train quickly:

- trim the dataset to only relatively short & simple sentences.
- maximum length: 10 words (includes ending punctuation)
- filtering to sentences that translate to the form "I am" or "He is" etc.

MAX_LENGTH = 10

eng_prefixes = (

"i am", "i am", "he is", "he s",

"she is", "she s", "you are", "you re",

"we are", "we re", "they are", "they re"

)

def filterPair(p):

return len(p[0].split(' ')) < MAX_LENGTH and \

len(p[1].split(' ')) < MAX_LENGTH and \

p[1].startswith(eng_prefixes)

def filterPairs(pairs):

return [pair for pair in pairs if filterPair(pair)]

Full process for preparing the data is:

- Read text file and split into lines, split lines into pairs
- Normalize text, filter by length & content
- Make word lists from sentences in pairs

```
def prepareData (lang1, lang2, reverse = False):  
    input_lang, output_lang, pairs = readLangs (lang1, lang2, reverse)  
    print ("Read %s sentence pairs" % len(pairs))  
    pairs = filterPairs (pairs)  
    print ("Trimmed to %s sentence pairs" % len(pairs))  
    print ("Counting words ...")  
    for pair in pairs:  
        input_lang.addSentence (pair[0])  
        output_lang.addSentence (pair[1])  
    print ("Counted words: ")  
    print (input_lang.name, input_lang.n_words)  
    print (output_lang.name, output_lang.n_words)  
    return input_lang, output_lang, pairs
```

```
input_lang, output_lang, pairs = prepareData ('eng', 'fra', True)  
print (random.choice (pairs))
```

The Seq2Seq Model

- RNN (Recurrent Neural Network)

: a network that operates on a sequence and uses its own output as input for subsequent steps.


- Encoder: reads an input sequence

↓ outputs a single vector

- Decoder: reads the vector to produce an output sequence

The Encoder

- RNN that outputs some value for every word from the input sentence.
- For every input word the encoder outputs a vector and a hidden state
- uses the hidden state for the next input words



```
class EncoderRNN(nn.Module):
```

```
    def __init__(self, input_size, hidden_size):
```

```
        super(EncoderRNN, self).__init__()
```

```
        self.hidden_size = hidden_size
```

```
        self.embedding = nn.Embedding(input_size, hidden_size)
```

```
        self.gru = nn.GRU(hidden_size, hidden_size)
```

```
    def forward(self, input, hidden):
```

```
        embedded = self.embedding(input).view(1, 1, -1)
```

```
        output = embedded
```

```
        output, hidden = self.gru(output, hidden)
```

```
        return output, hidden
```

```
    def initHidden(self):
```


```
        return torch.zeros(1, 1, self.hidden_size, device = device)
```


The Decoder

: another RNN that takes the encoder output vector(s)
and outputs a sequence of words to create the translation

Simple Decoder

- use only last output of the encoder.
sometimes called "context vector"
- Context vector is used as the initial hidden state of the decoder.
- At every step of decoding, the decoder is given an input token & hidden state.
 - initial input token: start-of-string <SOS>
 - first hidden state: context vector (the encoder's last hidden state)




Class DecoderRNN (nn.Module):


```
def __init__(self, hidden_size, output_size):  
    super(DecoderRNN, self).__init__()  
    self.hidden_size = hidden_size  
  
    self.embedding = nn.Embedding(output_size, hidden_size)  
    self.gru = nn.GRU(hidden_size, hidden_size)  
    self.out = nn.Linear(hidden_size, output_size)  
    self.softmax = nn.LogSoftmax(dim=1)  
  
    def forward(self, input, hidden):  
        output = self.embedding(input).view(1, 1, -1)  
        output = F.relu(output)  
        output, hidden = self.gru(output, hidden)  
        output = self.softmax(self.out(output[0]))  
        return output, hidden  
  
    def initHidden(self):  
        return torch.zeros(1, 1, self.hidden_size, device=device)
```

Attention Decoder

- Attention allows the decoder network to "focus" on a different part of the encoder's outputs for every step of the decoder's own outputs.



- the result should contain information about the specific part of the input sequence
→ help the decoder choose the right output words



- have to choose
a maximum sentence length
- sentences of maximum length
will use all the attention weights
 - Shorter sentences will only use
the first few.

```
class AttnDecoderRNN(nn.Module):
```

```
    def __init__(self, hidden_size, output_size, dropout_p = 0.1, max_length = MAX_LENGTH):
```

```
        super(AttnDecoderRNN, self).__init__()
```

```
        self.hidden_size = hidden_size
```

```
        self.output_size = output_size
```

```
        self.dropout_p = dropout_p
```

```
        self.max_length = max_length
```

```
        self.embedding = nn.Embedding(self.output_size, self.hidden_size)
```

```
        self.attn = nn.Linear(self.hidden_size * 2, self.max_length)
```

```
        self.attn_combine = nn.Linear(self.hidden_size * 2, self.hidden_size)
```

```
        self.dropout = nn.Dropout(self.dropout_p)
```

```
        self.gru = nn.GRU(self.hidden_size, self.hidden_size)
```

```
        self.out = nn.Linear(self.hidden_size, self.output_size)
```

```
    def forward(self, input, hidden, encoder_outputs):
```

```
        embedded = self.embedding(input).view(1, 1, -1)
```

```
        embedded = self.dropout(embedded)
```

```
        attn_weights = F.softmax(self.attn(torch.cat((embedded[0], hidden[0]), 1)), dim = 1)
```

```
        attn_applied = torch.bmm(attn_weights.unsqueeze(0), encoder_outputs.unsqueeze(0))
```

```
        output = torch.cat((embedded[0], attn_applied[0]), 1)
```

```
        output = self.attn_combine(output).unsqueeze(0)
```

```
        output = F.relu(output)
```

```
        output, hidden = self.gru(output, hidden)
```

```
        output = F.log_softmax(self.out(output[0]), dim = 1)
```

```
        return output, hidden, attn_weights
```

```
    def initHidden(self):
```

```
        return torch.zeros(1, 1, self.hidden_size, device = device)
```

Training

Preparing Training Data

- each pair, we will need an input tensor (indexes of the words in the input sentence)
 - & target tensor (indexes of the words in the target sentence)
- while creating these vectors, we will append the EOS token to both sequences.

```
def indexesFromSentences (lang, sentence):
```

```
    return [lang.word2index[word] for word in sentence.split(' ')]
```

```
def tensorFromSentence (lang, sentence):
```

```
    indexes = indexesFromSentence (lang, sentence)
```

```
    indexes.append (EOS_token)
```

```
    return torch.tensor (indexes, dtype = torch.long, device = device).view(-1, 1)
```

```
def tensorsFromPair (pair)
```

```
    input_tensor = tensorFromSentence (input_lang, pair[0])
```

```
    target_tensor = tensorFromSentence (output_lang, pair[1])
```

```
    return (input_tensor, target_tensor)
```

Training the model

- Encoder

- run the input sentence
- keep track of every output & latest hidden state.

- Decoder

- given the <SOS> token as its first input
- last hidden state of encoder as its first hidden state.

- Teacher forcing

: the concept of using real target outputs as each next input, instead of using the decoder's guess as the next input.

↓

- teacher-forced networks: coherent grammar, but not correct translation

(why?) it has learned to represent the output grammar &

can "pick up" the meaning once the teacher tells it the first few words.

it has not properly learned how to create the sentence from the translation

teacher_forcing_ratio = 0.5

```
def train (input_tensor, target_tensor, encoder, decoder,
           encoder_optimizer, decoder_optimizer, criterion, max_length = MAX_LENGTH):
    encoder_hidden = encoder.initHidden()

    encoder_optimizer.zero_grad()
    decoder_optimizer.zero_grad()

    input_length = input_tensor.size(0)
    target_length = target_tensor.size(0)

    encoder_outputs = torch.zeros (max_length, encoder.hidden_size, device = device)

    loss = 0

    for ei in range (input_length):
        encoder_output, encoder_hidden = encoder (input_tensor [ei], encoder_hidden)
        encoder_outputs [ei] = encoder_output [0,0]

    decoder_input = torch.tensor ([[ SOS_token ]], device = device)
    decoder_hidden = encoder_hidden

    use_teacher_forcing = True if random.random() < teacher_forcing_ratio else False

    if use_teacher_forcing :
        for di in range (target_length):
            decoder_output, decoder_hidden, decoder_attention = decoder(
                decoder_input, decoder_hidden, encoder_outputs)
            loss += criterion (decoder_output, target_tensor [di])
            decoder_input = target_tensor [di] # Teacher forcing
    else :
        # Without teacher forcing: use its own predictions as the next input
        for di in range (target_length):
            decoder_output, decoder_hidden, decoder_attention = decoder(
                decoder_input, decoder_hidden, encoder_outputs)
            topv, topi = decoder_output.*topk(1)
            if topi.item() == EOS_token :
                decode_words.append ('<EOS>')
                break
            else :
                decode_words.append (output_lang.index 2 word [topi.item()])

            decoder_input = topi.squeeze().detach()

    return decode_words, decoder_attentions [: di + 1 ]
```