Defect Types

10 Documentation 60 Checking
20 Syntax 70 Data
30 Build, Package 80 Function
40 Assignment 90 System
50 Interface

100 Environment

## TSPi Defect Recording Log – Form LOGD

Name	นายธนาธิ	นายธนาธิป บุญเนตร				12 ก.ค. 2564	
Team	4			Instructo	r	อ.อภิสิทธิ์ แสงใส	
Part/Level	Function	า (ดูข้อมูลพนัก	างานขับรถ)	Cycle		1 Sprint 7	
Date	Number	Туре	Inject	Remove	Fix Time	Fix Defect	
12 ก.ค. 64	1	60	Code	Compile	15	-	
Description:	ใส่ if-else ผิดทำให้ค่าไม่แสดงออก ในไฟล์ v_driver_infomation						
Date	Number	Туре	Inject	Remove	Fix Time	Fix Defect	
13 ก.ค. 64	2	50	Code	Compile	3	-	
Description: ใส่ Path ผิดในไฟล์ v_driver_infomation ทำให้จอแสดงผลไม่ตรงตามต้องการ							
Date	Number	Туре	Inject	Remove	Fix Time	Fix Defect	
13 ก.ค. 64	3	80	Code	Compile	8	-	
Description:	Description: ลืมใส่ ฟังก์ชัน get_id ในไฟล์ v_driver_detail						

## TSPi Defect Recording Log Instructions – Form LOGD

Purpose	-	Use this form to hold data on the defects you find and correct.
General	-	Keep a separate log for each program component.
	-	Record each defect separately and completely.
	-	If you need additional space, use another copy of the form.
Header	-	Enter your name, date, team name, and instructor's name.
	-	Name the part or assembly and its level.
	-	Enter the cycle number.
Date	-	Enter the date you found the defect.
Number	-	Enter the defect number.
	-	For each program component (or module), use a sequential number
		starting with 1 (or 001, etc.).
Туре	-	Enter the defect type from the defect type list summarized in the
		top left corner of the log form.
	-	See Appendix G for the defect type standard.
	-	Use your best judgment in selecting which type applies.
Inject	-	Enter the phase when this defect was injected.
	-	Use your best judgment.
Remove	-	Enter the phase during which you fixed the defect.
	-	This will generally be the phase when you found the defect.
Fix Time	-	Enter the time you took to fix the defect.
	-	This time can be determined by stopwatch or by judgment.
Fix Defect	-	If you or someone else injected this defect while fixing another
		defect, record the number of the improperly fixed defect.
	-	If you cannot identify the defect number, enter an X in the Fix
		Defect box.
Description	-	Write a succinct description of the defect that is clear enough to
		later remind you about the error and help you to remember why
		you made it.
	-	If the defect was injected in a prior cycle, give the cycle number and
		put an * by the phase injected (i.e. code* or design*).