TSPi Plan Summary - Form SUMP

Name	นางสาวปรีชญา ชูศรีทอง (PM)	D	ate	29 ม.ค. 2565
	นายกล้ายุทธ คลองแก้ว (P)			
Team	4	In	structor	อ.อภิสิทธิ์ แสงใส
Part/Level	System	Cycle		3
Product Size Requirements pages (SRS)		Plan		Actual
		200		274
เอกกสารการประชุม		80		107
High-level design pages (SDS)		50		62
Base LOC (B) (measured) Deleted LOC (D)		0		0
		0		0
Modified LOC (M)		(Estimated)		(Counted)
modified BOC (M)		(Estimated)		(Counted)
Added LOC (A)		0		8,991
Reused LOC (R)		(N-M) ()		(T-B+D-R) 0
		(Estimated)		(Counted)
Total New & Changed LOC (N)		0		0
Total LOC (T)		(Estimated)		(A+M) 8,991
		(N+B-M-D+R)		(Measured)
Total New Reuse LOC		0		0
Estimated Obje				
	on Interval (70%)			
	on Interval (70%)			4 4 10/
Time in Phase (hours)		Plan 60	Actual 60	Actual % 100
Management and miscellaneous Launch and strategy		10	 ไม่ทราบข้อมูล	
		187	176	94.12
Planning Requirements		33	61.24	185.58
Test plan		6	4.25	70.83
Requirements review		23	20.40	88.70
High-level design		15.40	19.40	125.97
High-level design review		8.30	5.47	35.52
Implementation planning		79.10	76.40	194.31
Code		81.2	88.46	108.94
Code review		23.3	20.06	86.09
Compile		ไม่ทราบข้อมูล	ไม่ทราบข้อมูล	ไม่ทราบข้อมูล
Unit test		ไม่ทราบข้อมูล	ไม่ทราบข้อมูล	ไม่ทราบข้อมูล
Build and integration		147.55	156.26	105.9
System test		4	ไม่ทราบข้อมูล	ไม่ทราบข้อมูล
Documentation		308.50	363.39	117.79
Postmortem		180		ไม่ทราบข้อมูล
Total		1166.35	1051.33	90.14
Total Time UPI (70%)				
Total Time LPI (70%)				

TSPi Plan Summary - Form SUMP (continued)

Name	นางสาวปรีชญา ชูศรีทอง (PM)		Date	29 ม.ค. 2565
	้ นายกล้ายุทธ คลองแก้ว (P)			
Team	4		Instructor	อ.อภิสิทธิ์ แสงใส
Part/Level	System		Cycle	3
Defects Injected		Plan	Actual	Actual %
Strategy and Planning		0	0	0
Requirements		0	0	0
System test plan		0	0	0
Requirements inspection		0	0	0
High-level design		0	_ 1	0
Integration test plan		0	0	0
High-level desig	n inspection	0	0	0
Detailed design		0	0	0
Detailed design	review	0	0	0
Test developmen	nt	0	0	0
Detailed design	inspection	0	0	0
Code		80	75	93.45
Code review		0	0	0
Compile		0	0	0
Code inspection		0	0	0
Unit Test		0	1	0
Build and integration		0	0	0
System test		0	0	0
Total Development		80	77	
Defects Removed		Plan	Actual	Actual %
Strategy and Pla	nning	0	0	0
Requirements		0	0	0
System test plan		0	0	0
Requirements inspection		0	0	0
High-level design		0	0	0
Integration test plan		0	0	0
High-level design inspection		0	0	0
Detailed design		0	0	0
Detailed design review		0	0	0
Test development		0	0	0
Detailed design inspection		0	0	0
Code		0	0	0
Code review		0	13	หาค่าไม่ได้
Compile		70	63	90
Code inspection		0	0	0
Unit Test		0	1	0
Build and integration		0	0	0
System test		0	0	0
Total Developm	ent	70	77	
1				

TSPi Plan Summary Instructions - Form SUMP

Purpose	- This form holds plan and actual data for program parts or assemblies.	
General	- An assembly could be a system with multiple products, a product with	
	multiple components, or a component with multiple modules.	
	- A part could be a module, component, or product.	
	- Note: the lowest-level parts or modules typically have no system-level	
	data, such as requirements, high-level design, or system test.	
Using the TSPi Tool	When using the TSPi tool, the plan values are automatically generated.	
	- The time and size data are computed from the TASK and SUMS forms.	
	- The defect values are automatically generated during the quality planning process (SUMQ).	
	The actual values are also automatically generated by the TSPi tool.	
	- Time and size values come from the LOGT, TASK, and SUMS forms.	
	Defect data come from the LOGD forms.	
	When not using the TSPi tool, follow the instructions below.	
Header	- Enter your name, date, team name, and instructor's name.	
	- Name the part or assembly and its level.	
	- Enter the cycle number.	
Columns	- Plan: This column holds the part or assembly plan data.	
	- Actual: For assemblies, this column holds the sum of the actual data for	
	the parts of the assembly (at the lowest level, the modules).	
Product Size	- For text and designs, enter only the new and changed size data.	
	- For program parts or assemblies, enter all the indicated LOC data.	
	- Obtain the data from the SUMS form.	
Time in Phase	- Enter estimated and actual time by phase.	
	- For parts, obtain these data from the TASK forms for those parts.	
	- For assemblies, obtain the part-level time data from the totals on the	
	SUMT form and the assembly-level data from the assembly-level TASK form.	
	- For example, HLD time would come from the assembly TASK form	
	while total part unit test time would come from the SUMT form.	
	- Actual %: Enter the percent of the actual development time by phase.	
Defects Injected	- Enter estimated and actual defects injected by phase.	
	- Enter the defect estimates while producing the quality plan.	
	- For parts, obtain actual data from the LOGD forms for those parts.	
	- For assemblies, get part-level defect data from the totals of the SUMDI	
	form and assembly-level data from the assembly LOGD form.	
	- For example, HLD defects would come from the assembly LOGD form while the total part coding defects would come from the SUMDI form.	
	- Actual %: Enter the percent of the actual defects injected by phase.	
Defects Removed	- Enter estimated and actual defects removed by phase.	
2 Jiens Homorea	- Enter the defect estimates while producing the quality plan.	
	- For parts, obtain actaul data from the LOGD forms for those parts.	
	- For assemblies, obtain part-level defect data from the totals of the	
	SUMDR form and assembly-level data from the assembly LOGD form.	
	- For example, HLD review defects would come from the assembly LOGD	
	form while the total part code review defects would come from the	
	SUMDR form.	
	- Actual %: Enter the percent of the actual defects removed by phase.	