TSPi Defect Recording Log – Form LOGD

Name	ทัศวรรณ แววหงษ์	Date	07 ส.ค. 2564
Team	4	Instructor	อ.อภิสิทธิ์ แสงใส
Part/Level	Function (เพิ่มข้อมูลรถ)	Cycle	1 Sprint 6

Date	Number	Type	Inject	Remove	Fix Time	Fix Defect
07 ก.ค. 64	1	70	Code	Compile	5	-

Description: กำหนดค่า ในไฟล์ Da_cdms_car ผิด

Date	Number	Type	Inject	Remove	Fix Time	Fix Defect
07 ส.ค. 64	2	40	Code	Compile	2	-

Description: เขียนชื่อ Function ผิด car_input เป็น input

Date	Number	Type	Inject	Remove	Fix Time	Fix Defect
08 ส.ค. 64	3	40	Code	Compile	10	-

Description: ลืมใส่ value ให้กับ dropdown ประเภทรถ จังหวัด

Date	Number	Type	Inject	Remove	Fix Time	Fix Defect
08 ส.ค. 64	4	70	Code	Compile	15	-

Description: ลืมเขียนไฟล์ Da_cdms_province และ M_cdms_province

Date	Number	Type	Inject	Remove	Fix Time	Fix Defect
09 ส.ค. 64	5	80	Code	Compile	30	-

Description: เขียนส่งค่า upload รูปภาพผิด

Date	Number	Type	Inject	Remove	Fix Time	Fix Defect
09 ส.ค. 64	6	50	Code	Compile	15	-

Description: ชื่อไฟล์รูปไม่แสดง

TSPi Defect Recording Log Instructions – Form LOGD

Purpose	- Use this form to hold data on the defects you find and correct.
General	- Keep a separate log for each program component. - Record each defect separately and completely. - If you need additional space, use another copy of the form.
Header	- Enter your name, date, team name, and instructor's name. - Name the part or assembly and its level. - Enter the cycle number.
Date	- Enter the date you found the defect.
Number	- Enter the defect number. - For each program component (or module), use a sequential number starting with 1 (or 001, etc.).
Type	- Enter the defect type from the defect type list summarized in the top left corner of the log form. - See Appendix G for the defect type standard. - Use your best judgment in selecting which type applies.
Inject	- Enter the phase when this defect was injected. - Use your best judgment.
Remove	- Enter the phase during which you fixed the defect. - This will generally be the phase when you found the defect.
Fix Time	- Enter the time you took to fix the defect. - This time can be determined by stopwatch or by judgment.
Fix Defect	- If you or someone else injected this defect while fixing another defect, record the number of the improperly fixed defect. - If you cannot identify the defect number, enter an X in the Fix Defect box.
Description	- Write a succinct description of the defect that is clear enough to later remind you about the error and help you to remember why you made it. - If the defect was injected in a prior cycle, give the cycle number and put an * by the phase injected (i.e. code* or design*).