

**PRACTICAL FILE ON**

**INTRODUCTION TO COMPUTERS AND PROGRAMING IN C [ES202]**



**SUBMITTED TO: DR. RAJNI SEHGAL**

**ASSOCIATE PROFESSOR**

**SUBMITTED BY:**

**Name: Ansh Sharma**

**Enrolment number:A2305220407**

**B.Tech. CSE-6**

**COMPUTER SCIENCE AND ENGINEERING AMITY SCHOOL OF  
ENGINEERING & TECHNOLOGY AMITY UNIVERSITY, UTTAR  
PRADESH SESSION- 2020-2021**

## INDEX:

| S. NO. AND NAME OF PROGRAM   | DATE OF EXPERIMENT | DATE OF SUBMISSION | TOTAL MARKS | FACULTY'S SIGNATURE |
|--|--------------------|--------------------|-------------|---------------------|
| 1. (a) Write a C program to add two numbers<br>(b) Write a C program to add three numbers<br><br>2. (a) Write a C program to find area of circle<br>(b) Write a C program to calculate simple interest<br><br>3. Write a C program to print a block F using hash (#), where the F has a height of six characters and width of five and four characters<br><br>4. Write a C program that accepts two item's weight (floating points' values) and number of purchase (floating points' values) and calculate the average value of the items<br><br>5. (a) Write a C program to swap two variables using a third variable<br>(b) Write a C program to swap two variables without using a third variable<br><br>6. (a) Write a C program to convert a given integer (in seconds) to hours, minutes, and seconds.<br>(b) Write a C program to convert specified days into years, weeks, and days. |                    |                    |             |                     |

Note: Ignore leap year.  
Test Data : Number of days : 1329-3 years,33 weeks and 3 days  
(c) Write a C program to check whether a number is even or odd.

7. Write a C program to check whether a given year is Leap year or not

8. (a) Write a C program to check whether a triangle is Equilateral, scalene, or isosceles  
(b) Write a C program to check whether a triangle is right angles, obtuse, acute triangle

9. Write a C program to covert temperature from Fahrenheit to Celsius and Celsius to Fahrenheit (User must provide the choice of type of temperature)

10. (a) Write a C program to check whether a character is an alphabet, digit  
(b) Write a C program a program to check whether an alphabet is a vowel or consonant

11. (a) Write a C program to find smallest of two numbers  
(b) Write a C program to find largest of three numbers

12. Write a program in C to implement Simple Calculator.

|  |  |  |  |  |
|--|--|--|--|--|
| <p>13. WAP to calculate the root of a Quadratic Equation</p> <p>14. WAP to accept a coordinate point in a XY coordinate system and determine in which quadrant the coordinate point lies.</p> <p>15. Write a program to find gross salary of employee if DA is 40% of basic Salary and HRA is 20% of basic salary. Basic salary will be entered as input by keyboard.</p> <p>16. Write a program in C to calculate and print the Electricity bill of a given customer. The customer id and unit consumed by the user should be taken from the keyboard and display the total amount to pay to the customer.</p> <p>upto 199-----1.20<br/> 200-500-----1.80<br/> Above 500-----2.00<br/> If bill exceeds Rs. 400 then a surcharge of 15% will be charged and the minimum bill should be of Rs. 100/-</p> <p>17. A library charges a fine for every book returned late. For first 5 days the fine is 50 paisa, for 6-10 days, fine is one rupee and above 10 days, fine is 5 rupees. If you return the book after 30 days your</p> |  |  |  |  |
|--|--|--|--|--|

membership will be cancelled. Write a program to accept the number of days the member is late to return the book and display the fine or appropriate message.

18. Write a program to find the factorial of any number.

19. Write a program to print Fibonacci sequence 0 1 1 2 3 5 8 13..... N terms and prints the sum of sequence.

20. Write a program in C to accept an integer numbers and find sum of digits.

21. Write a program in C to accept an integer numbers and find reverse of this number and check this number for palindrome

22. Write a program in C to accept an integer numbers and to check a number is Armstrong or not

23. Write a program in C to accept an integer numbers and to check a number is Perfect or not

24. Write a program to find the sum of following series:  
 $S = 2+4+6+8+\dots+N$   
**terms.**

25. Write a program to check a number whether it is prime number or not.

26. Write a program to find the sum of following series:  
 $1 - 1/2 + 1/3 - 1/4 + 1/5 - \dots$  up to n terms.

27. Write a program to find the sum of following series:  
 $1! + 2! + 3! + 4! + \dots + n!$

28. Write a program to find the sum of following series:  
 $S = -13 + 33 - 53 + 73 - 93 + 113 - \dots N$  terms.

29. Write a program to find the sum of following series:  
 $S = 1/1! + 2/2! + 3/3! + \dots$  7 terms.

30. Write a program to convert binary number to decimal number.

31. Write a program to find the sum of following series:  
 $S = 14 + 34 + 54 + 74 + \dots$  100 terms

32. Write a program in C to print the following pattern:

```
* * *  
* * *  
* * *
```

33. Write a program in C to print the following pattern:

1 2 3

1 2 3

1 2 3

34. Write a program in C to print the following pattern:

1 1 1

2 2 2

3 3 3

35. Write a program in C to print the following pattern:

3 2 1

3 2 1

3 2 1

36. Write a program in C to print the following pattern:

3                    3 3

2                    2 2

1                    1 1

37. Write a program in C to print the following pattern:

\*

\*       \*

\*  
\*      \*

38. Write a program in C to print the following pattern:

1  
1      2  
1      2    3

39. Write a program in C to print the following pattern:

1  
2    2  
3   3   3

40. Write a program in C to print the following pattern:

3  
3    2  
3   2   1

41. Write a program in C to print the following pattern:

3  
2    2  
1   1   1

42. Write a program in C to print the following pattern:

\*



```

      *   *   *
    *   *   *   *   *
  *   *   *   *   *   *

```

43. Write a program in C to print the following pattern:

```

  1
 1 2 1
1 2 3 2 1
1 2 3 4 3 2 1

```

44. Write a program in C to print the following pattern:

```

      5
     5 4 5
    5 4 3 4 5
   5 4 3 2 3 4 5
  5 4 3 2 1 2 3 4 5

```

45. Write a program in C to print the following pattern

```

1
0 1
1 0 1
0 1 0 1
1 0 1 0 1

```

46. Write a program to print all prime numbers <= a given number.

47. Write a program to convert Decimal no to Binary No.

48. Write a program to find product, sum, average, max and min from a list of n numbers.

49. Write a program in C to display the index of

|  |  |  |  |  |
|--|--|--|--|--|
| <p>smallest and largest element in 10 integers</p> <p>50. Write a program in C to display the index of smallest and largest element in 3 X 4 matrix of integers.</p> <p>51. Write a program in C that accepts N*N matrix as input and print transpose of this matrix</p> <p>52. Write a program to accept two matrices of some order. (Order must be given by user) find out the sum of these matrices and print the sum of matrices.</p> <p>53. Write a program to find out the product/Multiplication of two matrices and print the product matrix. (order of matrices must be given by user)</p> <p>54. Write a program to accept two matrices of some order. (Order must be given by user) find out the subtraction of these matrices and print the sum of matrices.</p> <p>55. Write a C Program to implement Simple Calculator (Addition, Subtraction, Multiplication, Division) using the concept of function</p> |  |  |  |  |
|--|--|--|--|--|

56. Write a C Program  
to swap two values  
using function

57. Write a C Program  
to Calculate the factorial  
of a number using  
function

58. Write a C Program  
to Calculate the factorial  
of a number using  
recursion

- Q1. (a) Write a C program to add two numbers.  
(b) Write a C program to add three numbers.

(a)

```
#include <stdio.h>

int main()
{
    int n1; int n2; int sum;
    printf("Enter first number:");
    scanf("%d", &n1);
    printf("\n Enter second number:");
    scanf("%d", &n2);
    sum = n1+n2;
    printf("\n The sum of two numbers is %d",sum);

}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter first number:12

Enter second number:12

The sum of two numbers is 24❏
```

(b)

```
#include <stdio.h>
int main()
{
    int n1,n2,n3; int sum;
    printf("Enter first number: ");
    scanf("%d", &n1);
    printf("\n Enter second number: ");
    scanf("%d", &n2);
    printf("\n Enter third number: ");
    scanf("%d", &n3);
    sum = n1+n2+n3;
    printf("\n The sum of two numbers is %d",sum);
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter first number:1

Enter second number:2

Enter third number:3

The sum of two numbers is 6❖ █
```

- Q2. (a) Write a C program to find area of circle  
(b) Write a C program to calculate simple interest

(a)

```
#include <stdio.h>
```

```
main()
```

```
{
```

```
    float r; float ar;
```

```
    printf("Enter radius:\n");
```


```
    scanf("%f", &r);
```

```
    ar = 3.14*r*r;
```

```
    printf("\n The area of the circle is %f ", ar);
```

```
}
```

OUTPUT:



```
Enter radius:
```

```
7
```

```
The area of the circle is 153.860001
```

(b)

```
#include <stdio.h>
int main()
{
    float p,r,t;
    printf("Enter principle:");
    scanf("%f", &p);
    printf("\nEnter rate:");
    scanf("%f", &r);
    printf("\nEnter time:");
    scanf("%f", &t);
    printf("\n Simple Interest: %.2f",p*r*t/100.0);
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter principle:100

Enter rate:8

Enter time:2

Simple Interest: 16.00❏
```

Q3. Write a C program to print a block F using hash (#), where the F has a height of six characters and width of five and four characters.

```
#include <stdio.h>
```

```
int main()
```


```
{
```

```
    printf("#####\n#\n#####\n#\n#\n#\n ");
```

```
    return 0;
```

```
}
```

OUTPUT:



```
#####
#
#####
#
#
#

...Program finished with exit code 0
Press ENTER to exit console.
```



Q4. Write a C program that accepts two item's weight (floating points' values) and number of purchase (floating points' values) and calculate the average value of the items.

```
#include <stdio.h>

int main()
{
    float a,b;
    int n1,n2;
    printf("Enter weight of article 1: ");
    scanf("%f", &a);
    printf("\nEnter weight of article 2: ");
    scanf("%f", &b);
    printf("\nEnter number of article 1: ");
    scanf("%d", &n1);
    printf("\nEnter number of article 2: ");
    scanf("%d", &n2);
    printf("Average: %f",((a*n1)+(b*n2))/(n1+n2));
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter weight of article 1: 12

Enter weight of article 2: 45

Enter number of article 1: 10

Enter number of article 2: 10
Average: 28.500000❖ █
```

- Q5. (a) Write a C program to swap two variables using a third variable.  
(b) Write a C program to swap two variables without using a third variable.

(a)

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a;int b;int t;
```

```
    printf("Enter first number:");
```

```
    scanf("%d",&a);
```

```
    printf("Enter second number:");
```

```
    scanf("%d",&b);
```

```
    t = a;
```

```
    a = b;
```

```
    b = t;
```

```
    printf("Exchanged numbers are: %d , %d",a,b);
```

```
    return 0;
```

```
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter first number:5
Enter second number:8
Exchanged numbers are: 8 , 5❖
```

(b)

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a;int b;int t;
```

```
    printf("Enter first number:")
```

```
    scanf("%d",&a);
```

```
    printf("Enter second number:")
```

```
    scanf("%d",&b);
```

```
    a= a+b;
```

```
    b=a-b;
```

```
    a=a-b;
```

```
    printf("Exchanged numbers are: %d , %d",a,b);
```

```
    return 0;
```

```
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter first number:5
Enter second number:8
Exchanged numbers are: 8 , 5
```

Q6. (a) Write a C program to convert a given integer (in seconds) to hours and minutes.  
(b) Write a C program to convert specified days into years, weeks, and days.  
Note: Ignore leap year. Test Data: Number of days: 1329-3 years,33 weeks and 3 days  
(c) Write a C program to check whether a number is even or odd.

(a)

```
#include <stdio.h>
int main()
{
    int t,h,m,s;
    printf("Enter time in seconds: ");
    scanf("%d", &t);
    h=(int)(t/3600.0);
    m=(t%3600)/60;
    s=(t%3600)%60;
    printf("%dhr %dmin %dsec",h,m,s);
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter time in seconds: 60
0hr 1min 0sec❏
```

(b)

```
#include <stdio.h>
int main()
{
    int t,y,m,d;
    printf("Enter days: ");
    scanf("%d", &t);
    y=(int)(t/365);
    m=(t%365)/7;
    d=(t%365)%7;
    printf("%dyears %dweeks %ddays",y,m,d);
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter days: 30
0years 4weeks 2days❏
```

(c)

```
#include <stdio.h>
int main()
{
    int n;
    printf("Enter number: ");
    scanf("%d", &n);
    if(n%2==0)
        printf("%d is an Even number.",n);
    else
        printf("%d is an Odd number.",n);
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter number: 12
12 is an Even number.❖
```

Q7. Write a C program to check whether a given year is Leap year or not.

```
#include <stdio.h>
int main()
{
    int y;
    printf("Enter year: ");
    scanf("%d", &y);
    if (y % 400 == 0)
        printf("%d is a leap year.", y);
    else if (y % 100 == 0)
        printf("%d is not a leap year.", y);
    else if (y % 4 == 0)
        printf("%d is a leap year.", y);
    else
        printf("%d is not a leap year.", y);
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter year: 2004
2004 is a leap year.❖
```

- Q8. (a) Write a C program to check whether a triangle is Equilateral, scalene, or isosceles.  
(b) Write a C program to check whether a triangle is right angles, obtuse, acute triangle.

(a)

```
#include <stdio.h>
int main()
{
    int a,b,c;
    printf("Enter side 1: ");
    scanf("%d", &a);
    printf("Enter side 2: ");
    scanf("%d", &b);
    printf("Enter side 3: ");
    scanf("%d", &c);
    if (a==b&&b==c)
        printf("EQUILATERAL TRIANGLE");
    else if (a==b||b==c)
        printf("ISOCELES TRIANGLE");
    else
        printf("SCALENE TRIANGLE");
}
```



```
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter side 1: 12
Enter side 2: 12
Enter side 3: 8
ISOCELES TRIANGLE❖
```

(b)

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a,b,c;
```

```
    printf("Enter angle 1: ");
```

```
    scanf("%d", &a);
```

```
    printf("Enter angle 2: ");
```

```
    scanf("%d", &b);
```

```
    printf("Enter angle 3: ");
```

```
    scanf("%d", &c);
```

```
    if(a+b+c==180)
```

```
    {
```

```
        if (a==90||b==90||c==90)
```

```
            printf("RIGHT TRIANGLE");
```

```
        else if (a>90||b>90||c>90)
```

```
            printf("OBTUSE TRIANGLE");
```

```
        else
```

```
            printf("ACUTE TRIANGLE");
```

```
    }
```

```
    else
```

```
        printf("TRIANGLE NOT POSSIBLE!");
```

```
}
```

OUTPUT:

```
> clang-7 -pthread -lm -o main main.c
> ./main
Enter angle 1: 45
Enter angle 2: 45
Enter angle 3: 90
RIGHT TRIANGLE> |
```

Q9. Write a C program to convert temperature from Fahrenheit to Celsius and Celsius to Fahrenheit (User must provide the choice of type of temperature).

```
#include <stdio.h>


int main()
{
    float t,r;
    int ch;
    printf("Enter temp: ");
    scanf("%f",&t);
    printf("Enter 1 for converting fahrenheit to celsius and 2 for vice versa: ");
    scanf("%d",&ch);
    if(ch==1)
    {
        r=(t-32)/1.8;
```

```

    printf("Temperature in celsius: ");
}
else if(ch==2)
{
    r=(1.8*t)+32;
    printf("Temperature in fahrenheit: ");
}
printf("%f",r);
return 0;
}

```

OUTPUT:



```

❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter temp: 98
Enter 1 for converting fahrenheit to celsius and 2 for vice versa: 1
Temperature in celsius: 36.666668❏

```

- Q10. (a) Write a C program to check whether a character is an alphabet OR digit.  
 (b) Write a C program a program to check whether an alphabet is a vowel or consonant.

(a)

```

#include <stdio.h>
int main()
{
    char c;
    printf("Enter character: ");
    scanf("%c",&c);
    if(c>=65&&c<=90||c>=97&&c<=122)
        printf("It is an alphabet.");
    else if(c>=48&&c<=57)
        printf("It is a digit.");
    else
        printf("It is a special character.");
}

```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter character: t
It is an alphabet.❖
```

(b)

```
#include <stdio.h>
int main()
{
    char c;
    printf("Enter character: ");
    scanf("%c",&c);
    if(c>=65&&c<=90 || c>=97&&c<=122)
    {
        if(c=='A' || c=='E' || c=='I' || c=='O' || c=='U' || c=='a' || c=='e' || c=='i' || c=='o' || c=='u')
            printf("%c' is a vowel.",c);
        else
            printf("%c' is a consonant.",c);
    }
    else
        printf("%c' IS NOT AN ALPHABET",c);
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter character: t
't' is a consonant.❏
```


- Q11. (a) Write a C program to find smallest of two numbers.  
(b) Write a C program to find largest of three numbers.

(a)

```
#include <stdio.h>
int main()
{
    int n1,n2;
    printf("Enter number 1: ");
    scanf("%d",&n1);
    printf("Enter number 2: ");
    scanf("%d",&n2);
    if(n1<n2)
        printf("%d is smaller among the two numbers.",n1);
    else if(n2<n1)
        printf("%d is smaller among the two numbers.",n2);
```

```
else
    printf("Numbers are Equal.");
}
```

OUTPUT:



```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter number 1: 12
Enter number 2: 12
Numbers are Equal.❏
```

(b)

```
#include <stdio.h>
int main()
{
    int n1,n2,n3;
    printf("Enter number 1: ");
    scanf("%d",&n1);
    printf("Enter number 2: ");
    scanf("%d",&n2);
    printf("Enter number 3: ");
    scanf("%d",&n3);
    if(n1>n2&& n1>n3)
        printf("%d is the greatest among the three numbers.",n1);
    else if(n2>n1&& n2>n3)
        printf("%d is the greatest among the three numbers.",n2);
    else if(n3>n1&& n3>n2)
        printf("%d is the greatest among the three numbers.",n3);
    else
        printf("Numbers are equal.");
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter number 1: 12
Enter number 2: 45
Enter number 3: 23
45 is the greatest among the three numbers.❏
```

Q12. Write a program in C to implement Simple Calculator.

```
#include <stdio.h>
int main()
{
    char op;
    double a,b;
    printf("Enter an operator (+, -, *, /): ");
    scanf("%c", &op);
    printf("Enter two operands: ");
    scanf("%lf %lf", &a, &b);

    switch (op)
    {
        case '+': printf("%.2lf + %.2lf = %.2lf", a, b, a + b);
                  break;
        case '-': printf("%.2lf - %.2lf = %.2lf", a, b, a - b);
                  break;
        case '*': printf("%.2lf * %.2lf = %.2lf", a, b, a * b);
                  break;
        case '/': printf("%.2lf / %.2lf = %.2lf", a, b, a / b);
                  break;
    }
}
```

```

        default : printf("Error! operator is not correct");
    }
}

```

OUTPUT:

```

❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter an operator (+, -, *, /): +
Enter two operands: 12
45
12.00 + 45.00 = 57.00❏

```

Q13. WAP to calculate the root of a Quadratic Equation.

```

#include <math.h>
#include <stdio.h>
#include <stdlib.h>
void main()
{
    int a,b,c;
    printf("Enter value of a: ");
    scanf("%d",&a);
    printf("Enter value of b: ");
    scanf("%d",&b);
    printf("Enter value of c: ");
    scanf("%d",&c);
    if (a == 0)
    {
        printf("Invalid");
        return;
    }

    int d = b * b - 4 * a * c;

```



```

double sqrt_val = sqrt(abs(d));

if (d > 0)
{
    printf("Roots are real and different \n");
    printf("%f\n%f", (double)(-b + sqrt_val) / (2 * a),
        (double)(-b - sqrt_val) / (2 * a));
}
else if (d == 0)
{
    printf("Roots are real and same \n");
    printf("%f", -(double)b / (2 * a));
}
else
{
    printf("Roots are complex \n");
    printf("%f + i%f\n%f - i%f", -(double)b / (2 * a),
        sqrt_val, -(double)b / (2 * a), sqrt_val);
}
}

```

OUTPUT:

```

Enter value of a: 1
Enter value of b: 2
Enter value of c: 1
Roots are real and same
-1.000000exit status 9

```

Q14. WAP to accept a coordinate point in a XY coordinate system and determine in which quadrant the coordinate point lies.

```

#include<stdio.h>
void main()
{
    int a,b;
    printf("enter the co-ordinates\n");
    printf("Enter value: ");
    scanf("%d",&a);
    printf("Enter value: ");
    scanf("%d",&b);
    int *ptr1=&a;
    int *ptr2=&b;
    if(*ptr1>=0)
    {
        if(*ptr2>=0)
        {
            printf("first quadrant");
        }
        else
        {

```

```

        printf("fourth quadrant");
    }
}
else
{
    if(*ptr2>=0)
    {
        printf("second quadrant");
    }
    else
    {
        printf("third quadrant");
    }
}
}
}

```

OUTPUT:

```

❏ ./main
enter the co-ordinates
Enter value: 12
Enter value: 12
first quadrantexit status 14
❏

```

Q15. Write a program to find gross salary of employee if DA is 40% of basic Salary and HRA is 20% of basic salary. Basic salary will be entered as input by keyboard.

```

#include <math.h>
void main()
{
    float bs;
    printf("Enter basic salary: ");
    scanf("%f",&bs);
    printf("Gross salary: %.2f",(bs+.4*bs+.2*bs));
}

```

OUTPUT:

```

❏ ./main
Enter basic salary: 1000
Gross salary: 1600.00exit status 21

```

Q16. Write a program in C to calculate and print the Electricity bill of a given customer. The customer id and unit consumed by the user should be taken from the keyboard and display the total amount to pay to the customer.

up to 199-----1.20

200-500-----1.80

Above 500-----2.00

If bill exceeds Rs. 400 then a surcharge of 15% will be charged and the minimum bill should be of Rs. 100/-

```
#include <math.h>
void main()
{
    char cid[30];float u,b;
    printf("Enter Customer ID: ");
    scanf("%s",&cid);
    printf("Enter number of units consumed: ");
    scanf("%f",&u);
    if(u<200)
        b=u*1.20;
    else if(u<500)
        b=(199*1.20)+(u-199)*1.80;
    else
        b=(199*1.20)+(301*1.50)+(u-500)*2.00;
    if(b<100)
        printf("BILL\nCUSTOMER ID: %s\nTotal Bill Amount: 100",cid);
```

```

else if(b>400)
    printf("BILL\nCUSTOMER ID: %s\nTotal Bill Amount: %.2f",cid,1.15*b);
else
    printf("BILL\nCUSTOMER ID: %s\nTotal Bill Amount: %.2f",cid,b);
}

```

OUTPUT:

```

Warnings generated:
./main
Enter Customer ID: 1234
Enter number of units consumed: 12
BILL
CUSTOMER ID: 1234
Total Bill Amount: 100exit status 45

```

Q17. A library charges a fine for every book returned late. For first 5 days the fine is 50 paisa, for 6-10 days, fine is one rupee and above 10 days, fine is 5 rupees. If you return the book after 30 days your membership will be cancelled. Write a program to accept the number of days the member is late to return the book and display the fine or appropriate message.

```

#include <math.h>
void main()
{
    int d;
    printf("Enter number of days late: ");
    scanf("%d",&d);
    if(d<=5)
        printf("Your fine is %.2f.",d*.50);
    else if(d<=10)
        printf("Your fine is %.2f.",2.50+(d-5)*1.00);
    else
        printf("Your fine is %.2f.",7.50+(d-10)*5);
    if(d>30)
        printf("\nYOUR MEMBERSHIP IS CANCELLED!");
}

```

OUTPUT:

5 warnings generated.

❏ ./main

Enter number of days late: 12

Your fine is 17.50.**exit status 19**

Q18. Write a program to find the factorial of any number.

```
#include <stdio.h>
```

```
int main(void) {
```

```
    int n;int f=1;
```

```
    printf("Enter number:");
```

```
    scanf("%d",&n);
```

```
    for(int i=n;i>0;--i)
```

```
        f*=i;
```

```
    printf("The factorial of %d is %d.",n,f) ;
```

```
    return 0;
```

```
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter number:5
The factorial of 5 is 120.❖
```

Q19. Write a program to print Fibonacci sequence  
0 1 1 2 3 5 8 13..... N terms and prints the sum of sequence.

```
#include <stdio.h>

int main(void) {
    int n,n1=0,n2=1,n3,sum=1;
    printf("Enter number of terms to be displayed:\n");
    scanf("%d",&n);

    printf("%d,%d",n1,n2);
    for(int i=2;i<n;++i)
    {
        n3=n1+n2;
        sum+=n3;
        printf(",%d",n3);
        n1=n2;
        n2=n3;
    }
    printf("\nSum of these numbers: %d",sum);
}
```

OUTPUT:

```
> clang-7 -pthread -lm -o main main.c
> ./main
Enter number of terms to be displayed:
10
0,1,1,2,3,5,8,13,21,34
Sum of these numbers: 88
```

Q20. Write a program in C to accept an integer numbers and find sum of digits.

```
#include <stdio.h>
int sum=0;
int SoD(int n)
{
    if(n!=0)
    {
        sum+=n%10;
        SoD(n/10);
    }
    return sum;
}

void main()
{
    int n;
```


```

printf("Enter number: ");
scanf("%d",&n);
printf("Sum of Digits of %d is %d. ",n,SoD(n));

}

```

OUTPUT:



```

❯ ./main
Enter number: 123
Sum of Digits of 123 is 6. exit status 27
❯

```

Q21. Write a program in C to accept an integer numbers and find reverse of this number and check this number for palindrome.

```

#include <stdio.h>
int reverse(int n)
{
static int sum=0,rem;
if(n!=0)
{
    rem=n%10;
    sum=sum*10+rem;
    reverse(n/10);
}
return sum;
}

```

```

void main()

```



```

{
int n;
printf("Enter number: ");
scanf("%d",&n);
if(n==reverse(n))
printf("%d is a Palindrome number.",n);
else
printf("%d is not a Palindrome number.",n);
}

```

OUTPUT:

```

Enter number: 121
121 is a Palindrome number.exit status 27

```

Q22. Write a program in C to accept an integer numbers and to check a number is Armstrong or not.

```

#include <math.h>
#include <stdio.h>

int main() {
int n, t, r, a = 0;
float ans = 0.0;
printf("Enter an integer: ");
scanf("%d", &n);
t=n;
for (t = n; t != 0; ++a)
t /= 10;

for (t = n; t != 0; t /= 10)
{
r = t % 10;
ans += pow(r, a);
}
if ((int)ans == n)


```

```

    printf("%d is an Armstrong number.", n);
else
    printf("%d is not an Armstrong number.", n);
return 0;
}

```

OUTPUT:



```

➤ ./main
Enter an integer: 135
135 is not an Armstrong number.➤

```

Q23. Write a program in C to accept an integer numbers and to check a number is Perfect or not.

```

#include <stdio.h>
int main()
{
    int n,r, sum= 0;
    printf("Enter number: ");
    scanf("%d", &n);
    for (int i=1;i<=n/2;++i)
        if(n%i==0)
            sum+=i;
    if(sum==n)
        printf("%d is a Perfect Number.",n);
    else
        printf("%d is not a Perfect Number",n);
}

```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter number: 145
145 is not a Perfect Number❖ █
```

Q24. Write a program to find the sum of following series:  
 $S = 2+4+6+8+\dots+N$  terms.

```
#include <stdio.h>
int main()
{
    int n,sum= 0;
    printf("Enter number of terms to be added : ");
    scanf("%d", &n);
    for (int i=0,k=2;i<n;++i,k+=2)
        sum+=k;
    printf("Sum of the series: %d",sum);
}
```

OUTPUT:

```
➤ clang-7 -pthread -lm -o main main.c
➤ ./main
Enter number of terms to be added : 10
Sum of the series: 110
```

Q25. Write a program to check a number whether it is prime number or not.

```
#include <stdio.h>
```

```
int main(void) {
    int n;int f=0;
    printf("Enter number:");
    scanf("%d",&n);
    for(int i=2;i<=n/2;++i)
    {
        if(n%i==0)
            f=1;
```

```

    }
    if(f==0)
        printf("%d is a Prime number.",n);
    else
        printf("%d is not a Prime number.",n);

}

```

OUTPUT:

```

❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter number:11
11 is a Prime number.❏

```

Q26. Write a program to find the sum of following series:  
 $1 - 1/2 + 1/3 - 1/4 + 1/5 - \dots$  up to n terms.

```

#include <stdio.h>
int main ()
{
    int n;float sum= 0.0;
    printf("Enter number of terms to be added : ");
    scanf("%d", &n);
    for (int i=1;i<=n;++i)
    {
        if(i%2==0)
            sum-=1.0/i;
        else
            sum+=1.0/i;
    }
    printf("Sum of the series: %f",sum);
}

```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter number of terms to be added : 20
Sum of the series: 0.668771❖
```

Q27. Write a program to find the sum of following series:  
 $1! + 2! + 3! + 4! + \dots + n!$

```
#include <stdio.h>
int fact(int a)
{
    if(a==0||a==1)
        return 1;
    else
        return a*fact(a-1);
}
int main()
{
    int n,sum= 0.0;
    printf("Enter number of terms to be added : ");
    scanf("%d", &n);
    for (int i=1;i<=n;++i)
    {
        sum+=fact(i);
    }
}
```

```
    printf("Sum of the series: %d",sum);  
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c  
❏ ./main  
Enter number of terms to be added : 10  
Sum of the series: 4037913❏
```

Q28. Write a program to find the sum of following series:

$S = -1^3 + 3^3 - 5^3 + 7^3 - 9^3 + 11^3 - \dots N \text{ terms.}$

```
#include <stdio.h>
```

```
int main()  
{  
    int n,sum= 0;  
    printf("Enter number of terms to be added : ");  
    scanf("%d", &n);  
    for (int i=1,k=1;i<=n;++i,k+=2)  
    {  
        if(i%2!=0)  
            sum-=k*k*k;  
        else  
            sum+=k*k*k;  
    }  
    printf("Sum of the series: %d",sum);  
}
```

OUTPUT:

```
➤ clang-7 -pthread -lm -o main main.c
➤ ./main
Enter number of terms to be added : 10
Sum of the series: 3970➤ █
```

Q29. Write a program to find the sum of following series:  
 $S = 1/1! + 2/2! + 3/3! + \dots n \text{ terms.}$

```
#include <stdio.h>
float fact(int a)
{
    if(a==0||a==1)
        return 1.0;
    else
        return a*fact(a-1);
}
int main()
{
    int n;float sum= 0.0;
    printf("Enter number of terms to be added : ");
    scanf("%d", &n);
    for (int i=1;i<=n;++i)
    {
        sum+=i/fact(i);
    }
}
```



```
printf("Sum of the series: %f",sum);  
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c  
❏ ./main  
Enter number of terms to be added : 10  
Sum of the series: 2.718282❏
```

Q30. Write a program to convert binary number to decimal number.

```
#include <stdio.h>  
#include <math.h>  
int main()  
{  
    char c[100];int n=-1,dec=0,k=0;  
    printf("Enter number in Binary: ");  
    scanf("%s", &c);  
    for (int i=0;i<100;++i)  
    {  
        if(c[i]=='\0')  
            break;  
        else  
            ++n;  
    }  
  
    for(int i=n;i>=0;--i)  
        dec+=(c[i]-48)*(int)pow(2,k++);  
    printf("The Decimal equivalent of the entered binary is: %d",dec);  
}
```

OUTPUT:

```
> ./main
Enter number in Binary: 11
The Decimal equivalent of the entered binary is: 3>
```

Q31. Write a program to find the sum of following series:  
 $S = 1^4 + 3^4 + 5^4 + 7^4 + \dots$  100 terms

```
#include <stdio.h>

int main()
{
    int sum= 0;

    for (int i=1,k=1;i<=100;++i,k+=2)
        sum+=k*k*k*k;
    printf("Sum of the series: %d",sum);
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Sum of the series: 1932562308❏
```

Q32. Write a program in C to print the given pattern.

```
*      *      *
*      *      *
*      *      *
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=0;i<3;++i)
    {
        for(int j=0;j<3;++j)
            printf("*\t");
        printf("\n");
    }
}
```

OUTPUT:

```
> clang-7 -pthread -lm -o main main.c
```

```
> ./main
```

```
*   *   *  
*   *   *  
*   *   *
```

```
>
```

Q33. Write a program in C to print the given pattern.

```
1   2   3  
1   2   3  
1   2   3
```

```
#include <stdio.h>
```

```
int main()  
{  
    for(int i=0;i<3;++i)  
    {  
        for(int j=1;j<=3;++j)  
            printf("%d\t",j);  
        printf("\n");  
    }  
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
1  2  3
1  2  3
1  2  3
❏
```

Q34. Write a program in C to print the given pattern.

```
1      1      1
2      2      2
3      3      3
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=1;i<=3;++i)
    {
        for(int j=1;j<=3;++j)
            printf("%d\t",i);
        printf("\n");
    }
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
1   1   1
2   2   2
3   3   3
❏
```

Q35. Write a program in C to print the given pattern.

```
3   2   1
3   2   1
3   2   1
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=1;i<=3;++i)
    {
        for(int j=3;j>=1;--j)
            printf("%d\t",j);
        printf("\n");
    }
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
3   2   1
3   2   1
3   2   1
❏
```

Q36. Write a program in C to print the given pattern.

```
3   3   3
2   2   2
1   1   1
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=3;i>=1;--i)
    {
        for(int j=3;j>=1;--j)
            printf("%d\t",i);
        printf("\n");
    }
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
3   3   3
2   2   2
1   1   1
❖
```

Q37. Write a program in C to print the given pattern.

```
•
•   •
•   •   •
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=1;i<=3;++i)
    {
        for(int j=1;j<=i;++j)
            printf("*\t");
        printf("\n");
    }
}
```

OUTPUT:



```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
*
*   *
*   *   *
❏
```

Q38. Write a program in C to print the given pattern.

```
1
1   2
1   2   3
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=1;i<=3;++i)
    {
        for(int j=1;j<=i;++j)
            printf("%d\t",j);
        printf("\n");
    }
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
1
1 2
1 2 3
❏
```

Q39. Write a program in C to print the given pattern.

```
1
2 2
3 3 3
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=1;i<=3;++i)
    {
        for(int j=1;j<=i;++j)
            printf("%d\t",i);
        printf("\n");
    }
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
1
2   2
3   3   3
❏
```

Q40. Write a program in C to print the given pattern.

```
3
3   2
3   2   1
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=3;i>=1;--i)
    {
        for(int j=3;j>=i;--j)
            printf("%d\t",j);
        printf("\n");
    }
}
```

OUTPUT:

```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
3
3 2
3 2 1
❖
```

Q41. Write a program in C to print the given pattern.

```
3
2      2
1      1      1
```

```
#include <stdio.h>
```

```
int main()
{
    for(int i=3;i>=1;--i)
    {
        for(int j=3;j>=i;--j)
            printf("%d\t",i);
        printf("\n");
    }
}
```

OUTPUT:

```

❏ clang-7 -pthread -lm -o main main.c
❏ ./main
3
2  2
1  1  1
❏ █

```

Q42. Write a program in C to print the given pattern.

```

          *
        * *
      * * *
    * * * *
  * * * * *
* * * * *

```

```

#include <stdio.h>
int main()
{
    int i, s, k = 0;
    for (i = 1; i <= 5; ++i, k = 0)
    {
        for (s = 1; s <= 5 - i; ++s)
        {
            printf("\t");
        }
        while (k != 2 * i - 1) {
            printf("*\t");
            ++k;
        }
        printf("\n");
    }
}

```

```

}
}

```

OUTPUT:

```

❖ clang-7 -pthread -lm -o main main.c
❖ ./main
          *
        * * *
      * * * *
    * * * * *
  * * * * * *
* * * * * * *
❖ █

```

Q43. Write a program in C to print the given pattern.

```

          1
        1 2 1
      1 2 3 2 1
    1 2 3 4 3 2 1

```

```
#include <stdio.h>
```

```
void main()
```

```

{
    int i,j;
    for(i=0;i<=5;i++)
    {
        for(j=1;j<=5-i;j++)
            printf("\t");
        for(j=1;j<=i;j++)
            printf("%d\t",j);
        for(j=i-1;j>=1;j--)

```

```

        printf("%d\t",j);
    printf("\n");
}
}

```

OUTPUT:

```

1 warning generated.
❏ ./main
      1
    1 2 1
  1 2 3 2 1
1 2 3 4 3 2 1
1 2 3 4 5 4 3 2 1

```

Q44. Write a program in C to print the given pattern.

```

      5
    5 4 5
  5 4 3 4 5
5 4 3 2 1 2 3 4 5

```

```
#include <stdio.h>
```

```
void main()
```

```

{
    int i=1,j,k,l,m;
    for(i=1,m=5; i<=5,m>=1; i++,m--)

    {
        for(j=5-i; j>=1; j--)
            printf("\t");
        for(k=5; k>=6-i; k--)

```

```

        printf("%d\t",k);
        for(l=m+1; l<=5;l++)
            printf("%d\t",l);
        printf("\n");
    }
}

```

OUTPUT:

```

./main
      5
    5 4 5
  5 4 3 4 5
5 4 3 2 3 4 5
5 4 3 2 1 2 3 4 5

```

45. Write a program in C to print the given pattern.

```

1
0  1
1  0  1
0  1  0  1
1  0  1  0  1

```

```
#include <stdio.h>
```

```

void main()
{
    int i,j;
    for(i=0;i<=6;i++)
    {
        for(j=1;j<i;j++)
        {
            if((i+j)%2==0)
            {
                printf("0\t");
            }
        }
    }
}

```




```

else
{
printf("1\t");
}
}
printf("\n");
}
}

```

OUTPUT:



```

./main

1
0 1
1 0 1
0 1 0 1
1 0 1 0 1

```

Q46. Write a program to print all prime numbers  $\leq$  a given number.

```

#include <stdio.h>
#include <stdbool.h>
bool prime(int n)
{
    int f=0;
    for(int i=2;i<=n/2;++i)
    {
        if(n%i==0)
            f=1;
    }
    if(f==0)
        return true;
    else
        return false;
}

int main()


```

```

{
    int n;
    printf("Enter limit under which prime numbers are to be printed: ");
    scanf("%d",&n);
    for(int i=2;i<=n;++i)
    {
        if(prime(i))
            printf("%d ",i);
    }
}

```

OUTPUT:



```

❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter limit under which prime numbers are to be printed: 10
2 3 5 7 ❖

```

Q47. Write a program to convert Decimal number to Binary Number.


```

#include <stdio.h>
int main()
{
    int n;
    printf("Enter decimal number: ");
    scanf("%d",&n);
    int bin[32];
    int i = 0;
    while (n > 0)
    {
        bin[i] = n % 2;
        n = n / 2;
        i++;
    }
    printf("Binary equivalent for the given decimal number: ");
    for (int j = i - 1; j >= 0; j--)

```

```
        printf("%d",bin[j]);  
    }
```

OUTPUT:



```
> clang-7 -pthread -lm -o main main.c  
> ./main  
Enter decimal number: 10  
Binary equivalent for the given decimal number: 1010>
```

Q48. Write a program to find product, sum, average, max and min from a list of n numbers.

```
#include <stdio.h>  
int main()  
{  
    int n,p=1;float s=0.0;  
    printf("How many elements you want to enter: ");  
    scanf("%d",&n);  
    int arr[n];  
    for(int i=0;i<n;++i)  
    {  
        printf("Enter element %d: ",i+1);  
        scanf("%d",&arr[i]);  
        p*=arr[i];  
        s+=arr[i];  
    }  
    for (int c = 0 ; c < n - 1; c++)  
    {  
        for (int d = 0 ; d < n - c - 1; d++)  
        {
```

```

        if (arr[d] > arr[d+1])
        {
            int swap    = arr[d];
            arr[d]    = arr[d+1];
            arr[d+1] = swap;
        }
    }
}

printf("Product of elements: %d\nSum of elements: %d\nAverage of elements:
%f\nMaximum Value: %d\nMinimum Value: %d",p,(int)s,s/n,arr[n-1],arr[0]);
}

```

OUTPUT:

```

How many elements you want to enter: 2
Enter element 1: 12
Enter element 2: 9
Product of elements: 108
Sum of elements: 21
Average of elements: 10.500000
Maximum Value: 12
Minimum Value: 9

```

Q49. Write a program in C to display the index of smallest and largest element in 10 integers.

```

#include <stdio.h>
int main()
{
    int a[10];
    for(int i=0;i<10;++i)
    {
        printf("Enter element %d: ",i);
        scanf("%d",&a[i]);
    }
    int s=0,h=0;
    for(int i=1;i<10;++i)
    {
        if(a[i]>a[h])
            h=i;
        else if(a[i]<a[s])
            s=i;
    }
    printf("Index of highest number: %d\nIndex for lowest number: %d",h,s);
}

```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
❏ ./main
Enter element 0: 10
Enter element 1: 21
Enter element 2: 12
Enter element 3: 35
Enter element 4: 123
Enter element 5: 483
Enter element 6: 1074
Enter element 7: 297
Enter element 8: 32097
Enter element 9: 287
Index of highest number: 8
Index for lowest number: 0❏
```

Q50. Write a program in C to display the index of smallest and largest element in 3 X 4 matrix of integers.

```
#include <stdio.h>
void main()
{
    int a[3][4];
    for(int i=0;i<3;++i)
    {
        for(int j=0;j<4;++j)
        {
            printf("Enter element: ");
            scanf("%d",&a[i][j]);
        }
    }
    int h=0, hh=0, s=0, ss=0;
    for(int i=0;i<3;++i)
    {
        for(int j=0;j<4;++j)
        {
            if(a[i][j]>a[h][hh])
```

```

        {h=i;hh=j;}
    else if(a[i][j]<a[h][hh])
        {s=i;ss=j;}
    }
}
printf("Index of highest number: (%d,%d)\nIndex of smallest number: (%d,%d)",h,hh,s,ss);
}
OUTPUT:

```

```

❏ ./main
Enter element: 10
Enter element: 193
Enter element: 983269
Enter element: 234
Enter element: 2345
Enter element: 5745
Enter element: 435
Enter element: 346543
Enter element: 35476
Enter element: 687
Enter element: 345
Enter element: 2
Index of highest number: (0,2)
Index of smallest number: (2,3)exit status 62
❏

```

Q51. Write a program in C that accepts N\*N matrix as input and print transpose of this matrix.

```

#include <stdio.h>
void main()
{
    int n;
    printf("Enter size: ");
    scanf("%d",&n);
    int a[n][n];
    for(int i=0;i<n;++i)
    {
        for(int j=0;j<n;++j)
        {
            printf("Enter element: ");
            scanf("%d",&a[i][j]);
        }
    }
    printf("TRANSPOSE OF THE MATRIX IS:\n");
    for(int i=0;i<n;++i)
    {
        for(int j=0;j<n;++j)

```

```

        printf("%d\t",a[j][i]);
    printf("\n");
}
}

```

OUTPUT:

```

./main
Enter size: 3
Enter element: 1
Enter element: 2
Enter element: 3
Enter element: 4
Enter element: 5
Enter element: 6
Enter element: 7
Enter element: 8
Enter element: 9
TRANSPOSE OF THE MATRIX IS:
1  4  7
2  5  8
3  6  9

```

Q52. Write a program to accept two matrices of some order. (Order must be given by user) find out the sum of these matrices and print the sum of matrices.

```

#include <stdio.h>
void main()
{
    int m,n;
    printf("Enter size: ");
    scanf("%d %d",&m,&n);
    int a[m][n],b[m][n];
    printf("ENTER ELEMENTS FOR MATRIX 1\n");
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
        {
            printf("Enter element : ");
            scanf("%d",&a[i][j]);
        }
    }
    printf("\nENTER ELEMENTS FOR MATRIX 2\n");

```

```
for(int i=0;i<m;++i)
{
for(int j=0;j<n;++j)
{
printf("Enter element : ");
scanf("%d",&b[i][j]);
}
}
printf("SUM OF THE MATRICES IS:\n");
for(int i=0;i<m;++i)
{
for(int j=0;j<n;++j)
printf("%d\t",a[i][j]+b[i][j]);
printf("\n");
}
}
```

OUTPUT:



```
➤ ./main
Enter size: 3
3
ENTER ELEMENTS FOR MATRIX 1
Enter element : 1
Enter element : 2
Enter element : 3
Enter element : 4
Enter element : 5
Enter element : 6
Enter element : 7
Enter element : 8
Enter element : 9

ENTER ELEMENTS FOR MATRIX 2
Enter element : 1
Enter element : 2
Enter element : 3
Enter element : 4
Enter element : 5
Enter element : 6
Enter element : 7
Enter element : 8
Enter element : 9
SUM OF THE MATRICES IS:
2  4  6
8  10 12
14 16 18
```

Q53. Write a program to find out the product/Multiplication of two matrices and print the product matrix. (order of matrices must be given by user).

```
#include <stdio.h>
```

```

void main()
{
    int m,n;
    printf("Enter size: ");
    scanf("%d %d",&m,&n);
    int a[m][n],b[m][n],c[m][n];
    printf("ENTER ELEMENTS FOR MATRIX 1\n");
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
        {
            printf("Enter element : ");
            scanf("%d",&a[i][j]);
        }
    }
    printf("\nENTER ELEMENTS FOR MATRIX 2\n");
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
        {
            printf("Enter element : ");
            scanf("%d",&b[i][j]);
        }
    }
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
        {
            c[i][j]=0;
            for(int k=0;k<n;++k)
                c[i][j]+=a[i][k]*b[k][j];
        }
    }
    printf("\nPRODUCT OF THE MATRICES:\n");
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
            printf("%d\t",c[i][j]);
        printf("\n");
    }
}
OUTPUT:

```

```
➤ ./main
Enter size: 2
2
ENTER ELEMENTS FOR MATRIX 1
Enter element : 1
Enter element : 2
Enter element : 3
Enter element : 4

ENTER ELEMENTS FOR MATRIX 2
Enter element : 5
Enter element : 6
Enter element : 7
Enter element : 8

PRODUCT OF THE MATRICES:
19 22
43 50
```

Q54. Write a program to accept two matrices of some order. (Order must be given by user) find out the subtraction of these matrices and print the sum of matrices.

```

#include <stdio.h>
void main()
{
    int m,n;
    printf("Enter size: ");
    scanf("%d %d",&m,&n);
    int a[m][n],b[m][n];
    printf("ENTER ELEMENTS FOR MATRIX 1\n");
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
        {
            printf("Enter element : ");
            scanf("%d",&a[i][j]);
        }
    }
    printf("\nENTER ELEMENTS FOR MATRIX 2\n");
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
        {
            printf("Enter element : ");
            scanf("%d",&b[i][j]);
        }
    }
    printf("DIFFERENCE OF THE MATRICES IS:\n");
    for(int i=0;i<m;++i)
    {
        for(int j=0;j<n;++j)
            printf("%d\t",a[i][j]-b[i][j]);
        printf("\n");
    }
}

```

OUTPUT:

```
➤ ./main
Enter size: 2
2
ENTER ELEMENTS FOR MATRIX 1
Enter element : 1
Enter element : 2
Enter element : 3
Enter element : 4

ENTER ELEMENTS FOR MATRIX 2
Enter element : 5
Enter element : 6
Enter element : 7
Enter element : 8
DIFFERENCE OF THE MATRICES IS:
-4  -4
-4  -4
```

Q55. Write a C Program to implement Simple Calculator (Addition, Subtraction, Multiplication, Division) using the concept of function.

```
#include <stdio.h>
void add(double a,double b)
{
    printf("%.2lf + %.2lf = %.2lf", a, b, a + b);
}
void sub(double a,double b)
{
    printf("%.2lf - %.2lf = %.2lf", a, b, a - b);
}
void pro(double a,double b)
{
    printf("%.2lf * %.2lf = %.2lf", a, b, a * b);
}
void div(double a,double b)
{
    printf("%.2lf / %.2lf = %.2lf", a, b, a / b);
}
int main()
{
    char op;
    double a,b;
    printf("Enter an operator (+, -, *, /): ");
    scanf("%c", &op);
    printf("Enter two operands: ");
    scanf("%lf %lf", &a, &b);

    switch (op)
    {
        case '+': add(a,b);
                break;
        case '-': sub(a,b);
                break;
        case '*': pro(a,b);
                break;
        case '/': div(a,b);
                break;
        default : printf("Error! operator is not correct");
    }
}
```

OUTPUT:

```
❏ clang-7 -pthread -lm -o main main.c
```



```
❏ ./main
```

```
Enter an operator (+, -, *, /): -
```

```
Enter two operands: 23
```

```
45
```

```
23.00 - 45.00 = -22.00❏
```


Q56. Write a C Program to swap two values using function.

```
#include <stdio.h>

void swap(int a,int b)
{
    a=a+b;
    b=a-b;
    a=a-b;
    printf("Swapped: %d %d",a,b);
}

int main(void) {
    int a,b;
    printf("Enter two numbers: ");
    scanf("%d",&a);
    scanf("%d",&b);
    swap(a,b);
    return 0;
}
```

OUTPUT:

A terminal window with a dark background. It shows the compilation of a C program using 'clang-7' with flags '-pthread -lm -o main main.c'. Then, it runs './main'. The program prompts 'Enter two numbers: 12' and '223'. Finally, it outputs 'Swapped: 223 12' followed by a cursor.


```
❖ clang-7 -pthread -lm -o main main.c
❖ ./main
Enter two numbers: 12
223
Swapped: 223 12❖
```



Q57. Write a C Program to Calculate the factorial of a number using function.

```
#include <stdio.h>
int fact(int n)
{
    int f=1;
    if(n==0||n==1)
        return 1;
    else
    {
        for(int i=n;i>0;--i)
            f*=i;
        return f;
    }
}
int main()
{
    int n;
    printf("Enter number: ");
    scanf("%d",&n);
    printf("Factorial of %d is: %d",n,fact(n));
}
```

OUTPUT:




```
> clang-7 -pthread -lm -o main main.c
> ./main
Enter number: 5
Factorial of 5 is: 120
```

Q58. Write a C Program to Calculate the factorial of a number using recursion.

```
#include <stdio.h>
int fact(int n)
{
    if(n==0||n==1)
        return 1;
    else
        return n*fact(n-1);
}
int main()
{
    int n;
    printf("Enter number: ");
    scanf("%d",&n);
    printf("Factorial of %d is: %d",n,fact(n));
}
```

OUTPUT:



```
❯ clang-7 -pthread -lm -o main main.c
❯ ./main
Enter number: 5
Factorial of 5 is: 120❯
```