

# Source code audit speed run

Bsides Canberra 2019

xen1thLabs

A DARKMATTER COMPANY

SMART AND SAFE DIGITAL

# Content

**01 Introduction**

**02 Theory**

**03 Vulnerabilities**

**04 Auditing**

**05 Vulnerability speed run**

**06 Conclusion**

# 01

## Introduction

# Source code review

---

“

---

**Code review** (sometimes referred to as peer **review**) is a software quality assurance activity in which one or several humans check a program mainly by viewing and reading parts of its source **code**, and they do so after implementation or as an interruption of implementation.

---

*Wikipedia*

“

---

**Security code review** is the process of auditing the source code for an application to verify that the proper security controls are present, that they work as intended, and that they have been invoked in all the right places.

---

*OWASP*

“

---


**Speed run** is a play-through (or a recording thereof) of a video game performed with the intention of completing it as fast as possible.

---

*Wikipedia*

Introduce concepts to  
identify vulnerabilities in  
source code **fast**

**YOU GET A CVE AND YOU  
GET A CVE AND YOU AND YOU**



**EVERYONE GETS A CVE**

`whoami`

---



**Eldar Marcussen**  
Lead security researcher

Proven history of performing security research that result in 0day vulnerabilities, conference presentation and security tools. I have written a source code scanner and auditing source code is often part of my security research process. My past research and security tools have also featured in industry related cyber security text books.

A former

Developer

System administrator

Penetration tester

Currently

Husband and Father

Security researcher

Trainer

# 02

## Theory




# Code review is a skill

-- The Art Of Software Security Assessment

# Skills and knowledge

---



```

while (1) {
    unsigned int time_stamp;
    char luggage_id[LUGGAGE_ID_LENGTH + 1];
    char flight_id[FLIGHT_ID_LENGTH + 1];
    char departure[AIRPORT_CODE_LENGTH + 1];
    char arrival[AIRPORT_CODE_LENGTH + 1];
    char comments[COMMENTS_LENGTH + 1];
    comments[0] = 0; // comments are optional.

    if (scanf("%d ", &time_stamp) == EOF) {
        break;
    }
    if (scanf("%8[A-Z0-9] %6[A-Z0-9] ",
        luggage_id, flight_id) == EOF) {
        break;
    }
    if (scanf("%3[A-Z] %3[A-Z]", departure, arrival) == EOF) {
        break;
    }
    if (scanf("%80[^\n]", comments) == EOF) {
        break;
    }

    RoutingDirective *new_directive =
        (RoutingDirective*) calloc(1, sizeof(RoutingDirective));
    new_directive->time_stamp = time_stamp;
    strcpy(new_directive->luggage_id, luggage_id);
    strcpy(new_directive->flight_id, flight_id);
}

```

comments

```
    ", &time_stamp) == EOF;  
    if (ferror(fp))  
        return 0;  
    if (fscanf(fp, "%8[A-Z0-9] %6[A-Z0-9] ",  
               page_id, flight_id) ==
```

# Theory

---

## Considerations

- Systems don't exist in a vacuum
  - Race conditions
  - PHP configuration
- Compiler optimizations can introduce vulnerabilities



## Limitations

- Dynamic evaluation
- Callbacks
- Dynamic data operations



# Flow

---

Flow is fundamental to understanding not just code, but how the various components interact




Data flow is how data is advanced through the system

Control flow is the order in which individual statements, instructions or function calls are executed

Consider interruptions to flow

# Code flow graph



# Flow

---

## Source

- The origin of the data as it enters the flow is the **"source"**
- Usually we only care about sources that introduce untrusted or user supplied data
- **Identifying user controlled data is not always simple**

## Sink

- The function that the data ends up in is the **"sink"**
- The only sinks worth tracking is functions that must receive clean data
- **The source to sink flow may not direct or even intended to exist**

## Other

- Trust boundaries
- State change



# Taint analysis

---

```
#include <string.h>

void hello (char *n) {
    char name[40];
    strcpy(name, n);
}

int main (int argc, char **argv) {
    hello(argv[1]);
    return 0;
}
```

# Taint analysis

---

```
#include <string.h>
```

```
void hello (char *n) {
```

```
    char name[40];
```

```
    strcpy(name, n);
```

```
}
```

```
int main (int argc, char **argv) {
```

```
    hello(argv[1]);
```

```
    return 0;
```

```
}
```

A green line with arrows at both ends illustrates the flow of data. It starts at the argument 'argv[1]' in the 'hello(argv[1]);' call within the 'main' function. The line extends upwards and to the left, then curves downwards to point at the 'n' parameter in the 'strcpy(name, n);' call inside the 'hello' function. This indicates that the string pointed to by 'argv[1]' is being copied into the 'name' array.

# Approaches

---

Hot spot  
checking




Control flow  
sensitive




Data flow  
sensitive



Focus  
oriented



Forward  
tracing



Backwards  
tracing



# 03

## Vulnerabilities

# Vulnerability

---

“

The existence of a weakness, design, or implementation error that can lead to an unexpected, undesirable event compromising the security of the computer system, network, application, or protocol involved.

*ENISA*

# Vulnerability classification

---

## OWASP Top10

- While some are broad, it is only 10 categories of bugs
- Semi-static
- Based on commonality, not risk or impact
- Silos
  - Top10 Web
  - Top10 Mobile
- <https://www.owasp.org/>

## Common Weakness Enumeration (CWE)

- Has classified 716 software weaknesses
- Typically has a good definition with source code examples and description
- <https://cwe.mitre.org/>

## Other

- Web Application Security Consortium
- Detailed advisories
- White papers
- Conference presentations

# Identifying weaknesses

---



- Read the documentation
- Learn to recognize weakness patterns in source code
- Learn to recognize weakness patterns in design/process
- Anticipate poor decision making
- Implement short test cases to verify behavior if unsure
- Take breaks from complex/difficult code

# Presence of something

---

**The code contains a flaw**

**Logical or functional**

Examples:

Insecure  
default variable  
value

Format string

Double free()





# Absence of something

---

**When the lack of code causes the vulnerability**

Examples:

Not halting  
execution

Not encoding user  
supplied output in  
html/javascript/  
whatever context

Not using  
boundary  
checks



# 04

## Auditing

# Objectives

---

1

Identify weaknesses

---

2

Prioritize high impact vulnerabilities

---

3

Check exploitability

# Tools

---

- STATIC SOURCE CODE ANALYSIS TOOLS
  - <https://github.com/mre/awesome-static-analysis>
  - [https://www.owasp.org/index.php/Source\\_Code\\_Analysis\\_Tools](https://www.owasp.org/index.php/Source_Code_Analysis_Tools)
- **GREP**
- TOOLS CANNOT FIND SOME TYPES OF VULNERABILITIES
- **HUMAN ANALYSIS IS REQUIRED**



# Not greps

---

Ack

Ag  
(the silver  
searcher)

ripgrep

more

# Benefits of grep

---



- + Can be used on incomplete code
- + Cross platform support
- + Text matching supports most programming languages
- + Easy support for templating languages of custom framework APIs
- + Regular expression support for better matching
- + Text matching supports most programming languages
- + Presents user with code view
- + Versatile use due to large number of command line options

# memsad

---

```
memset[:space:]*\([^,]+,[[:0,.*\]);  
memset[:space:]*\([^,]+,[^,]+,[[:space:]]*0\);
```

# Wordpress rules

---

`_weak_escape`

`_do_query`

`\$_(GET|POST|REQUEST|COOKIE|SERVER)`

`\$[^\\,\\;\\(\\> ]+\\->prepare[[:space:]]*\\(.*\\$.*`

`\$[^\\,\\;\\(\\> ]+\\->get_(row|col|var|results).*\\$.*`

`\$[^\\,\\;\\(\\> ]+\\->get_param.*\\$.*`

`\$[^\\,\\;\\(\\> ]+\\->get_body_param.*\\$.*`

`\$[^\\,\\;\\(\\> ]+\\->get_header.*`

`\$[^\\,\\;\\(\\> ]+\\->get_json_params.*`

`\$[^\\,\\;\\(\\> ]+\\->get_file_params.*`

`\$[^\\,\\;\\(\\> ]+\\->get_query_param.*`



# Regular expressions

WHENEVER I LEARN A NEW SKILL I CONCOCT ELABORATE FANTASY SCENARIOS WHERE IT LETS ME SAVE THE DAY.

OH NO! THE KILLER MUST HAVE FOLLOWED HER ON VACATION!



BUT TO FIND THEM WE'D HAVE TO SEARCH THROUGH 200 MB OF EMAILS LOOKING FOR SOMETHING FORMATTED LIKE AN ADDRESS!



IT'S HOPELESS!

EVERYBODY STAND BACK.



I KNOW REGULAR EXPRESSIONS.



# Rules/Regular expressions


---

require

require\(.\*\\$..\*\);

(require|require\_once)\(.\*\\$..\*\);

require(\_once)?[[:space:]]\*(\\(|\\'|\\").\*\\\$\_(GET|POST|REQUEST|ENV|COOKIE).\*\\(|\\'|\\")\\;



# Taint analysis with grep

---

```
#!/bin/sh
# PHP taint checking with graudit - PoC script
# Written by Wireghoul - http://www.justanotherhacker.com
# Released under the GPL licence
VERSION=0.1
if [ -z "$1" ]; then
    echo "Usage: $0 /path/to/check"
    exit 2
fi
graudit -z -d php "$1" | \
perl -ne 'if ($_ =~ m/\$(\S+?)\s*=\s*\$_(GET|POST|REQUEST|COOKIE)\[.*?\]/) { print "\\$1\n"; }' | \
sort | uniq | \
graudit -d - "$1"
```

# Quickly build custom scripts

---

```
#!/bin/sh
echo "function.*__(wakeup|destruct|autoload)[[:space:]]*\\(\" | \
graudit -x *.js -d - -- -A 20 $1 | \
graudit -c 30 -d php -
```

# 05

## Vulnerability speed run

# Computer time

```
ubuntu ~/bsides ls
a2billing-develop FoolFuuka-master lwan-master pgpooladmin-3_7_0 rac-master
AdminLTE-master Froxlor-master MadelineProto-master pgpooladmin-4_0_0 RadiusAdmin-master
akismet Gearman-Monitor-master microweber-master pgpooladmin-master RedisMyAdmin-master
assetic-master GetSimpleCMS-master Monitoring-master pgpool-II-4.0.0 rockmongo-master
ASTPP-3.6 glpi-9.4-bugfixes Monocypher-master phpbu-master rosariosis-mobile
bike-master guacamole-server-master mumble-master phpipam-master server-status-master
bitcoind-status-master heartland-php MyWebSQL-master phpLDAPadmin-master ServerStatus-master
Bitcoin-mining-proxy-master hotelmanagement-master Nagdash-master php-malware-scanner-master Simple-Web-Server-master
bitcoin-php-master intersango-master nginx-rtmp-module-master phpmemcachedadmin-master sulu-standard-develop
centreon-master Kliqqi-CMS-master openlitespeed-master phppgadmin-master supervisord-monitor-master
cms-dev LampCMS-master openstamanager-master phpRedisAdmin-master Tattle-master
cms-master libmbus-master OpenVPN-Admin-master phpservermon-develop typemill-master
CMS-master librenms-master out Picasso-master woocommerce-master
contact-form-7 libsndfile-master out-justc Pico-master wordpress-seo
Cosmo-master libssh2-master PAMI-master pinboard-master yubikey-personalization-master
deltachat-core-master ls-module-merchantwarrior-master pdnsmanager-master Provisioner-master
easyhadoop-master
ubuntu ~/bsides du -sh .
1.3G .
```

# Computer time

```
ubuntu ~/bsides ls
a2billing-develop FoolFuuka-master lwan-master pgpooladmin-3_7_0 rac-master
AdminLTE-master Froxlor-master MadelineProto-master pgpooladmin-4_0_0 RadiusAdmin-master
akismet Gearman-Monitor-master microweber-master pgpooladmin-master RedisMyAdmin-master
assetic-master GetSimpleCMS-master Monitoring-master pgpool-II-4.0.0 rockmongo-master
ASTPP-3.6 glpi-9.4-bugfixes Monocypher-master phpbu-master rosariosis-mobile
bike-master guacamole-server-master mumble-master phpipam-master server-status-master
bitcoind-status-master heartland-php MyWebSQL-master phpLDAPadmin-master ServerStatus-master
Bitcoin-mining-proxy-master hotelmanagement-master Nagdash-master php-malware-scanner-master Simple-Web-Server-master
bitcoin-php-master interspace-master nginx-rtmp-module-master phpmemcachedadmin-master sulu-standard-develop
centreon-master
cms-dev
cms-master
CMS-master
contact-form-7
Cosmo-master
deltachat-core-master
easyhadoop-master
ubuntu ~/bsides du -sh .
1.3G .
real    0m6.051s
user    0m5.584s
sys     0m0.473s
ubuntu ~/bsides 2
```

# Computer time

```
ubuntu ~/bsides ls
a2billing-develop FoolFuuka-master lwan-master pgpooladmin-3_7_0 rac-master
AdminLTE-master Froxlor-master MadelineProto-master pgpooladmin-4_0_0 RadiusAdmin-master
akismet Gearman-Monitor-master microweber-master pgpooladmin-master RedisMyAdmin-master
assetic-master GetSimpleCMS-master Monitoring-master pgpool-II-4.0.0 rockmongo-master
ASTPP-3.6 glpi-9.4-bugfixes Monocypher-master phpbu-master rosariosis-mobile
bike-master guacamole-server-master mumble-master phpipam-master server-status-master
bitcoind-status-master heartland-php MyWebSQL-master phpLDAPadmin-master ServerStatus-master
Bitcoin-mining-proxy-master hotelmanagement-master Nagdash-master php-malware-scanner-master Simple-Web-Server-master
bitcoin-php-master interspace-master nginx-rtmp-module-master phpmemcachedadmin-master sulu-standard-develop
centreon-master
cms-dev
cms-master
CMS-master
contact-form-7
Cosmo-master
deltachat-core-master
easyhadoop-master
```

```
ubuntu ~/bsides time ~/graudit/graudit -d flatline . > ../grout.txt
/bin/grep: ./phpipam-master/functions/locale/cs_CZ.UTF8/cs_CZ.UTF8: Too many levels of symbolic links
/bin/grep: ./phpipam-master/functions/locale/cs_CZ.UTF-8/cs_CZ.UTF8: Too many levels of symbolic links
/bin/grep: ./phpipam-master/functions/locale/cs/cs_CZ.UTF8: Too many levels of symbolic links
/bin/grep: ./phpipam-master/functions/locale/cs_CZ/cs_CZ.UTF8: Too many levels of symbolic links
real    0m6.051s
user    0m5.584s
sys     0m0.473s
ubuntu ~/bsides 2
```


```
ubuntu ~/bsides time find . -name "*.c" -exec ~/flatline/cpptaint.sh {} \; | xargs -n1 ~/flatline/b0ftaint.sh > out-justc
real    0m15.490s
user    0m23.138s
sys     0m4.328s
```




# Improving human processing time

---

- AVOID FALSE POSITIVES
- THIS MIGHT MEAN MISSING VULNERABILITIES (false negatives)
  - You can always take another look later
- SHORTLIST OF VULNERABILITY CLASSES
  - Easy to analyse
  - Avoid drowning in XSS
  - Rules can be tweaked to match the worst developer habits





grep rough audit - static analysis tool  
v2.1 written by @Wireghoul

===== [justanotherhacker.com] =====

```
index.php-78-      <meta name="Description" content="">
index.php-79-      <meta name="title" content="<?php print $title = $User->get_site_title ($_GET); ?>">
index.php-80-      <meta name="robots" content="noindex, nofollow">
#####
index.php-265-          print "<td id='subnetsLeft'>";
index.php:266-          print "<div id='leftMenu' class='menu-$_GET[page]'>";
index.php-267-              if($_GET['page'] == "subnets" || $_GET['page'] == "vlan" ||
#####
index.php-276-          print "<td id='subnetsContent'>";
index.php:277-          print "<div class='row menu-$_GET[page]' id='content'>";
index.php-278-              # subnets
#####
index.php-298-
index.php:299-          if(file_exists("app/tools/$_GET[section]/index.php")) {
index.php-300-              include("app/tools/$_GET[section]/index.php");
index.php-301-          }
index.php:302-          else {
index.php-303-              include("app/tools/custom/$_GET[section]/index.php");
          }
```

# SSL/TLS Validation Failure

---

```
grep -rsE 'CURLOPT_SSL_VERIFY(Peer|HOST|STATUS).*([Ff][Aa][Ll][Ss][Ee]|0)' .
```

# SSL/TLS Validation Failure

```
grep -rsE 'CURLOPT_SSL_VERIFY(PER|
```

Repositories	0
Code	3
Commits	635
Issues	2
Marketplace	0
Topics	0
Wikis	0
Users	0

[Advanced search](#) [Cheat sheet](#)

635 commit results Sort: Best match ▾

added `CURLOPT_SSL_VERIFYPEER = false` on curl request to bypass ssl ve...

456dce6 <>

glauberportella committed to `glauberportella/skyhub-php` on Jul 29, 2018 ✓

Added `CURLOPT_SSL_VERIFYHOST = false` when `verify_ssl === false`.

8a9dcf5 <>

RAMPKORV committed to `Textalk/xJsonRpc-PHP` on May 12, 2014

Merge pull request #1 from RAMPKORV/master

7fe9d02 <>

fiddur committed to `Textalk/xJsonRpc-PHP` on May 16, 2014

SSL Certificate Verification ...

f2d92d5 <>

thiagof committed to `nFnK/JsonRPC` on Jan 19, 2015

SSL Certificate Verification ...

f2d92d5 <>

thiagof committed to `matasare/JsonRPC` on Jan 19, 2015

ADD: honor `verify_peer_name` in `stream_context`

c881856 <>

apeabody authored and Hhvm Bot committed to `Vxychen/facebook_hhvm_c-` on Jul 12, 2016



5b47bdee23f3f23f180

```

./Provisioner-master/samples/Pest.php:14:    CURLOPT_SSL_VERIFYPEER => false, // stop cURL from verifying the peer's certificate
./Provisioner-master/samples/Pest.php:15:    CURLOPT_FOLLOWLOCATION => true, // follow redirects, Location: headers
#####
./bitcoind-status-master/php/functions.php:344-
./bitcoind-status-master/php/functions.php:345:    curl_setopt($curl_handle, CURLOPT_SSL_VERIFYPEER, false);
./bitcoind-status-master/php/functions.php:346-    curl_setopt($curl_handle, CURLOPT_RETURNTRANSFER, true);
#####
./bitcoind-status-master/php/easybitcoin.php:164-    // so we set this flag to FALSE to allow the connection
./bitcoind-status-master/php/easybitcoin.php:165:    $options[CURLOPT_SSL_VERIFYPEER] = false;
./bitcoind-status-master/php/easybitcoin.php:166-    }
#####
./openstamanager-master/lib/util.php:524-    }
./openstamanager-master/lib/util.php:525:    curl_setopt($c, CURLOPT_SSL_VERIFYHOST, false);
./openstamanager-master/lib/util.php:526:    curl_setopt($c, CURLOPT_SSL_VERIFYPEER, false);
./openstamanager-master/lib/util.php:527-    curl_setopt($c, CURLOPT_COOKIE, 'CookieName=Value;');
#####
./openstamanager-master/plugins/exportFE/src/FatturaElettronica.php:223-    // Configurazione per localhost: CURLOPT_SSL_VERIFYPEER
./openstamanager-master/plugins/exportFE/src/FatturaElettronica.php:224:    $client = new Client(['curl' => [CURLOPT_SSL_VERIFYPEER => false]]);
./openstamanager-master/plugins/exportFE/src/FatturaElettronica.php:225-
#####
./openstamanager-master/src/Validate.php:144-    CURLOPT_TIMEOUT => 0,
./openstamanager-master/src/Validate.php:145:    CURLOPT_SSL_VERIFYPEER => 0,
./openstamanager-master/src/Validate.php:146-    CURLOPT_FOLLOWLOCATION => true,
#####
./microweber-master/userfiles/modules/shop/payments/gateways/lib/paypal_pro.inc.php:51-    curl_setopt($ch, CURLOPT_VERBOSE, 1);
./microweber-master/userfiles/modules/shop/payments/gateways/lib/paypal_pro.inc.php:52:    curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, FALSE);
./microweber-master/userfiles/modules/shop/payments/gateways/lib/paypal_pro.inc.php:53:    curl_setopt($ch, CURLOPT_SSL_VERIFYHOST, FALSE);
./microweber-master/userfiles/modules/shop/payments/gateways/lib/paypal_pro.inc.php:54-    curl_setopt($ch, CURLOPT_RETURNTRANSFER, 1);
#####
./microweber-master/userfiles/modules/shop/payments/gateways/payza/notify.php:22-    curl_setopt($ch, CURLOPT_TIMEOUT, 60);
./microweber-master/userfiles/modules/shop/payments/gateways/payza/notify.php:23:    curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);
./microweber-master/userfiles/modules/shop/payments/gateways/payza/notify.php:24-
#####
./microweber-master/userfiles/modules/twitter_feed/TwitterAPIExchange.php:196-    CURLOPT_RETURNTRANSFER => true,
./microweber-master/userfiles/modules/twitter_feed/TwitterAPIExchange.php:197:    CURLOPT_SSL_VERIFYPEER => false,
./microweber-master/userfiles/modules/twitter_feed/TwitterAPIExchange.php:198-    CURLOPT_TIMEOUT => 10,
#####
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:207-    curl_setopt($ch, CURLOPT_TIMEOUT, $this->timeout);
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:208:    curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:209-    curl_setopt($ch, CURLOPT_CAINFO, __DIR__ . DS . 'cacert.pem.txt');
#####
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:310-    CURLOPT_VERBOSE => 1,
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:311:    CURLOPT_SSL_VERIFYPEER => false,
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:312-    //CURLOPT_TIMEOUT => 30,
#####
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:326-    //$this->headers[CURLOPT_HEADER] = 1;
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:327:    $this->headers[CURLOPT_SSL_VERIFYHOST] = false;
./microweber-master/src/Microweber/Uti/Adapters/Http/Curl.php:328-    }

```


Sort: Best match ▾

 456dce6 

 8a90cf5 

 7fe9d02 

 f2d92d5 

 f2d92d5 

 c881856 

# SQL injection

---

```
query[[:space:]]*\..*\$_(GET|POST|REQUEST|COOKIE)\[  
[Ss][Ee][Ll][Ee][Cc][Tt].*\$_(GET|POST|REQUEST|COOKIE)\[.*[Ff][Rr][Oo][Mm]  
[Ss][Ee][Ll][Ee][Cc][Tt].*[Ff][Rr][Oo][Mm].*\$_(GET|POST|REQUEST|COOKIE)\[  
[Ww][Hh][Ee][Rr][Ee].*=.*\$_(GET|POST|REQUEST|COOKIE)\[  
[\"'\]([Aa][Nn][Dd]|[Oo][Rr]).*=.*\$_(GET|POST|REQUEST|COOKIE)\[
```



# SQL injection

query[[:space:]]\*\  
[Ss][Ee][Ll][Ee][Cc]  
[Ss][Ee][Ll][Ee][Cc]  
[Ww][Hh][Ee][Rr][E]  
[\"'\"]([Aa][Nn][Dd])

```
./Kliqqi-CMS-master/modules/status/status.php-30-  
./Kliqqi-CMS-master/modules/status/status.php:31:  
WHERE like_update_id='{$_GET['lid']}'");  
./Kliqqi-CMS-master/modules/status/status.php-32-  
#####  
./Kliqqi-CMS-master/modules/status/status.php-46-  
er_id  
./Kliqqi-CMS-master/modules/status/status.php:47:  
./Kliqqi-CMS-master/modules/status/status.php-48-  
#####  
./Kliqqi-CMS-master/modules/status/status.php-171-  
./Kliqqi-CMS-master/modules/status/status.php:172:  
id='{$_GET['did']}'");  
./Kliqqi-CMS-master/modules/status/status.php-173-  
./Kliqqi-CMS-master/modules/status/status.php:174:  
id='{$_GET['did']}' AND update_user_id='{$_current_user->user_id}';  
./Kliqqi-CMS-master/modules/status/status.php-175-}  
#####  
./Kliqqi-CMS-master/modules/status/status.php-179-  
{$_GET['lid']}', like_user_id='{$_current_user->user_id}'))  
./Kliqqi-CMS-master/modules/status/status.php:180:  
likes+1 WHERE update_id='{$_GET['lid']}'");  
./Kliqqi-CMS-master/modules/status/status.php-181-  
./Kliqqi-CMS-master/modules/status/status.php-182-  
./Kliqqi-CMS-master/modules/status/status.php:183:  
pdate id='{$_GET['lid']}' AND like user id='{$_current user->user id}';
```

```
$results = $db->get_results("SELECT * FROM ".table_prefix."likes  
  
$user = new User;  
  
LEFT JOIN ".table_prefix."users c ON a.update_user_id=c.us  
  
WHERE update_id='{$_GET['id']}";  
$update = $db->get_row($sql);  
  
if ($isadmin || $isadmin)  
$db->query("DELETE FROM ".table_prefix."updates WHERE update  
  
else  
$db->query("DELETE FROM ".table_prefix."updates WHERE update  
  
if ($db->query("INSERT INTO ".table_prefix."likes SET like_update_id='  
{$_GET['lid']}', like_user_id='{$_current_user->user_id}'))  
$db->query("UPDATE ".table_prefix."updates SET update_likes=update_l  
  
else  
{  
$db->query("DELETE FROM ".table_prefix."likes WHERE like_u
```

./Kliqqi-CMS-master/modules/status/status.php-30-{

```
./glpi-9.4-bugfixes/front/backup.php-443-    } else {
./glpi-9.4-bugfixes/front/backup.php:444:        $rowlimit = $_GET["rowlimit"];
./glpi-9.4-bugfixes/front/backup.php-445-    }
#####
./glpi-9.4-bugfixes/front/pluginimage.send.php-69-if (file_exists($Path.$_GET["name"])) {
./glpi-9.4-bugfixes/front/pluginimage.send.php:70:    readfile($Path.$_GET["name"]);
./glpi-9.4-bugfixes/front/pluginimage.send.php-71-    if (isset($_GET["clean"])) {
#####
./glpi-9.4-bugfixes/ajax/dropdownSoftwareLicense.php-52-        FROM `glpi_softwarelicenses`
./glpi-9.4-bugfixes/ajax/dropdownSoftwareLicense.php:53:        WHERE `glpi_softwarelicenses`.`softwares_id` =
    "$_POST['softwares_id']."
./glpi-9.4-bugfixes/ajax/dropdownSoftwareLicense.php-54-        $restrict
#####
./glpi-9.4-bugfixes/ajax/dropdownInstallVersion.php-60-        LEFT JOIN `glpi_states` ON (`glpi_softwareversions`.`sta
tes_id` = `glpi_states`.`id`)
./glpi-9.4-bugfixes/ajax/dropdownInstallVersion.php:61:        WHERE `glpi_softwareversions`.`softwares_id` = '
    "$_POST['softwares_id']."
./glpi-9.4-bugfixes/ajax/dropdownInstallVersion.php-62-        $where
#####
./glpi-9.4-bugfixes/tools/cleanhistory.php-96-
./glpi-9.4-bugfixes/tools/cleanhistory.php:97:$where = "`date_mod` < SUBDATE(NOW(), INTERVAL " . $_GET['delay'] . "
month)";
./glpi-9.4-bugfixes/tools/cleanhistory.php-98-
./glpi-9.4-bugfixes/tools/cleanhistory.php-99-if (isset($_GET['item'])) {
./glpi-9.4-bugfixes/tools/cleanhistory.php:100:    $where .= " AND `itemtype` = '" . $_GET['item'] . "'";
./glpi-9.4-bugfixes/tools/cleanhistory.php-101-}
```

refix."likes  
ate\_user\_id=c.us  
E update  
E update  
like\_update\_id='  
e\_likes=update\_l  
E like\_u





# Cross site scripting

---

```
<?=*\$_(GET|POST|REQUEST|COOKIE|SERVER)
echo.*\$_(GET|POST|REQUEST|COOKIE)
print.*\$_(GET|POST|REQUEST|COOKIE)
PHP_SELF</pre
```

# Cross site scripting

```
<?=.*\$_(GET|POST|REQUEST|COOKIE|SERVER)</pre
```

```
echo.*\$_(GET|POST|REQUEST|COOKIE)
```

```
print.*\$_(GET|POST|REQUEST|COOKIE)
```

```
./bitcoind-status-master/chartdata.php-54-// Start output
P./bitcoind-status-master/chartdata.php:55:echo "var " . $_GET['stat'] . "ChartData = [\n";
./bitcoind-status-master/chartdata.php-56-
#####
./Nagdash-master/htdocs/settings_dialog.php-22-<legend>Hostname regex</legend>
./Nagdash-master/htdocs/settings_dialog.php:23:<input type="input" name="hostfilter" value="<?php echo $_COOKIE['nagdash_hostfilter']; ?>">
./Nagdash-master/htdocs/settings_dialog.php-24-</fieldset>
#####
./mumble-master/scripts/server/ice/icedemo.php-90-    } else {
./mumble-master/scripts/server/ice/icedemo.php:91:        echo "<form method=\"post\" action=\"\". $_SERVER['PHP_SELF']. \">\n";
./mumble-master/scripts/server/ice/icedemo.php-92-        echo "<p>\n";
```

```

./librenms-master/html/pages/search/ipv6.inc.php:87-
./librenms-master/html/pages/search/ipv6.inc.php:88-
./librenms-master/html/pages/search/ipv6.inc.php:89-
./librenms-master/html/pages/search/ipv6.inc.php:90-
./librenms-master/html/pages/search/ipv6.inc.php:91-
#####
./librenms-master/html/pages/search/ipv4.inc.php:75-
./librenms-master/html/pages/search/ipv4.inc.php:76-
./librenms-master/html/pages/search/ipv4.inc.php:77-
#####
./librenms-master/html/pages/search/ipv4.inc.php:86-
./librenms-master/html/pages/search/ipv4.inc.php:87-
./librenms-master/html/pages/search/ipv4.inc.php:88-
./librenms-master/html/pages/search/ipv4.inc.php:89-
./librenms-master/html/pages/search/ipv4.inc.php:90-
#####
./librenms-master/html/pages/search/arp.inc.php:78-
./librenms-master/html/pages/search/arp.inc.php:79-
./librenms-master/html/pages/search/arp.inc.php:80-
#####
./librenms-master/html/pages/search/arp.inc.php:91-
./librenms-master/html/pages/search/arp.inc.php:92-
./librenms-master/html/pages/search/arp.inc.php:93-
./librenms-master/html/pages/search/arp.inc.php:94-
./librenms-master/html/pages/search/arp.inc.php:95-
#####
./librenms-master/html/pages/search/mac.inc.php:75-
./librenms-master/html/pages/search/mac.inc.php:76-
./librenms-master/html/pages/search/mac.inc.php:77-
#####
./librenms-master/html/pages/search/mac.inc.php:89-
./librenms-master/html/pages/search/mac.inc.php:90-
./librenms-master/html/pages/search/mac.inc.php:91-
./librenms-master/html/pages/search/mac.inc.php:92-
./librenms-master/html/pages/search/mac.inc.php:93-

```

# Unsafe deserialization

---

```
unserialize[[:space:]]*\..*\$_(GET|POST|REQUEST|COOKIE|SERVER|SESSION)
```



```

./phpipam-master/app/tools/circuits/all-circuits-map.php:12-    print "<h3>"._('Map of circuits')."</h3>";
./phpipam-master/app/tools/circuits/all-circuits-map.php:13-    $circuits_to_map = unserialize($_GET['circuits_to_map']);
./phpipam-master/app/tools/circuits/all-circuits-map.php:14-}else{
#####
./phppgadmin-master/fulltext.php:266-
./phppgadmin-master/fulltext.php:267-    if ($_POST['formParser'] != '') $formParser = unserialize(
$_POST['formParser']);
./phppgadmin-master/fulltext.php:268-
./phppgadmin-master/fulltext.php:269-    if ($_POST['formTemplate'] != '') $formTemplate = unserialize(
$_POST['formTemplate']);
./phppgadmin-master/fulltext.php:270-
./phppgadmin-master/fulltext.php:271-    else $formTemplate = '';
#####
./phppgadmin-master/fulltext.php:669-    if(isset($_POST['formTemplate']))
./phppgadmin-master/fulltext.php:670-        $formTemplate = unserialize($_POST['formTemplate']);
./phppgadmin-master/fulltext.php:671-    else
#####
./phppgadmin-master/display.php:33-    else
./phppgadmin-master/display.php:34-        $key = unserialize(urldecode($_REQUEST['key']));
./phppgadmin-master/display.php:35-
#####
./phppgadmin-master/display.php:240-    else {
./phppgadmin-master/display.php:241-        $status = $data->deleteRow($_POST['table'], unserialize(
urldecode($_POST['key'])));
./phppgadmin-master/display.php:242-
./phppgadmin-master/display.php:243-        if ($status == 0)
#####
./phppgadmin-master/views.php:218-        for ($i = 0; $i < $tblCount; $i++) {
./phppgadmin-master/views.php:219-            $arrSelTables[] = unserialize($_POST['formTables'][$i]);
./phppgadmin-master/views.php:220-
#####
./phppgadmin-master/tables.php:328-
./phppgadmin-master/tables.php:329-        $status = $data->createTableLike($_REQUEST['name'],
unserialize($_REQUEST['like']), isset($_REQUEST['withdefaults']),
isset($_REQUEST['withconstraints']), isset($_REQUEST['withindexes']), $_REQUEST['tablespace']);
./phppgadmin-master/tables.php:330-
#####
./phppgadmin-master/tables.php:561-        if (!isset($_POST['nulls'])) $_POST['nulls'] = array();
./phppgadmin-master/tables.php:562-        $_POST['fields'] = unserialize(htmlspecialchars_decode(
$_POST['fields'], ENT_QUOTES));
./phppgadmin-master/tables.php:563-
#####
./phppgadmin-master/constraints.php:40-        if (!isset($_POST['initially'])) $_POST['initially'] = null;
./phppgadmin-master/constraints.php:41-        $_REQUEST['target'] = unserialize(
$_REQUEST['target']);
./phppgadmin-master/constraints.php:42-
#####
./phppgadmin-master/constraints.php:130-        // Unserialize target
./phppgadmin-master/constraints.php:131-        $_POST['target'] = unserialize($_POST['target']);
./phppgadmin-master/constraints.php:132-
./phppgadmin-master/constraints.php:133-        // Check that they've given at least one c

```

(ON)

```

./phpipam-master/app/tools/circuits/all-circuits-map.php-12- print "<h3>"._('Map of circuits')."</h3>";
./phpipam-master/app/tools/circuits/all-circuits-map.php-13: $circuits_to_map = unserialize($_GET['circuits_to_map']);
./phpipam-master/app/tools/circuits/all-circuits-map.php-14-}else{
#####
./phpipam-master/fulltext.php-266-
./phpipam-master/fulltext.php-267: if ($_POST['formParser'])
$ _POST['formParser'];
./phpipam-master/fulltext.php-268-
./phpipam-master/fulltext.php-269: else $formParser
if ($_POST['formTemplate'])
else $formTemplate
#####
./phpipam-master/fulltext.php-270-
./phpipam-master/fulltext.php-669-
./phpipam-master/fulltext.php-670: if(isset($_POST['formTemplate']))
else
#####
./phpipam-master/fulltext.php-671-
./phpipam-master/display.php-33-
./phpipam-master/display.php-34: $key = unserialize($_POST['key']);
./phpipam-master/display.php-35-
#####
./phpipam-master/display.php-240-
./phpipam-master/display.php-241: $status = unserialize(urldecode($_POST['key']));
./phpipam-master/display.php-242-
#####
./phpipam-master/views.php-218-
./phpipam-master/views.php-219: $Tables[$_POST['i']] = unserialize(urldecode($_POST['key']));
./phpipam-master/views.php-220-
#####
./phpipam-master/tables.php-328-
./phpipam-master/tables.php-329: $status = unserialize($_REQUEST['like']), isset($_REQUEST['withdefaults']),
./phpipam-master/tables.php-330-
ST['withindexes']), $_REQUEST['tablespace']);
#####
./phpipam-master/tables.php-561-
./phpipam-master/tables.php-562: code($_POST['fields'], ENT_QUOTES));
./phpipam-master/tables.php-563-
#####
./phpipam-master/constraints.php-40-
initially'] = null;
./phpipam-master/constraints.php-41: $_REQUEST['target'];
./phpipam-master/constraints.php-42-
#####
./phpipam-master/constraints.php-130-
./phpipam-master/constraints.php-131: OST['target'];
./phpipam-master/constraints.php-132-
./phpipam-master/constraints.php-133-

```

```

/_____/      V      V
grep rough audit - static analysis tool
v2.1 written by @Wireghoul
===== [justanotherhacker.com] =====
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-152-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-153:
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-154-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-155-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-156-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-157-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-158-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-159-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-160-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-161-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-162-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-163-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-164-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-165-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-166-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-167-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-168-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-169-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-170-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-171-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-172-
phpipam-master/functions/PEAR/Net/DNS2/Cache/File.php-173-
#####
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-187-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-188:
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-189-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-190-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-191-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-192-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-193-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-194-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-195-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-196-
phpipam-master/functions/PEAR/Net/DNS2/Cache/Shm.php-197-
--
phpipam-master/functions/PEAR/Net/DNS2/Socket.php-121-
phpipam-master/functions/PEAR/Net/DNS2/Socket.php-122-
phpipam-master/functions/PEAR/Net/DNS2/Socket.php-123-
phpipam-master/functions/PEAR/Net/DNS2/Socket.php-124-
// Unserialize target
$_POST['target'] = unserialize($_P
// Check that they've given at least one c

```

```

*/
public function __destruct()
{
    //
    // if there's no cache file set, then there's nothing to do
    //
    if (strlen($this->cache_file) == 0) {
        return;
    }

    //
    // open the file for reading/writing
    //
    $fp = fopen($this->cache_file, 'a+');
    if ($fp !== false) {
        //
        // lock the file just in case
        //
        flock($fp, LOCK_EX);

        //
    }

    */
public function __destruct()
{
    //
    // if there's no cache file set, then there's nothing to do
    //
    if (strlen($this->cache_file) == 0) {
        return;
    }

    $fp = fopen($this->cache_file, 'r');

    /**
    * sets the local address/port for the socket to bind to
    *

```

# Buffer overflow

---

```
#!/bin/sh
VERSION=0.1
if [ -z "$1" ]; then
    echo "Usage: $0 /path/to/check"
    exit 2
Fi
echo 'char[:space:])+[a-zA-Z0-9\.\-\_][a-zA-Z0-9\.\-\_]+\[' | ~/flatline/graudit -B -z -d - "$1" | \
perl -ne 'if ($_ =~ m/char\s+([a-zA-Z0-9\.\-\_]+)\[/) {
    @rulz=(
        "strcat(at|py)[:space:])*\\(",
        "sprintf[:space:])*\\(",
    );
    print "$1\n" . join("\n", map $_."$1", @rulz) . "\n";
}' | \sort | uniq | \~/flatline/graudit -c 3 -B -d - "$1"
```



# Buffer overflow

```
./openlitespeed-master/src/http/httpvhost.cpp-3222-}  
./openlitespeed-master/src/http/httpvhost.cpp-3223-  
./openlitespeed-master/src/http/httpvhost.cpp-3224-  
./openlitespeed-master/src/http/httpvhost.cpp:3225:void HttpVHost::getAppName(const char *suffix, char *appName, int maxlen)  
./openlitespeed-master/src/http/httpvhost.cpp-3226-{  
./openlitespeed-master/src/http/httpvhost.cpp-3227-    assert(maxlen >= 255);  
./openlitespeed-master/src/http/httpvhost.cpp:3228-    strcpy(appName, suffix);  
./openlitespeed-master/src/http/httpvhost.cpp:3229-    strcat(appName, "_");  
./openlitespeed-master/src/http/httpvhost.cpp:3230-    strcat(appName, getName());  
./openlitespeed-master/src/http/httpvhost.cpp-3231-}  
./openlitespeed-master/src/http/httpvhost.cpp-3232-  
./openlitespeed-master/src/http/httpvhost.cpp-3233-/**  
#####  
./openlitespeed-master/src/http/httpvhost.cpp-3245-    HttpMime *pHttpMime = getMIME();  
./openlitespeed-master/src/http/httpvhost.cpp-3246-    const char *suffix = NULL;  
./openlitespeed-master/src/http/httpvhost.cpp-3247-    php_xml_st *pPhpXmlNodeS;  
./openlitespeed-master/src/http/httpvhost.cpp:3248-    char appName[256];  
./openlitespeed-master/src/http/httpvhost.cpp-3249-  
./openlitespeed-master/src/http/httpvhost.cpp-3250-    //HttpMime::configScriptHandler(pList, getMIME(), this);  
./openlitespeed-master/src/http/httpvhost.cpp-3251-    for (int i=0; i<getPhpXmlNodeSSize(); ++i)  
./openlitespeed-master/src/http/httpvhost.cpp-3252-    {  
./openlitespeed-master/src/http/httpvhost.cpp-3253-        pPhpXmlNodeS = getPhpXmlNodeS(i);  
./openlitespeed-master/src/http/httpvhost.cpp-3254-        suffix = pPhpXmlNodeS->suffix.c_str();  
./openlitespeed-master/src/http/httpvhost.cpp:3255-        getAppName(suffix, appName, 256);  
./openlitespeed-master/src/http/httpvhost.cpp:3256-        const HttpHandler *pHdlr = HandlerFactory::getHandler("lsapi", appName);  
./openlitespeed-master/src/http/httpvhost.cpp-3257-        HttpMime::addMimeHandler(pHdlr, NULL, pHttpMime, suffix);  
./openlitespeed-master/src/http/httpvhost.cpp-3258-    }  
./openlitespeed-master/src/http/httpvhost.cpp-3259-    return 0;  
},
```

```
print "$1\n" . join("\n", map $_."$1", @rulz) . "\n";
```

```
}'| \sort | uniq | \~/flatline/graudit -c 3 -B -d - "$1"
```

# Buffer overflow

```
./openlitespeed-master/src/http/httpvhost.cpp-3222-}  
./openlitespeed-master/src/http/httpvhost.cpp-3223-  
./openlitespeed-master/src/http/httpvhost.cpp-3224-  
./openlitespeed-master/src/http/httpvhost.cpp:3225:void HttpVHost::getAppName(const char *suffix, char *appName, int maxlen)  
./openlitespeed-master/src/http/httpvhost.cpp-3226-{  
./openlitespeed-master/src/http/httpvhost.cpp-3227-    assert(maxlen >= 255);  
./openlitespeed-master/src/http/httpvhost.cpp:3228-    strcpy(appName, suffix);  
./openlitespeed-master/src/http/httpvhost.cpp:3229-    strcat(appName, "_");  
./openlitespeed-master/src/http/httpvhost.cpp:3230-    strcat(appName, getName());  
./openlitespeed-master/src/http/httpvhost.cpp-3231-}  
./openlitespeed-master/src/http/httpvhost.cpp-3232-  
./openlitespeed-master/src/http/httpvhost.cpp-3233-/**  
#####/openlitespeed-master/src/http/httplogsource.cpp-262-    }  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp-129-    //    LS_ERROR( "[config] denied path is too long - %s!", pDir ));  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp-130-    //    break;  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp-131-    //}  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp:132-    char buf[256];  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp-133-    bool includeSub = false;  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp:134-    strcpy(buf, pDir);  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp:135-    char *pEnd = buf + len - 1;  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp-136-    if (*(pEnd) == '*')  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp-137-    {  
./openlitespeed-master/src/http/httpvhost.c/openlitespeed-master/src/http/denieddir.cpp-138-        includeSub = true;  
./openlitespeed-master/src/http/httpvhost.cpp:3255-    getAppName(suffix, appName, 256);  
./openlitespeed-master/src/http/httpvhost.cpp:3256-    const HttpHandler *pHdlr = HandlerFactory::getHandler("lsapi", appName);  
./openlitespeed-master/src/http/httpvhost.cpp-3257-    HttpMime::addMimeHandler(pHdlr, NULL, pHttpMime, suffix);  
./openlitespeed-master/src/http/httpvhost.cpp-3258-    }  
./openlitespeed-master/src/http/httpvhost.cpp-3259-    return 0;  
},  
  
    print "$1\n" . join("\n", map $_."$1", @rulz) . "\n";  
}' | \sort | uniq | \~/flatline/graudit -c 3 -B -d - "$1"
```

# 06

## Conclusion

## CONCLUSION



Vulnerability discovery doesn't have to be advanced

Some vulnerabilities can be very hard to identify

Source code review may not be the simplest approach

Finding the vulnerability is usually just the start of the journey

# Questions?