Bug hunting

with grep

\$(whoami)




- Hacker
- Speaker
- Trainer
- Wireghoul

www.justanotherhacker.com


Bug hunting

- Collecting enough information to get
 - CVE
 - Shell





Bug hunting with grep



Finding vulnerability candidates in source code

grep is a filter

Human analysis is required


```
", &time_stamp) == E0.


K;

B[A-Z0-9] %6[A-Z0-9] ",

rage_id, flight_id) ==
```

Process





2grep ||

! 2grep




Benefits of grep

- Can be used on partial code
- Versatile cross platform support
- /Regex/
- Most programming languages are text based
- Easy to add support for new languages or frameworks
- Shows code directly

Limitations of grep


- Matching across lines
- Semantic understanding
- Only as good as the regex



Not greps



coccinelle semgrep ripgrep more



```
grep -rsE 'CURLOPT_SSL_VERIFY(PEER|HOST|STATUS).*([Ff][Aa][Ll][Ss][Ee]|0)' .
```



SSL/TLS Validation Failure




graudit

https://github.com/wireghoul/graudit

```
grep rough audit - static analysis tool
               v2.1 written by @Wireghoul
                          ====[justanotherhacker.com]===
                     <meta name="Description" content="">
index.php-78-
                     <meta name="title" content="<?php print $title = $User->get site title ($ GET); ?>">
                     <meta name="robots" content="noindex, nofollow">
index.php-265-
                                           print "";
                                           print "<div id='leftMenu' class='menu-$ GET[page]'>";
index.php:266:
                                                  index.php-267-
index.php-276-
                                   print "";
                                   print "<div class='row menu-$ GET[page]' id='content'>";
index.php:277
                                           # subnets
                                                         if(file exists("app/tools/$ GET[section]/index.php"))
index.php-298-
                                                                include("app/tools/$ GET[section]/index.php");
index.php:299:
index.php-300-
index.php-301-
                                                         else {
                                                             include("app/tools/custom/$ GET[section]/index.php");
index.php:302:
index.php-303
```

WHENEVER I LEARN A
NEW SKILL I CONCOCT
ELABORATE FANTASY
SCENARIOS WHERE IT
LETS ME SAVE THE DAY.






BUT TO FIND THEM WE'D HAVE TO SEARCH THROUGH 200 MB OF EMAILS LOOKING FOR SOMETHING FORMATTED LIKE AN ADDRESS!



IT'S HOPELESS!












Regex



- Extended
- PCRE



Rules



```
require
require\(.*\$.*\);
(require|require_once)\(.*\$.*\);
require(\_once)?[[:space:]]*(\(|\'\'").*\$\_(GET|POST|REQUEST|ENV|COOKIE).*(\)|\'|\'")\;
```



AMPscript / SSJS

```
runat
%%=<u>[</u>^%]+\@[^%]+=%%
%%\[
[Rr][Ee][Qq][Uu][Ee][Ss][Tt][Pp][Aa][Rr][Aa
][Mm][Ee][Tt][Ee][Rr][[:space:]]*\(
Invoke(Create|Delete|Execute|Perform|Retrie
RaiseError[[:space:]]\(.*\@
SetObjectProperty
UpsertContact
AttachFile
BarCodeURL
BuildRowSetFrom(String|XML)
(Create|End|Set)SmsConversation(NextKeyword)
)?
TreatAsContent(Area)?
ClaimRow(Value)?
CataExtensionRowCount
DeleteD(E|ata)[[:space:]]*\(
ExecuteFilter(OrderedRows)?
```

```
InsertD(E|ata)
Lookup[[:space:]]\([^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+,[^,]+
   (En | De) crypt Symmetric
  MD5[[:space:]]*\(
 SHA(1|256|512)[[:space:]]*\(HTTP(Get|Post|Post2|RequestHeader)
 (Update|Upsert|SetState|Create|Retrieve)MscrmRecords?(FetchXML)?
   AddMscrmListMember
  DescribeMscrmEntit(ies|yAttributes)
     (Create Retrieve UpdateSingle)Salesforce(Ob
    ject JobSource)s?
eval[[:space:]]*\([^\)\;]+[\'\"][[:space:]]
*\+[[:space:]]*[^\'\"]+
[\"\'][[Ss][Ee][Ll][Ee][Cc][Tt][[:space:]]+
```



Noise/Signal



graudit -d php.

graudit -d default.

echo "rule" | graudit -d - .

graudit -d php/ssl.

graudit -d fruit .

graudit -d flatline.

```
grep rough audit - static analysis tool
                 v2.8 written by @Wireghoul
                       =======[justanotherhacker.com]===
                                -/-CHROME_MAIN_VERSION=`google-chrome-stable --version | sed -E 's/(^Google Chrome |\.[0-9]+
)//g'
                                *8:CHROMEDRIVER_VERSION=`curl -s "https://chromedriver.storage.googleapis.com/LATEST_
RELEASE_$CHROME_MAIN_VERSION"
                                     let sep = cmdSep();
                                     let delAssets = isWin() ? '(For /D %i in (static\\assets\\*.*) do (rmdir %i /S /Q))' :
${rm} -rf static/assets/*/`;
                                     let dirSep = isWin() ? "\\" : '/';
                                     let jsFile = `static${dirSep}js${dirSep}humhub-*.js`;
                                     let cssFile = `static${dirSep}css${dirSep}humhub-*.css`;
                                     return `${rm} ${jsFile} ${sep} ${rm} ${cssFile} ${sep} ${delAssets} ${sep} cd pr
otected ${sep} php yii asset humhub/config/assets.php humhub/config/assets-prod.php';
                                     let sep = cmdSep();
                                     return 'cd protected ${sep} php yii search/rebuild';
************************************
                                     let codeceptPath = `${base}/protected/vendor/codeception/codecept`
                                     let rootTestPath = `${base}/protected/humhub/tests`;
                                     if(moduleName) {
                                         testPath = `${base}/protected/humhub/modules/${moduleName}/tests`;
```

```
$result_owns = @mysql_query("SELECT id FROM servers WHERE id = '$gpx_srvid'
                       #12:
d = '$qpx_userid' LIMIT 1") or die('Failed to check ownership');
                                             = mysql_fetch_row($result_owns);
                               $row_owns
                                      @mysql_query("UPDATE default_games SET startup = '0' WHERE id =
die('Failed to update startup type');
                                      echo 'success';
                                      Omysql_query("UPDATE default_games SET startup = '1' WHERE id = '$url_id'") or
die('Failed to update startup type');
                                      $add_query = substr($add_query, 0, -1); // Lose last comma
                                      @mysql_query($add_query) or die('Failed to add items: '.mysql_error());
                                      @mysql_query($update_item_query) or die('Failed to update items: '.mysql_error(
));
                                      @mysql_query($update_val_query) or die('Failed to update values: '.mysql_error(
                                      @mysql_query($update_usred_query) or die('Failed to update user editable: '.mys
ql_error());
                                      if($sort_order) @mysql_query($update_sort_query) or die('Failed to update order
: '.mysql_error());
                         +190-
                                  $simplecmd = '';
                                  $result_smp = @mysql_query("SELECT cmd_item,cmd_value FROM default_startup WHERE de
fid = '$url_id' ORDER BY sort_order ASC") or die('Failed to get item/vals!');
```

```
grep rough audit - static analysis tool
                 v2.7 written by @Wireghoul
                       ======[justanotherhacker.com]===
                                                   $id_agents = json_decode(io_safe_output(get_parameter('id_agents')));
                                                   $filter = '%'.get_parameter('q', '').'%';
                                                   $other_filter = json_decode(io_safe_output(get_parameter('other_filter'))
, true);
                                                   } else {
                                                       $limit = ' LIMIT '.$config['block_size'].' OFFSET '.get_par
 meter('offset', 0);
                                                                                               'max_interval'
                                                                                           ).';'.get_paramete
r('min_interval');
                                                                                           $values['text'] = $intervals;
case 'postgresql':
                                                                  $sql .= ' LIMIT '.$config['block_size'].' OFFSET '
.get_parameter('offset', 0);
                                                              break;
                                                                 $sql .= ' LIMIT '.$config['block_size'].' OFFSET '
.get_parameter('offset', 0);
                                                            case 'postgresgl':
                                                                $sql .= ' LIMIT '.$config['block_size'].' OFFSET '
.get_parameter('offset', 0);
```

```
printf("file to be enciphered = ");
               :66:
                      gets(ifname);
                      fli=FALSE:
**********************************
                             printf("output filename = ");
                             gets(ofname);
                         } while (strlen(ofname)==0);
*************************************
                      printf("file to be encoded = ");
              -63-
               :64:
                      gets(ifname);
                      fli=FALSE:
printf("output filename = ");
                             gets(ofname);
              :85:
                         } while (strlen(ofname)==0);
***********************************
                        printf("Enter Raw random string= ");
                        scanf("%s",raw);
                :222:
                        getchar();
*********************************
               -241-{ /* insert a status setting into status line */
               :242:
                        strncpy(&status[ptr], strg, strlen(strg));
               -243-}
**********************************
               -117-
                        printf("Enter name of .ecs file= ");
                       gets(fname);
                        strip(fname);
*************************************
                        printf("Enter name of .ecs file= ");
                :100:
                        gets(fname);
                        strip(fname);
```

```
/nconf-master/include/ajax/json/history.php-34 {
                                                    $sLimit = "LIMIT ".mysql_real_escape_string( $_GET['iDisplayS'
/nconf-master/include/ajax/json/history.php:35:
t'] ).", ".
/nconf-master/include/ajax/json/history.php-36-
                                                        mysql_real_escape_string( $_GET['iDisplayLength'] );
/nconf-master/include/tabs/history.php-35-
                                               $query = 'SELECT timestamp, action, attr_name FROM History
/nconf-master/include/tabs/history.php 36:
                                                       WHERE fk_id_item='.$_GET["id"].'
                                                       AND action <> "edited"
/nconf-master/clone_host_write2db.php-176-
                                                                   SELECT '.$new_host_id.',fk_item_linked2,fk_id_attr,cust_ord
                                                                       FROM ItemLinks WHERE fk_id_item = '.$_POST["templ
/nconf-master/clone_host_write2db.php:177:
ate_id"].'
/nconf-master/clone_host_write2db.php-178-
                                                                       ORDER BY fk_item_linked2';
/nconf-master/clone_host_write2db.php-179-
                                                       $history_query = 'SELECT '.$new_host_id.',fk_item_linked2,fk_id_attr
/nconf-master/clone_host_write2db.php:180:
                                                                       FROM ItemLinks WHERE fk_id_item = '.$_POST["templ
ate_id"].'
                                                                       ORDER BY fk_item_linked2';
/nconf-master/clone_host_write2db.php-186-
                                                                   SELECT '.$new_host_id.',fk_item_linked2,fk_id_attr,cust_ord
/nconf-master/clone_host_write2db.php:187:
                                                                       FROM ItemLinks WHERE fk_id_item = '.$_POST["templ
ate_id"].'
/nconf-master/clone_host_write2db.php-188-
                                                                           AND ((SELECT attr_name FROM ConfigAttrs WHERE id_at
tr=fk_id_attr) <> "parents"
                                                       $history_query = 'SELECT '.$new_host_id.',fk_item_linked2,fk_id_attr
                                                                       FROM ItemLinks WHERE fk_id_item = '.$_POST["templ
/nconf-master/clone_host_write2db.php:192:
ate_id"].'
/nconf-master/clone_host_write2db.php-193-
                                                                           AND ((SELECT attr_name FROM ConfigAttrs WHERE id_at
```



Is a hammer!


Everything looks like a nail





```
MIIEvgIBADANBgkghkiG9w0BAQEFAASCBKgwggSkAgEAAoIBAQDHCpm/hOVkXyYu
                           *1:----BEGIN PRIVATE KEY----
                           -2-MIIEvQIBADANBgkghkiG9w0BAQEFAASCBKcwggSjAgEAAoIBAQDhepMoc7w0000g
............
                               -12733-CREATE TABLE t1(a CHAR(255)) ENGINE=archive;
                               -14-MASTER_USER=
                                               'pluq_user',
                               *15:MASTER_PASSWORD= 'plug_user'.
                               -16-MASTER RETRY COUNT= 0:
                                     -38-Warning
                                                     Integer display width is deprecated and will be removed in a future
                                               1681
                                     INSERT INTO t1 VALUES (1, 'a545f661efdd1fb66fdee3aab79945bf');
                                     -40-SELECT 1 FROM t1 WHERE tmp=AES_DECRYPT(tmp, "password");
                            -92-SET sql_mode = default;
                             *93:INSERT INTO t1 VALUES (21,'e45703b64de71482360de8fec94c3ade',3,7800,'n','1999-12-23 17:22:21');
                            :94: INSERT INTO t1 VALUES (22,'e45703b64de71482360de8fec94c3ade',4,5000,'y','1999-12-23 17:22:21');
                            :95:INSERT INTO t1 VALUES (18,'346d1cb63c89285b2351f0ca4de40eda',3,13200,'b','1999-12-23 11:58:04');
                             *96:INSERT INTO t1 VALUES (17,'ca6ddeb689e1b48a04146b1b5b6f936a',4,15000,'b','1999-12-23 11:36:53');
                             *97:INSERT INTO t1 VALUES (16, 'ca6ddeb689e1b48a04146b1b5b6f936a', 3, 13200, 'b', '1999-12-23 11:36:53');
                            *101 INSERT INTO t1 VALUES (27, 'a71250b7ed780f6ef3185bfffe027983',3,6200, 'b', '1999-12-27 09:44:24');
                            :102:INSERT INTO t1 VALUES (28,'a71250b7ed780f6ef3185bfffe027983',3,5400,'y','1999-12-27 09:44:36');
                             *103 INSERT INTO t1 VALUES (29, 'a71250b7ed780f6ef3185bfffe027983',4,17700,'b','1999-12-27 09:45:05');
                             -104-CREATE TABLE t2 (
                                        -32-CREATE USER test_user2 IDENTIFIED WITH mysql_native_password BY 'azundris2';
                                        :33:CHANGE MASTER TO MASTER_PASSWORD='azundris3':
                                        -34-CREATE USER 'test_user4'@'localhost' IDENTIFIED WITH mysgl_native_password;
-18-SET GLOBAL relay_log_info_repository = 'TABLE';
```

T ---- DEGIN PRIVATE KEY----







```
#include <string.h>
void hello (char *n) {
      char name[40];
      strcpy(name, n);
int main (int argc, char **argv) {
      hello(argv[1]);
      return 0;
```




```
#!/bin/sh
# PHP taint checking with graudit - PoC script
# Written by Wireghoul - http://www.justanotherhacker.com
# Released under the GPL licence
VERSION=0.1
if [ -z "$1" ]; then
    echo "Usage: $0 /path/to/check"
    exit 2
fi
graudit -z -d php "$1" | \
perl -ne 'if (\ =\sim m/\(\S+?)\s*=\s*\$_(GET|POST|REQUEST|COOKIE)\[.*?\]/) { print "\\\$$1\n"; }' | \
sort | uniq | \
graudit -d - "$1"
```


```
// Get/Set Task ID - as sent from cronjob when this script
s stored in DB.nodes table also
 /rconfig-master/lib/compareReportScript.php-35-// get task details from DB
 rconfig-master/lib/compareReportScript.php:36://$taskResult = $db->q("SELECT * FROM tasks WHERE id = $tid AND s
tatus = '1'");
 rconfig-master/lib/compareReportScript.php-37-$db2->query("SELECT * FROM tasks WHERE id = :tid AND status = '1'");
rconfig-master/lib/compareReportScript.php:38:$db2->bind(':tid', $tid);
                                           <del>-39-</del>$taskRow = $db2->resultset();
 rconfig-master/lib/compareReportScript.php-48-$title = "rConfig Report - " . $taskname;
 /rconfig-master/lib/compareReportScript.php:49:$report->header($title, $title, basename($_SERVER['PHP_SELF']), $tid
m, $startTime);
                                            -50-$reportFail = '<font color="red">Fail</font>';
                                           -54-// Query to retireve row for given ID (tidxxxxxx is stored in nodes and is gen
erated when task is created)
   onfig-master/lib/compareReportScript.php:55:$db2->query("SELECT id, deviceName FROM nodes WHERE taskId" . $tid
 . " = 1 AND status = 1");
                                            -56-$resultSelect = $db2->resultset();
```

Auto taint

- Sink and source on same line
- fruit and flatline databases



Auto taint




```
./MCHostPanel-master/ajax.php-43-
                                                if (is_file($user['home'] . $_POST['file']))
./MCHostPanel-master/ajax.php:44:
                                                         echo file_get_contents($user['home'] . $_POST['file']);
./MCHostPanel-master/ajax.php-45-
                                                break;
./bgpanel-master/utilitiesrcontool.php-46-{
                                             if (query_numrows( "SELECT `name` FROM `".DBPREFIX."server` WHERE `serve
./bgpanel-master/utilitiesrcontool.php:47:
rid' = '".$_GET['serverid']."'" ) == 0)
/bgpanel-master/utilitiesrcontool.php-48-
./bgpanel-master/admin/utilitiesrcontool.php-49-{
./bgpanel-master/admin/utilitiesrcontool.php:50:
                                                     if (query_numrows( "SELECT `name` FROM `".DBPREFIX."server` WHER
E `serverid` = '".$_GET['serverid']."'" ) == 0)
./bgpanel-master/admin/utilitiesrcontool.php-51-
/bgpanel-master/admin/serveradd.php-59-{
                                             if (query_numrows( "SELECT `game` FROM `".DBPREFIX."game` WHERE `gameid`
/bgpanel-master/admin/serveradd.php:60:
= '".$_GET['gameid']."'" ) == 0)
./bgpanel-master/admin/serveradd.php-61-
```

BOf taint



```
#!/bin/sh
#testing C taint
~/flatline/graudit -B -z -d /dev/stdin -c 0 $1 | \
perl -ne 'if ($_ =~ m/char\s+([a-zA-Z0-9\.\-\_]+)\[/) { print "$1\n"; }' | \
sort -u > /tmp/test
while read var; do
echo "(memcpy|strcat|strcpy|sprintf).*$var"
done </tmp/test | '</pre>
~/flatline/graudit -B -z -d /dev/stdin -c 0 $1 | \
grep -o -f /tmp/test | sort -u > /tmp/taint
while read var; do
echo "char[[:space:]]+[\*]?$var\["
echo "(memcpy|strcat|strcpy|sprintf).*$var"
done </tmp/taint | \</pre>
~/flatline/graudit -c 3 -d /dev/stdin $1
```

Buffer overflow





gitscan



```
#!/bin/sh
# download and scan a single github repo, output to stdout
if [ -z $1 ]; then
echo "$0 <https://github/repo/url>"
exit 2
fi
url=$1
echo "Scanning $url!"
mkdir -p churn
cd churn
git clone $url
graudit -x *.js,*.json,*.map,*.sql -d ./flatline.db .
```

```
#!/bin/bash
# gitlog - A graudit augmentation script
# Written by @Wireghoul - justanotherhacker.com
# Check recent history for some n-day?
# usage: cd repo;gitlog.sh 50
git --no-pager log --oneline
grep -Ei '(security|sqli|sql inj|xss| rce |command
injection|vulnerability|cmdi| lfi |traversal)' | \
head -$1| \
while read diff; do
  git --no-pager show $(echo $diff|cut -d' ' -f1)
done
```



```
commit 1e6000d3be00649e2516538dd03c0ba55ba62a67
Author: Gary Allan <github@gallan.co.uk>
Date: Fri Sep 27 18:26:17 2019 +0100
    Bugfix: SQL injections processing `tableName`. #2738;
diff --git a/functions/classes/class.Admin.php b/functions/classes/class.Admin.php
index 6a5b815f..04c05ca5 100644
--- a/functions/classes/class.Admin.php
+++ b/functions/classes/class.Admin.php
@@ -289,6 +289,9 @@ class Admin extends Common_functions {
         * @return null|false
        public function remove_object_references ($table, $field, $old_value, $new_value = NULL) {
                try { $this->Database->runQuery("update `$table` set `$field` = ? where `$field` = ?;", array($new_value, $old_value)); }
                catch (Exception $e) {
                        $this->Result->show("danger", _("Error: ").$e->getMessage(), false);
@@ -307,6 +310,9 @@ class Admin extends Common_functions {
         * @return null|false
         */
        public function update_object_references ($table, $field, $old_value, $new_value) {
                try { $this->Database->runQuery("update `$table` set `$field` = ? where `$field` = ?;", array($new_value, $old_value)); }
                catch (Exception $e) {
                        $this->Result->show("danger", _("Error: ").$e->getMessage(), false);
@@ -601,6 +607,8 @@ class Admin extends Common_functions {
         * @return void
        public function replace_fields ($field, $search, $replace) {
                # check number of items
                $count = $this->count_database_objects ("ipaddresses", $field, "%$search%", true);
```

Automated scanning



- Daily gitscan cron for PHP updated repos
- Flatline rules and basic taint analysis
- ~112 vulnerability candidates a day on average

```
eldar@JAH:~/flatline$ ls vulnreport-201* | head -1
vulnreport-20161001.txt
eldar@JAH:~/flatline$ ls vulnreport-201* | tail -1
vulnreport-20181206.txt
eldar@JAH:~/flatline$ ls vulnreport-201* | wc -l
793
eldar@JAH:~/flatline$ grep -E './.*:[^\:]+:' vulnreport-201* | wc -l
88818
eldar@JAH:~/flatline$ |
```

Conclusion



- Vulnerability discovery doesn't have to be advanced
- Some bug classes are harder to detect than others
- Finding a vulnerability is usually only the start of the journey



Questions?