
Wisent Guard: A General Framework for Reliable Representation Identification and Representation Steering

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Representation engineering is a powerful method for identifying and modifying
2 high-level concepts within the internal layers of large language models. Despite
3 its potential, real-life deployments of activation steering remain difficult. We
4 present Wisent-Guard, a flexible, open-source framework for monitoring and
5 steering internal activations of large language models. Practical applications of the
6 framework show 95 percent hallucination reduction, 25 percent improvement in
7 coding ability and deep personalization capabilities.

8 1 Introduction

9 Large language models, with billions of parameters and Internet-scale training dataset, have displayed
10 significant capabilities across a wide range of tasks, such as writing, coding or reasoning. However,
11 their internal mechanisms of generating the next token cannot be precisely explained, with interactions
12 between layers and parameters increasing in complexity as the size of these models increases.

13 Experiments with representation engineering (also known as steering or activation steering) have
14 shown activation modification to be a powerful method of identifying and influencing high-level
15 concepts (representations) within the layers of an LLM. Despite strong empirical performance on
16 selected truthfulness, safety or personalization tasks, representation engineering methods lack a
17 universal formulation and a unifying framework for understanding the underlying phenomenon,
18 comparing methods and applying them to new problems.

19 We propose Wisent-Guard, a modular framework for analyzing the internal mechanisms within a
20 large language model and influencing them to improve performance and individual alignment.

21 2 Representation Engineering Problem

22 We formulate the **Representation Engineering Problem** as the following:

23 For a given model M and a Representation

24 3 Representation Reading Functionalities

25 3.1 Classifier

26 3.2 Detection Handling Method

27 4 Representation Control Functionalities

28 References

- 29 [1] Aida Amini, Saadia Gabriel, Peter Lin, Rik Koncel-Kedziorski, Yejin Choi, and Hannaneh
30 Hajishirzi. Mathqa: Towards interpretable math word problem solving with operation-based
31 formalisms. *arXiv preprint arXiv:1905.13319*, 2019.
- 32 [2] Stéphane Aroca-Ouellette, Cory Paik, Alessandro Roncone, and Katharina Kann. Prost: Physical
33 reasoning about objects through space and time. 2021.
- 34 [3] Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David
35 Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. Program synthesis
36 with large language models. *arXiv preprint arXiv:2108.07732*, 2021.
- 37 [4] Lucas et al. Bandarkar. The belebele benchmark: a parallel reading comprehension dataset in
38 122 language variants. *arXiv preprint arXiv:2308.16884*, 2023.
- 39 [5] Jonathan Berant, Andrew Chou, Roy Frostig, and Percy Liang. Semantic parsing on freebase
40 from question-answer pairs. In *Proceedings of the 2013 Conference on Empirical Methods in*
41 *Natural Language Processing*, pages 1533–1544, Seattle, Washington, USA, 2013. Association
42 for Computational Linguistics.
- 43 [6] Yonatan Bisk, Rowan Zellers, Ronan Le Bras, Jianfeng Gao, and Yejin Choi. Piqa: Reasoning
44 about physical commonsense in natural language. *arXiv preprint arXiv:1911.11641*, 2019.
- 45 [7] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D. Kaplan, Prafulla
46 Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language
47 models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*,
48 2020.
- 49 [8] Federico Cassano, John Gouwar, Daniel Nguyen, Sydney Nguyen, Luna Phipps-Costin, Donald
50 Pinckney, Ming-Ho Yee, Yangtian Zi, Carolyn Jane Anderson, Molly Q. Feldman, Arjun Guha,
51 Michael Greenberg, and Abhinav Jangda. Multipl-e: A scalable and extensible approach to
52 benchmarking neural code generation. *arXiv preprint arXiv:2208.08227*, 2022.
- 53 [9] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto,
54 Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul
55 Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke
56 Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad
57 Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias
58 Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex
59 Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain,
60 William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Josh Achiam, Vedant Misra,
61 Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer,
62 Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech
63 Zaremba. Evaluating large language models trained on code. 2021.
- 64 [10] Eunsol Choi, He He, Mohit Iyyer, Mark Yatskar, Wen-tau Yih, Yejin Choi, Percy Liang, and
65 Luke Zettlemoyer. Quac: Question answering in context. *arXiv preprint arXiv:1808.07036*,
66 2018.
- 67 [11] Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and
68 Kristina Toutanova. Boolq: Exploring the surprising difficulty of natural yes/no questions.
69 *arXiv preprint arXiv:1905.10044*, 2019.

- [12] Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.
- [13] Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, John Schulman, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, and Jerry Tworek. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.
- [14] Alexis Conneau, Ruty Rinott, Guillaume Lample, Adina Williams, Samuel R. Bowman, Holger Schwenk, and Veselin Stoyanov. Xnli: Evaluating cross-lingual sentence representations. 2018.
- [15] Leyang Cui, Yu Wu, Shujie Liu, Yue Zhang, and Ming Zhou. Mutual: A dataset for multi-turn dialogue reasoning. 2020.
- [16] Pradeep Dasigi, Kyle Lo, Iz Beltagy, Arman Cohan, Noah A. Smith, and Matt Gardner. A dataset of information-seeking questions and answers anchored in research papers. *arXiv preprint arXiv:2105.03011*, 2021.
- [17] Marie-Catherine de Marneffe, Mandy Simons, and Judith Tonhauser. The commitmentbank: Investigating projection in naturally occurring discourse. In *Proceedings of Sinn und Bedeutung 23*, volume 2, pages 107–124, Bellaterra (Cerdanyola del Vallès), 2019. Universitat Autònoma de Barcelona.
- [18] William B. Dolan and Chris Brockett. Automatically constructing a corpus of sentential paraphrases. *Proceedings of the Third International Workshop on Paraphrasing (IWP 2005)*, 2005.
- [19] Mingzhe Du, Anh Tuan Luu, Bin Ji, Liu Qian, and See-Kiong Ng. Mercury: A code efficiency benchmark for code llms. *arXiv preprint arXiv:2402.07844*, 2024.
- [20] Xinrun Du, Yifan Yao, Kaijing Ma, Bingli Wang, Tianyu Zheng, Kang Zhu, Minghao Liu, Yiming Liang, and et al. Supergpqa: Scaling llm evaluation across 285 graduate disciplines. *arXiv preprint arXiv:2502.14739*, 2025.
- [21] Dheeru Dua, Yizhong Wang, Pradeep Dasigi, Gabriel Stanovsky, Sameer Singh, and Matt Gardner. Drop: A reading comprehension benchmark requiring discrete reasoning over paragraphs. *arXiv preprint arXiv:1903.00161*, 2019.
- [22] Thomas Hartvigsen, Saadia Gabriel, Hamid Palangi, Maarten Sap, Dipankar Ray, and Ece Kamar. Toxigen: A large-scale machine-generated dataset for adversarial and implicit hate speech detection. 2022.
- [23] Dan Hendrycks, Steven Basart, Saurav Kadavath, Mantas Mazeika, Akul Arora, Ethan Guo, Collin Burns, Samir Puranik, Horace He, Dawn Song, and Jacob Steinhardt. Measuring coding challenge competence with apps. *arXiv preprint arXiv:2105.09938*, 2021.
- [24] Dan Hendrycks, Collin Burns, Steven Basart, Andrew Critch, Jerry Li, Dawn Song, and Jacob Steinhardt. Aligning ai with shared human values. *arXiv preprint arXiv:2008.02275*, 2020.
- [25] Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.
- [26] Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*, 2021.
- [27] Srinivasan Iyer, Ioannis Konstas, Alvin Cheung, and Luke Zettlemoyer. Mapping language to code in programmatic context. *arXiv preprint arXiv:1808.09588*, 2018.
- [28] Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. Livecodebench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*, 2024.

- [29] Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *arXiv preprint arXiv:2009.13081*, 2020.
- [30] Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William W. Cohen, and Xinghua Lu. Pubmedqa: A dataset for biomedical research question answering. 2019.
- [31] Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. Triviaqa: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1601–1611, Vancouver, Canada, 2017. Association for Computational Linguistics.
- [32] Daniel Khashabi, Snigdha Chaturvedi, Michael Roth, Shyam Upadhyay, and Dan Roth. Looking beyond the surface: A challenge set for reading comprehension over multiple sentences. 2018.
- [33] Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:452–466, 2019.
- [34] Guokun Lai, Qizhe Xie, Hanxiao Liu, Yiming Yang, and Eduard Hovy. Race: Large-scale reading comprehension dataset from examinations. *arXiv preprint arXiv:1704.04683*, 2017.
- [35] Yuhang Lai, Chengxi Li, Yiming Wang, Tianyi Zhang, Ruiqi Zhong, Luke Zettlemoyer, Scott Wen-tau Yih, Daniel Fried, Sida Wang, and Tao Yu. Ds-1000: A natural and reliable benchmark for data science code generation. *arXiv preprint arXiv:2211.11501*, 2022.
- [36] Hector J. Levesque, Ernest Davis, and Leora Morgenstern. The winograd schema challenge. *arXiv preprint arXiv:1105.4590*, 2011.
- [37] Hector J. Levesque, Ernest Davis, and Leora Morgenstern. The winograd schema challenge. 2012.
- [38] Stephanie Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. *arXiv preprint arXiv:2109.07958*, 2021.
- [39] Xi Victoria Lin, Todor Mihaylov, Mikel Artetxe, Tianlu Wang, Shuohui Chen, Daniel Simig, Myle Ott, Naman Goyal, Shruti Bhosale, Jingfei Du, Ramakanth Pasunuru, Sam Shleifer, Punit Singh Koura, Vishrav Chaudhary, Brian O’Horo, Jeff Wang, Luke Zettlemoyer, Zornitsa Kozareva, Mona T. Diab, Veselin Stoyanov, and Xian Li. Few-shot learning with multilingual language models. *arXiv preprint arXiv:2112.10668*, 2021.
- [40] Hanmeng Liu, Jian Liu, Leyang Cui, Zhiyang Teng, Nan Duan, Ming Zhou, and Yue Zhang. Logiqa 2.0—an improved dataset for logical reasoning in natural language understanding. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 2023.
- [41] Jian Liu, Leyang Cui, Hanmeng Liu, Dandan Huang, Yile Wang, and Yue Zhang. Logiqa: A challenge dataset for machine reading comprehension with logical reasoning. *arXiv preprint arXiv:2007.08124*, 2020.
- [42] Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation. In *NeurIPS 2023 Datasets and Benchmarks Track*, 2023.
- [43] Junnan Liu, Hongwei Liu, Linchen Xiao, Ziyi Wang, Kuikun Liu, Songyang Gao, Wenwei Zhang, Songyang Zhang, and Kai Chen. Are your llms capable of stable reasoning? *arXiv preprint arXiv:2412.13147*, 2024.
- [44] Shuai Lu, Daya Guo, Shuo Ren, Junjie Huang, Alexey Svyatkovskiy, Ambrosio Blanco, Colin Clement, Dawn Drain, Daxin Jiang, Duyu Tang, Ge Li, Lidong Zhou, Linjun Shou, Long Zhou, Michele Tufano, Ming Gong, Ming Zhou, Nan Duan, Neel Sundaresan, Shao Kun Deng, Shengyu Fu, and Shujie Liu. Codexglue: A machine learning benchmark dataset for code understanding and generation. *arXiv preprint arXiv:2102.04664*, 2021.

- [45] Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.
- [46] Shen-Yun Miao, Chao-Chun Liang, and Keh-Yih Su. A diverse corpus for evaluating and developing english math word problem solvers. *arXiv preprint arXiv:2106.15772*, 2021.
- [47] Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. Can a suit of armor conduct electricity? a new dataset for open book question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2018.
- [48] Niklas Muennighoff, Qian Liu, Armel Zebaze, Qinkai Zheng, Binyuan Hui, Terry Yue Zhuo, Swayam Singh, Xiangru Tang, Leandro von Werra, and Shayne Longpre. Octopack: Instruction tuning code large language models. *arXiv preprint arXiv:2308.07124*, 2023.
- [49] Nikita Nangia, Clara Vania, Rasika Bhalerao, and Samuel R. Bowman. Crows-pairs: A challenge dataset for measuring social biases in masked language models. 2020.
- [50] Yixin Nie, Adina Williams, Emily Dinan, Mohit Bansal, Jason Weston, and Douwe Kiela. Adversarial nli: A new benchmark for natural language understanding. *arXiv preprint arXiv:1910.14599*, 2020.
- [51] Denis Paperno, Germán Kruszewski, Angeliki Lazaridou, Quan Pham, Raffaella Bernardi, Sandro Pezzelle, Gemma Boleda, Marco Baroni, et al. The lambada dataset: Word prediction requiring a broad discourse context. 2016.
- [52] Anselmo Peñas, Eduard Hovy, Pamela Forner, Álvaro Rodrigo, Richard Sutcliffe, and Roser Morante. Qa4mre 2011–2013: Overview of question answering for machine reading evaluation. *CLEF 2013: Information Access Evaluation. Multilinguality, Multimodality, and Visualization*, 2013.
- [53] Long Phan, Alice Gatti, Ziwen Han, Nathaniel Li, and et al. Humanity’s last exam. *arXiv preprint arXiv:2501.14249*, 2025.
- [54] Mohammad Taher Pilehvar and Jose Camacho-Collados. Wic: the word-in-context dataset for evaluating context-sensitive meaning representations. 2019.
- [55] Edoardo Maria Ponti, Maarten Sap, Christo Kirov, Aksel Langedijk, Felix Hill, Ekaterina Shutova, Peter Clark, Ivan Vulić, and Anna Korhonen. Xcopa: A multilingual dataset for causal commonsense reasoning. 2020.
- [56] Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don’t know: Unanswerable questions for squad. *arXiv preprint arXiv:1806.03822*, 2018.
- [57] Siva Reddy, Danqi Chen, and Christopher D. Manning. Coqa: A conversational question answering challenge. *arXiv preprint arXiv:1808.07042*, 2019.
- [58] David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. Gpqa: A graduate-level google-proof q&a benchmark. *arXiv preprint arXiv:2311.12022*, 2023.
- [59] Melissa Roemmele, Cosmin Adrian Bejan, and Andrew S. Gordon. Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In *AAAI Spring Symposium on Logical Formalizations of Commonsense Reasoning*, Stanford, CA, 2011.
- [60] Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *arXiv preprint arXiv:1907.10641*, 2019.
- [61] Maarten Sap, Hannah Rashkin, Derek Chen, Ronan Le Bras, and Yejin Choi. Social iqa: Commonsense reasoning about social interactions. *arXiv preprint arXiv:1904.09728*, 2019.
- [62] Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. Language models are multilingual chain-of-thought reasoners. *arXiv preprint arXiv:2210.03057*, 2022.

- [63] Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Y. Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. 2013.
- [64] Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, and et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *arXiv preprint arXiv:2206.04615*, 2022.
- [65] Alexey Tikhonov, Mikhail Ryabinin, Yuri Kuratov, and Thomas Wolf. It’s all in the heads: Using attention heads as a baseline for cross-lingual transfer in commonsense reasoning. *arXiv preprint arXiv:2106.12066*, 2021.
- [66] David Vilares and Carlos Gómez-Rodríguez. Head-qa: A healthcare dataset for complex reasoning. 2019.
- [67] Shiqi Wang, Zheng Li, Haifeng Qian, Chenghao Yang, Zijian Wang, Mingyue Shang, Varun Kumar, Samson Tan, Baishakhi Ray, Parminder Bhatia, Ramesh Nallapati, Murali Krishna Ramanathan, Dan Roth, and Bing Xiang. Recode: Robustness evaluation of code generation models. *arXiv preprint arXiv:2212.10264*, 2022.
- [68] Yiming Wang, Pei Zhang, Jialong Tang, Haoran Wei, Baosong Yang, Rui Wang, Chenshu Sun, Feitong Sun, Jiran Zhang, Junxuan Wu, Qiqian Cang, Yichang Zhang, Fei Huang, Junyang Lin, Fei Huang, and Jingren Zhou. Polymath: Evaluating mathematical reasoning in multilingual contexts. *arXiv preprint arXiv:2504.18428*, 2025.
- [69] Alex Warstadt, Alicia Parrish, Haokun Liu, Anhad Mohananey, Wei Peng, and Samuel R. Bowman. Blimp: The benchmark of linguistic minimal pairs for english. *arXiv preprint arXiv:1912.00582*, 2020.
- [70] Johannes Welbl, Nelson F. Liu, and Matt Gardner. Crowdsourcing multiple choice science questions. *arXiv preprint arXiv:1707.06209*, 2017.
- [71] Yinfei Yang, Yuan Zhang, Chris Tar, and Jason Baldridge. Paws-x: A cross-lingual adversarial dataset for paraphrase identification. 2019.
- [72] Pengcheng Yin, Bowen Deng, Edgar Chen, Bogdan Vasilescu, and Graham Neubig. Learning to mine aligned code and natural language pairs from stack overflow. In *Proceedings of the 15th IEEE/ACM International Conference on Mining Software Repositories (MSR)*, pages 476–486. IEEE, 2018.
- [73] Rowan Zellers, Yonatan Bisk, Roy Schwartz, and Yejin Choi. Swag: A large-scale adversarial dataset for grounded commonsense inference. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 93–104, Brussels, Belgium, 2018. Association for Computational Linguistics.
- [74] Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? *arXiv preprint arXiv:1905.07830*, 2019.
- [75] Sheng Zhang, Xiaodong Liu, Jingjing Liu, Jianfeng Gao, Kevin Duh, and Benjamin Van Durme. Record: Bridging the gap between human and machine commonsense reading comprehension. *arXiv preprint arXiv:1810.12885*, 2018.
- [76] Wanjun Zhong, Ruixiang Cui, Yiduo Guo, Yaobo Liang, Shuai Lu, Yanlin Wang, Amin Saied, Weizhu Chen, and Nan Duan. Agieval: A human-centric benchmark for evaluating foundation models. *arXiv preprint arXiv:2304.06364*, 2023.
- [77] Ben Zhou, Daniel Khashabi, Qiang Ning, and Dan Roth. “going on a vacation” takes longer than “going for a walk”: A study of temporal commonsense understanding. 2019.

259 A Wisent Guard Primitives

260 A.1 Model

261 A.2 Contrastive Pair

262 A.3 Activations

263 A.4 Activation Collection Method

264 A.5 Additional Utilities

265 B Representation Reading Functionalities

266 B.1 Classifier

267 B.2 Detection Handling Method

268 C Representation Control Functionalities

269 D Ablation

270 A All supported benchmarks

271 This section enumerates all benchmarks used in our study, the task traits, the evaluation protocol, and
272 the contrastive pair generation method applied to produce minimally perturbed negative targets. We
273 first merged the *coding* and *mathematics* benchmark lists you provided and then appended them to
274 the original master list.

275 Contrastive pair generation methods (definitions)

276 **Reading Comprehension Abstention Swap** [RC-Abstain] For extractive/open-domain RC: posi-
277 tive is the gold span; negative is an abstention (e.g., “Not provided in the text.”). If gold is
278 *No answer*, the negative is a confident but wrong claim.

279 **Conversational Reading Comprehension Abstention** [ConvRC-Abstain] As RC-Abstain, but
280 with dialogue context (CoQA). Negatives are generic abstentions; yes/no items are flipped
281 when applicable.

282 **Language Modeling Corrupted Continuation** [LM-CorruptCont] Language modeling: positive
283 is the true continuation; negative is a corrupted continuation (local shuffles/randomization)
284 to break coherence.

285 **Two-Choice Flip** [2C-Flip] Two-option tasks (PIQA, COPA, WinoGrande, CB): negative is simply
286 the other option.

287 **Multichoice First Distractor** [MC-FirstDistr] Multi-choice tasks: negative is the first incorrect
288 option in the provided order (deterministic).

289 **Multichoice Random Distractor** [MC-RandDistr] Multi-choice tasks: negative is a randomly cho-
290 sen incorrect option from the same set.

291 **Exact Match Partial Mask** [EM-PartialMask] Exact-match free-form answers (HLE-EM): nega-
292 tive is the gold text with partial token masking (approximately 1/3 words, or partial masking
293 for single-word answers).

294 **Keyword-Preserving Token Deletion** [KP-Del] Coding tasks: negative program created by delet-
295 ing non-keyword tokens while preserving syntax-critical keywords; aims to remain plausible
296 but fail unit tests.

297 **Numeric Offset (+1) Perturbation** [Num+1] Negative is the correct numeric answer offset by a
298 small integer (typically +1); for non-integer answers, apply the minimal unit offset.

299	Summary Content-Polarity Flip [Summ-PolFlip] Code to text summarization: make a negative
300	description by flipping key action words with simple opposites or adding “not” (e.g., “return”
301	to “does not return”, “add” to “remove”), while keeping the rest of the sentence the same.
302	Library Specific Flip [Lib-Spec-Filip] Coding tasks: negative program created by flipping func-
303	tions, parameters (e.g. for numpy flip axis 0 to 1, for pandas flip mean() to sum()).
304	Logic inversion [Log-Inv] Coding tasks: negative program created by flipping bools, operators in
305	code (e.g. return True to return False, <= to >=).
306	Offset (+-1) [+1] Coding tasks: negative program created by adding/subtracting 1 from range or
307	numeric value.
308	Replace empty [Empty] Coding tasks: negative program created by replacing string to empty string,
309	list to empty list.
310	Generic incorrect continuation [Gen-Inc-Cont] Answer generation tasks: negative is created by
311	generic incorrect answer.
312	Early return [Return] Coding tasks: negative program created by early return.
313	Evaluation types (definitions)
314	Log-likelihood option scoring [LL] The model scores each provided option/target by conditional
315	log-probability given the prompt. Metrics typically compute accuracy over the highest-
316	likelihood choice (MC tasks) or compare likelihoods of gold vs. negative targets.
317	Text generation string matching [TG] The model generates free-form text (or a number), which
318	is then judged by task-specific metrics (e.g., exact match on numerical value for
319	GSM8K/MATH; span/string matching for RC tasks; structured checks for DROP). Used
320	also for CoT/generative GPQA variants and HLE-Exact-Match.
321	Perplexity (language modeling) [PPL] The model’s next-token distribution is evaluated over a
322	reference text to compute Perplexity (lower is better). Used for language-modeling corpora
323	like WikiText.
324	Code execution against unit tests [CE] The model generates code, which is executed in a sandbox
325	against unit tests provided by a dataset (e.g., pass@1). Applies to HumanEval/MBPP/APPS,
326	MultiPL-E, DS-1000, LiveCodeBench, etc.

Table 1: Benchmarks (short names), evaluation abbreviations, contrastive method (short), and traits. Versions merged where applicable.

Benchmark	Eval	Method [CM]	Traits
DROP [21]	[TG]	RC-Abstain	reading comprehension
ReCoRD [75]	[TG]	RC-Abstain	reading comprehension
SQuAD2 [56]	[TG]	RC-Abstain	reading comprehension
WebQuestions [5]	[TG]	RC-Abstain	factual QA
Natural Questions [33]	[TG]	RC-Abstain	factual QA
TriviaQA [31]	[TG]	RC-Abstain	factual QA
CoQA [57]	[TG]	ConvRC-Abstain	conversational RC
BoolQ [11]	[LL]	2C-Flip	boolean RC
Race [34]	[LL]	MC-FirstDistr	reading comprehension
QA4MRE [52]	[LL]	MC-FirstDistr	machine reading
QASPER [16]	[TG]	RC-Abstain	scientific QA
QuAC [10]	[TG]	ConvRC-Abstain	conversational QA
MultiRC [32]	[LL]		multi-sentence reasoning
WinoGrande [60]	[LL]	2C-Flip	commonsense
PIQA [6]	[LL]	2C-Flip	commonsense
COPA [59]	[LL]	2C-Flip	causal reasoning
HellaSwag [74]	[LL]	MC-FirstDistr	commonsense
SWAG [73]	[LL]	MC-FirstDistr	commonsense







Benchmark	Eval	Method [CM]	Traits
OpenBookQA [47]	[LL]	MC-FirstDistr	science MCQ
ARC Easy [12]	[LL]	MC-FirstDistr	science reasoning
ARC Challenge [12]	[LL]	MC-FirstDistr	science reasoning
AI2 ARC [12]	[LL]	MC-FirstDistr	science reasoning
LogiQA [41]	[LL]	MC-FirstDistr	logical reasoning
LogiQA2 [40]	[LL]	MC-FirstDistr	logical reasoning
AGIEval LogiQA EN [76]	[LL]	MC-FirstDistr	logical reasoning
AGIEval LogiQA ZH [76]	[LL]	MC-FirstDistr	logical reasoning
WSC [36]	[LL]	2C-Flip	commonsense reasoning
WSC273 [37]	[LL]	2C-Flip	commonsense reasoning
MC-TACO [77]	[LL]	2C-Flip	temporal commonsense
Social IQA [61]	[LL]	MC-FirstDistr	social reasoning
PROST [2]	[LL]	MC-FirstDistr	physical reasoning
MMLU [25]	[LL]	MC-FirstDistr	multi-subject exams
GPQA [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
SuperGPQA [20]		MC-FirstDistr	expert STEM exams
SuperGPQA Biology [20]			expert STEM exams
SuperGPQA Chemistry [20]		MC-FirstDistr	expert STEM exams
SuperGPQA Physics [20]		MC-FirstDistr	expert STEM exams
HLE [53]	[TG]/[LL]	EM-PartialMask; MC-FirstDistr	expert exams
MMMLU []	[LL]	MC-FirstDistr	multilingual knowledge
TruthfulQA MC1 [38]	[LL]	MC-FirstDistr	truthfulness
TruthfulQA MC2 [38]	[LL]		truthfulness
TruthfulQA Gen [38]	[TG]		truthfulness
PubMedQA [30]	[LL]		biomedical QA
SciQ [70]	[LL]	MC-FirstDistr	science MCQ
Hendrycks Ethics [24]	[LL]	MC-FirstDistr	moral reasoning
HeadQA [66]	[LL]	MC-FirstDistr	healthcare QA
MedQA [29]	[LL]	MC-FirstDistr	medical QA
GPQA Diamond [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Diamond CoT N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Diamond CoT Zeroshot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Diamond Generative N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Diamond N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Diamond Zeroshot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Extended [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Extended CoT N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Extended CoT Zeroshot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Extended Generative N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Extended N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Extended Zeroshot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Main CoT N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Main CoT Zeroshot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Main Generative N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
GPQA Main N-shot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams

Benchmark	Eval	Method [CM]	Traits
GPQA Main Zeroshot [58]	[LL]/[TG]	MC-RandDistr	expert STEM exams
HLE Exact Match [53]	[TG]	EM-PartialMask	expert exams
HLE Multiple Choice [53]	[LL]	MC-FirstDistr	expert exams
GSM8K [13]	[TG]	Num+1	mathematics
ASDiv [46]	[TG]	Num+1	mathematics
Arithmetic [7]	[TG]	Num+1	mathematics
MATH [26]	[TG]	Num+1	mathematics (contest)
MATH-500	[TG]	Num+1	mathematics (contest)
AIME	[TG]	Num+1	mathematics (contest)
AIME2024	[TG]	Num+1	mathematics (contest)
AIME2025	[TG]	Num+1	mathematics (contest)
HMMT	[TG]	Num+1	mathematics (contest)
HMMT Feb 2025	[TG]	Num+1	mathematics (contest)
PolyMath [68]	[TG]	Num+1	multilingual mathematics
PolyMath EN Medium [68]	[TG]	Num+1	mathematics (olympiad)
PolyMath ZH Medium [68]	[TG]	Num+1	mathematics (olympiad)
PolyMath EN High [68]	[TG]	Num+1	mathematics (olympiad)
PolyMath ZH High [68]	[TG]	Num+1	mathematics (olympiad)
LiveMathBench [43]	[TG]	Num+1	mathematics
LiveMathBench CNMO EN [43]	[TG]	Num+1	mathematics
LiveMathBench CNMO ZH [43]	[TG]	Num+1	mathematics
Hendrycks MATH [26]	[TG]	Num+1	mathematics (contest)
Math QA [1]	[TG]	MC-FirstDistr	mathematics
MGSM [62]	[TG]	Num+1	multilingual mathematics
MBPP [3]	[CE]	+-1; Empty; Return	coding (Python)
MBPP+ [42]	[CE]	+-1; Empty; Return	coding (Python)
HumanEval [9]	[CE]	Log-Inv; +-1	coding (Python)
HumanEval+ [42]	[CE]	Log-Inv; +-1	coding (Python)
HumanEvalPack [48]	[CE]	Log-Inv; +-1	coding (multi-language)
InstructHumanEval	[CE]	Log-Inv; +-1	coding (Python)
CoNaLa [72]	[CE]	KP-Del	coding (Python)
CONCODE [27]	[CE]	KP-Del	coding (Java)
Mercury [19]	[CE]	Log-Inv; +-1	coding (multi-language)
APPS [23]	[CE]	KP-Del	coding (Python)
DS-1000 [35]	[CE]	Lib-Spec-Flip	coding (Python)
ReCode [67]	[CE]	Log-Inv; +-1	coding (Python)
LiveCodeBench [28]	[CE]	KP-Del	coding (Python)
Multiple CPP [8]	[CE]		coding (C++)
Multiple Go [8]	[CE]		coding (Go)
Multiple Java [8]	[CE]		coding (Java)
Multiple JS [8]	[CE]		coding (JavaScript)
Multiple PY [8]	[CE]		coding (Python)
Multiple RS [8]	[CE]		coding (Rust)
CodeXGLUE Code to Text Python [44]	[TG]	Summ-PolFlip	coding (code-to-text)
CodeXGLUE Code to Text Go [44]	[TG]	Summ-PolFlip	coding (code-to-text)
CodeXGLUE Code to Text Java [44]	[TG]	Summ-PolFlip	coding (code-to-text)
CodeXGLUE Code to Text JavaScript [44]	[TG]	Summ-PolFlip	coding (code-to-text)

Benchmark	Eval	Method [CM]	Traits
CodeXGLUE Code to Text PHP [44]	[TG]	Summ-PolFlip	coding (code-to-text)
CodeXGLUE Code to Text Ruby [44]	[TG]	Summ-PolFlip	coding (code-to-text)
CB [17]	[LL]		NLI
WikiText [45]	[PPL]	LM-CorruptCont	language modeling
MRPC [18]	[LL]	2C-Flip	paraphrase detection
QNLI	[LL]	2C-Flip	NLI
QQP	[LL]	2C-Flip	paraphrase detection
RTE	[LL]	2C-Flip	NLI
SST2 [63]	[LL]	2C-Flip	sentiment analysis
WNLI	[LL]	2C-Flip	NLI
WiC [54]	[LL]		word-in-context
Mutual [15]	[LL]	MC-FirstDistr	dialogue reasoning
ANLI [50]	[LL]	MC-FirstDistr	NLI
BLIMP [69]	[LL]		linguistic knowledge
Toxigen [22]	[LL]		toxicity detection
Crows Pairs [49]	[LL]		bias measurement
PAWS-X [71]	[LL]		cross-lingual paraphrase
Unscramble	[TG]		word unscrambling
LAMBADA [51]	[LL]		language modeling
LAMBADA Cloze [51]	[LL]		language modeling
LAMBADA Multilingual [51]	[LL]		multilingual LM
LAMBADA Standard Cloze	[LL]		language modeling
YAML [51]			
Belebele [4]	[LL]	MC-firstDistr	multilingual RC
XCOPA [55]	[LL]	2C-Flip	cross-lingual reasoning
XNLI [14]	[LL]		cross-lingual NLI
XStoryCloze [39]	[LL]	2C-Flip	cross-lingual story
XWinograd [65]	[LL]	2C-Flip	cross-lingual reasoning
BIG-Bench [64]	[LL]/[TG]	MC-FirstDistr; Gen-Inc-Cont	comprehensive evaluation

327

Category legend


	RC/ODQA
	Multi-choice Reasoning
	Exams & Knowledge Tests
	Mathematics
	Coding
	Other (Truthfulness/NLI/LM)

Abbreviation legend

[LL]	Log-likelihood option scoring
[TG]	Text generation (string match)
[PPL]	Perplexity (LM)
[CE]	Code execution vs. unit tests

Method [CM] codes

RC-Abstain	RC abstention swap
ConvRC-Abstain	Conversational RC abstention
LM-CorruptCont	LM corrupted continuation
2C-Flip	Two-choice flip
MC-FirstDistr	First distractor (MC)
MC-RandDistr	Random distractor (MC)
MC-LetterSwap	Letter swap (MC)
Bool-Flip	Boolean flip
EM-PartialMask	Exact-match partial mask
KP-Del	Keyword-preserving deletion
Summ-WordDrop	Summary word drop
Num+1	Numeric offset (+1)



330 *Figure: GSM8K evaluation pipeline showing data flow from task loading through dual evaluation.*