Order - operational storage ER

Current amendment to ER item 1 - 2026-10-14 - Original ER pages/PDF archives retained

Operational dispute state is stored in dispute_case, not WORKFLOW_STATE logs.
Address tables each contain owner PK/FK plus seven typed address fields.
Attribution and product sync are durable job tables. IDs are unchanged on retry.
Checkout totals remain derived from order amounts; audit history is retained.

orders

PK	order_id	TEXT NN
FK	checkout_id	TEXT NULL
FK/UQ	basket_id	TEXT NULL
-	buyer_id	TEXT NN
-	seller_id	TEXT NN
-	product_id	TEXT NN
-	product_title	TEXT NULL
-	campaign_code	TEXT NULL
-	pre_dispute_status	TEXT NULL
-	campaign_id	TEXT NULL
UQ	auction_id	TEXT NULL
-	order_type	TEXT NN
-	original_amount	DECIMAL(18, 2) NN
-	orders_amount	DECIMAL(18, 2) NN
-	status	TEXT NN
-	version	INT NN
-	created_at	TIMESTAMP(3) NN
-	updated_at	TIMESTAMP(3) NN

dispute_case

PK	dispute_case_id	TEXT NN
FK/UQ	order_id	TEXT NN
-	created_by	TEXT NN
-	reason	TEXT NN
-	decision	TEXT NULL
-	dispute_type	TEXT NN
-	dispute_case_version	INT NN
-	assigned_to	TEXT NULL
-	assigned_at	TIMESTAMP(3) NULL
-	status	TEXT NN
-	created_at	TIMESTAMP(3) NN
-	assigned_role	TEXT NULL
-	decision_reason	TEXT NULL
-	decided_by	TEXT NULL
-	decided_at	TIMESTAMP(3) NULL
UQ	verdict_key	TEXT NULL
-	escalation_note	TEXT NULL
-	escalated_by	TEXT NULL
-	priority	TEXT NN
-	priority_score	INT NN
-	risk_report_count	INT NN
-	sla_expires_at	TIMESTAMP(3) NULL
-	sla_policy_version	TEXT NULL
-	first_review_due_at	TIMESTAMP(3) NULL
-	first_reviewed_at	TIMESTAMP(3) NULL
-	decision_due_at	TIMESTAMP(3) NULL

checkouts

PK	checkout_id	TEXT NN
-	buyer_id	TEXT NN
-	address_id	TEXT NN
-	status	TEXT NN
-	paid_at	TIMESTAMP(3) NULL
-	cancel_at	TIMESTAMP(3) NN
-	created_at	TIMESTAMP(3) NN
-	updated_at	TIMESTAMP(3) NN

shipping

PK	shipping_id	TEXT NN
FK/UQ	order_id	TEXT NN
-	address_id	TEXT NN
-	company	TEXT NULL
-	tracking_number	TEXT NULL
-	status	TEXT NN
-	updated_at	TIMESTAMP(3) NN

checkout_address_snapshots

PK/FK	checkout_id	TEXT NN
-	recipient_name	TEXT NN
-	phone	TEXT NN
-	address_line	TEXT NN
-	subdistrict	TEXT NN
-	district	TEXT NN
-	province	TEXT NN
-	postal_code	TEXT NN

shipping_address_snapshots

PK/FK	shipping_id	TEXT NN
-	recipient_name	TEXT NN
-	phone	TEXT NN
-	address_line	TEXT NN
-	subdistrict	TEXT NN
-	district	TEXT NN
-	province	TEXT NN
-	postal_code	TEXT NN

order_attribution_jobs

PK	id	TEXT NN
FK/UQ	order_id	TEXT NN
-	campaign_id	TEXT NN
-	gross_amount	DECIMAL(18, 2) NN
-	discount_amount	DECIMAL(18, 2) NN
-	net_amount	DECIMAL(18, 2) NN
-	completed_at	TIMESTAMP(3) NN
-	attempts	INT NN
-	last_error	TEXT NULL
-	next_attempt_at	TIMESTAMP(3) NN
-	processed_at	TIMESTAMP(3) NULL
-	created_at	TIMESTAMP(3) NN

order_product_sync_jobs

PK	event_id	TEXT NN
FK	order_id	TEXT NN
-	product_id	TEXT NN
-	action	TEXT NN
-	reservation_id	TEXT NULL
-	target_status	TEXT NULL
-	actor_id	TEXT NN
-	created_at	TIMESTAMP(3) NN
-	processed_at	TIMESTAMP(3) NULL

Relationship keys (physical FK unless marked logical)

R1: dispute_case -> orders [parent:child 1 : 0..1]

```
order_id -> order_id
```

R2: orders -> checkouts [parent:child 1 : 0..N]

```
checkout_id -> checkout_id
```

R3: shipping -> orders [parent:child 1 : 0..1]

```
order_id -> order_id
```

R4: checkout_address_snapshots -> checkouts [parent:child 1 : 0..1]

```
checkout_id -> checkout_id
```

R5: shipping_address_snapshots -> shipping [parent:child 1 : 0..1]

```
shipping_id -> shipping_id
```

R6: order_attribution_jobs -> orders [parent:child 1 : 0..1]

```
order_id -> order_id
```

R7: order_product_sync_jobs -> orders [parent:child 1 : 0..N]

```
order_id -> order_id
```

PK primary key | FK foreign key | UQ unique | NN not null | IDs to other services are logical references