

Definicje tagów HTML w JSF [Java Server Faces]

Ta podręczna lista referencji, definiuje standardowe tagi HTML, które są generowane przez JSF. Dla tych tagów, musisz, użyć podanego uri atrybutu dla dyrektywy taglib w pliku JSP: <http://java.sun.com/jsf/html>

Tabela ukazuje przykłady HTML kodów, oraz użycie proporcjonalne dla JSF biblioteki tagów:

Tag JSF	Odpowiednik HTML
UIForm	
form	
<pre><h:form id="jsftags"> ... </h:form></pre>	<pre><form id="jsftags" method="post" action="/jsftags/faces/pages/tags.js p" enctype="application/x-www-form- urlencoded"> ... <input type="hidden" name="jsftags" value="jsftags" /> <input type="hidden" name="jsftags:link" /> </form></pre>
UICommand	
commandButton	
<pre><h:commandButton id="submit" value="#{msg.buttonHeader}" action="nextPage"> </h:commandButton></pre>	<pre><input id="_id0:submit" type="submit" name="_id0:submit" value="Next Step" /></pre>
commandLink	
<pre><h:commandLink id="link" action="goto"> <h:outputText value="#{msg.linkName}" /> </h:commandLink></pre>	<pre>Next Page</pre>
UIGraphic	
graphicImage	
<pre><h:graphicImage id="image" alt="jsf-sun" url="/images/jsf-sun.gif"> </h:graphicImage></pre>	<pre></pre>
UIInput	

inputText	
<code><h:inputText id="address" value="#{jsfexample.address}" /></code>	<code><input type="text" name="jsftags:_id1" value="123 JSF Ave" /></code>
inputSecret	
<code><h:inputSecret redisplay="false" value="#{jsfexample.password}" /></code>	<code><input id="jsftags:password" type="password" name="jsftags:password" value="secret" /></code>
inputHidden	
<code><h:inputHidden id="hidden" value="userPreference" /></code>	<code><input id="jsftags:hidden" type="hidden" name="jsftags:hidden" value="userPreference" /></code>
inputTextArea	
<code><h:inputTextarea id="textArea" rows="4" cols="7" value="Text goes here.." /></code>	<code><textarea id="jsftags:textArea" name="jsftags:textArea" cols="5" rows="3"> Text goes here.. </textarea></code>
UIOutput	
outputText	
<code><h:outputText value="#{jsfexample.zipCode}" /></code>	10032
outputLabel	
<code><h:outputLabel for="address"> <h:outputText id="addressLabel" value="User Home Address" /> </h:outputLabel></code>	<code> User Home Address</code>
outputLink	
<code><h:outputLink value="#{msg['jsfstudio.home.url']}"> <f:verbatim>Funkcje.net</f:verbatim> </h:outputLink></code>	<code> Funkcje.net </code>
outputFormat	
<code><h:outputFormat value="#{msg.jsfstudioThankYou}"> <f:param value="Joe Blow" /> <f:param id="productName" value="#{msg['jsfstudio.label']}" /> </h:outputFormat></code>	Thank you, Joe Blow, for trying Exadel JSF Studio!
UIMessage and UIMessages	
message	
Enter address:	Enter address:

<pre> <h:message style="color: red" for="useraddress" /> <h:inputText id="useraddress" value="#{jsfexample.address}" required="true"/> <h:commandButton action="save" value="Save" /> </pre>	<pre> Validation Error: Value is required. <input id="jsftags:useraddress" type="text" name="jsftags:useraddress" value="" /> <input type="submit" name="jsftags:_idl" value="Save" /> </pre>
UISelectBoolean	
selectBooleanCheckbox	
<pre> <h:selectBooleanCheckbox title="emailUpdates" value="#{jsfexample.wantsEmailUpdates}" > </h:selectBooleanCheckbox> <h:outputText value="Tekst.." /> </pre>	<pre> <input type="checkbox" name="jsftags:_id6" checked title="emailUpdates" /> Tekst..? </pre>
UISelectMany	
selectManyCheckboxlist	
<pre> <h:selectManyCheckbox id="cars" value="#{carsBean.car}"> <f:selectItems value="#{carBean.carList}" /> </h:selectManyCheckbox> </pre>	<pre> <table> <tr> <td><label for="jsftags:cars"> <input name="jsftags:cars" value="accord" type="checkbox"> Honda Accord</input> </label></td> <td><label for="jsftags:cars"> <input name="jsftags:cars" value="4runner" type="checkbox"> Toyota 4Runner</input> </label></td> <td><label for="jsftags:cars"> <input name="jsftags:cars" value="nissan-z" type="checkbox"> Nissan Z350</input> </label></td> </tr> </table> </pre>
selectManyMenu	
<pre> <h:selectManyMenu id="cars_selectManyMenu" value="#{carBean.car}"> <f:selectItems value="#{carBean.carList}" /> </h:selectManyMenu> </pre>	<pre> <select id="jsftags:cars_selectManyMenu" name="jsftags:cars_selectManyMenu" multiple size="1"> <option value="accord">Honda Accord</option> <option value="4runner">Toyota </pre>

	<pre> 4Runner</option> <option value="nissan-z">Nissan Z350</option> </select> </pre>
selectManyListbox	
<pre> <h:selectManyListbox id="cars_selectManyListbox" value="#{carBean.car}"> <f:selectItems value="#{carBean.carList}" /> </h:selectManyListbox> </pre>	<pre> <select id="jsftags:cars_selectManyListbox" name="jsftags:cars_selectManyListbox" multiple size="3"> <option value="accord">Honda Accord</option> <option value="4runner">Toyota 4Runner</option> <option value="nissan-z">Nissan Z350</option> </select> </pre>
UISelectOne	
selectOneRadio	
<pre> <h:selectOneRadio value="#{carBean.currentCar}"> <f:selectItems value="#{carBean.carList}" /> </h:selectOneRadio> </pre>	<pre> <table><tr> <td> <label for="jsftags:_id9"> <input type="radio" name="jsftags:_id9" value="accord"> Honda Accord </input></label> </td> <td> <label for="jsftags:_id9"> <input type="radio" name="jsftags:_id9" value="4runner"> Toyota 4Runner </input></label> </td> <td> <label for="jsftags:_id9"> <input type="radio" name="jsftags:_id9" value="nissan-z"> Nissan Z350 </input></label> </td> </tr></table> </pre>
selectOneMenu	
<pre> <h:selectOneMenu id="selectCar" value="#{carBean.currentCar}"> <f:selectItems value="#{carBean.carList}" /> </h:selectOneMenu> </pre>	<pre> <select id="jsftags:selectCar" name="jsftags:selectCar" size="1"> <option value="accord">Honda Accord</option> <option value="4runner">Toyota 4Runner</option> <option value="nissan-z">Nissan Z350</option> </pre>

	</select>
selectOneListbox	
<pre> <h:selectOneListbox id="pickCar" value="#{carBean.currentCar}"> <f:selectItems value="#{carBean.carList}" /> </h:selectOneListbox> </pre>	<pre> <select id="jsftags:pickCar" name="jsftags:selectCar" size="3"> <option value="accord">Honda Accord</option> <option value="4runner">Toyota 4Runner</option> <option value="nissan-z">Nissan Z350</option> </select> </pre>
UIPanel	
Grid and Group	
<pre> <h:panelGrid columns="4" footerClass="subtitle" headerClass="subtitlebig" styleClass="medium" columnClasses="subtitle,medium"> <f:facet name="header"> <h:outputText value="Table with numbers"/> </f:facet> <h:outputText value="1" /> <h:outputText value="2" /> <h:outputText value="3" /> <h:outputText value="4" /> <h:outputText value="5" /> <h:outputText value="6" /> <h:outputText value="7" /> <f:facet name="footer"> <h:panelGroup> <h:outputText value="one row" /> <h:outputText value=" " /> <h:outputText value="grouped with panelGroup" /> </h:panelGroup> </f:facet> </h:panelGrid> </pre>	<pre> <table class="medium"> <thead> <tr><th class="subtitlebig" colspan="4" scope="colgroup">Table with numbers</th> </tr> </thead> <tfoot> <tr><td class="subtitle" colspan="4"> one row grouped with panelGroup </td> </tr> </tfoot> <tbody> <tr> <td class="subtitle">1</td> <td class="medium">2</td> <td class="subtitle">3</td> <td class="medium">4</td> </tr> <tr> <td class="subtitle">5</td> <td class="medium">6</td> <td class="subtitle">7</td> </tr> </tbody> </table> </pre>
UIColumn and UIData	
dataTable and column	
<pre> <h:dataTable id="books" columnClasses="list-column-center, list-column-right, list-column- center, list-column-right" headerClass="list- header" rowClasses="list-row" styleClass="list- </pre>	<pre> <table id="jsftags:books" class="list-background"> <thead> <tr> <th class="list-header" scope="col">Title</th> <th class="list-header" scope="col">Subject</th> </pre>

<pre>background" value="#{BookStore.items}" var="store"> <h:column> <f:facet name="header"> <h:outputText value="#{msg.storeNameLabel}"/> </f:facet> <h:outputText value="#{store.name}"/> </h:column> <h:column> <f:facet name="header"> <Subject </f:facet> <h:outputText value="#{store.subject}"/> </h:column> <h:column> <f:facet name="header"> <h:outputText value="#{msg.storePriceLabel}"/> </f:facet> <h:outputText value="#{store.price}"/> </h:column> </h:dataTable></pre>	<pre><th class="list-header" scope="col">Price (\$)</th> </tr> </thead> <tbody> <tr class="list-row"> <td class="list-column-center"> JSF For Dummies</td> <td class="list-column-right"> JSF</td> <td class="list-column-center"> 25.0</td> </tr> <tr class="list-row"> <td class="list-column-center"> Struts For Dummies</td> <td class="list-column-right"> Struts</td> <td class="list-column-center"> 22.95</td> </tr> </tbody> </table></pre>
---	--

UISelectItems

selectItems

<pre><h:selectOneMenu id="selectOneCar" value="#{carBean.currentCar}"> <f:selectItems value="#{carBean.carList}" /> </h:selectOneMenu></pre>	<pre><select id="jsftags:selectOneCar" name="jsftags:selectCar" size="1"> <option value="accord">Honda Accord</option> <option value="4runner">Toyota 4Runner</option> <option value="nissan-z">Nissan Z350</option> </select></pre>
--	--

UISelectItem

selectItem

<pre><h:outputText value="Select car color:" /> <h:selectOneMenu id="chooseCarColor" value="apple"> <f:selectItem itemValue="red" itemLabel="Red"/> <f:selectItem itemValue="blue" itemLabel="Blue"/> <f:selectItem itemValue="black" itemLabel="Black"/> <f:selectItem itemValue="green" itemLabel="Green"/> <f:selectItem itemValue="white"</pre>	<pre>Select car color: <select id="jsftags:chooseCarColor" name="jsftags:chooseCarColor" size="1"> <option value="red">Red</option> <option value="blue">Blue</option> <option value="black">Black</option> <option value="green">Green</option> <option value="white">White</option> </select></pre>
--	---

```
itemLabel="White"/>  
</h:selectOneMenu>
```