

Technical Datasheet

Hardie™ Plank & Hardie™ VL Plank Screw for Timber Frame

Product

Hardie™ Plank & Hardie™ VL Plank Screw for Timber Frame

Screws Intended Purpose:

Screw fixing both Hardie® Plank & Hardie® VL Plank to timber battens

If lining timber sheathing boards the batten thickness can be 25mm

If lining masonry the timber batten thickness should be at least 38mm

If cross battening for a vertical installation 2 of 25x50mm is acceptable



Applicable Hardie® Plank & Hardie® VL Plank Installation Styles:

- i) Hardie® Plank – Horizontal LAP
- ii) Hardie® VL Plank – Vertical and Horizontal installations

Fixing Spacings:

Maximum 600mm fixing / batten centres.

Always cross reference site wind loadings against the performance figures stated in the wind load table

Recommendations:

- i) When using the Hardie™ Plank & Hardie™ VL Plank Screw for Timber Frame, we always recommend using a screwdriver.
- ii) James Hardie does not recommend using a impact driver with this screw.
- iii) No pre-drilling is required.
- iv) Ensure all fixings are installing using a low torque setting to avoid overtightening and potential damage to both the screw fixing and the Hardie® Plank and Hardie® VL Plank

Hardie™ Plank & Hardie™ VL Plank Screw for Timber Frame Details:

Size	4.2Ø x 40mm
Screw Head Ø	9.5mm
Screw Head Type	T15 Torx
Material Grade	Stainless Steel A2
Pack Quantity	250x screws & 2x T15 Torx drill bits

**Hardie™ Plank & Hardie™ VL Plank Screw
for Timber Frame Wind Load Table:**

	Batten Centres [mm]	Max. Wind load [kPa]*
Hardie® VL Plank & Hardie® Plank	400	2.53
	600	2.0

* kPa figures include a safety factor of 3x

Handling & Storage

All James Hardie products should be handled with care.

Additional Information

Our recommendations are based on extensive tests and practical experience. They do not replace guidelines, standards, approvals, and applicable technical data sheets. Due to the multitude of possible influences during processing and application, we recommend testing the processing and application prior to installation. However, because of factors that fall beyond James Hardie's knowledge and control, which can affect the use of the products, no warranty is given or implied with respect to such information. James Hardie's policy is one of continuous improvement. James Hardie therefore reserves the right to alter specifications at any time and without notice. Delivery, processing, and warranty for the properties guaranteed by us are carried out in accordance with our General Terms and Conditions.

Hardie™ Plank & Hardie™ VL Plank Screw for Timber Frame Product Code:

5300319