```
user www-data;
worker_processes auto;
pid /run/nginx.pid;
include /etc/nginx/modules-enabled/*.conf;
events {
  worker_connections 768;
  # multi_accept on;
}
http {
  ##
  # Basic Settings
  ##
  sendfile on;
  tcp_nopush on;
  tcp_nodelay on;
  keepalive_timeout 65;
  types_hash_max_size 2048;
  server_tokens off;
  server_names_hash_bucket_size 64;
  # server_name_in_redirect off;
  include /etc/nginx/mime.types;
  default_type application/octet-stream;
  ##
  # SSL Settings
  ##
  ssl_protocols TLSv1.2 TLSv1.3; # Dropping SSLv3, ref: POODLE
  ssl_prefer_server_ciphers on;
  ##
  # Logging Settings
  ##
  access_log /var/log/nginx/access.log;
  error_log /var/log/nginx/error.log;
  ##
  # Gzip Settings
  gzip on;
  # gzip_vary on;
  # gzip_proxied any;
  # gzip_comp_level 6;
```

```
# gzip_buffers 16 8k;
# gzip_http_version 1.1;
# gzip_types text/plain text/css application/json application/javascript text/xml application/xml
application/xml+rss text/javascript;

##
# Virtual Host Configs
##

include /etc/nginx/conf.d/*.conf;
include /etc/nginx/sites-enabled/*;
}
```