

Templates


Agenda

- Need for a tempting engine
- Handlebars
- Handlebars in Hapi

reply

- In order to render web pages we could pass html content
- This would become very unwieldy and unmaintainable

```
exports.index = {  
  handler: function (request, h) {  
    return('<h1> Hello! </h1>');  
  }  
};
```



Tempting Engine

Context

```
var person = {  
  firstName: 'Eric',  
  surname: 'Praline'  
};
```

Template

```
<p>First name: {{firstName}}</p>  
<p>Surname: {{surname}}</p>
```

Template engine




Rendered HTML

```
<p>First name: Eric</p>  
<p>Surname: Praline</p>
```

Template Engines: Handlebars

“Handlebars provides the power necessary to let you build semantic templates effectively with no frustration.”

Handlebars is largely compatible with Mustache templates. In most cases it is possible to swap out Mustache with Handlebars and continue using your current templates..”



```
<div class="entry">
  <h1>{{title}}</h1>
  <div class="body">
    {{body}}
  </div>
</div>
```

Template Expressions

- A handlebars expression is a {{, some contents, followed by a }}

```
<div class="entry">
  <h1>{{title}}</h1>
  <div class="body">
    {{body}}
  </div>
</div>
```

```
var context = {title: "My New Post", body: "This is my first post!"};
var html    = template(context);
```

- In Javascript, create an object literal with matching properties
- When rendered, the properties replace the handlebars expressions

```
<div class="entry">
  <h1>My New Post</h1>
  <div class="body">
    This is my first post!
  </div>
</div>
```

Handlebars Features

- Expressions
 - Helpers
 - Partial
- } must be mastered by developer
- <http://handlebarsjs.com/expressions>
http://handlebarsjs.com/builtin_helpers
<http://handlebarsjs.com/helpers>
- Precompilation
 - Execution
- } integrated into Hapi by 'views' plugin

Helpers

- Block expressions allow you to define helpers that will invoke a section of your template with a different context than the current.
- These block helpers are identified by a # preceeding the helper name and require a matching closing mustache, /, of the same name.

```
<div class="entry">
  {{#if author}}
    <h1>{{firstName}} {{lastName}}</h1>
  {{/if}}
</div>
```

- if
- unless

```
<div class="entry">
  {{#unless license}}
    <h3 class="warning">WARNING: This entry does not have a license!</h3>
  {{/unless}}
</div>
```

```
<ul class="people_list">
  {{#each people}}
    <li>{{this}}</li>
  {{/each}}
</ul>
```

- each
- with
- lookup
- log

```
<div class="entry">
  <h1>{{title}}</h1>

  {{#with author}}
    <h2>By {{firstName}} {{lastName}}</h2>
  {{/with}}
</div>
```


each helper

You can iterate over a list using the built-in each helper. Inside the block, you can use this to reference the element being iterated over.

```
<ul class="people_list">
  {{#each people}}
    <li>{{this}}</li>
  {{/each}}
</ul>
```

when used with this context:

```
{
  people: [
    "Yehuda Katz",
    "Alan Johnson",
    "Charles Jolley"
  ]
}
```

will result in:

```
<ul class="people_list">
  <li>Yehuda Katz</li>
  <li>Alan Johnson</li>
  <li>Charles Jolley</li>
</ul>
```

Partials

- Handlebars partials allow for code reuse by creating shared templates.
- Calling the partial is done through the partial call syntax:

```
{{> myPartial }}
```


- Will render the partial named myPartial. When the partial executes, it will be run under the current execution context.

myPartial.hbs

```
<section class="ui raised segment">
  <div class="ui grid">
    <aside class="six wide column">
      
    </aside>
    <article class="eight wide column">
      <table class="ui celled table segment">
        <thead>
          <tr>
            <th>Amount</th>
            <th>Method donated</th>
          </tr>
        </thead>
        <tbody>
          {{#each donations}}
            <tr>
              <td> {{amount}} </td>
              <td> {{method}} </td>
            </tr>
          {{/each}}
        </tbody>
      </table>
    </article>
  </div>
</section>
```

Handlebars in Hapi

- Vision Plugin loads and manages a templating engine
- Supports a range of templating languages



vision

Templates rendering plugin support for hapi.js.

vision `5.x.x` Supports hapi `v17.x.x`, `v18.x.x`. For use with hapi `16.x.x`, use vision `4.x.x`

build `passing` coverage `100%`

Lead Maintainer - [William Woodruff](#)

vision decorates the [server](#), [request](#), and `h` response [toolkit](#) interfaces with additional methods for managing view engines that can be used to render templated responses.

vision also provides a built-in [handler](#) implementation for creating templated responses.

Usage

See also the [API Reference](#)

```
const Hapi = require('hapi');
const Vision = require('vision');

const server = Hapi.Server({ port: 3000 });

const provision = async () => {

  await server.register(Vision);
  await server.start();

  console.log('Server running at:', server.info.uri);
};

provision();
```

Plugin Install

- Install the Vision plugin + the specific tempting engine you wish to use

```
npm install vision
```

```
npm install handlebars
```

package.json

```
{
  "name": "donation-web",
  "version": "1.0.0",
  "description": "",
  "main": "index.js",
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1"
  },
  "author": "",
  "license": "ISC",
  "dependencies": {
    "handlebars": "^4.0.12",
    "hapi": "^18.0.0",
    "inert": "^5.1.2",
    "vision": "^5.4.4"
  },
  "devDependencies": {
    "prettier": "^1.16.0"
  },
  "prettier": {
    "singleQuote": true,
    "printWidth": 120
  }
}
```

general purpose
node modules

Hapi plugin node
modules

modules used in
development only



Additional settings
for specific module

Register the Plugin

Import & register
the plugin

Initialise to use
Handlebars
engine

Define template
locations and
cache settings



index.js

```
'use strict';

const Hapi = require('hapi');

const server = Hapi.server({
  port: 3000,
  host: 'localhost'
});

async function init() {
  await server.register(require('inert'));
  await server.register(require('vision'));

  server.views({
    engines: {
      hbs: require('handlebars')
    },
    relativeTo: __dirname,
    path: './app/views',
    isCached: false
  });


  server.route(require('./routes'));
  await server.start();
  console.log(`Server running at: ${server.info.uri}`);
}

process.on('unhandledRejection', err => {
  console.log(err);
  process.exit(1);
});

init();
```

Rename views to '.hbs'


- View can now add new handlebars expressions, which will be interpolated if the correct context is provided



```
<!DOCTYPE html>
<html>
  <head>
    <title>{{title}}</title>
    <meta charset="UTF-8">
```


Rendering the Context

- view function accepts a 'context' object



```
handler: function(request, h) {  
  return h.view('main', { title: 'Welcome to Donations' });  
}
```

- 'main' template loaded

- handlebars expressions retrieve information from the 'context'

```
<!DOCTYPE html>  
<html>  
  <head>  
    <title>{{title}}</title>  
    <meta charset="UTF-8">  
    <script type="text/javascript" src="/
```

```
handler: function(request, h) {  
  return h.view('main', { title: 'Welcome to Donations' });  
}
```

Handler method

The handler option is a function that accepts two parameters, `request`, and `h`.

The `request` parameter is an object with details about the end user's request, such as path parameters, an associated payload, authentication information, headers, etc. Full documentation on what the `request` object contains can be found in the [API reference](https://hapijs.com/tutorials/routing).

<https://hapijs.com/tutorials/routing>

```
handler: function(request, h) {  
  return h.view('main', { title: 'Welcome to Donations' });  
}
```

The second parameter, `h`, is the response toolkit, an object with several methods used to respond to the request. As you've seen in the previous examples, if you wish to respond to a request with some value, you simply return it from the handler. The payload may be a string, a buffer, a JSON serializable object, a stream or a promise.

Alternatively you may pass the same value to `h.response(value)` and return that from the handler. The result of this call is a response object, that can be chained with additional methods to alter the response before it is sent. For example `h.response('created').code(201)` will send a payload of `created` with an HTTP status code of `201`. You may also set headers, content type, content length, send a redirection response, and many other things that are documented in the [API reference](https://hapijs.com/tutorials/routing).

Partials & Layouts

- Partials & Layouts play a prominent role in enabling DRY (Dont Repeat Yourself) principles
- Partials: Reusable templates
- Layouts: Reusable Page Structure
- These features must be explicitly enabled

```
...
server.views({
  engines: {
    hbs: require('handlebars'),
  },
  relativeTo: __dirname,
  path: './app/views',
  layoutPath: './app/views/layout',
  partialsPath: './app/views/partials',
  layout: true,
  isCached: false,
});
...
```

partials &
layouts
directories
in project




Revised Project Layout

```
...
server.views({
  engines: {
    hbs: require('handlebars'),
  },
  relativeTo: __dirname,
  path: './app/views',
  layoutPath: './app/views/layout',
  partialsPath: './app/views/partials',
  layout: true,
  isCached: false,
});
...
```

partials &
layouts
directories
in project

- Templates can now assume these folders part of the rendering pipeline



Layouts & Partials in Action

layout.hbs

```
<!DOCTYPE html>
<html>
  <head>
    <title>{{title}}</title>
    <meta charset="UTF-8">
    ...include stylesheets
  </head>
  <body>
    <section class="ui container">
      {{{content}}}
    </section>
    <script>
  </body>
</html>
```


welcomemenu.hbs

```
<nav class="ui inverted menu">
  <header class="header item"> <a href="/"> Donation </a> </header>
  <div class="right menu">
    <a class="item" href="/signup"> Signup</a>
    <a class="item" href="/login"> Login</a>
  </div>
</nav>
```

main.hbs

```
{{> welcomemenu }}

<section class="ui stacked segment">
  <div class="ui grid">
    <aside class="six wide column">
      
    </aside>
    <article class="ten wide column">
      <header class="ui header"> Help Me Run Springfield</header>
      <p> Donate what you can now – No Bitcoins accepted! </p>
    </article>
  </div>
</section>
```



- main content is based on layout - replacing `{{content}}` expression
- welcomemenu is injected into main to provide menu

```
<!DOCTYPE html>
<html>
  <head>
    <title>{{title}}</title>
    <meta charset="UTF-8">
    ...include stylesheets
  </head>
  <body>
    <section class="ui container">
      {{{content}}}
    </section>
    <script>
  </body>
</html>
```


layout.hbs

```
<nav class="ui inverted menu">
  <header class="header item"> <a href="/"> Donation </a> </header>
  <div class="right menu">
    <a class="item" href="/signup"> Signup</a>
    <a class="item" href="/login"> Login</a>
  </div>
</nav>
```

welcomemenu.hbs

```
{{> welcomemenu }}

<section class="ui stacked segment">
  <div class="ui grid">
    <aside class="six wide column">
      
    </aside>
    <article class="ten wide column">
      <header class="ui header"> Help Me Run Springfield</header>
      <p> Donate what you can now - No Bitcoins accepted! </p>
    </article>
  </div>
</section>
```



main.hbs

Alternatives to Handlebars

vision

Templates rendering plugin support for hapi.js.

vision 5.x.x Supports hapi v17.x.x , v18.x.x . For use with hapi 16.x.x , use vision 4.x.x

build passing coverage 100%

Lead Maintainer - William Woodruff

vision decorates the server, request, and h response toolkit interfaces with additional methods for managing view engines that can be used to render templated responses.

vision also provides a built-in handler implementation for creating templated responses.

Usage

See also the API Reference

```
const Hapi = require('hapi');
const Vision = require('vision');

const server = Hapi.Server({ port: 3000 });

const provision = async () => {
  await server.register(Vision);
  await server.start();

  console.log('Server running at:', server.info.uri);
};

provision();
```

Branch: master vision / examples /

woutrbe Remove trailing commas

..

cms	Update handlebars examples
ejs	Update examples
handlebars	Set isCached to false on examples/handlebars/helpers
jsx	Update examples
marko	extended marko example
mixed	Update examples
mustache	Update examples
nunjucks	Update examples
pug	Remove trailing commas
twig	feat: add example for Twig template engine

<https://github.com/hapijs/vision/tree/master/examples>

 cms

 ejs

 handlebars

 jsx

 marko

 mixed

 mustache

 nunjucks

 pug

 twig


Nunchucks

 templates

 index.js

 includes

 index.html

 layout.html

<https://markojs.com/>



[docs](#)

[try online](#)

[github](#)



marko

Server-side rendering + Client-side rendering = **Awesomorphic**

[Get started](#)



GitHub 8,083★

simple.

If you know HTML, CSS, and Javascript, you know Marko

fast.

Faster loads via streaming and a tiny (~10kb gzip) runtime

progressive.

From simple HTML templates to powerful UI components

trusted.

Marko is powering high-traffic websites like ebay.com

Choose a syntax

Write in a familiar HTML-like style or drop the angle brackets and use Marko's concise syntax

```
<!doctype html>
<html>
<head>
  <title>Hello Marko</title>
</head>
<body>
  <h1>My favorite colors</h1>
  <ul.colors>
    <li for(color in input.colors)>
      ${color}
    </li>
  </ul>
</body>
</html>
```



```
<!doctype html>
html
  head
    title -- Hello Marko
  body
    h1 -- My favorite colors
    ul.colors
      li for(color in input.colors)
        -- ${color}
```