

Playlist Controller





· Full playlist displayed when 'View' selected

Dashboard.hbs

{{> menu id="dashboard"}} {{#each playlists}} <section class="ui segment"> <h2 class="ui header"> {{title}} </h2> <thead> Song Artist </thead> {{#each songs}} {{title}} {{artist}} {{/each}} </section> {{/each}}

No change to controller

```
const dashboard = {
  index(request, response) {
    logger.info('dashboard rendering');
    const viewData = {
       title: 'Playlist Dashboard',
       playlists: playlistCollection,
    };
    logger.info('about to render', playlistCollection);
    response.render('dashboard', viewData);
  },
};
```


Revised dashboard.hbs

Dashboard View

New Route

routes.js

 New Route not initially supported



Error message when link pressed

```
router.get('/', dashboard.index);
router.get('/dashboard', dashboard.index);
router.get('/about', about.index);
```



Introducing a new view

- Typically need 3 things:
 - Controller
 - View
 - Route

controller: playlist.js

```
'use strict';

const logger = require('../utils/logger');
const playlistCollection = require('../models/playlist-store.js');

const playlist = {
   index(request, response) {
     const viewData = {
       title: 'Playlist',
     };
     response.render('playlist', viewData);
   },
};

module.exports = playlist;
```

view: playlist.hbs

route: routes.js

```
router.get('/playlist/:id', playlist.index);
```

Controller

In order to
display the
correct playlist,
we need to
extract the id
from the url.

```
index(request, response) {

const playlistId = request.params.id;

logger.debug('Playlist id = ', playlistId);

const viewData = {
   title: 'Playlist',
  };

response.render('playlist', viewData);
}
```

Revised Model

- playlistStore is an object with 2 methods:
 - retrieve all playlists from store
 - retrieve a
 specific playlist
 by it's id from
 the store.

```
const playlistStore = {
   playlistCollection: require('./playlist-store.json').playlistCollection,
   getAllPlaylists() {
      return this.playlistCollection;
   },
   getPlaylist(id) {
      return _.find(this.playlistCollection, { id: id });
   },
};
```

Dont worry about how this is implemented for the moment!

Revised playlist Controller

- Recover playlist ID in request
- Get playlist matching this id and insert into viewData
- Pass viewData to to the view (containing the playlist)

```
const playlistStore = require('../models/playlist-store');
const playlist = {
  index(request, response) {
    const playlistId = request.params.id;
    logger.debug('Playlist id = ', playlistId);

    const viewData = {
        title: 'Playlist',
        playlist: playlistStore.getPlaylist(playlistId),
    };

    response.render('playlist', viewData);
},
};
```

```
index(request, response) {
   const playlistId = request.params.id;
   logger.debug('Playlist id = ', playlistId);

   const viewData = {
      title: 'Playlist',
      playlist: playlistStore.getPlaylist(playlistId),
   };

   response.render('playlist', viewData);
}
```

Song Artist Piano Sonata No. 3 Beethoven Piano Sonata No. 7 Beethoven Piano Sonata No. 10 Beethoven

Revised Playlist View

```
<thead>
 Song
  Artist
 </thead>
{{#each playlist.songs}}
  <td>
    {{title}}
   {{artist}}
   {{/each}}
```

listsongs.hbs