

# Object interactions

## Lecture 6

Waterford Institute of Technology


January 18, 2016

John Fitzgerald

# Abstraction revisited

## BlueJ Clock

- demonstrates **abstraction**
- Application decomposed into modules
- Implementation details hidden
- Public interface only exposed
- Development separable by both
  - Location
  - Time




# Class diagram

## BlueJ Clock Example

### Class diagram

- *Static* view
- Represents class design
- Arrow means *ClockDisplay* **has a** *NumberDisplay*
- One *ClockDisplay* has one or many *NumberDisplay* fields




# Object composition

## BlueJ ClockDisplay

Both Object & Class diagrams reveal

- ClockDisplay has 2 NumberDisplay fields
- ClockDisplay exclusive owner fields
- *Object Composition* example




# NumberDisplay class

## NumberDisplay

- Represents digital number display
- Fields
  - `int` limit
  - `int` value
- *value* range 0 to *limit-1*
- *value* resumes at 0 when limit reached
- *modular* or *clock* arithmetic

```
public class NumberDisplay
{
    private int limit;
    private int value;
    public NumberDisplay(int limit)
    {
        this.limit = limit;
        value = 0;
    }
}
```

# NumberDisplay class



## NumberDisplay

- Updating *value* attribute
- Accepts parameter only if in valid range
- Otherwise no action

```
public void setValue(int value)
{
    if(value >= 0 && value < limit)
    {
        this.value = value;
    }
}
```

# Conditional and Unary Operators

## Conditional operators

- Logical **AND** &&
- Logical **OR** ||

## Unary operator

- Logical complement !
- Also called **NOT** operator
- Inverts value of boolean

```
boolean a = false;  
boolean b = true;  
/* !a is true  
 * !b is false  
 * a && b is false  
 * a || b is true  
 */
```

# Truth table for logical operations

Table 1 : Using **booleans**

a	b	a&&b	a  b
false	false	false	false
false	true	false	true
true	false	false	true
true	true	true	true

Table 2 : Alternative representation


a	b	a&&b	a  b
0	0	0	0
0	1	0	1
1	0	0	1
1	1	1	1



# NumberDisplay class

## NumberDisplay

- Return time to display
- String concatenation used
- Leading zero inserted




```
public String getDisplayValue()
{
    if(value < 10) {
        return "0" + value;
    }
    else {
        return "" + value;
    }
}
```

# NumberDisplay class

## NumberDisplay

- Increment time
- Use modulus operator %
- Forces a roll-over to zero at limit




```
public void increment()
{
    value = (value + 1) % limit;
}
```

# NumberDisplay class

## NumberDisplay

- Increment time
- Use modulus operator %
- Forces a roll-over to zero at limit



Time Start	Time +1	Check limit	End Time
57	58	58%60	58
58	59	59%60	59
59	60	60%60	00
00	01	01%60	01


Table 3 : Increment clock minutes display

# ClockDisplay class

ClockDisplay composition

Has fields

- *NumberDisplay*
- *String*



```
public class ClockDisplay
{
    private NumberDisplay hours;
    private NumberDisplay minutes;
    private String displayString;
    ...
}
```

# ClockDisplay class

## ClockDisplay instantiation

### Default constructor

- Two new *NumberDisplay* objects
  - Minute display
  - Hour display
- Initializes *limit* attributes
- Sets clock display 00.00

```
public ClockDisplay()
{
    hours = new NumberDisplay(24);
    minutes = new NumberDisplay(60);
    updateDisplay();
}
```

# ClockDisplay class

ClockDisplay instantiation

Overloaded constructor

- Two new *NumberDisplay* objects
  - Minute display
  - Hour display
- Initializes *limit* attributes
- Updates clock display

```
public ClockDisplay(int hour, int minute)
{
    hours = new NumberDisplay(24);
    minutes = new NumberDisplay(60);
    setTime(hour, minute);
}
```

# ClockDisplay class

Simulate ticking clock

- Advance one minute
- Check minute elapsed
- Then increment hour

```
public void timeTick()
{
    minutes.increment();
    //if minute display zero
    //time to advance an hour
    if(minutes.getValue() == 0) {
        hours.increment();
    }
    updateDisplay(); }
}
```

# ClockDisplay class

## Update clock display

- Get hour value
- Get minute value
- Concatenate values
- Example display 00:20

```
private void updateDisplay()
{
    displayString = hours.getDisplayValue()
                    + ":"
                    + minutes.getDisplayValue();
}
```



# Strings

## String class

```
String greeting = "Hello ICTSkills group: the future is bright";
```

- Java String class widely used
- Java *Strings* are objects
  - Comprise series of characters
- Direct creation
  - `String s = "this is a string"`
  - "this is a string" is a String literal
- Creation using *new* operator
  - `String s = new String("this is a string")`

# Strings

## String methods

Extensive set of methods available

- String length
  - `String s = "this is a string";`
  - `int length = s.length;`
    - length is 16
- String concatenation method 1
  - `String s1 = "Hello ";`
  - `String s2 = "ICTSkills group";`
  - `String s3 = s1.concat(s2);`
    - `s3` : *Hello ICTSkills group*
- String concatenation method 2
  - `String s1 = "Hello ";`
  - `String s2 = "ICTSkills group";`
  - `String s3 = s1 + s2;`
    - Result: *Hello ICTSkills group*

# Strings

## Converting String to number

- `String s = "100.45";`
  - `double d = Double.parseDouble(s);`
  - `System.out.println("d is " + d);`
    - Output: d is 100.45
- `String s = "100";`
  - `int number = Integer.parseInt(s);`
  - `System.out.println("number is " + number);`
    - Output: number is 100

Two members of the **Number** family:

- **Integer** class contains a single field whose type is *int*.
- **Double** class contains a single field whose type is *double*.

# Strings

## Converting number to String

### Method 1 : Concatenate with empty string

- ```
int num = 100;  
String s1 = "" + num;
```

### Method 2: Invoke String method *valueOf*

- ```
int num = 100;  
String s1 = String.valueOf(num);
```

### Method 3: Use one of *Number* family

- ```
int num = 100;  
double dnum = 100.35;  
String s1 = Integer.toString(num);  
String s2 = Double.toString(dnum);
```

Other *Number* family members are Byte, Float, Long, Short

# Strings

## Comparing String objects

Using *String equals* and *equalsIgnoreCase* methods

- ```
String s0 = "ICTSkills Group";  
String s1 = "ICTSkills group";  
boolean b1 = s0.equals(s1);  
boolean b2 = s0.equalsIgnoreCase(s1);
```
- b1 is *false*
- b2 is *true*

Some other methods are

```
boolean endsWith(String suffix); //true if string ends with suffix  
boolean startsWith(String prefix) //true if string begins with prefix
```

# Primitive type conversion

## Explicit conversion & explicit cast

Table 4 : **Explicit conversion**

Expression	Type	Value
Math.round(3.14)	long	3
Math.round(2.71)	long	3

Table 5 : **Explicit cast**

Expression	Type	Value
(int)Math.round(3.14)	int	3
(int)3.14	int	3
(int)2.71	int	2

# Primitive type conversion

Automatic promotion - no loss of data

Java automatically converts data to type with larger range

- No need for explicit cast

```
double val = 0.3*11; //11 transparently promoted to 11.0
```

```
int b = 10;  
int c = 10;  
int d = b*b - 4*c;  
double e = b*b - 4.0*c;
```

# Primitive type conversion

Explicit cast required where loss of data

```
public class Circle {  
    double radius;  
    ...  
    //this will not compile  
    public int getRadius() {return radius;}  
}
```

```
public class Circle {  
    double radius;  
    ...  
    //this will compile  
    public int getRadius() {return (int)radius;}  
}
```



# Summary

- Abstraction: focussing on bigger picture at expense of details
- Modularization : decomposing system into components
- Boolean algebra, truth tables, conditional & unary operators
- Primitive type : fundamental variable types such as *int*, *double*
- Class diagram : shows classes of application
- Object diagram : instantaneous view of objects & relationships
- Object instantiation : class constructor invocation
- Overloading : method with same name but various parameters
- Internal method call : method invokes other method same class
- External method call : method calls method other object using dot operator

## Referenced material

1. Sedgewick R. Wayne K. Introduction fo Programming in Java  
Precedence and associativity of Java operators  
<http://introcs.cs.princeton.edu/java/11precedence/>  
[Accessed 2014-02-12]
2. Java 7 String API <http://docs.oracle.com/javase/7/docs/api/java/lang/String.html?is-external=true>  
[Accessed 2014-31-4]
3. Class Double <http://docs.oracle.com/javase/7/docs/api/java/lang/Double.html> [Accessed 2014-04-01]
4. Integer Class <http://docs.oracle.com/javase/7/docs/api/java/lang/Integer.html?is-external=true> [Accessed 2014-04-01]
5. Comparing Strings <http://docs.oracle.com/javase/tutorial/java/data/comparestrings.html> [Accessed 2014-04-01]