

JavaScript

Lecture 2

Waterford Institute of Technology

May 5, 2016

John Fitzgerald

JavaScript Introduction

Topics discussed this presentation

- Identifiers
- Comments
- Reserved Words
- Operators
- Control Flow
- Truthy and Falsy

Identifiers

Style Guide Requirements

- May comprise only letters, numbers, \$ sign, underscore
- Avoid single letter names.
- camelCase for objects, functions, instances.
- PascalCase for constructors, classes.
- Leading underscore _ for private properties.
- Number disallowed as first character.

```
function q() {...} // bad
function query {...} // good: descriptive
const my_object = {} // bad
const myObject = {} // good: camelCase
const good = new User({...}); // good: PascalCase
const $domElement = $(this).get(0); // good: jQuery variable
```

Reserved words

Java Overlap

- `break`
- `case`
- `catch`
- `continue`
- `debugger`
- `default`
- `delete`
- `do`
- `else`
- `finally`
- `for`
- `function`
- `if`
- `in`
- `instanceof`
- `new`
- `return`
- `switch`
- `this`
- `throw`
- `try`
- `typeof`
- `var`
- `void`
- `while`
- `with`

- Significant overlap with Java
- However, meaning often different in subtle ways

Comments

Single line comments

- Use `//` for single line comment.
 - Position on new line above target of comment.
 - If not start block, add blank line before comment.

```
function getRadius() {  
    // return radius of circle.  
    ...  
}
```

Comments

Multi-line comments

- Use `/**...*/` for multi-line comments.
 - Include description.
 - Specify parameter types and values.
 - Specify return type and value.

```
/*  
 * find() returns sought value based on parameter key.  
 *  
 * @param {String} key  
 * @return {Value} value.  
 */  
function find(key) {  
  // ...  
  return value;  
}
```

Operators

Assignment

```
const x = 5;  
const y = 2;  
let z = x + y;  
z *= 2; // => 18  
z /= 3; // => 6  
x % 3; // => 2
```

Operator	Example	Same As
=	x = y	x = y
+=	x += y	x = x + y
-=	x -= y	x = x - y
*=	x *= y	x = x * y
/=	x /= y	x = x / y
%=	x %= y	x = x % y

Operators

Arithmetic

```
const x = 5;  
const y = 2;  
const z = x * y; // => 10  
z--; // => 9
```

Operator	Description
+	Addition
-	Subtraction
*	Multiplication
/	Division
%	Modulus
++	Increment
--	Decrement

Operators

String

```
let txt1 = 'What a very ';  
txt1 += 'nice day.';
```

```
// Output  
What a very nice day.
```

Operators

Add Number to String

```
const x = 5 + 5;    // => 10  
const y = '5' + 5;  // => 55  
const z = 'Hello' + 5; // => Hello5
```

Operators

Comparison & Logical

```
const s = '5';  
const n = 5;  
s == n // => true (coercion)  
s === n // => false (strict)
```

Operator	Description
==	equal to
===	equal value and equal type
!=	not equal
!==	not equal value or not equal type
>	greater than
<	less than
>=	greater than or equal to
<=	less than or equal to
?	ternary operator

Operators

Type

```
const car = 'Nissan';  
typeof car; // => string
```

```
const cars = ['Saab', 'Volvo', 'BMW'];  
cars instanceof Array; // => true
```

Operator	Description
typeof	Returns the type of a variable
instanceof	Returns true if an object is an instance of an object type

Operators

Equals and not equals

```
// Use always  
===  
!==  
// Evil twin (Crockford)  
==  
!=
```



Control Flow

Truthy and Falsy

- Expression either truthy or falsy.
- Some developers avoid use.
- Not reserved words.

false
undefined
null
0
NaN
Empty string ("")

Falsy: these evaluate to false

Control Flow

Truthy and Falsy

Falsy

- false
- null
- undefined
- Empty string ""
- Number 0
- NaN

Truthy

- All values not truthy
- Warning: string 'false' is truthy

Control Flow

Truthy and Falsy

Function to determine if value falsy

```
/**
 * Determines if argument resolves to a falsy or truthy value.
 *
 * @see https://developer.mozilla.org/en-US/docs/Web/JavaScript/Reference
 * @param arg Argument to be checked if falsy.
 * @return Returns true if argument is falsy, otherwise false.
 */
function falsy(arg) {
  return [false, null, undefined, '', 0, NaN].includes(arg);
}
```


Control Flow

Logical Operators (AND, OR)

Significantly different behaviour to Java

`x && y // => x if x falsy otherwise y`

`x || y // => x if x truthy otherwise y`

`// Use OR to insert default values`

`const person = {};`

`let name = person.name || 'No such person';`

`console.log(name); // => No such person`

`person.name = 'Jane Doe';`

`name = person.name || 'no such person';`

`console.log(name); // => Jane Doe`

Control Flow

Logical Operators (AND, OR)

Significantly different behaviour to Java

`x && y // => x if x falsy otherwise y`

`x || y // => x if x truthy otherwise y`

`// Use AND to avoid TypeError exception`

`const flight = {};`

`flight.airline; // => undefined`

`flight.airline.nationality; // => TypeError`

`flight.airline && flight.airline.nationality; // undefined`

Control Flow

Loop using **for**

```
const limit = 5;
for (let i = 0; i < limit; i++) {
  text += 'The number is ' + i + '<br>';
}
```

```
for (i = 0; i < 5; i++) {
  text += 'The number is ' + i + '<br>';
}
```

Control Flow

Using **while**

```
let i = 0;
while (i < 10) {
  text += 'The number is ' + i;
  i++;
}
```

```
while (condition) {
  code block to be executed
}
```

Control Flow

Using **do-while**

```
let i = 0;
const limit = 10;
do {
  text += 'The number is ' + i;
  i++;
} while (i < limit);
```

```
do {
  code block to be executed
}
while (condition);
```

Control Flow

Using if-else

```
if (hour < 18) {  
    greeting = 'Good day';  
} else {  
    greeting = 'Good evening';  
}
```

```
if (condition) {  
    block of code to be executed if the condition is true  
} else {  
    block of code to be executed if the condition is false  
}
```

Control Flow

Using **break** statement

break statement

- Checks for condition
- If met then immediately exits loop

```
// This trivial function return 0
function foo()
{
  const limit = 10;
  const sum = 0;
  for (let i = 0; i < limit; i += 1) {
    if (i % 2 == 0)
      break;
    else
      sum += i;
  }

  return sum;
};
```

Control Flow

Using **continue** statement

continue statement

- Checks for condition
- If met, skips remainder iteration
- Continues with next iteration

```
// Calculate sum of odd integers in range [0, 10]
function addOdd() {
  const limit = 10;
  let sum = 0;
  for (let i = 0; i < limit; i += 1) {
    if (i % 2 == 0)
      continue;
    else
      sum += i;
  }

  return sum;
};
```


Control Flow

Ternary (Conditional) Operator

// If argument a is negative return -a.

Otherwise, return a

```
function absoluteValue(a)
{
  return a < 0 ? -a : a;
};
```

```
variablename = (condition) ? value1:value2
```

Control Flow

Logical Operators

```
function foo() {  
  const limit = 5;  
  let i = 0;  
  let j = 0;  
  let sum = 0;  
  while (++i < limit && ++j < limit) {  
    sum += i + j;  
  }  
  
  return sum;  
};  
  
console.log(foo()); // 20
```

Operator	Description	Example
&&	and	(x < 10 && y > 1) is true
	or	(x == 5 y == 5) is false
!	not	!(x == y) is true

Control Flow

Using **switch** statement

```
switch (new Date().getDay()) {  
  case 0:  
  case 6:  
    day = 'Weekend';  
    break;  
  default:  
    day = 'Weekday';  
}
```

```
switch(expression) {  
  case n:  
    code block  
    break;  
  case n:  
    code block  
    break;  
  default:  
    default code block  
}
```



Except where otherwise noted, this content is licensed under a Creative Commons Attribution-NonCommercial 3.0 License.

For more information, please see <http://creativecommons.org/licenses/by-nc/3.0/>



Waterford Institute of Technology
INSTITIÚD TEICNEOLAÍOCHTA PHORT LÁIRGE

