

Handling Touches

Displaying a basic button

- `Button` provides a basic button component that is rendered nicely on all platforms. The minimal example to display a button looks like this:

```
<Button
  onPress={() => {
    alert('You tapped the button!');
  }}
  title="Press Me"
/>
```

```
import React from 'react';
import { StyleSheet, Text, View, Button } from 'react-native';
```

```
const BasicButton = () => {
  const _onPressButton = () => {
    alert('You tapped the button')
  }

  return(
    <View style={styles.container}>
      <View style={styles.box1}>
        <Text>Test Button</Text>
        <Button
          title='Press me'
          onPress={_onPressButton}
        />
      </View>
      <View style={styles.box2}></View>
      <View style={styles.box3}></View>
    </View>
  );
}
```

```
const styles = StyleSheet.create({
  container: {
    flex: 1,
    backgroundColor: 'white',
  },
  box1: {
    flex: 1,
    backgroundColor: 'white',
    alignItems: 'center',
    justifyContent: 'center'
  },
  box2: {
    flex: 2,
    backgroundColor: 'darkorange'
  },
  box3: {
    flex: 1,
    backgroundColor: 'green'
  }
});
```

```
export default BasicButton
```

12:12



Test Button

Press me



```
import React from 'react',
import { StyleSheet, Text, View, Button } from 'react-native';
```

```
const BasicButton = () => {
  const _onPressButton1 = () => {
    alert('You tapped the button1')
  }

  const _onPressButton2 = () => {
    alert('You tapped the button2')
  }

  return(
    <View style={styles.container}>
      <View style={styles.buttonContainer1}>
        <Button
          title='Press Me 1'
          onPress={_onPressButton1}
        />
      </View>
      <View style={styles.buttonContainer2}>
        <Button
          title='Press Me 2'
          onPress={_onPressButton2}
        />
      </View>
    </View>
  );
}
```

```
const styles = StyleSheet.create({
  container: {
    flex: 1,
    backgroundColor: 'white',
    justifyContent: 'center'
  },
  buttonContainer1: {
    margin: 20,
    backgroundColor: 'lightgray',
  },
  buttonContainer2: {
    margin: 20,
    backgroundColor: 'black',
  },
});
```

```
export default BasicButton
```

12:51



Press Me 1

Press Me 2

```
import React from 'react';
import { StyleSheet, Text, View, Button } from 'react-native';
```

```
const BasicButton = () => {
  const _onPressButton = () => {
    alert('You tapped the button!')
  }

  return (
    <View style={styles.container}>
      <View style={styles.buttonContainer}>
        <Button
          onPress={_onPressButton}
          title="Press Me"
        />
      </View>
      <View style={styles.buttonContainer}>
        <Button
          onPress={_onPressButton}
          title="Press Me"
          color="#841584"
        />
      </View>
      <View style={styles.alternativeLayoutButtonContainer}>
        <Button
          onPress={_onPressButton}
          title="Button1!"
        />
        <Button
          onPress={_onPressButton}
          title="Button2!"
          color="#841584"
        />
      </View>
    </View>
  );
};
```

```
const styles = StyleSheet.create({
  container: {
    flex: 1,
    justifyContent: 'center',
  },
  buttonContainer: {
    margin: 20
  },
  alternativeLayoutButtonContainer: {
    margin: 20,
    flexDirection: 'row',
    justifyContent: 'space-between'
  }
});
```

1:00



Press Me

Press Me

Button1!

Button2!

Touchable

- If the basic button doesn't look right for your app, you can build your own button using any of the "Touchable" components provided by React Native. The "Touchable" components provide the capability to capture tapping gestures, and can display feedback when a gesture is recognized. These components do not provide any default styling, however, so you will need to do a bit of work to get them looking nicely in your app.

```
import React from 'react';
import { StyleSheet, Text, View, TouchableOpacity } from 'react-native';
```

```
const Touchables = () => {
  const _onPressButton = () => {
    alert('You tapped the button')
  }
  return(
    <View style={styles.container}>
      <TouchableOpacity onPress={_onPressButton}>
        <View style={styles.button}>
          <Text style={styles.buttonText}>Press Me</Text>
        </View>
      </TouchableOpacity>
    </View>
  );
}
```

```
const styles = StyleSheet.create({
  container: {
    flex: 1,
    backgroundColor: 'white',
    justifyContent: 'center',
    alignItems: 'center'
  },
  button: {
    width: 260,
    alignItems: 'center',
    backgroundColor: '#2196F3'
  },
  buttonText: {
    textAlign: 'center',
    padding: 20,
    color: 'white'
  }
});
```

```
export default Touchables
```

Press Me

```

const Touchables = () => {
  const _onPressButton1 = () => {
    alert('You tapped the button 1')
  }

  const _onPressButton2 = () => {
    alert('You tapped the button 2')
  }

  return(
    <View style={styles.container}>
      <TouchableOpacity onPress={_onPressButton1}>
        <View style={styles.button1}>
          <Text style={styles.buttonText}>Button1</Text>
        </View>
      </TouchableOpacity>

      <TouchableOpacity onPress={_onPressButton2}>
        <View style={styles.button2}>
          <Text style={styles.buttonText}>Button2</Text>
        </View>
      </TouchableOpacity>
    </View>
  );
}

const styles = StyleSheet.create({
  container: {
    flex: 1,
    backgroundColor: 'white',
    justifyContent: 'center',
    alignItems: 'center'
  },
  button1: {
    margin: 20,
    width: 260,
    alignItems: 'center',
    backgroundColor: '#2196F3'
  },
  button2: {
    margin: 20,
    width: 260,
    alignItems: 'center',
    backgroundColor: 'darkgreen',
    borderRadius: 10
  },
  buttonText: {
    textAlign: 'center',
    padding: 20,
    color: 'white'
  }
});

```

1:36



Button1

Button2