

Where the continuous host stands

Built and tested offline, run live only in bounded windows, not running at check time

master af62b7b, workspace 0.2.3. Sources - docs/rung-host*.md, rung-host/live/runs/.

Built. Host loop, free-time kernel, cache pack and durable record (#153); engine split out as `rung-agent-core` (#152); ladder with listing filter and probes (#177, #214); ACP over stdio and HTTP (#178, #182); `run --config` (#196); shadow decision desk (#199); status report (#241); 24 h simulated soak (#238); opt-in idle rule (#247); named ladder default (#250); decision model switched to `microsoft/microsoft-decision-1` (#260, #271).

Running: nothing. No `rung-host` process, no rung unit under `~/.config/systemd/user`, no rung port open. Newest live record: `rung-host/live/runs/2026-10-06-named-ladder/`, started by hand with `live.sh`.

Measured. Offline, 11 gates pass at \$0 (`docs/rung-host-results.md`), including 50 `kill -9` restarts losing nothing. Live, on free models: a 26 min first run failed owner latency and found four defects; a 2 h run had 154 turns, 42% failed upstream, cache 0.95; a named-ladder pair compared the idle rule off and on. No crash; agent spend \$0.

Not built or not proven. Worker delegation (names reserved only). Idle rule: barely exercised, no verdict. Decision-model disagreement audit: 6 real fixtures replayed (26 of 30 agree), the 50-item shadow sheet has no verdicts. Shadow week: never run; longest window 2 h. Decision mode `decide` never run live. Issue #259 still open.

Observe and control, as built. No metrics endpoint, no MCP, no instance registry.

SURFACE	ADDRESS AND AUTH	SHAPE
ACP	stdio <code>--acp</code> (process owner); HTTP <code>acp.http</code> , bearer token per role from env vars	prompts; <code>_rung/status</code> , <code>report</code> , <code>calendar</code> , <code>stimulus</code> , <code>stop</code> , <code>release</code>
Files	<code><state>/record/</code> , <code>inbox</code> , <code>stop_file</code> , <code>desk.kill_file</code> ; file permissions	NDJSON record (the only log); <code>*.msg</code> stimuli; a file halts the host or mutes the decision model
Process	SIGTERM, <code>sd_notify</code>	clean stop; ready and watchdog

More than one instance? By config only: separate `state`, `workspace`, `inbox`, stop file and ACP port. No lock guards a shared state dir; nothing lists instances.