SCORECARD · ONE CARD

vbm-json: scorecard (sandboxed run)

Strict result: FAIL. 12 metrics pass, 5 fail, 2 not measurable; 1 of 6 dimensions pass. Subject commands ran in the sandbox only.

IDEAL	METRIC	STATUS	VALUE	FLOOR
Verified	unproved escapes	pass	0	== 0
Verified	specified share	pass	100	>= 100
Verified	nonstandard axioms	pass	0	== 0
Verified	trusted c lines	pass	350	tracked
Verified	trust ledger entries	pass	13	tracked
Verified	non vacuity	pass	100	>= 100
Bare metal	freestanding build	FAIL	0	== 1
Bare metal	wasm freestanding build	pass	60745 B	== 1
Bare metal	libc symbols	FAIL	5	== 0
By construction	hand written tests	FAIL	11	== 0
By construction	mutation score	pass	100	>= 100
Efficiency	throughput vs best	FAIL	30.2	>= 50
Velocity	tier1 seconds	FAIL	102.9	< 60
Velocity	open prs	pass	0	== 0
Velocity	commits per hour	pass	2.018	tracked
Velocity	p90 commit to main seconds	pass	565	tracked
Honesty	gate selftests	pass	100	>= 100
Honesty	gates self tested	not measurable (1)	-	>= 100
Honesty	attack suite	not measurable (1)	-	== 1

Not measurable. (1) not implemented in this runner version.
Hand-written cases (11): `vectors.rs` 3, `abi_test.c` 1, `test_python.py` 4, `wasm_test.mjs` 3. Drivers, 0 cases: `abi_dump.c`, `vbm_json.mjs` (paths in the card).
Fast gate timed: `scripts/tier1.sh`, cold, 2 CPUs.

Libc symbols needed (5): `free`, `malloc`, `memcpy`, `memset`, `pthread_once`.
Throughput MB/s, one corpus `857fc854`: simdjson 1711.3, serde_json 170.4, python-json 122.9, vbm-json 51.5. Gap to simdjson: 33.2x (non-scalar, not floored); best scalar serde_json is 3.31x faster (floor: within 2x). Pinned, with hashes in the card: python-json 3.14.8, serde_json 1.0.150, simdjson 5.0.5.