SCORECARD · ONE CARD

vbm-json: scorecard (sandboxed run)

Correctness: FAIL (3 of 4 primary dimensions measured; Trusted generation not yet defined)
Landedness: FAIL

IDEAL	METRIC	STATUS	VALUE	FLOOR
CORRECTNESS: FAIL (3 OF 4; TRUSTED GENERATION NOT YET DEFINED)				
Verified	unproved escapes	pass	0	== 0
Verified	specified share	pass	100	>= 100
Verified	nonstandard axioms	pass	0	== 0
Verified	trusted c lines	pass	430	tracked
Verified	trust ledger entries	pass	13	tracked
Verified	non vacuity	pass	100	>= 100
By construction	hand written tests	pass	0	== 0
By construction	mutation score	pass	100	>= 100
Honesty	gate selftests	pass	100	>= 100
Honesty	gates self tested	pass	100	>= 100
Honesty	selftests ran cases	not measurable (1)	-	>= 1
Honesty	attack suite	pass	1	== 1
LANDEDNESS: FAIL				
Velocity	tier1 seconds warm	pass	25.2 (skipped 13 of 24 gates)	< 60
Velocity	tier1 seconds cold	FAIL	625.9	<= 600
Velocity	open prs	pass	0	== 0
Velocity	commits per hour	pass	3.429	tracked
Velocity	p90 commit to main seconds	pass	7373	tracked
PROFILE (IN NEITHER VERDICT): BARE METAL PASS, EFFICIENCY PASS				
Bare metal	freestanding build	pass	1	== 1
Bare metal	wasm freestanding build	pass	54230 B	== 1
Bare metal	libc symbols	pass	0	== 0
Efficiency	throughput vs best	pass	73.5	>= 50

6 corpora, MB/s (the first is floored, the rest only reported): 4 of 6 at or above the 50% line.

CORPUS	KB	VBM-JSON	PYTHON-JSON	SERDE_JSON	SIMDJSON	% BEST
scorecard-corpus	1033	26.1	22.4	35.5	347	73.5%
twitter	631	46.6	56	77.4	1055.4	60.2%
canada	2251	29.9	19.6	75.9	304.2	39.4%
citm_catalog	1727	62.8	61.3	135.8	1179.1	46.2%
small-objects	2412	17.9	20.8	21.6	319.6	82.9%
string-heavy	2915	50	58	76.6	885.8	65.3%

Gates with self-test evidence in the run: 24 of 24.

Attack suite: PASS relabel-attacks: 60 of 60 attacks refused (55 s); gates stubbed: FAIL relabel-attacks: 0 of 60 attacks refused (5 s).

Level 2 (Measured) card. Level 1, Certified (an independent proof recheck), is not built yet: this is not a certificate.

Run conditions. Shared host under heavy load (about 25): the cold run is 26 s over its ceiling.

Throughput MB/s, the floored corpus `857fc854` : simdjson 347, serde_json 35.5, vbm-json 26.1, python-json 22.4. Gap to simdjson: 13.3x (non-scalar, not floored); best scalar serde_json is 1.36x faster (floor: within 2x). Pinned: python-json 3.14.8, serde_json 1.0.150, simdjson 5.0.5.

Not measurable. (1) the adapter declares no [tier1] ran_names: the evidence lines must name exactly the declared gates (DECISIONS 19), so a subject without them is not measured (and fails its floor).

Hand-written cases (0). Drivers, 0 cases: 8 files.

Warm run (what a landing costs, floor under 60 s): the fast gate after a typical change, on the cache the cold run left; skipped 13 of 24 gates by design: C ABI test, wasm32 build test, freestanding native test, language bindings test, workflow lint, protected-set gate, lander, commit-on-main guard, parallel test runner, delta test selection, crash-record check, gate-diff judge, relabel-attack suite.

Cold run (what an outside contributor pays, ceiling 600 s, shown beside the warm run): 2 CPUs, 4 GB cap, a fresh clone with no cache.