SCORECARD · ONE CARD

vbm-sse: scorecard (sandboxed run)

Correctness: PASS (3 of 4 primary dimensions measured; Trusted generation not yet defined)
Landedness: PASS

IDEAL	METRIC	STATUS	VALUE	FLOOR
CORRECTNESS: PASS (3 OF 4; TRUSTED GENERATION NOT YET DEFINED)				
Verified	unproved escapes	pass	0	== 0
Verified	specified share	pass	100	>= 100
Verified	nonstandard axioms	pass	0	== 0
Verified	trusted c lines	pass	464	tracked
Verified	trust ledger entries	pass	13	tracked
Verified	non vacuity	pass	100	>= 100
By construction	hand written tests	pass	0	== 0
By construction	mutation score	pass	100	>= 100
Honesty	gate selftests	pass	100	>= 100
Honesty	gates self tested	pass	100	>= 100
Honesty	selftests ran cases	pass	2315	>= 1
Honesty	attack suite	pass	1	== 1
LANDEDNESS: PASS				
Velocity	tier1 seconds warm	pass	29.5 (skipped 14 of 24 gates)	< 60
Velocity	tier1 seconds cold	pass	131.5	<= 600
Velocity	open prs	pass	0	== 0
Velocity	commits per hour	pass	3.139	tracked
Velocity	p90 commit to main seconds	pass	7475	tracked
PROFILE (IN NEITHER VERDICT): BARE METAL PASS, EFFICIENCY PASS				
Bare metal	freestanding build	pass	1	== 1
Bare metal	wasm freestanding build	pass	46526 B	== 1
Bare metal	libc symbols	pass	0	== 0
Efficiency	throughput vs best	pass	55.1	>= 50

15 corpora, MB/s (the first is floored, the rest only reported): 15 of 15 at or above the 50% line.

CORPUS	KB	VBM-SSE	EVENTSOURCE-PARSER	EVENTSOURCE-STREAM	LEAN-FAST	REFERENCE	% BEST
small-events@1	3616	24.4	29.3	12.2	62.2	24.1	83.3%
small-events@7	3616	120.8	161.9	68.6	226	24.1	74.6%
small-events@4096	3616	1408	2553.2	390.7	1863.7	24.1	55.1%
large-data@1	1500	26.2	29.9	0.3	66.7	22.6	87.6%
large-data@7	1500	159.9	197.8	2	324.3	22.6	80.8%
large-data@4096	1500	2458.5	2880.6	461.3	3389	22.6	85.3%
ends-crlf@1	3681	24.8	30	12.3	63.6	23.9	82.7%
ends-crlf@7	3681	121.5	157.3	69.1	219.6	23.9	77.2%
ends-crlf@4096	3681	1263.3	1388.4	392.7	1597.7	23.9	91%
ends-cr@1	3616	24.1	28.7	11.8	61.9	23.5	84%
ends-cr@7	3616	120.5	155.1	68.7	223.1	23.5	77.7%
ends-cr@4096	3616	1371.9	1717.4	381.9	1858.4	23.5	79.9%
ends-mixed@1	3638	24.6	29.3	12	62.9	23.7	84%
ends-mixed@7	3638	120.1	152.4	65.5	217.6	23.7	78.8%
ends-mixed@4096	3638	1206.2	1161.5	365.9	1498.7	23.7	103.8%

Self-tests that ran (ran-evidence): 2315 cases in 7 evidence lines, 7 declared names present. Weakness: a count regex proves a count was printed, not that every case was meaningful.

Attack suite: PASS relabel-attacks: 67 of 67 attacks refused (26 s); gates stubbed: FAIL relabel-attacks: 0 of 67 attacks refused (1 s).

Level 2 (Measured) card. Level 1, Certified (an independent proof recheck), is not built yet: this is not a certificate.

Throughput MB/s, the floored corpus `490f3c11`: eventsource-parser 2553.2, vbm-sse 1408, eventsource-stream 390.7. ; best scalar eventsource-parser is 1.81x faster (floor: within 2x). Pinned: eventsource-parser 4.1.3, eventsource-stream 0.2.3.

Warm run (what a landing costs, floor under 60 s): the fast gate after a typical change, on the cache the cold run left; skipped 14 of 24 gates by design (the list is in card.json).

Cold run (what an outside contributor pays, ceiling 600 s, shown beside the warm run): 2 CPUs, 4 GB cap, a fresh clone with no cache.

Gates with self-test evidence in the run: 24 of 24.

Carve-outs (specified share 100 outside them). Four named shims of the pinned verified library vbm-simd (findAvx2, hasAvx2, ld64, ctz), 36 nodes, held at that baseline: the kernel is proved and the shim is tested in its own repository; what stays trusted is the shim C code and the CPU, listed there. Protected by the pinned-libraries lock.