

## Name

KHR\_vulkan\_glsl

## Name Strings

GL\_KHR\_vulkan\_glsl

## Contact

John Kessenich (johnkessenich 'at' google.com), Google

## Contributors

Jeff Bolz, NVIDIA  
Kerch Holt, NVIDIA  
Kenneth Benzie, Codeplay  
Neil Henning, Codeplay  
Neil Hickey, ARM  
Daniel Koch, NVIDIA  
Timothy Lottes, Epic Games  
David Neto, Google

## Notice

Copyright (c) 2015 The Khronos Group Inc. Copyright terms at  
<http://www.khronos.org/registry/speccopyright.html>

## Status

Approved by Vulkan working group 03-Dec-2015.  
Ratified by the Khronos Board of Promoters 15-Jan-2016.

## Version

Last Modified Date: 7-Mar-2016  
Revision: 28

## Number

TBD.

## Dependencies

This extension can be applied to OpenGL GLSL versions 1.40  
(#version 140) and higher.

This extension can be applied to OpenGL ES ESSL versions 3.10 (#version 310) and higher.

All these versions map GLSL/ESSL semantics to the same SPIR-V 1.0 semantics (approximating the most recent versions of GLSL/ESSL).

## Overview

This is version 100 of the GL\_KHR\_vulkan\_glsl extension.

This extension modifies GLSL to be used as a high-level language for the Vulkan API. GLSL is compiled down to SPIR-V, which the Vulkan API consumes.

The following features are removed:

- \* default uniforms (uniform variables not inside a uniform block), except for opaque types
- \* atomic-counter bindings: atomic counters form a one-dimensional space
- \* subroutines
- \* shared and packed block layouts
- \* the already deprecated texturing functions (e.g., texture2D())
- \* compatibility-mode-only features
- \* DepthRangeParameters
- \* gl\_VertexID and gl\_InstanceID

The following features are added:

- \* push-constant buffers
- \* shader-combining of separate textures and samplers
- \* descriptor sets
- \* specialization constants
- \* gl\_VertexIndex and gl\_InstanceIndex
- \* subpass inputs

The following features are changed:

- \* gl\_FragColor will no longer indicate an implicit broadcast
- \* arrays of opaque uniforms take only one binding number for the entire object, not one per array element
- \* the default origin is origin\_upper\_left instead of origin\_lower\_left

Each of these is discussed in more detail below.

## Enabling These Features

---

This extension is not enabled with a #extension as other extensions are. It is also not enabled through use of a profile or #version. The intended level of GLSL/ESSL features, independent from Vulkan-specific usage, comes

from the traditional use of `#version`, `profile`, and `#extension`.

Instead, use of this extension is an effect of using a GLSL front-end in a mode that has it generate SPIR-V for Vulkan. Such tool use is outside the scope of using the Vulkan API and outside the definition of GLSL and this extension. See the documentation of the compiler to see how to request generation of SPIR-V for Vulkan.

When a front-end is used to accept this extension, it must error check and reject shaders not adhering to this specification, and accept those that do. Implementation-dependent maximums and capabilities are supplied to, or part of, the front-end, so it can do error checking against them.

A shader can query the level of Vulkan support available, using the predefined

```
#define VULKAN 100
```

This allows shader code to say, for example,

```
#ifdef VULKAN
    layout(set = 1, binding = 0) uniform sampler s;
    layout(set = 1, binding = 1) uniform texture2D t;
    #if VULKAN > 100
        ...
    #endif
#else
    layout(binding = 0) uniform sampler2D ts;
#endif
```

#### Push Constants

Push constants reside in a uniform block declared using the new layout-qualifier-id "push\_constant" applied to a uniform-block declaration. The API writes a set of constants to a push-constant buffer, and the shader reads them from a push\_constant block:

```
layout(push_constant) uniform BlockName {
    int member1;
    float member2;
    ...
} InstanceName;

... = InstanceName.member2; // read a push constant
```

The memory accounting used for the push\_constant uniform block is different

than for other uniform blocks: There is a separate small pool of memory it must fit within. By default, a push\_constant buffer follows the std430 packing rules.

#### Combining separate samplers and textures

---

A sampler, declared with the keyword 'sampler', contains just filtering information, containing neither a texture nor an image:

```
uniform sampler s;    // a handle to filtering information
```

A texture, declared with keywords like 'texture2D', contains just image information, not filtering information:

```
uniform texture2D t; // a handle to a texture (an image in SPIR-V)
```

Constructors can then be used to combine a sampler and a texture at the point of making a texture lookup call:

```
texture2D(sampler2D(t, s), ...);
```

Note, layout() information is omitted above for clarity of this feature.

#### Descriptor Sets

---

Bound objects can further declare which Vulkan descriptor set they belong to, using 'set':

```
layout(set = N, ...) ... // declared object belongs to descriptor set N
```

For example, two combined texture/sampler objects can be declared in two different descriptor sets as follows

```
layout(set = 0, binding = 0) uniform sampler2D ts3;
layout(set = 1, binding = 0) uniform sampler2D ts4;
```

See the API documentation for more detail on the operation model of descriptor sets.

#### Specialization Constants

---

SPIR-V specialization constants, which can be set later by the client API, can be declared using "layout(constant\_id=...)". For example, to make a specialization constant with a default value of 12:

```
layout(constant_id = 17) const int arraySize = 12;
```

Above, "17" is the ID by which the API or other tools can later refer to this specific specialization constant. The API or an intermediate tool can then change its value to another constant integer before it is fully lowered to executable code. If it is never changed before final lowering, it will retain the value of 12.

Specialization constants have const semantics, except they don't fold. Hence, an array can be declared with 'arraySize' from above:

```
vec4 data[arraySize]; // legal, even though arraySize might change
```

Specialization constants can be in expressions:

```
vec4 data2[arraySize + 2];
```

This will make data2 be sized by 2 more than whatever constant value 'arraySize' has when it is time to lower the shader to executable code.

An expression formed with specialization constants also behaves in the shader like a specialization constant, not a like a constant.

```
arraySize + 2          // a specialization constant (with no constant_id)
```

Such expressions can be used in the same places as a constant.

The constant\_id can only be applied to a scalar \*int\*, a scalar \*float\* or a scalar \*bool\*.

Only basic operators and constructors can be applied to a specialization constant and still result in a specialization constant:

```
layout(constant_id = 17) const int arraySize = 12;
sin(float(arraySize)); // result is not a specialization constant
```

While SPIR-V specialization constants are only for scalars, a vector can be made by operations on scalars:

```
layout(constant_id = 18) const int scX = 1;
layout(constant_id = 19) const int scZ = 1;
const vec3 scVec = vec3(scX, 1, scZ); // partially specialized vector
```

A built-in variable can have a 'constant\_id' attached to it:

```
layout(constant_id = 18) gl_MaxImageUnits;
```

This makes it behave as a specialization constant. It is not a full redeclaration; all other characteristics are left intact from the original built-in declaration.

The built-in vector `gl_WorkGroupSize` can be specialized using special layout `local_size_{xyz}_id`'s applied to the "in" qualifier. For example:

```
layout(local_size_x_id = 18, local_size_z_id = 19) in;
```

This leaves `gl_WorkGroupSize.y` as a non-specialization constant, with `gl_WorkGroupSize` being a partially specialized vector. Its `x` and `z` components can be later specialized using the ID's 18 and 19.

#### `gl_VertexIndex` and `gl_InstanceIndex`

---

Adds two new built-in variables, `gl_VertexIndex` and `gl_InstanceIndex` to replace the existing built-in variables `gl_VertexID` and `gl_InstanceID`.

In the situations where the indexing is relative to some base offset, these built-in variables are defined, for Vulkan, to take on values as follows:

<code>gl_VertexIndex</code>	<code>base, base+1, base+2, ...</code>
<code>gl_InstanceIndex</code>	<code>base, base+1, base+2, ...</code>

Where it depends on the situation what the base actually is.

#### Subpass Inputs

---

Within a rendering pass, a subpass can write results to an output target that can then be read by the next subpass as an input subpass. The "Subpass Input" feature regards the ability to read an output target.

Subpasses are read through a new set of types, available only to fragment shaders:

```
subpassInput
subpassInputMS
isubpassInput
isubpassInputMS
usubpassInput
usubpassInputMS
```

Unlike sampler and image objects, subpass inputs are implicitly addressed

by the fragment's (x, y, layer) coordinate.

A subpass input is selected by using a new layout qualifier identifier 'input\_attachment\_index'. For example:

```
layout(input_attachment_index = i, ...) uniform subpassInput t;
```

An input\_attachment\_index of i selects the ith entry in the input pass list. (See API specification for more information.)

These objects support reading the subpass input through the following functions:

```
gvec4 subpassLoad(gsubpassInput subpass);
gvec4 subpassLoad(gsubpassInputMS subpass, int sample);
```

gl\_FragColor

The fragment-stage built-in gl\_FragColor, which implies a broadcast to all outputs, is not present in SPIR-V. Shaders where writing to gl\_FragColor is allowed can still write to it, but it only means to write to an output:

- of the same type as gl\_FragColor
- decorated with location 0
- not decorated as a built-in variable.

There is no implicit broadcast.

Mapping to SPIR-V

For informational purposes (non-specification), the following is an expected way for an implementation to map GLSL constructs to SPIR-V constructs:

Mapping of storage classes:

uniform sampler2D...;	-> UniformConstant
uniform blockN { ... } ...;	-> Uniform, with Block decoration
in / out variable	-> Input/Output, possibly with block (below)
in / out block...	-> Input/Output, with Block decoration
buffer blockN { ... } ...;	-> Uniform, with BufferBlock decoration
... uniform atomic_uint ...	-> AtomicCounter
shared	-> Workgroup
<normal global>	-> Private

Mapping of input/output blocks or variables is the same for all versions of GLSL or ESSL. To the extent variables or members are available in a

version, its location is as follows:

These are mapped to SPIR-V individual variables, with similarly spelled built-in decorations (except as noted):

Any stage:

```
in gl_NumWorkGroups
in gl_WorkGroupSize
in gl_WorkGroupID
in gl_LocalInvocationID
in gl_GlobalInvocationID
in gl_LocalInvocationIndex

in gl_VertexIndex
in gl_InstanceIndex
in gl_InvocationID
in gl_PatchVerticesIn      (PatchVertices)
in gl_PrimitiveIDIn        (PrimitiveID)
in/out gl_PrimitiveID      (in/out based only on storage qualifier)
in gl_TessCoord

in/out gl_Layer
in/out gl_ViewportIndex

patch in/out gl_TessLevelOuter (uses Patch decoration)
patch in/out gl_TessLevelInner (uses Patch decoration)
```

Fragment stage only:

```
in gl_FragCoord
in gl_FrontFacing
in gl_ClipDistance
in gl_CullDistance
in gl_PointCoord
in gl_SampleID
in gl_SamplePosition
in gl_HelperInvocation
out gl_FragDepth
in gl_SampleMaskIn         (SampleMask)
out gl_SampleMask          (in/out based only on storage qualifier)
```

These are mapped to SPIR-V blocks, as implied by the pseudo code, with the members decorated with similarly spelled built-in decorations:

Non-fragment stage:



```

    in/out gl_PerVertex {
        gl_Position
        gl_PointSize
        gl_ClipDistance
        gl_CullDistance
    }

```

(name of block is for debug only)

There is at most one input and one output block per stage in SPIR-V.

Mapping of precision qualifiers:

```

lowp      -> RelaxedPrecision, on variable and operation
mediump   -> RelaxedPrecision, on variable and operation
highp     -> 32-bit, same as int or float

```

```

portability tool/mode -> OpQuantizeToF16

```

Mapping of precise:

```

precise -> NoContraction

```

Mapping of images

```

subpassInput -> OpTypeImage with 'Dim' of SubpassData
subpassLoad() -> OpImageRead
imageLoad()   -> OpImageRead
imageStore()   -> OpImageWrite
texelFetch()  -> OpImageFetch

imageAtomicXXX(params, data) -> %ptr = OpImageTexelPointer params
                                OpAtomicXXX %ptr, data

XXXQueryXXX(combined) -> %image = OpImage combined
                        OpXXXQueryXXX %image

```

Mapping of layouts

```

std140/std430 -> explicit offsets/strides on struct
shared/packed -> not allowed
<default>     -> not shared, but std140 or std430

max_vertices -> OutputVertices

```

Mapping of other instructions

```

%      -> OpUMod/OpSMod
mod()  -> OpFMod

```

NA -> OpSRem/OpFRem

atomicExchange() -> OpAtomicExchange  
imageAtomicExchange() -> OpAtomicExchange  
atomicCompSwap() -> OpAtomicCompareExchange  
imageAtomicCompSwap() -> OpAtomicCompareExchange  
NA -> OpAtomicCompareExchangeWeak

#### Changes to Chapter 1 of the OpenGL Shading Language Specification

Change the last paragraph of "1.3 Overview": "The OpenGL Graphics System Specification will specify the OpenGL entry points used to manipulate and communicate with GLSL programs and GLSL shaders."

Add a paragraph: "The Vulkan API will specify the Vulkan entry points used to manipulate SPIR-V shaders. Independent offline tool chains will compile GLSL down to the SPIR-V intermediate language. Vulkan use is not enabled with a #extension, #version, or a profile. Instead, use of GLSL for Vulkan is determined by offline tool-chain use. See the documentation of such tools to see how to request generation of SPIR-V for Vulkan."

"GLSL -> SPIR-V compilers must be directed as to what SPIR-V \*Capabilities\* are legal at run-time and give errors for GLSL feature use outside those capabilities. This is also true for implementation-dependent limits that can be error checked by the front-end against constants present in the GLSL source: the front-end can be informed of such limits, and report errors when they are exceeded."

#### Changes to Chapter 2 of the OpenGL Shading Language Specification

Change the name from

"2 Overview of OpenGL Shading"

to

"2 Overview of OpenGL and Vulkan Shading"

Remove the word "OpenGL" from three introductory paragraphs.

#### Changes to Chapter 3 of the OpenGL Shading Language Specification

Add a new paragraph at the end of section "3.3 Preprocessor": "When shaders are compiled for Vulkan, the following predefined macro is available:

```
#define VULKAN 100
```

Add the following keywords to section 3.6 Keywords:

texture1D	texture2D	texture3D
textureCube	texture2DRect	texture1DArray
texture2DArray	textureBuffer	texture2DMS
texture2DMSArray	textureCubeArray	
itexture1D	itexture2D	itexture3D
itextureCube	itexture2DRect	itexture1DArray
itexture2DArray	itextureBuffer	
itexture2DMS	itexture2DMSArray	
itextureCubeArray		
utexture1D	utexture2D	utexture3D
utextureCube	utexture2DRect	utexture1DArray
utexture2DArray	utextureBuffer	utexture2DMS
utexture2DMSArray	utextureCubeArray	
sampler	samplerShadow	
subpassInput	isubpassInput	usubpassInput
subpassInputMS	isubpassInputMS	usubpassInputMS

Changes to Chapter 4 of the OpenGL Shading Language Specification

Add into the tables in section 4.1, interleaved with the existing types, using the existing descriptions (when not supplied below):

Floating-Point Opaque Types

texture1D	
texture2D	
texture3D	
textureCube	
texture2DRect	
texture1DArray	
texture2DArray	
textureBuffer	
texture2DMS	
texture2DMSArray	
textureCubeArray	
subpassInput	a handle for accessing a floating-point   subpass input
subpassInputMS	a handle for accessing a multi-sampled   floating-point subpass input

## Signed Integer Opaque Types

itexture1D	
itexture2D	
itexture3D	
itextureCube	
itexture2DRect	
itexture1DArray	
itexture2DArray	
itextureBuffer	
itexture2DMS	
itexture2DMSArray	
itextureCubeArray	
isubpassInput	a handle for accessing an integer subpass input
isubpassInputMS	a handle for accessing a multi-sampled integer   subpass input

## Unsigned Integer Opaque Types

utexture1D	
utexture2D	
utexture3D	
utextureCube	
utexture2DRect	
utexture1DArray	
utexture2DArray	
utextureBuffer	
utexture2DMS	
utexture2DMSArray	
utextureCubeArray	
usubpassInput	a handle for accessing an unsigned integer   subpass input
usubpassInputMS	a handle for accessing a multi-sampled unsigned   integer subpass input

Add a new category in this section

## "Sampler Opaque Types

sampler	a handle for accessing state describing how to   sample a texture (without comparison)"
-----	
samplerShadow	a handle for accessing state describing how to   sample a depth texture with comparison"

Remove "structure member selection" from 4.1.7 and instead add a sentence "Opaque types cannot be declared or nested in a structure (struct)."

Add a subsection to 4.1.7 Opaque Types:

#### "4.1.7.x Texture, \*sampler\*, and \*samplerShadow\* Types

"Texture (e.g., \*texture2D\*), \*sampler\*, and \*samplerShadow\* types are opaque types, declared and behaving as described above for opaque types. When aggregated into arrays within a shader, these types can only be indexed with a dynamically uniform expression, or texture lookup will result in undefined values. Texture variables are handles to one-, two-, and three-dimensional textures, cube maps, etc., as enumerated in the basic types tables. There are distinct texture types for each texture target, and for each of float, integer, and unsigned integer data types. Textures can be combined with a variable of type \*sampler\* or \*samplerShadow\* to create a sampler type (e.g., sampler2D, or sampler2DShadow). This is done with a constructor, e.g., sampler2D(texture2D, sampler) or sampler2DShadow(texture2D, samplerShadow), and is described in more detail in section 5.4 "Constructors"."

#### "4.1.7.x Subpass Inputs

"Subpass input types (e.g., subpassInput) are opaque types, declared and behaving as described above for opaque types. When aggregated into arrays within a shader, they can only be indexed with a dynamically uniform integral expression, otherwise results are undefined.

"Subpass input types are handles to two-dimensional single sampled or multi-sampled images, with distinct types for each of float, integer, and unsigned integer data types.

"Subpass input types are only available in fragment shaders. It is a compile-time error to use them in any other stage."

Change section 4.3.3 Constant Expressions:

Add a new very first sentence to this section:

"SPIR-V specialization constants are expressed in GLSL as const, with a layout qualifier identifier of constant\_id, as described in section 4.4.x Specialization-Constant Qualifier."

Add to this sentence:

"A constant expression is one of...

\* a variable declared with the `const` qualifier and an initializer, where the initializer is a constant expression”

To make it say:

”A constant expression is one of...

- \* a variable declared with the `const` qualifier and an initializer, where the initializer is a constant expression; this includes both `const` declared with a specialization-constant layout qualifier, e.g., `'layout(constant_id = ...).'` and those declared without a specialization-constant layout qualifier”

Add to ”including getting an element of a constant array,” that

”an array access with a specialization constant as an index does not result in a constant expression”

Add to this sentence:

”A constant expression is one of...

- \* the value returned by a built-in function...”

To make it say:

”A constant expression is one of...

- \* for non-specialization-constants only: the value returned by a built-in function... (when any function is called with an argument that is a specialization constant, the result is not a constant expression)”

Rewrite the last half of the last paragraph to be its own paragraph saying:

”Non-specialization constant expressions may be evaluated by the compiler’s host platform, and are therefore not required ...  
[rest of paragraph stays the same]”

Add a paragraph

”Specialization constant expressions are never evaluated by the front-end, but instead retain the operations needed to evaluate them later on the host.”

Add to the table in section 4.4 Layout Qualifiers:

	Individual Variable	Block	Allowed Interface
--	---------------------	-------	-------------------

-----

constant_id =	scalar only		const
push_constant		X	uniform
set =	opaque only	X	uniform
input_attachment_index	subpass types only		uniform

(The other columns remain blank.)

Also add to this table:

	Qualifier Only	Allowed Interface
local_size_x_id =	X	in
local_size_y_id =	X	in
local_size_z_id =	X	in

(The other columns remain blank.)

Expand this sentence in section 4.4.1 Input Layout Qualifiers:

"Where integral-constant-expression is defined in section 4.3.3 Constant Expressions as 'integral constant expression' "

To include the following:

", with it being a compile-time error for integer-constant-expression to be a specialization constant: The constant used to set a layout identifier X in layout(layout-qualifier-name = X) must evaluate to a front-end constant containing no specialization constants."

Change the rules about locations and inputs for doubles, by removing

"If a vertex shader input is any scalar or vector type, it will consume a single location. If a non-vertex shader input is a scalar or vector type other than dvec3 or dvec4..."

Replacing the above with

"If an input is a scalar or vector type other than dvec3 or dvec4..."

(Making all stages have the same rule that dvec3 takes two locations...)

Change section 4.4.1.3 "Fragment Shader Inputs" from

"By default, gl\_FragCoord assumes a lower-left origin for window

coordinates ... For example, the (x, y) location (0.5, 0.5) is returned for the lowerleft-most pixel in a window. The origin can be changed by redeclaring `gl_FragCoord` with the `origin_upper_left` identifier."

To

"The `gl_FragCoord` built-in variable assumes an upper-left origin for window coordinates ... For example, the (x, y) location (0.5, 0.5) is returned for the upper-left-most pixel in a window. The origin can be explicitly set by redeclaring `gl_FragCoord` with the `origin_upper_left` identifier. It is a compile-time error to change it to `origin_lower_left`."

Add to the end of section 4.4.3 Uniform Variable Layout Qualifiers:

"The `/push_constant/` identifier is used to declare an entire block, and represents a set of "push constants", as defined by the API. It is a compile-time error to apply this to anything other than a uniform block declaration. The values in the block will be initialized through the API, as per the Vulkan API specification. A block declared with `layout(push_constant)` must have an `/instance-name/` supplied, or a compile-time error results. There can be only one `push_constant` block per stage, or a compile-time or link-time error will result. A `push-constant` array can only be indexed with dynamically uniform indexes. Uniform blocks declared with `push_constant` use different resources than those without; and are accounted for separately. See the API specification for more detail."

After the paragraphs about binding ("The binding identifier..."), add

"The `/set/` identifier specifies the descriptor set this object belongs to. It is a compile-time error to apply `/set/` to a standalone qualifier or to a member of a block. It is a compile-time error to apply `/set/` to a block qualified as a `push_constant`. By default, any non-`push_constant` uniform or shader storage block declared without a `/set/` identifier is assigned to descriptor set 0. Similarly, any sampler, texture, or subpass input type declared as a uniform, but without a `/set/` identifier is also assigned to descriptor set 0.

"If applied to an object declared as an array, all elements of the array belong to the specified `/set/`.

"It is a compile-time error for either the `/set/` or `/binding/` value to exceed a front-end-configuration supplied maximum value."

Change section 4.4.6 Opaque-Uniform Layout Qualifiers:



Change

"If the binding identifier is used with an array, the first element of the array takes the specified unit and each subsequent element takes the next consecutive unit."

To

"If the binding identifier is used with an array, the entire array takes just the provided binding number. The next consecutive binding number is available for a different object."

Add a new subsection at the end of section 4.4:

"4.4.x Specialization-Constant Qualifier

"Specialization constants are declared using `layout(constant_id=...)`". For example:

```
layout(constant_id = 17) const int arraySize = 12;
```

"The above makes a specialization constant with a default value of 12. 17 is the ID by which the API or other tools can later refer to this specific specialization constant. If it is never changed before final lowering, it will retain the value of 12. It is a compile-time error to use the `constant_id` qualifier on anything but a scalar bool, int, uint, float, or double.

"Built-in constants can be declared to be specialization constants. For example,

```
layout(constant_id = 31) gl_MaxClipDistances; // add specialization id
```

"The declaration uses just the name of the previously declared built-in variable, with a `constant_id` layout declaration. It is a compile-time error to do this after the constant has been used: Constants are strictly either non-specialization constants or specialization constants, not both.

"The built-in constant vector `gl_WorkGroupSize` can be specialized using the `local_size_{xyz}_id` qualifiers, to individually give the components an id. For example:

```
layout(local_size_x_id = 18, local_size_z_id = 19) in;
```

"This leaves `gl_WorkGroupSize.y` as a non-specialization constant, with

gl\_WorkGroupSize being a partially specialized vector. Its x and z components can be later specialized using the ids 18 and 19. These ids are declared independently from declaring the work-group size:

```
layout(local_size_x = 32, local_size_y = 32) in;    // size is (32, 32, 1)
layout(local_size_x_id = 18) in;                  // constant_id for x
layout(local_size_z_id = 19) in;                  // constant_id for z
```

"Existing rules for declaring local\_size\_x, local\_size\_y, and local\_size\_z are not changed by this extension. For the local-size ids, it is a compile-time error to provide different id values for the same local-size id, or to provide them after any use. Otherwise, order, placement, number of statements, and replication do not cause errors.

"Two arrays sized with specialization constants are the same type only if sized with the same symbol, involving no operations.

```
layout(constant_id = 51) const int aSize = 20;
const int pad = 2;
const int total = aSize + pad; // specialization constant
int a[total], b[total];        // a and b have the same type
int c[22];                     // different type than a or b
int d[aSize + pad];             // different type than a, b, or c
int e[aSize + 2];              // different type than a, b, c, or d
```

"Types containing arrays sized with a specialization constant cannot be compared, assigned as aggregates, or used in initializers. They can, however, be passed as arguments to functions having formal parameters of the same type.

"Arrays inside a block may be sized with a specialization constant, but the block will have a static layout. Changing the specialized size will not re-layout the block. In the absence of explicit offsets, the layout will be based on the default size of the array."

Add a new subsection at the end of section 4.4:

#### "4.4.y Subpass Qualifier

"Subpasses are declared with the basic 'subpassInput' types. However, they must have the layout qualifier "input\_attachment\_index" declared with them, or a compile-time error results. For example:

```
layout(input_attachment_index = 2, ...) uniform subpassInput t;
```

This selects which subpass input is being read from. The value assigned to 'input\_attachment\_index', say i (input\_attachment\_index = i), selects

that entry (ith entry) in the input list for the pass. See the API documentation for more detail about passes and the input list.

"If an array of size N is declared, it consume N consecutive input\_attachment\_index values, starting with the one provided.

"It is a compile-time or link-time error to have different variables declared with the same input\_attachment\_index. This includes any overlap in the implicit input\_attachment\_index consumed by array declarations.

"It is a compile-time error if the value assigned to an input\_attachment\_index is greater than or equal to gl\_MaxInputAttachments."

Remove all mention of the 'shared' and 'packed' layout qualifiers.

Change section 4.4.5 Uniform and Shader Storage Block Layout Qualifiers

"The initial state of compilation is as if the following were declared:

```
layout(std140, column_major) uniform; // without push_constant
layout(std430, column_major) buffer;
```

"However, when push\_constant is declared, the default layout of the buffer will be std430. There is no method to globally set this default."

Changes to Chapter 5 of the OpenGL Shading Language Specification

Add a new subsection at the end of section 5.4 "Constructors":

"5.4.x Sampler Constructors

"Sampler types, like \*sampler2D\* can be declared with an initializer that is a constructor of the same type, and consuming a texture and a sampler. For example:

```
layout(...) uniform sampler s; // handle to filtering information
layout(...) uniform texture2D t; // handle to a texture
in vec2 tCoord;
...
texture2D(sampler2D(t, s), tCoord);
```

The result of a sampler constructor cannot be assigned to a variable:

```
... sampler2D sConstruct = sampler2D(t, s); // ERROR
```

Sampler constructors can only be consumed by a function parameter.

Sampler constructors of arrays are illegal:

```
layout(...) uniform texture2D tArray[6];
...
... sampler2D[] (tArray, s) ... // ERROR
```

Formally:

- \* every sampler type can be used as a constructor
- \* the type of the constructor must match the type of the variable being declared
- \* the constructor's first argument must be a texture type
- \* the constructor's second argument must be a scalar of type `*sampler*` or `*samplerShadow*`
- \* the dimensionality (1D, 2D, 3D, Cube, Rect, Buffer, MS, and Array) of the texture type must match that of the constructed sampler type (that is, the suffixes of the type of the first argument and the type of the constructor will be spelled the same way)
- \* the presence or absence of depth comparison (Shadow) must match between the constructed sampler type and the type of the second argument
- \* there is no control flow construct (e.g., `"?:"`) that consumes any sampler type

Change section 5.9 Expressions

Add under "The sequence (,) operator..."

"Texture and sampler types cannot be used with the sequence (,) operator."

Change under "The ternary selection operator (?:)..."

"The second and third expressions can be any type, as long their types match."

To

"The second and third expressions can be any type, as long their types match, except for texture and sampler types, which result in a compile-time error."

Add a section at the end of section 5

"5.x Specialization Constant Operations"

Only some operations discussed in this section may be applied to a specialization constant and still yield a result that is as

specialization constant. The operations allowed are listed below. When a specialization constant is operated on with one of these operators and with another constant or specialization constant, the result is implicitly a specialization constant.

- int(), uint(), float(), and bool() constructors for type conversions from any of the following types to any of the following types:
  - \* int
  - \* uint
  - \* float
  - \* double
  - \* bool
- vector versions of the above conversion constructors
- allowed implicit conversions of the above
- The operators
  - \* unary negative ( - )
  - \* not ( ! )
  - \* binary operations ( + , - , \* , / , % )
  - \* shift ( << , >> )
  - \* bitwise operations ( & , | , ^ )
  - \* swizzles (e.g., foo.yx)
  - \* logical operations ( && , || , ^^ )
  - \* comparison ( == , != , > , >= , < , <= )

## Changes to Chapter 7 of the OpenGL Shading Language Specification

### Changes to section 7.1 Built-In Language Variables

Replace gl\_VertexID and gl\_InstanceID, for non-ES with:

```
"in int gl_VertexIndex;"
"in int gl_InstanceIndex;"
```

For ES, add:

```
"in highp int gl_VertexIndex;"
"in highp int gl_InstanceIndex;"
```

The following definition for gl\_VertexIndex should replace the definition for gl\_VertexID:

"The variable gl\_VertexIndex is a vertex language input variable that holds an integer index for the vertex, [See issue 7 regarding which name goes with which semantics] relative to a base. While the variable gl\_VertexIndex is always present, its value is not always defined. See XXX in the API specification."

The following definition for `gl_InstanceIndex` should replace the definition for `gl_InstanceID`:

"The variable `gl_InstanceIndex` is a vertex language input variable that holds the instance number of the current primitive in an instanced draw call, relative to a base. If the current primitive does not come from an instanced draw call, the value of `gl_InstanceIndex` is zero."  
[See issue 7 regarding which name goes with which semantics]

Changes to section 7.3 Built-In Constants

Add

"const int `gl_MaxInputAttachments` = 1;"

Changes to Chapter 8 of the OpenGL Shading Language Specification

Add a section

"8.X Subpass Functions

"Subpass functions are only available in a fragment shader.

"Subpass inputs are read through the built-in functions below. The `gvec...` and `gsubpass...` are matched, where they must both be the same floating point, integer, or unsigned integer variants.

Add a table with these two entries (in the same cell):

"`gvec4 subpassLoad(gsubpassInput subpass)`  
`gvec4 subpassLoad(gsubpassInputMS subpass, int sample)`"

With the description:

"Read from a subpass input, from the implicit location (x, y, layer) of the current fragment coordinate."

Changes to the grammar

Arrays can no longer require the size to be a compile-time folded constant expression. Change

| LEFT\_BRACKET constant\_expression RIGHT\_BRACKET

to

| LEFT\_BRACKET conditional\_expression RIGHT\_BRACKET

and change

```
| array_specifier LEFT_BRACKET constant_expression RIGHT_BRACKET
```

to

```
| array_specifier LEFT_BRACKET conditional_expression RIGHT_BRACKET
```

## Issues

1. Can we have specialization sizes in an array in a block? That prevents putting known offsets on subsequent members.

RESOLUTION: Yes, but it does not affect offsets.

2. Can a specialization-sized array be passed by value?

RESOLUTION: Yes, if they are sized with the same specialization constant.

3. Can a texture array be variably indexed? Dynamically uniform?

Resolution (bug 14683): Dynamically uniform indexing.

4. Are arrays of a descriptor set all under the same set number, or does, say, an array of size 4 use up 4 descriptor sets?

RESOLUTION: There is no array of descriptor sets. Arrays of resources are in a single descriptor set and consume a single binding number.

5. Which descriptor set arrays can be variably or non-uniformly indexed?

RESOLUTION: There is no array of descriptor sets.

6. Do we want an alternate way of doing composite member specialization constants? For example,

```
layout(constant_id = 18) gl_WorkGroupSize.y;
```

Or

```
layout(constant_id = 18, local_size_y = 16) in;
```

Or

```
layout(constant_id = 18) wgy = 16;  
const ivec3 gl_WorkGroupSize = ivec3(1, wgy, 1);
```

RESOLUTION: No. Use `local_size_x_id` etc. for workgroup size, and defer any more generalized way of doing this for composites.

7. What names do we really want to use for

<code>gl_VertexIndex</code>	<code>base, base+1, base+2, ...</code>
<code>gl_InstanceIndex</code>	<code>base, base+1, base+2, ...</code>

RESOLUTION: Use the names above.

Note that `gl_VertexIndex` is equivalent to OpenGL's `gl_VertexID` in that it includes the value of the `baseVertex` parameter. `gl_InstanceIndex` is NOT equivalent to OpenGL's `gl_InstanceID` because `gl_InstanceID` does NOT include the `baseInstance` parameter.

8. What should "input subpasses" really be called?

RESOLVED: `subpassInput`.

9. The spec currently does not restrict where sampler constructors can go, but should it? E.g., can the user write a shader like the following:

```
uniform texture2D t[MAX_TEXTURES];
uniform sampler s[2];

uniform int textureCount;
uniform int sampleCount;
uniform bool samplerCond;

float ShadowLookup(bool pcf, vec2 tcBase[MAX_TEXTURES])
{
    float result = 0;

    for (int textureIndex = 0; textureIndex < textureCount; ++textureIndex)
    {
        for (int sampleIndex = 0; sampleIndex < sampleCount; ++sampleIndex)
        {
            vec2 tc = tcBase[textureIndex] + offsets[sampleIndex];
            if (samplerCond)
                result += texture(sampler2D(t[textureIndex], s[0]), tc).r;
            else
                result += texture(sampler2D(t[textureIndex], s[1]), tc).r;
        }
    }
}
```

Or, like this?

```
uniform texture2D t[MAX_TEXTURES];
```



```

uniform sampler s[2];

uniform int textureCount;
uniform int sampleCount;
uniform bool samplerCond;

sampler2D combined0[MAX_TEXTURES] = sampler2D(t, s[0]);
sampler2D combined1[MAX_TEXTURES] = sampler2D(t, s[1]);

float ShadowLookup(bool pcf, vec2 tcBase[MAX_TEXTURES])
{
    for (int textureIndex = 0; textureIndex < textureCount; ++textureIndex) {
        for (int sampleIndex = 0; sampleIndex < sampleCount; ++sampleIndex) {
            vec2 tc = tcBase[textureIndex] + offsets[sampleIndex];
            if (samplerCond)
                result += texture(combined0[textureIndex], tc).r;
            else
                result += texture(combined1[textureIndex], tc).r;
        }
    }
    ...
}

```

RESOLUTION (bug 14683): Only constructed at the point of use, where passed as an argument to a function parameter.

#### Revision History

Rev.	Date	Author	Changes
28	7-Mar-2016	JohnK	Make push_constants not have sets
27	28-Feb-2016	JohnK	Make the default by origin_upper_left
26	17-Feb-2016	JohnK	Expand specialized array semantics
25	10-Feb-2016	JohnK	Incorporate resolutions from the face to face
24	28-Jan-2016	JohnK	Update the resolutions from the face to face
23	6-Jan-2016	Piers	Remove support for gl_VertexID and gl_InstanceID since they aren't supported by Vulkan.
22	29-Dec-2015	JohnK	support old versions and add semantic mapping
21	09-Dec-2015	JohnK	change spelling *subpass* -> *subpassInput* and include this and other texture/sample types in the descriptor-set-0 default scheme
20	01-Dec-2015	JohnK	push_constant default to std430, opaque types can only aggregate as arrays
19	25-Nov-2015	JohnK	Move "Shadow" from texture types to samplerShadow
18	23-Nov-2015	JohnK	Bug 15206 - Indexing of push constant arrays
17	18-Nov-2015	JohnK	Bug 15066: std140/std43 defaults
16	18-Nov-2015	JohnK	Bug 15173: subpass inputs as arrays
15	07-Nov-2015	JohnK	Bug 14683: new rules for separate texture/sampler

14	07-Nov-2015	JohnK	Add specialization operators, <code>local_size*_id</code> rules, and input <code>dvec3/dvec4</code> always use two locations
13	29-Oct-2015	JohnK	Rules for input att. numbers, <code>constant_id</code> , and no <code>subpassLoadMS()</code>
12	29-Oct-2015	JohnK	Explain how <code>gl_FragColor</code> is handled
11	9-Oct-2015	JohnK	Add issue: where can sampler constructors be
10	7-Sep-2015	JohnK	Add first draft specification language
9	5-Sep-2015	JohnK	- make specialization <code>id</code> 's scalar only, and add <code>local_size_x_id...</code> for component-level workgroup size setting
8	2-Sep-2015	JohnK	- address several review comments switch to using the <code>*target*</code> style of target types (bug 14304)
7	15-Aug-2015	JohnK	add overview for input targets
6	12-Aug-2015	JohnK	document <code>gl_VertexIndex</code> and <code>gl_InstanceIndex</code>
5	16-Jul-2015	JohnK	<code>push_constant</code> is a layout qualifier <code>VULKAN</code> is the only versioning macro <code>constantID</code> -> <code>constant_id</code>
4	12-Jul-2015	JohnK	Rewrite for clarity, with proper overview, and prepare to add full semantics
3	14-May-2015	JohnK	Minor changes from meeting discussion
2	26-Apr-2015	JohnK	Add controlling features/capabilities
1	26-Mar-2015	JohnK	Initial revision