



SPIR-V Specification

John Kessenich, Google, Boaz Ouriel, Intel, and Raun Krisch, Intel

Version 1.3, Revision 1, Unified

March 6, 2018



Copyright © 2014-2018 The Khronos Group Inc. All Rights Reserved.

This specification is protected by copyright laws and contains material proprietary to the Khronos Group, Inc. It or any components may not be reproduced, republished, distributed, transmitted, displayed, broadcast, or otherwise exploited in any manner without the express prior written permission of Khronos Group. You may use this specification for implementing the functionality therein, without altering or removing any trademark, copyright or other notice from the specification, but the receipt or possession of this specification does not convey any rights to reproduce, disclose, or distribute its contents, or to manufacture, use, or sell anything that it may describe, in whole or in part.

Khronos Group grants express permission to any current Promoter, Contributor or Adopter member of Khronos to copy and redistribute UNMODIFIED versions of this specification in any fashion, provided that NO CHARGE is made for the specification and the latest available update of the specification for any version of the API is used whenever possible. Such distributed specification may be reformatted AS LONG AS the contents of the specification are not changed in any way. The specification may be incorporated into a product that is sold as long as such product includes significant independent work developed by the seller. A link to the current version of this specification on the Khronos Group website should be included whenever possible with specification distributions.

Khronos Group makes no, and expressly disclaims any, representations or warranties, express or implied, regarding this specification, including, without limitation, any implied warranties of merchantability or fitness for a particular purpose or non-infringement of any intellectual property. Khronos Group makes no, and expressly disclaims any, warranties, express or implied, regarding the correctness, accuracy, completeness, timeliness, and reliability of the specification. Under no circumstances will the Khronos Group, or any of its Promoters, Contributors or Members or their respective partners, officers, directors, employees, agents, or representatives be liable for any damages, whether direct, indirect, special or consequential damages for lost revenues, lost profits, or otherwise, arising from or in connection with these materials.

Khronos, SYCL, SPIR, WebGL, EGL, COLLADA, StreamInput, OpenVX, OpenKCam, glTF, OpenKODE, OpenVG, OpenWF, OpenGL ES, OpenMAX, OpenMAX AL, OpenMAX IL and OpenMAX DL are trademarks and WebCL is a certification mark of the Khronos Group Inc. OpenCL is a trademark of Apple Inc. and OpenGL and OpenML are registered trademarks and the OpenGL ES and OpenGL SC logos are trademarks of Silicon Graphics International used under license by Khronos. All other product names, trademarks, and/or company names are used solely for identification and belong to their respective owners.

Contents

1	Introduction	9
1.1	Goals	9
1.2	About this document	9
1.3	Extendability	10
1.4	Debuggability	10
1.5	Design Principles	10
1.6	Static Single Assignment (SSA)	11
1.7	Built-In Variables	11
1.8	Specialization	11
1.9	Example	12
2	Specification	15
2.1	Language Capabilities	15
2.2	Terms	15
2.2.1	Instructions	15
2.2.2	Types	16
2.2.3	Module	17
2.2.4	Control Flow	17
2.3	Physical Layout of a SPIR-V Module and Instruction	20
2.4	Logical Layout of a Module	21
2.5	Instructions	22
2.5.1	SSA Form	22
2.6	Entry Point and Execution Model	23
2.7	Execution Modes	23
2.8	Types and Variables	23
2.9	Function Calling	24
2.10	Extended Instruction Sets	24
2.11	Structured Control Flow	25
2.12	Specialization	26
2.13	Linkage	27
2.14	Relaxed Precision	28
2.15	Debug Information	29
2.15.1	Function-Name Mangling	29
2.16	Validation Rules	29
2.16.1	Universal Validation Rules	29

2.16.2	Validation Rules for Shader Capabilities	32
2.16.3	Validation Rules for Kernel Capabilities	33
2.17	Universal Limits	34
2.18	Memory Model	34
2.18.1	Memory Layout	35
2.18.2	Aliasing	35
2.18.3	Null pointers	35
2.19	Derivatives	36
2.20	Code Motion	36
2.21	Deprecation	36
2.22	Unified Specification	36
3	Binary Form	37
3.1	Magic Number	37
3.2	Source Language	37
3.3	Execution Model	37
3.4	Addressing Model	38
3.5	Memory Model	38
3.6	Execution Mode	38
3.7	Storage Class	43
3.8	Dim	44
3.9	Sampler Addressing Mode	45
3.10	Sampler Filter Mode	45
3.11	Image Format	45
3.12	Image Channel Order	46
3.13	Image Channel Data Type	47
3.14	Image Operands	47
3.15	FP Fast Math Mode	50
3.16	FP Rounding Mode	50
3.17	Linkage Type	50
3.18	Access Qualifier	51
3.19	Function Parameter Attribute	51
3.20	Decoration	52
3.21	BuiltIn	57
3.22	Selection Control	63
3.23	Loop Control	63
3.24	Function Control	63
3.25	Memory Semantics <id>	64

3.26	Memory Access	66
3.27	Scope <id>	66
3.28	Group Operation	68
3.29	Kernel Enqueue Flags	70
3.30	Kernel Profiling Info	70
3.31	Capability	71
3.32	Instructions	78
3.32.1	Miscellaneous Instructions	78
3.32.2	Debug Instructions	80
3.32.3	Annotation Instructions	83
3.32.4	Extension Instructions	85
3.32.5	Mode-Setting Instructions	86
3.32.6	Type-Declaration Instructions	88
3.32.7	Constant-Creation Instructions	94
3.32.8	Memory Instructions	99
3.32.9	Function Instructions	103
3.32.10	Image Instructions	105
3.32.11	Conversion Instructions	125
3.32.12	Composite Instructions	130
3.32.13	Arithmetic Instructions	134
3.32.14	Bit Instructions	142
3.32.15	Relational and Logical Instructions	147
3.32.16	Derivative Instructions	158
3.32.17	Control-Flow Instructions	161
3.32.18	Atomic Instructions	165
3.32.19	Primitive Instructions	174
3.32.20	Barrier Instructions	175
3.32.21	Group Instructions	177
3.32.22	Device-Side Enqueue Instructions	188
3.32.23	Pipe Instructions	197
3.32.24	Non-Uniform Instructions	212
A	Changes	228
A.1	Changes from Version 0.99, Revision 31	228
A.2	Changes from Version 0.99, Revision 32	229
A.3	Changes from Version 1.00, Revision 1	229
A.4	Changes from Version 1.00, Revision 2	230
A.5	Changes from Version 1.00, Revision 3	231

A.6	Changes from Version 1.00, Revision 4	231
A.7	Changes from Version 1.00, Revision 5	231
A.8	Changes from Version 1.00, Revision 6	232
A.9	Changes from Version 1.00, Revision 7	232
A.10	Changes from Version 1.00, Revision 8	232
A.11	Changes from Version 1.00, Revision 9	232
A.12	Changes from Version 1.00, Revision 10	233
A.13	Changes from Version 1.00, Revision 11	233
A.14	Changes from Version 1.00	234
A.15	Changes from Version 1.1, Revision 1	234
A.16	Changes from Version 1.1, Revision 2	234
A.17	Changes from Version 1.1, Revision 3	234
A.18	Changes from Version 1.1, Revision 4	234
A.19	Changes from Version 1.1, Revision 5	234
A.20	Changes from Version 1.1, Revision 6	235
A.21	Changes from Version 1.1, Revision 7	235
A.22	Changes from Version 1.1	235
A.23	Changes from Version 1.2, Revision 1	235
A.24	Changes from Version 1.2, Revision 2	235
A.25	Changes from Version 1.2, Revision 3	235
A.26	Changes from Version 1.2	236

List of Tables

1	First Words of Physical Layout	20
2	Instruction Physical Layout	20
3	Limits	34

Contributors and Acknowledgments

Connor Abbott, Intel
Ben Ashbaugh, Intel
Alexey Bader, Intel
Dan Baker, Oxide Games
Kenneth Benzie, Codeplay
Gordon Brown, Codeplay
Pat Brown, NVIDIA
Diana Po-Yu Chen, MediaTek
Stephen Clarke, Imagination
Patrick Doane, Blizzard Entertainment
Stefanus Du Toit, Google
Tim Foley, Intel
Ben Gaster, Qualcomm
Alexander Galazin, ARM
Christopher Gautier, ARM
Neil Henning, Codeplay
Kerch Holt, NVIDIA
Lee Howes, Qualcomm
Roy Ju, MediaTek
John Kessenich, Google
Daniel Koch, NVIDIA
Ashwin Kolhe, NVIDIA
Raun Krisch, Intel
Graeme Leese, Broadcom
Yuan Lin, NVIDIA
Yaxun Liu, AMD
Timothy Lottes, Epic Games
John McDonald, Valve
David Neto, Google
Boaz Ouriel, Intel
Christophe Riccio, Unity
Andrew Richards, Codeplay
Ian Romanick, Intel
Graham Sellers, AMD
Robert Simpson, Qualcomm
Bartosz Sochacki, Intel
Brian Sumner, AMD
Andrew Woloszyn, Google
Weifeng Zhang, Qualcomm

Note

Up-to-date HTML and PDF versions of this specification may be found at the [Khronos SPIR-V Registry](https://www.khronos.org/registry/spir-v/). (<https://www.khronos.org/registry/spir-v/>)

1 Introduction

Abstract

SPIR-V is a simple binary intermediate language for graphical shaders and compute kernels. A SPIR-V module contains multiple entry points with potentially shared functions in the entry point's call trees. Each function contains a control-flow graph (CFG) of basic blocks, with optional instructions to express structured control flow. Load/store instructions are used to access declared variables, which includes all input/output (IO). Intermediate results bypassing load/store use static single-assignment (SSA) representation. Data objects are represented logically, with hierarchical type information: There is no flattening of aggregates or assignment to physical register banks, etc. Selectable addressing models establish whether general pointer operations may be used, or if memory access is purely logical.

This document fully defines **SPIR-V**, a Khronos-standard binary intermediate language for representing graphical-shader stages and compute kernels for multiple Khronos APIs.

This is a [unified specification](#), specifying all versions since and including version 1.0.

1.1 Goals

SPIR-V has the following goals:

- Provide a simple binary intermediate language for all functionality appearing in Khronos shaders/kernels.
- Have a concise, transparent, self-contained specification (sections [Specification](#) and [Binary Form](#)).
- Map easily to other intermediate languages.
- Be the form passed by an API into a driver to set shaders/kernels.
- Can be targeted by new front ends for novel high-level languages.
- Allow the first steps of compilation and reflection to be done offline.
- Be low-level enough to require a reverse-engineering step to reconstruct source code.
- Improve portability by enabling shared tools to generate or operate on it.
- Allow separation of core specification from source-language-specific sets of built-in functions.
- Reduce compile time during application run time. (Eliminating most of the compile time during application run time is not a goal of this intermediate language. Target-specific register allocation and scheduling are still expected to take significant time.)
- Allow some optimizations to be done offline.

1.2 About this document

This document aims to:

- Include everything needed to fully understand, create, and consume SPIR-V. However:
 - Imported sets of instructions (which implement source-specific built-in functions) will need their own specification.
 - Many validation rules are client-API specific, and hence documented with client API and not in this specification.
- Separate expository and specification language. The specification-proper is in [Specification](#) and [Binary Form](#).

1.3 Extendability

SPIR-V can be extended by multiple vendors or parties simultaneously:

- Using the [OpExtension](#) instruction to require new semantics that must be supported. Such new semantics would come from an extension document.
- Reserving (registering) ranges of the token values, as described further below.
- Aided by instruction skipping, also further described below.

Enumeration Token Values. It is easy to extend all the types, storage classes, opcodes, decorations, etc. by adding to the token values.

Registration. Ranges of token values in the [Binary Form](#) section can be pre-allocated to numerous vendors/parties. This allows combining multiple independent extensions without conflict. To register ranges, see <https://www.khronos.org/registry/spir-v/api/spir-v.xml>.

Extended Instructions. Sets of extended instructions can be provided and specified in separate specifications. These help personalize SPIR-V for different source languages or execution environments (client APIs). Multiple sets of extended instructions can be imported without conflict, as the extended instructions are selected by {set id, instruction number} pairs.

Instruction Skipping. Tools are encouraged to skip opcodes for features they are not required to process. This is trivially enabled by the [word count](#) in an instruction, which makes it easier to add new instructions without breaking existing tools.

1.4 Debuggability

SPIR-V can decorate, with a text string, virtually anything created in the shader: types, variables, functions, etc. This is required for externally visible symbols, and also allowed for naming the result of any instruction. This can be used to aid in understandability when disassembling or debugging lowered versions of SPIR-V.

Location information (file names, lines, and columns) can be interleaved with the instruction stream to track the origin of each instruction.

1.5 Design Principles

Regularity. All instructions start with a word count. This allows walking a SPIR-V module without decoding each opcode. All instructions have an opcode that dictates for all operands what kind of operand they are. For instructions with a variable number of operands, the number of variable operands is known by subtracting the number of non-variable words from the instruction's word count.

Non Combinatorial. There is no combinatorial type explosion or need for large encode/decode tables for types. Rather, types are parameterized. Image types declare their dimensionality, arrayness, etc. all orthogonally, which greatly simplify code. This is done similarly for other types. It also applies to opcodes. Operations are orthogonal to scalar/vector size, but not to integer vs. floating-point differences.

Modeless. After a given execution model (e.g., pipeline stage) is specified, internal operation is essentially modeless: Generally, it will follow the rule: "same spelling, same semantics", and does not have mode bits that modify semantics. If a change to SPIR-V modifies semantics, it should use a different spelling. This makes consumers of SPIR-V much more robust. There are execution modes declared, but these are generally to affect the way the module interacts with the environment around it, not the internal semantics. Capabilities are also declared, but this is to declare the subset of functionality that is used, not to change any semantics of what is used.

Declarative. SPIR-V declares externally-visible modes like "writes depth", rather than having rules that require deduction from full shader inspection. It also explicitly declares what addressing modes, execution model, extended instruction sets, etc. will be used. See [Language Capabilities](#) for more information.

SSA. All results of intermediate operations are strictly SSA. However, declared variables reside in memory and use load/store for access, and such variables can be stored to multiple times.

IO. Some storage classes are for input/output (IO) and, fundamentally, IO will be done through load/store of variables declared in these storage classes.

1.6 Static Single Assignment (SSA)

SPIR-V includes a phi instruction to allow the merging together of intermediate results from split control flow. This allows split control flow without load/store to memory. SPIR-V is flexible in the degree to which load/store is used; it is possible to use control flow with no phi-instructions, while still staying in SSA form, by using memory load/store.

Some storage classes are for IO and, fundamentally, IO will be done through load/store, and initial load and final store can never be eliminated. Other storage classes are shader local and can have their load/store eliminated. It can be considered an optimization to largely eliminate such loads/stores by moving them into intermediate results in SSA form.

1.7 Built-In Variables

SPIR-V identifies built-in variables from a high-level language with an enumerant decoration. This assigns any unusual semantics to the variable. Built-in variables must otherwise be declared with their correct SPIR-V type and treated the same as any other variable.

1.8 Specialization

Specialization enables creating a portable SPIR-V module outside the target execution environment, based on constant values that won't be known until inside the execution environment. For example, to size a fixed array with a constant not known during creation of a module, but known when the module will be lowered to the target architecture.

See [Specialization](#) in the next section for more details.

1.9 Example

The SPIR-V form is binary, not human readable, and fully described in [Binary Form](#). This is an example disassembly to give a basic idea of what SPIR-V looks like:

GLSL fragment shader:

```
#version 450

in vec4 color1;
in vec4 multiplier;
noperspective in vec4 color2;
out vec4 color;

struct S {
    bool b;
    vec4 v[5];
    int i;
};

uniform blockName {
    S s;
    bool cond;
};

void main()
{
    vec4 scale = vec4(1.0, 1.0, 2.0, 1.0);

    if (cond)
        color = color1 + s.v[2];
    else
        color = sqrt(color2) * scale;

    for (int i = 0; i < 4; ++i)
        color *= multiplier;
}
```

Corresponding SPIR-V:

```
; Magic:      0x07230203 (SPIR-V)
; Version:    0x00010000 (Version: 1.0.0)
; Generator:  0x00080001 (Khronos Glslang Reference Front End; 1)
; Bound:      63
; Schema:     0

                OpCapability Shader
%1 = OpExtInstImport "GLSL.std.450"
                OpMemoryModel Logical GLSL450
                OpEntryPoint Fragment %4 "main" %31 %33 %42 %57
                OpExecutionMode %4 OriginLowerLeft

; Debug information
                OpSource GLSL 450
                OpName %4 "main"
                OpName %9 "scale"
                OpName %17 "S"
                OpMemberName %17 0 "b"
                OpMemberName %17 1 "v"
                OpMemberName %17 2 "i"
```

```

        OpName %18 "blockName"
        OpMemberName %18 0 "s"
        OpMemberName %18 1 "cond"
        OpName %20 ""
        OpName %31 "color"
        OpName %33 "color1"
        OpName %42 "color2"
        OpName %48 "i"
        OpName %57 "multiplier"

; Annotations (non-debug)
    OpDecorate %15 ArrayStride 16
    OpMemberDecorate %17 0 Offset 0
    OpMemberDecorate %17 1 Offset 16
    OpMemberDecorate %17 2 Offset 96
    OpMemberDecorate %18 0 Offset 0
    OpMemberDecorate %18 1 Offset 112
    OpDecorate %18 Block
    OpDecorate %20 DescriptorSet 0
    OpDecorate %42 NoPerspective

; All types, variables, and constants
    %2 = OpTypeVoid
    %3 = OpTypeFunction %2 ; void ()
    %6 = OpTypeFloat 32 ; 32-bit float
    %7 = OpTypeVector %6 4 ; vec4
    %8 = OpTypePointer Function %7 ; function-local vec4*
    %10 = OpConstant %6 1
    %11 = OpConstant %6 2
    %12 = OpConstantComposite %7 %10 %10 %11 %10 ; vec4(1.0, 1.0, 2.0, 1.0)
    %13 = OpTypeInt 32 0 ; 32-bit int, sign-less
    %14 = OpConstant %13 5
    %15 = OpTypeArray %7 %14
    %16 = OpTypeInt 32 1
    %17 = OpTypeStruct %13 %15 %16
    %18 = OpTypeStruct %17 %13
    %19 = OpTypePointer Uniform %18
    %20 = OpVariable %19 Uniform
    %21 = OpConstant %16 1
    %22 = OpTypePointer Uniform %13
    %25 = OpTypeBool
    %26 = OpConstant %13 0
    %30 = OpTypePointer Output %7
    %31 = OpVariable %30 Output
    %32 = OpTypePointer Input %7
    %33 = OpVariable %32 Input
    %35 = OpConstant %16 0
    %36 = OpConstant %16 2
    %37 = OpTypePointer Uniform %7
    %42 = OpVariable %32 Input
    %47 = OpTypePointer Function %16
    %55 = OpConstant %16 4
    %57 = OpVariable %32 Input

; All functions
    %4 = OpFunction %2 None %3 ; main()
    %5 = OpLabel
    %9 = OpVariable %8 Function
    %48 = OpVariable %47 Function

```

```

    OpStore %9 %12
%23 = OpAccessChain %22 %20 %21          ; location of cond
%24 = OpLoad %13 %23                     ; load 32-bit int from cond
%27 = OpINotEqual %25 %24 %26             ; convert to bool
    OpSelectionMerge %29 None             ; structured if
    OpBranchConditional %27 %28 %41        ; if cond
%28 = OpLabel                             ; then
%34 = OpLoad %7 %33
%38 = OpAccessChain %37 %20 %35 %21 %36    ; s.v[2]
%39 = OpLoad %7 %38
%40 = OpFAdd %7 %34 %39
    OpStore %31 %40
    OpBranch %29
%41 = OpLabel                             ; else
%43 = OpLoad %7 %42
%44 = OpExtInst %7 %1 Sqrt %43            ; extended instruction sqrt
%45 = OpLoad %7 %9
%46 = OpFMul %7 %44 %45
    OpStore %31 %46
    OpBranch %29
%29 = OpLabel                             ; endif
    OpStore %48 %35
    OpBranch %49
%49 = OpLabel
    OpLoopMerge %51 %52 None              ; structured loop
    OpBranch %53
%53 = OpLabel
%54 = OpLoad %16 %48
%56 = OpSLessThan %25 %54 %55             ; i < 4 ?
    OpBranchConditional %56 %50 %51        ; body or break
%50 = OpLabel                             ; body
%58 = OpLoad %7 %57
%59 = OpLoad %7 %31
%60 = OpFMul %7 %59 %58
    OpStore %31 %60
    OpBranch %52
%52 = OpLabel                             ; continue target
%61 = OpLoad %16 %48
%62 = OpIAdd %16 %61 %21                  ; ++i
    OpStore %48 %62
    OpBranch %49                          ; loop back
%51 = OpLabel                             ; loop merge point
    OpReturn
    OpFunctionEnd

```

2 Specification

2.1 Language Capabilities

A SPIR-V module is consumed by an execution environment, specified by a client API, that needs to support the features used by that SPIR-V module. Features are classified through [capabilities](#). Capabilities used by a particular SPIR-V module must be declared early in that module with the [OpCapability](#) instruction. Then:

- A validator can validate that the module uses only its declared capabilities.
- An execution environment is allowed to reject modules declaring capabilities it does not support. (See client API specifications for environment-specific rules.)

All available capabilities and their dependencies form a capability hierarchy, fully listed in the capability section. Only top-level capabilities need to be explicitly declared; their dependencies are implicitly declared.

When an instruction, enumerant, or other feature specifies multiple enabling capabilities, only one such capability needs to be declared to use the feature. This declaration does not itself imply anything about the presence of the other enabling capabilities: The execution environment needs to support only the declared capability.

This (SPIR-V) specification provides capability-specific validation rules, in the [validation section](#). To ensure portability, each client API needs to include the following:

- Which capabilities in the [capability](#) section it requires environments to support, and hence allows in SPIR-V modules.
- Required limits, if they are beyond the [Universal Limits](#).
- Any validation requirements specific to the environment that are not tied to specific capabilities, and hence not covered in the SPIR-V specification.

2.2 Terms

2.2.1 Instructions

Word: 32 bits.

<id>: A numerical name; the name used to refer to an object, a type, a function, a label, etc. An *<id>* always consumes one [word](#). The *<id>*s defined by a module obey [SSA](#).

Result <id>: Most instructions define a result, named by an *<id>* explicitly provided in the instruction. The *Result <id>* is used as an operand in other instructions to refer to the instruction that defined it.

Literal String: A nul-terminated stream of characters consuming an integral number of [words](#). The character set is Unicode in the UTF-8 encoding scheme. The UTF-8 octets (8-bit bytes) are packed four per [word](#), following the little-endian convention (i.e., the first octet is in the lowest-order 8 bits of the word). The final word contains the string's nul-termination character (0), and all contents past the end of the string in the final word are padded with 0.

Literal Number: A numeric value consuming one or more [words](#). An instruction will determine what type a literal will be interpreted as. When the type's bit width is larger than one word, the literal's low-order words appear first. When the type's bit width is less than 32-bits, the literal's value appears in the low-order bits of the word, and the high-order bits must be 0 for a [floating-point type](#), or 0 for an [integer type](#) with *Signedness* of 0, or sign extended when *Signedness* is 1. (Similarly for the remaining bits of widths larger than 32 bits but not a multiple of 32 bits.)

Literal: A *Literal String* or a *Literal Number*.

Operand: A one-[word](#) argument to an instruction. E.g., it could be an *<id>*, or a (part of a) [literal](#). Which form it holds is always explicitly known from the opcode.

Immediate: [Operand\(s\)](#) directly holding a literal value rather than an *<id>*. Immediate values larger than one [word](#) will consume multiple operands, one per word. That is, operand counting is always done per word, not per immediate.

WordCount: The complete number of [words](#) taken by an instruction, including the word holding the word count and opcode, and any optional operands. An instruction's word count is the total space taken by the instruction.

Instruction: After a header, a module is simply a linear list of instructions. An instruction contains a [word count](#), an opcode, an optional [Result <id>](#), an optional [<id>](#) of the instruction's type, and a variable list of operands. All instruction opcodes and semantics are listed in [Instructions](#).

Decoration: Auxiliary information such as built-in variable, stream numbers, invariance, interpolation type, relaxed precision, etc., added to [<id>s](#) or structure-type members through [Decorations](#). Decorations are enumerated in Decoration in the [Binary Form](#) section.

Object: An instantiation of a non-void type, either as the [Result <id>](#) of an operation, or created through [OpVariable](#).

Memory Object: An object created through [OpVariable](#). Such an object can die on function exit, if it was a function variable, or exist for the duration of an entry point.

Intermediate Object or Intermediate Value or Intermediate Result: An object created by an operation (not memory allocated by [OpVariable](#)) and dying on its last consumption.

Constant Instruction: Either a specialization-constant instruction or a fixed constant instruction: Instructions that start "OpConstant" or "OpSpec".

[a, b]: This square-bracket notation means the range from *a* to *b*, inclusive of *a* and *b*. Parenthesis exclude their end point, so, for example, (*a, b*) means *a* to *b* excluding *a* but including *b*.

2.2.2 Types

Boolean type: The type returned by [OpTypeBool](#).

Integer type: Any width signed or unsigned type from [OpTypeInt](#). By convention, the lowest-order bit will be referred to as bit-number 0, and the highest-order bit as bit-number *Width* - 1.

Floating-point type: Any width type from [OpTypeFloat](#).

Numerical type: An [integer](#) type or a [floating-point](#) type.

Scalar: A single instance of a [numerical type](#) or [Boolean type](#). Scalars will also be called *components* when being discussed either by themselves or in the context of the contents of a [vector](#).

Vector: An ordered homogeneous collection of two or more [scalars](#). Vector sizes are quite restrictive and dependent on the execution model.

Matrix: An ordered homogeneous collection of vectors. When vectors are part of a matrix, they will also be called *columns*. Matrix sizes are quite restrictive and dependent on the execution model.

Array: An ordered homogeneous collection of any non-void-type objects. When an object is part of an array, it will also be called an *element*. Array sizes are generally not restricted.

Structure: An ordered heterogeneous collection of any non-void types. When an object is part of a structure, it will also be called a *member*.

Aggregate: A [structure](#) or an [array](#).

Composite: An [aggregate](#), a [matrix](#), or a [vector](#).

Image: A traditional texture or image; SPIR-V has this single name for these. An image type is declared with [OpTypeImage](#). An image does not include any information about how to access, filter, or sample it.

Sampler: Settings that describe how to access, filter, or sample an [image](#). Can come either from literal declarations of settings or be an opaque reference to externally bound settings. A sampler does not include an [image](#).

Sampled Image: An [image](#) combined with a [sampler](#), enabling filtered accesses of the image's contents.

Concrete Type: A [numerical](#) scalar, vector, or matrix type, or [OpTypePointer](#) when using a [Physical addressing model](#), or any aggregate containing only these types.

Abstract Type: An [OpTypeVoid](#) or [OpTypeBool](#), or [OpTypePointer](#) when using the [Logical addressing model](#), or any aggregate type containing any of these.

Opaque Type: A type that is, or contains, or points to, or contains pointers to, any of the following types:

- [OpTypeImage](#)
- [OpTypeSampler](#)
- [OpTypeSampledImage](#)
- [OpTypeOpaque](#)
- [OpTypeEvent](#)
- [OpTypeDeviceEvent](#)
- [OpTypeReserveId](#)
- [OpTypeQueue](#)
- [OpTypePipe](#)
- [OpTypeForwardPointer](#)
- [OpTypePipeStorage](#)
- [OpTypeNamedBarrier](#)

Variable pointer: A pointer that results from one of the following instructions:

- [OpSelect](#)
- [OpPhi](#)
- [OpFunctionCall](#)
- [OpPtrAccessChain](#)
- [OpCopyObject](#)
- [OpLoad](#)
- [OpConstantNull](#)

2.2.3 Module

Module: A single unit of SPIR-V. It can contain multiple [entry points](#), but only one set of [capabilities](#).

Entry Point: A function in a [module](#) where execution begins. A single *entry point* is limited to a single [execution model](#). An entry point is declared using [OpEntryPoint](#).

Execution Model: A graphical-pipeline stage or OpenCL kernel. These are enumerated in [Execution Model](#).

Execution Mode: Modes of operation relating to the interface or execution environment of the module. These are enumerated in [Execution Mode](#). Generally, modes do not change the semantics of instructions within a SPIR-V module.

Vertex Processor: Any stage or execution model that processes vertices: Vertex, tessellation control, tessellation evaluation, and geometry. Explicitly excludes fragment and compute execution models.

2.2.4 Control Flow

Block: A contiguous sequence of instructions starting with an [OpLabel](#), ending with a [termination instruction](#). A *block* has no additional label or termination instructions.

Branch Instruction: One of the following, used as a [termination instruction](#):

- [OpBranch](#)
- [OpBranchConditional](#)
- [OpSwitch](#)
- [OpReturn](#)

- [OpReturnValue](#)

Termination Instruction: One of the following, used to terminate blocks:

- any [branch instruction](#)
- [OpKill](#)
- [OpUnreachable](#)

Dominate: A block *A* dominates a block *B*, where *A* and *B* are in the same function, if every path from the function's entry point to block *B* includes block *A*. *A strictly dominates B* only if *A dominates B* and *A* and *B* are different blocks.

Post Dominate: A block *B* post dominates a block *A*, where *A* and *B* are in the same function, if every path from *A* to a function-return instruction goes through block *B*.

Control-Flow Graph: The graph formed by a function's blocks and branches. The blocks are the graph's nodes, and the branches the graph's edges.

CFG: Control-flow graph.

Back Edge: If a depth-first traversal is done on a function's CFG, starting from the first block of the function, a *back edge* is a branch to a previously visited block. A *back-edge block* is the block containing such a branch.

Merge Instruction: One of the following, used before a branch instruction to declare structured control flow:

- [OpSelectionMerge](#)
- [OpLoopMerge](#)

Header Block: A block containing a [merge instruction](#).

Loop Header: A [header block](#) whose merge instruction is an [OpLoopMerge](#).

Merge Block: A block declared by the *Merge Block* operand of a [merge instruction](#).

Break Block: A block containing a branch to the *Merge Block* of a loop [header's merge instruction](#).

Continue Block: A block containing a branch to an [OpLoopMerge](#) instruction's *Continue Target*.

Return Block: A block containing an [OpReturn](#) or [OpReturnValue](#) branch.

Invocation: A single execution of an entry point in a SPIR-V module, operating only on the amount of data explicitly exposed by the semantics of the instructions. (Any implicit operation on additional instances of data would comprise additional invocations.) For example, in compute execution models, a single invocation operates only on a single work item, or, in a vertex execution model, a single invocation operates only on a single vertex.

Subgroup: Invocations are partitioned into subgroups, where invocations within a subgroup can synchronize and share data with each other efficiently. In compute models, the current workgroup is a superset of the subgroup.

Invocation Group: The complete set of invocations collectively processing a particular compute workgroup or graphical operation, where the scope of a "graphical operation" is implementation dependent, but at least as large as a single point, line, triangle, or patch, and at most as large as a single rendering command, as defined by the client API.

Derivative Group: Defined only for the **Fragment Execution Model**: The set of invocations collectively processing a single point, line, or triangle, including any helper invocations.

Dynamic Instance: Within a single invocation, a single static instruction can be executed multiple times, giving multiple dynamic instances of that instruction. This can happen when the instruction is executed in a loop, or in a function called from multiple call sites, or combinations of multiple of these. Different loop iterations and different dynamic function-call-site chains yield different dynamic instances of such an instruction. Dynamic instances are distinguished by the control-flow path within an invocation, not by which [invocation](#) executed it. That is, different invocations of an entry

point execute the same dynamic instances of an instruction when they follow the same control-flow path, starting from that entry point.

Dynamically Uniform: An `<id>` is dynamically uniform for a [dynamic instance](#) consuming it when its value is the same for all invocations (in the [invocation group](#)) that execute that dynamic instance.

Uniform Control Flow: Uniform control flow (or converged control flow) occurs when all invocations in the [invocation group](#) or [derivative group](#) execute the same control-flow path (and hence the same sequence of [dynamic instances](#) of instructions). Uniform control flow is the initial state at the entry point, and lasts until a conditional branch takes different control paths for different invocations (non-uniform or divergent control flow). Such divergence can reconverge, with all the invocations once again executing the same control-flow path, and this re-establishes the existence of uniform control flow. If control flow is uniform upon entry into a [header block](#), and all invocations leave that dynamic instance of the header block's control-flow construct via the header block's declared merge block, then control flow reconverges to be uniform at that merge block.

2.3 Physical Layout of a SPIR-V Module and Instruction

A SPIR-V module is a single linear stream of [words](#). The first words are shown in the following table:

Table 1: First Words of Physical Layout

Word Number	Contents
0	Magic Number .
1	Version number. The bytes are, high-order to low-order: $0 \mid \text{Major Number} \mid \text{Minor Number} \mid 0$ Hence, version 1.3 is the value 0x00010300.
2	Generator's magic number. It is associated with the tool that generated the module. Its value does not affect any semantics, and is allowed to be 0. Using a non-0 value is encouraged, and can be registered with Khronos at https://www.khronos.org/registry/spir-v/api/spir-v.xml .
3	<i>Bound</i> ; where all <id>s in this module are guaranteed to satisfy $0 < id < Bound$ <i>Bound</i> should be small, smaller is better, with all <id> in a module being densely packed and near 0.
4	0 (Reserved for instruction schema, if needed.)
5	First word of instruction stream, see below.

All remaining words are a linear sequence of instructions.

Each instruction is a stream of [words](#):

Table 2: Instruction Physical Layout

Instruction Word Number	Contents
0	Opcode: The 16 high-order bits are the WordCount of the instruction. The 16 low-order bits are the opcode enumerant.
1	Optional instruction type <id> (presence determined by opcode).
.	Optional instruction Result <id> (presence determined by opcode).
.	Operand 1 (if needed)
.	Operand 2 (if needed)
...	...
WordCount - 1	Operand <i>N</i> (<i>N</i> is determined by WordCount minus the 1 to 3 words used for the opcode, instruction type <id> , and instruction Result <id>).

Instructions are variable length due both to having optional instruction type [<id>](#) and [Result <id>](#) words as well as a variable number of operands. The details for each specific instruction are given in the [Binary Form](#) section.

2.4 Logical Layout of a Module

The instructions of a SPIR-V module must be in the following order. For sections earlier than function definitions, it is invalid to use instructions other than those indicated.

1. All [OpCapability](#) instructions.
2. Optional [OpExtension](#) instructions (extensions to SPIR-V).
3. Optional [OpExtInstImport](#) instructions.
4. The single required [OpMemoryModel](#) instruction.
5. All entry point declarations, using [OpEntryPoint](#).
6. All execution mode declarations, using [OpExecutionMode](#).
7. These [debug](#) instructions, which must be grouped in the following order:
 - a. all [OpString](#), [OpSourceExtension](#), [OpSource](#), and [OpSourceContinued](#), without forward references.
 - b. all [OpName](#) and all [OpMemberName](#)
 - c. all [OpModuleProcessed](#) instructions
8. All [annotation](#) instructions:
 - a. all decoration instructions ([OpDecorate](#), [OpMemberDecorate](#), [OpGroupDecorate](#), [OpGroupMemberDecorate](#), and [OpDecorationGroup](#)).
9. All type declarations ([OpTypeXXX](#) instructions), all [constant instructions](#), and all global variable declarations (all [OpVariable](#) instructions whose [Storage Class](#) is not **Function**). This is the preferred location for [OpUndef](#) instructions, though they can also appear in function bodies. All operands in all these instructions must be declared before being used. Otherwise, they can be in any order. This section is the first section to allow use of [OpLine](#) debug information.
10. All function declarations ("declarations" are functions without a body; there is no forward declaration to a function with a body). A function declaration is as follows.
 - a. Function declaration, using [OpFunction](#).
 - b. Function parameter declarations, using [OpFunctionParameter](#).
 - c. Function end, using [OpFunctionEnd](#).
11. All function definitions (functions with a body). A function definition is as follows.
 - a. Function definition, using [OpFunction](#).
 - b. Function parameter declarations, using [OpFunctionParameter](#).
 - c. Block
 - d. Block
 - e. ...
 - f. Function end, using [OpFunctionEnd](#).

Within a function definition:

- A block always starts with an [OpLabel](#) instruction. This may be immediately preceded by an [OpLine](#) instruction, but the **OpLabel** is considered as the beginning of the block.
- A block always ends with a [termination instruction](#) (see [validation rules](#) for more detail).
- All [OpVariable](#) instructions in a function must have a [Storage Class](#) of **Function**.
- All [OpVariable](#) instructions in a function must be in the first block in the function. These instructions, together with any immediately preceding [OpLine](#) instructions, must be the first instructions in that block. (Note the validation rules prevent [OpPhi](#) instructions in the first block of a function.)

- A function definition (starts with [OpFunction](#)) can be immediately preceded by an [OpLine](#) instruction.

Forward references (an operand *<id>* that appears before the [Result <id>](#) defining it) are allowed for:

- Operands that are an [OpFunction](#). This allows for recursion and early declaration of entry points.
- [Annotation](#)-instruction operands. This is required to fully know everything about a type or variable once it is declared.
- Labels.
- Loops can have forward references to a phi function.
- An [OpTypeForwardPointer](#) has a forward reference to an [OpTypePointer](#).
- An [OpTypeStruct](#) operand that's a forward reference to the *Pointer Type* operand to an [OpTypeForwardPointer](#).
- The list of *<id>* provided in the [OpEntryPoint](#) instruction.

In all cases, there is enough type information to enable a single simple pass through a module to transform it. For example, function calls have all the type information in the call, phi-functions don't change type, and labels don't have type. The pointer forward reference allows structures to contain pointers to themselves or to be mutually recursive (through pointers), without needing additional type information.

The [Validation Rules](#) section lists additional rules that must be satisfied.

2.5 Instructions

Most instructions create a [Result <id>](#), as provided in the *Result <id>* field of the instruction. These *Result <id>*s are then referred to by other instructions through their *<id>* operands. All instruction operands are specified in the [Binary Form](#) section.

Instructions are explicit about whether they require [immediates](#), rather than an *<id>* referring to some other result. This is strictly known just from the opcode.

- An immediate 32-bit (or smaller) integer is always one operand directly holding a 32-bit two's-complement value.
- An immediate 32-bit float is always one operand, directly holding a 32-bit IEEE 754 floating-point representation.
- An immediate 64-bit float is always two operands, directly holding a 64-bit IEEE 754 representation. The low-order 32 bits appear in the first operand.

2.5.1 SSA Form

A module is always in static single assignment (SSA) form. That is, there is always exactly one instruction resulting in any particular [Result <id>](#). Storing into variables declared in memory is not subject to this; such stores do not create *Result <id>*s. Accessing declared variables is done through:

- [OpVariable](#) to allocate an object in memory and create a *Result <id>* that is the name of a pointer to it.
- [OpAccessChain](#) or [OpInBoundsAccessChain](#) to create a pointer to a subpart of a [composite](#) object in memory.
- [OpLoad](#) through a pointer, giving the loaded object a *Result <id>* that can then be used as an operand in other instructions.
- [OpStore](#) through a pointer, to write a value. There is no *Result <id>* for an [OpStore](#).

[OpLoad](#) and [OpStore](#) instructions can often be eliminated, using [intermediate](#) results instead. When this happens in multiple control-flow paths, these values need to be merged again at the path's merge point. Use [OpPhi](#) to merge such values together.

2.6 Entry Point and Execution Model

The [OpEntryPoint](#) instruction identifies an [entry point](#) with two key things: an execution model and a function definition. Execution models include **Vertex**, **GLCompute**, etc. (one for each graphical stage), as well as **Kernel** for OpenCL kernels. For the complete list, see [Execution Model](#). An [OpEntryPoint](#) also supplies a name that can be used externally to identify the entry point, and a declaration of all the **Input** and **Output** variables that form its input/output interface.

The static function call graphs rooted at two entry points are allowed to overlap, so that function definitions and global variable definitions can be shared. The execution model and any execution modes associated with an entry point apply to the entire static function call graph rooted at that entry point. This rule implies that a function appearing in both call graphs of two distinct entry points may behave differently in each case. Similarly, variables whose semantics depend on properties of an entry point, e.g. those using the [Input Storage Class](#), may behave differently when used in call graphs rooted in two different entry points.

2.7 Execution Modes

Information like the following is declared with [OpExecutionMode](#) instructions. For example,

- number of invocations (**Invocations**)
- vertex-order CCW (**VertexOrderCcw**)
- triangle strip generation (**OutputTriangleStrip**)
- number of output vertices (**OutputVertices**)
- etc.

For a complete list, see [Execution Mode](#).

2.8 Types and Variables

Types are built up hierarchically, using [OpTypeXXX](#) instructions. The [Result <id>](#) of an [OpTypeXXX](#) instruction becomes a type [<id>](#) for future use where type [<id>](#)s are needed (therefore, [OpTypeXXX](#) instructions do not have a type [<id>](#), like most other instructions do).

The "leaves" to start building with are types like [OpTypeFloat](#), [OpTypeInt](#), [OpTypeImage](#), [OpTypeEvent](#), etc. Other types are built up from the [Result <id>](#) of these. The numerical types are parameterized to specify bit width and signed vs. unsigned.

Higher-level types are then constructed using opcodes like [OpTypeVector](#), [OpTypeMatrix](#), [OpTypeImage](#), [OpTypeArray](#), [OpTypeRuntimeArray](#), [OpTypeStruct](#), and [OpTypePointer](#). These are parameterized by number of components, array size, member lists, etc. The image types are parameterized by the return type, dimensionality, arrayness, etc. To do sampling or filtering operations, a type from [OpTypeSampledImage](#) is used that contains both an [image](#) and a [sampler](#). Such a [sampled image](#) can be set directly by the API, or combined in a SPIR-V module from an independent image and an independent sampler.

Types are built bottom up: A parameterizing operand in a type must be defined before being used.

Some additional information about the type of an [<id>](#) can be provided using the decoration instructions ([OpDecorate](#), [OpMemberDecorate](#), [OpGroupDecorate](#), [OpGroupMemberDecorate](#), and [OpDecorationGroup](#)). These can add, for example, **Invariant** to an [<id>](#) created by another instruction. See the full list of [Decorations](#) in the [Binary Form](#) section.

Two different type [<id>](#)s form, by definition, two different types. It is valid to declare multiple [aggregate](#) type [<id>](#)s having the same opcode and operands. This is to allow multiple instances of aggregate types with the same structure to be [decorated](#) differently. (Different decorations are not required; two different aggregate type [<id>](#)s are allowed to have identical declarations and decorations, and will still be two different types.) Pointer types are also allowed to have multiple [<id>](#)s for the same opcode and operands, to allow for differing decorations (e.g., **Volatile**) or different decoration values

(e.g., different *Array Stride* values for the **ArrayStride**). When new pointers are formed, their types must be decorated as needed, so the consumer knows how to generate an access through the pointer. Non-aggregate non-pointer types are different: It is invalid to declare multiple type *<id>s* for the same scalar, vector, or matrix type. That is, non-aggregate non-pointer type declarations must all have different opcodes or operands. (Note that non-aggregate non-pointer types cannot be decorated in ways that affect their type.)

Variables are declared to be of an already built type, and placed in a Storage Class. Storage classes include **UniformConstant**, **Input**, **Workgroup**, etc. and are fully specified in [Storage Class](#). Variables declared with the **Function** Storage Class can have their lifetime's specified within their function using the [OpLifetimeStart](#) and [OpLifetimeStop](#) instructions.

Intermediate results are typed by the instruction's type *<id>*, which must validate with respect to the operation being done.

Built-in variables needing special driver handling (having unique semantics) are declared using [OpDecorate](#) or [OpMemberDecorate](#) with the **BuiltIn Decoration**, followed by a **BuiltIn** enumerant. This decoration is applied to a variable or a structure-type member.

2.9 Function Calling

To call a function defined in the current module or a function declared to be imported from another module, use [OpFunctionCall](#) with an operand that is the *<id>* of the [OpFunction](#) to call, and the *<id>s* of the arguments to pass. All arguments are passed by value into the called function. This includes pointers, through which a callee object could be modified.

2.10 Extended Instruction Sets

Many operations and/or built-in function calls from high-level languages are represented through *extended instruction sets*. Extended instruction sets will include things like

- trigonometric functions: `sin()`, `cos()`, ...
- exponentiation functions: `exp()`, `pow()`, ...
- geometry functions: `reflect()`, `smoothstep()`, ...
- functions having rich performance/accuracy trade-offs
- etc.

Non-extended instructions, those that are core SPIR-V instructions, are listed in the [Binary Form](#) section. Native operations include:

- Basic arithmetic: `+`, `-`, `*`, `min()`, scalar * vector, etc.
- Texturing, to help with back-end decoding and support special code-motion rules.
- Derivatives, due to special code-motion rules.

Extended instruction sets are specified in independent specifications. They can be referenced (but not specified) in this specification. The separate extended instruction set specification will specify instruction opcodes, semantics, and instruction names.

To use an extended instruction set, first import it by name string using [OpExtInstImport](#) and giving it a **Result <id>**:

```
<extinst-id> OpExtInstImport "name-of-extended-instruction-set"
```

The "name-of-extended-instruction-set" is a literal string. The standard convention for this string is

```
"<source language name>.<package name>.<version>"
```


For example "GLSL.std.450" could be the name of the core built-in functions for GLSL versions 450 and earlier.

Note

There is nothing precluding having two "mirror" sets of instructions with different names but the same opcode values, which could, for example, let modifying just the import statement to change a performance/accuracy trade off.

Then, to call a specific extended instruction, use `OpExtInst`:

```
OpExtInst <extinst-id> instruction-number operand0, operand1, ...
```

Extended instruction-set specifications will provide semantics for each "instruction-number". It is up to the specific specification what the overloading rules are on operand type. The specification must be clear on its semantics, and producers/consumers of it must follow those semantics.

By convention, it is recommended that all external specifications include an **enum** `{...}` listing all the "instruction-numbers", and a mapping between these numbers and a string representing the instruction name. However, there are no requirements that instruction name strings are provided or mangled.

Note

Producing and consuming extended instructions can be done entirely through numbers (no string parsing). An extended instruction set specification provides opcode enumerant values for the instructions, and these will be produced by the front end and consumed by the back end.

2.11 Structured Control Flow

SPIR-V can explicitly declare structured control-flow *constructs* using [merge instructions](#). These explicitly declare a [header block](#) before the control flow diverges and a [merge block](#) where control flow subsequently converges. These blocks delimit constructs that must nest, and can only be entered and exited in structured ways, as per the following.

Structured control-flow declarations must satisfy the following rules:

- the [merge block](#) declared by a [header block](#) cannot be a merge block declared by any other header block
- each [header block](#) must **strictly dominate** its [merge block](#), unless the merge block is unreachable in the CFG
- all CFG [back edges](#) must branch to a [loop header](#), with each [loop header](#) having exactly one back edge branching to it
- for a given loop header, its [OpLoopMerge Continue Target](#), and corresponding back-edge block:
 - the *loop header* must dominate the *Continue Target*, unless the *Continue Target* is unreachable in the CFG
 - the *Continue Target* must dominate the back-edge block
 - the back-edge block must post dominate the *Continue Target*

A structured control-flow *construct* is then defined as one of:

- a *selection construct*: the set of blocks dominated by a selection header, minus the set of blocks dominated by the header's merge block
- a *continue construct*: the set of blocks dominated by an [OpLoopMerge's Continue Target](#) and post dominated by the corresponding back-edge block
- a *loop construct*: the set of blocks dominated by a [loop header](#), minus the set of blocks dominated by the loop's merge block, minus the loop's corresponding *continue construct*
- a *case construct*: the set of blocks dominated by an [OpSwitch Target](#) or *Default*, minus the set of blocks dominated by the [OpSwitch's](#) merge block (this construct is only defined for those [OpSwitch Target](#) or *Default* that are not equal to the [OpSwitch's](#) corresponding merge block)

The above structured control-flow constructs must satisfy the following rules:

- if a construct contains another header block, then it also contains that header's corresponding merge block
- the only blocks in a construct that can branch outside the construct are
 - a block branching to the construct's merge block
 - a block branching from one *case construct* to another, for the same **OpSwitch**
 - a [continue block](#) for the innermost loop it is nested inside of
 - a [break block](#) for the innermost loop it is nested inside of
 - a [return block](#)
- additionally for switches:
 - an **OpSwitch** block dominates all its defined *case constructs*
 - each *case construct* has at most one branch to another *case construct*
 - each *case construct* is branched to by at most one other *case construct*
 - if *Target T1* branches to *Target T2*, or if *Target T1* branches to the *Default* and the *Default* branches to *Target T2*, then *T1* must immediately precede *T2* in the list of the [OpSwitch Target](#) operands

2.12 Specialization

Specialization is intended for constant objects that will not have known constant values until after initial generation of a SPIR-V module. Such objects are called *specialization constants*.

A SPIR-V module containing specialization constants can consume one or more externally provided *specializations*: A set of final constant values for some subset of the module's *specialization constants*. Applying these final constant values yields a new module having fewer remaining specialization constants. A module also contains default values for any specialization constants that never get externally specialized.

Note

No optimizing transforms are required to make a *specialized* module functionally correct. The specializing transform is straightforward and explicitly defined below.

Note

Ad hoc specializing should not be done through constants ([OpConstant](#) or [OpConstantComposite](#)) that get overwritten: A SPIR-V → SPIR-V transform might want to do something irreversible with the value of such a constant, unconstrained from the possibility that its value could be later changed.

Within a module, a *Specialization Constant* is declared with one of these instructions:

- [OpSpecConstantTrue](#)
- [OpSpecConstantFalse](#)
- [OpSpecConstant](#)
- [OpSpecConstantComposite](#)
- [OpSpecConstantOp](#)

The literal operands to [OpSpecConstant](#) are the default numerical specialization constants. Similarly, the "True" and "False" parts of [OpSpecConstantTrue](#) and [OpSpecConstantFalse](#) provide the default Boolean specialization constants. These default values make an external specialization optional. However, such a default constant is applied only after all external specializations are complete, and none contained a specialization for it.

An external specialization is provided as a logical list of pairs. Each pair is a [SpecId Decoration](#) of a scalar specialization instruction along with its specialization constant. The numeric values are exactly what the operands would be to a corresponding [OpConstant](#) instruction. Boolean values are true if non-zero and false if zero.

Specializing a module is straightforward. The following specialization-constant instructions can be updated with specialization constants, and replaced in place, leaving everything else in the module exactly the same:

```
OpSpecConstantTrue  -> OpConstantTrue  or OpConstantFalse
OpSpecConstantFalse -> OpConstantTrue  or OpConstantFalse
OpSpecConstant      -> OpConstant
OpSpecConstantComposite -> OpConstantComposite
```

The [OpSpecConstantOp](#) instruction is specialized by executing the operation and replacing the instruction with the result. The result can be expressed in terms of a [constant instruction](#) that is not a specialization-constant instruction. (Note, however, this resulting instruction might not have the same size as the original instruction, so is not a "replaced in place" operation.)

When applying an external specialization, the following (and only the following) must be modified to be non-specialization-constant instructions:

- specialization-constant instructions with values provided by the specialization
- specialization-constant instructions that consume nothing but non-specialization constant instructions (including those that the partial specialization transformed from specialization-constant instructions; these are in order, so it is a single pass to do so)

A full specialization can also be done, when requested or required, in which all specialization-constant instructions will be modified to non-specialization-constant instructions, using the default values where required.

2.13 Linkage

The ability to have partially linked modules and libraries is provided as part of the [Linkage](#) capability.

By default, functions and global variables are private to a module and cannot be accessed by other modules. However, a module may be written to *export* or *import* functions and global (module scope) variables. Imported functions and global variable definitions are resolved at linkage time. A module is considered to be partially linked if it depends on imported values.

Within a module, imported or exported values are decorated using the [Linkage Attributes Decoration](#). This decoration assigns the following linkage attributes to decorated values:

- A [Linkage Type](#).
- A *name*, which is a [Literal String](#), and is used to uniquely identify exported values.

Note

When resolving imported functions, the [Function Control](#) and all [Function Parameter Attributes](#) are taken from the function definition, and not from the function declaration.

2.14 Relaxed Precision

The **RelaxedPrecision Decoration** allows 32-bit integer and 32-bit floating-point operations to execute with a relaxed precision of somewhere between 16 and 32 bits.

For a floating-point operation, operating at relaxed precision means that the minimum requirements for range and precision are as follows:

- the floating point range may be as small as $(-2^{14}, 2^{14})$
- the floating point magnitude range may be as small as $(2^{-14}, 2^{14})$
- the relative floating point precision may be as small as 2^{-10}

Relative floating-point precision is defined as the worst case (i.e. largest) ratio of the smallest step in relation to the value for all non-zero values:

$$\text{Precision}_{\text{relative}} = (\text{abs}(v_1 - v_2)_{\min} / \text{abs}(v_1))_{\max} \text{ for } v_1 \neq 0, v_2 \neq 0, v_1 \neq v_2$$

For integer operations, operating at relaxed precision means that the operation will be evaluated by an operation in which, for some N , $16 \leq N \leq 32$:

- the operation is executed as though its type were N bits in size, and
- the result is zero or sign extended to 32 bits as determined by the signedness of the result type of the operation.

The **RelaxedPrecision Decoration** can be applied to:

- The **<id>** of a variable, where the variable's type is a scalar, vector, or matrix, or an array of scalar, vector, or matrix. In all cases, the components in the type must be a 32-bit **numerical** type.
- The **Result <id>** of an instruction that operates on numerical types, meaning the instruction is to operate at relaxed precision.
- The **Result <id>** of an instruction that reads or filters from an image. E.g. **OpImageSampleExplicitLod**, meaning the instruction is to operate at relaxed precision.
- The **Result <id>** of an **OpFunction** meaning the function's returned result is at relaxed precision. It cannot be applied to **OpTypeFunction** or to an **OpFunction** whose return type is **OpTypeVoid**.
- A structure-type member (through **OpMemberDecorate**).

When applied to a variable or structure member, all loads and stores from the decorated object may be treated as though they were **decorated** with **RelaxedPrecision**. Loads may also be decorated with **RelaxedPrecision**, in which case they are treated as operating at relaxed precision.

All loads and stores involving relaxed precision still read and write 32 bits of data, respectively. Floating-point data read or written in such a manner is written in full 32-bit floating-point format. However, a load or store might reduce the precision (as allowed by **RelaxedPrecision**) of the destination value.

For debugging portability of floating-point operations, **OpQuantizeToF16** may be used to explicitly reduce the precision of a relaxed-precision result to 16-bit precision. (Integer-result precision can be reduced, for example, using left- and right-shift opcodes.)

For image-sampling operations, decorations can appear on both the sampling instruction and the image variable being sampled. If either is decorated, they both should be decorated, and when both are decorated their decorations must match. If only one is decorated, the sampling instruction can behave either as if both were decorated or neither were decorated.

2.15 Debug Information

Debug information is supplied with:

- Source-code text through [OpString](#), [OpSource](#), and [OpSourceContinued](#).
- Object names through [OpName](#) and [OpMemberName](#).
- Line numbers through [OpLine](#).

A module will not lose any semantics when all such instructions are removed.

2.15.1 Function-Name Mangling

There is no functional dependency on how functions are named. Signature-typing information is explicitly provided, without any need for name "unmangling". (Valid modules can be created without inclusion of mangled names.)

By convention, for debugging purposes, modules with [OpSource](#) *Source Language* of OpenCL use the Itanium name-mangling standard.

2.16 Validation Rules

2.16.1 Universal Validation Rules

All modules must obey the following, or it is an invalid module:

- The stream of instructions must be ordered as described in the [Logical Layout](#) section.
- Any use of a feature described by a capability in the [capability](#) section requires that capability to be declared, either directly, or as a "depends on" capability on a capability that is declared.
- Non-structure types (scalars, vectors, arrays, etc.) with the same operand parameterization cannot be type aliases. For non-structures, two type *<id>s* match if-and-only-if the types match.
- If the [Logical addressing model](#) is selected and the **VariablePointers** [capability](#) is not declared:
 - [OpVariable](#) cannot allocate an object whose type is a pointer type (that is, it cannot create an object in memory that is itself a pointer and whose result would thus be a pointer to a pointer)
 - A pointer can only be an operand to the following instructions:
 - * [OpLoad](#)
 - * [OpStore](#)
 - * [OpAccessChain](#)
 - * [OpInBoundsAccessChain](#)
 - * [OpFunctionCall](#)
 - * [OpImageTexelPointer](#)
 - * [OpCopyMemory](#)
 - * [OpCopyObject](#)
 - * all [OpAtomic](#) instructions
 - * extended instruction-set instructions that are explicitly identified as taking pointer operands
 - A pointer can be the [Result <id>](#) of only the following instructions:
 - * [OpVariable](#)
 - * [OpAccessChain](#)
 - * [OpInBoundsAccessChain](#)
 - * [OpFunctionParameter](#)
 - * [OpImageTexelPointer](#)

- * **OpCopyObject**
- All indexes in **OpAccessChain** and **OpInBoundsAccessChain** that are **OpConstant** with type of **OpTypeInt** with a *signedness* of 1 must not have their sign bit set.
- If the **Logical addressing model** is selected and the **VariablePointers** or **VariablePointersStorageBuffer** capability is declared (in addition to what is allowed above by the **Logical** addressing model):
 - **OpVariable** can allocate an object whose type is a pointer type, if the *Storage Class* of the **OpVariable** is one of the following:
 - * **Function**
 - * **Private**
 - A pointer can be the *Object* operand of **OpStore** or result of **OpLoad**, if the storage class the pointer is stored to or loaded from is one of the following:
 - * **Function**
 - * **Private**
 - A pointer type can be the:
 - * *Result Type* of **OpFunction**
 - * *Result Type* of **OpFunctionCall**
 - * *Return Type* of **OpTypeFunction**
 - A pointer can be a **variable pointer** or an operand to **OpPtrAccessChain**.
 - If the **VariablePointers** capability is declared, A **variable pointer** can be the *Pointer* operand of **OpStore** or **OpLoad**, or result of **OpConstantNull**, if it points to one of the following storage classes:
 - * **StorageBuffer**
 - * **Workgroup**
 - If the **VariablePointers** capability is not declared, A **variable pointer** can be the *Pointer* operand of **OpStore** or **OpLoad** only if:
 - * it points into the **StorageBuffer** storage classes
 - * it is selected from pointers pointing into the same structure, or is **OpConstantNull**
- A **variable pointer** with the **Logical** addressing model cannot
 - be an operand to an **OpArrayLength** instruction
 - point to an object that is or contains any **OpTypeMatrix** types
- SSA
 - Each **<id>** must appear exactly once as the **Result <id>** of an instruction.
 - The definition of an SSA **<id>** should dominate all uses of it, with the following exceptions:
 - * Function calls may call functions not yet defined. However, note that the function's argument and return types will already be known at the call site.
 - * Uses in a phi-function in a loop may consume definitions in the loop that don't dominate the use.
- Entry point and execution model
 - There is at least one **OpEntryPoint** instruction, unless the **Linkage** capability is being used.
 - No function can be targeted by both an **OpEntryPoint** instruction and an **OpFunctionCall** instruction.
- Functions
 - A function declaration (an **OpFunction** with no basic blocks), must have a **Linkage Attributes Decoration** with the **Import Linkage Type**.
 - A function definition (an **OpFunction** with basic blocks) cannot be **decorated** with the **Import Linkage Type**.

- A function cannot have both a declaration and a definition (no forward declarations).
- Global (Module Scope) Variables
 - It is illegal to initialize an imported variable. This means that a module-scope **OpVariable** with initialization value cannot be marked with the **Import Linkage Type**.
- Control-Flow Graph (CFG)
 - Blocks exist only within a function.
 - The first block in a function definition is the entry point of that function and cannot be the target of any branch. (Note this means it will have no **OpPhi** instructions.)
 - The order of blocks in a function must satisfy the rule that blocks appear before all blocks they dominate.
 - Each block starts with a label.
 - * A label is made by **OpLabel**.
 - * This includes the first block of a function (**OpFunction** is not a label).
 - * Labels are used only to form blocks.
 - The last instruction of each block is a **termination instruction**.
 - **Termination instructions** can only appear as the last instruction in a block.
 - **OpLabel** instructions can only appear within a function.
 - All **branches** within a function must be to labels in that function.
- All **OpFunctionCall** *Function* operands are an **<id>** of an **OpFunction** in the same module.
- Data rules
 - Scalar floating-point types can be parameterized only as 32 bit, plus any additional sizes enabled by **capabilities**.
 - Scalar integer types can be parameterized only as 32 bit, plus any additional sizes enabled by **capabilities**.
 - Vector types can only be parameterized with numerical types or the **OpTypeBool** type.
 - Vector types for can only be parameterized as having 2, 3, or 4 components, plus any additional sizes enabled by **capabilities**.
 - Matrix types can only be parameterized with floating-point types.
 - Matrix types can only be parameterized as having only 2, 3, or 4 columns.
 - Specialization constants (see **Specialization**) are limited to integers, Booleans, floating-point numbers, and vectors of these.
 - Forward reference operands in an **OpTypeStruct**
 - * must be later declared with **OpTypePointer**
 - * the type pointed to must be an **OpTypeStruct**
 - * had an earlier **OpTypeForwardPointer** forward reference to the same **<id>**
 - All **OpSampledImage** instructions must be in the same block in which their *Result <id>* are consumed. *Result <id>* from **OpSampledImage** instructions must not appear as operands to **OpPhi** instructions or **OpSelect** instructions, or any instructions other than the image lookup and query instructions specified to take an operand whose type is **OpTypeSampledImage**.
 - Instructions for extracting a scalar image or scalar sampler out of a composite must only use **dynamically-uniform** indexes. They must be in the same block in which their *Result <id>* are consumed. Such *Result <id>* must not appear as operands to **OpPhi** instructions or **OpSelect** instructions, or any instructions other than the image instructions specified to operate on them.
- Decoration rules
 - The **Aliased Decoration** can only be applied to **intermediate** objects that are pointers to non-void types.
 - The **Linkage Attributes Decoration** cannot be applied to functions targeted by an **OpEntryPoint** instruction.
 - A **BuiltIn Decoration** can only be applied as follows:

- * When applied to a structure-type member, all members of that structure type must also be **decorated** with **BuiltIn**. (No allowed mixing of built-in variables and non-built-in variables within a single structure.)
 - * When applied to a structure-type member, that structure type cannot be contained as a member of another structure type.
 - * There is at most one object per Storage Class that can contain a structure type containing members **decorated** with **BuiltIn**, consumed per entry-point.
- **OpLoad** and **OpStore** can only consume objects whose type is a pointer.
 - A **Result <id>** resulting from an instruction within a function can only be used in that function.
 - A function call must have the same number of arguments as the function definition (or declaration) has parameters, and their respective types must match.
 - An instruction requiring a specific number of operands must have that many operands. The **word count** must agree.
 - Each opcode specifies its own requirements for number and type of operands, and these must be followed.
 - Atomic access rules
 - The pointers taken by atomic operation instructions must be a pointer into one of the following **Storage Classes**:
 - * **Uniform** when used with the **BufferBlock Decoration**
 - * **StorageBuffer**
 - * **Workgroup**
 - * **CrossWorkgroup**
 - * **Generic**
 - * **AtomicCounter**
 - * **Image**
 - It is invalid to have a construct that uses the **StorageBuffer Storage Class** and a construct that uses the **Uniform Storage Class** with the **BufferBlock Decoration** in the same SPIR-V module.
 - The **FPRoundingMode decoration** can be applied only to a width-only conversion instruction that is used as the *Object* operand of an **OpStore** storing through a pointer to a 16-bit floating-point object in the **Uniform, PushConstant, Input, or Output Storage Classes**.

2.16.2 Validation Rules for Shader **Capabilities**

- CFG:
 - Loops must be structured, having an **OpLoopMerge** instruction in their header.
 - Selections must be structured, having an **OpSelectionMerge** instruction in their header.
- Entry point and execution model
 - Each **entry point** in a module, along with its corresponding static call tree within that module, forms a complete pipeline stage.
 - Each **OpEntryPoint** with the **Fragment Execution Model** must have an **OpExecutionMode** for either the **OriginLowerLeft** or the **OriginUpperLeft Execution Mode**. (Exactly one of these is required.)
 - An **OpEntryPoint** with the **Fragment Execution Model** can set at most one of the **DepthGreater, DepthLess, or DepthUnchanged Execution Modes**.
 - An **OpEntryPoint** with one of the **Tessellation Execution Modes** can set at most one of the **SpacingEqual, FractionalEven, or FractionalOdd Execution Modes**.
 - An **OpEntryPoint** with one of the **Tessellation Execution Models** can set at most one of the **Triangles, Quads, or Isolines Execution Modes**.
 - An **OpEntryPoint** with one of the **Tessellation Execution Models** can set at most one of the **VertexOrderCw or VertexOrderCcw Execution Modes**.

- An **OpEntryPoint** with the **Geometry Execution Model** must set exactly one of the **InputPoints**, **InputLines**, **InputLinesAdjacency**, **Triangles**, or **TrianglesAdjacency Execution Modes**.
- An **OpEntryPoint** with the **Geometry Execution Model** must set exactly one of the **OutputPoints**, **OutputLineStrip**, or **OutputTriangleStrip Execution Modes**.
- **Composite** objects in the **StorageBuffer**, **UniformConstant**, **Uniform**, and **PushConstant Storage Classes** must be explicitly laid out. The following apply to all the aggregate and matrix types describing such an object, recursively through their nested types:
 - Each structure-type member must have an **Offset Decoration**.
 - Each array type must have an **ArrayStride Decoration**.
 - Each structure-type member that is a matrix or array-of-matrices must have be **decorated** with
 - * a **MatrixStride Decoration**, and
 - * one of the **RowMajor** or **ColMajor Decorations**.
 - The **ArrayStride**, **MatrixStride**, and **Offset Decorations** must be large enough to hold the size of the objects they affect (that is, specifying overlap is invalid). Each **ArrayStride** and **MatrixStride** must be greater than zero, and no two members of a given structure can be assigned to the same **Offset**.
 - Each **OpPtrAccessChain** must have a *Base* whose type is **decorated** with **ArrayStride**.
 - When an array-element pointer is derived from an array (e.g., using **OpAccessChain**), and the resulting element-pointer type was **decorated** with **ArrayStride**, its *Array Stride* must match the *Array Stride* of the originating array's type.
- For **structure** objects in the **Input** and **Output Storage Classes**, the following apply:
 - When applied to structure-type members, the **Decorations Noperspective**, **Flat**, **Patch**, **Centroid**, and **Sample** can only be applied to the top-level members of the structure type. (Nested objects' types cannot be structures whose members are decorated with these decorations.)
- Decorations
 - At most one of **Noperspective** or **Flat Decorations** can be applied to the same object or member.
 - At most one of **Patch**, **Centroid**, or **Sample Decorations** can be applied to the same object or member.
 - At most one of **RowMajor** and **ColMajor Decorations** can be applied to a structure type.
 - At most one of **Block** and **BufferBlock Decorations** can be applied to a structure type.
- All *<id>* used for **Scope** and **Memory Semantics** must be of an **OpConstant**.

2.16.3 Validation Rules for Kernel **Capabilities**

- The *Signedness* in **OpTypeInt** must always be 0.

2.17 Universal Limits

These quantities are minimum limits for all implementations and validators. Implementations are allowed to support larger quantities. Specific APIs may impose larger minimums. See [Language Capabilities](#).

Validators must either

- inform when these limits are crossed, or
- be explicitly parameterized with larger limits.

Table 3: Limits

Limited Entity	Minimum Limit	
	Decimal	Hexadecimal
Characters in a literal string	65,535	FFFF
Instruction word count	65,535	FFFF
Result <i><id></i> bound	4,194,303	3FFFFFF
See Physical Layout for the shader-specific bound.		
Control-flow nesting depth		
Measured per function, in program order, counting the maximum number of OpBranch , OpBranchConditional , or OpSwitch that are seen without yet seeing their corresponding <i>Merge Block</i> , as declared by OpSelectionMerge or OpLoopMerge .	1023	3FF
Global variables (Storage Class other than Function)	65,535	FFFF
Local variables (Function Storage Class)	524,287	7FFFFFF
Decorations per target <i><id></i>	Number of entries in the Decoration table.	
Execution modes per entry point	255	FF
Indexes for OpAccessChain , OpInBoundsAccessChain , OpPtrAccessChain , OpInBoundsPtrAccessChain , OpCompositeExtract , and OpCompositeInsert	255	FF
Number of function parameters, per function declaration	255	FF
OpFunctionCall actual arguments	255	FF
OpExtInst actual arguments	255	FF
OpSwitch (literal, label) pairs	16,383	3FFF
OpTypeStruct members	16,383	3FFF
Structure nesting depth	255	FF

2.18 Memory Model

A memory model is chosen using a single [OpMemoryModel](#) instruction near the beginning of the module. This selects both an addressing model and a memory model.

The **Logical** [addressing model](#) means pointers are abstract, having no physical size or numeric value. In this mode, pointers can only be created from existing objects, and they cannot be stored into an object, unless additional [capabilities](#), e.g., **VariablePointers**, are declared to add such functionality.

The non-**Logical addressing models** allow physical pointers to be formed. **OpVariable** can be used to create objects that hold pointers. These are declared for a specific **Storage Class**. Pointers for one Storage Class cannot be used to access objects in another Storage Class. However, they can be converted with conversion opcodes. Any particular addressing model must describe the bit width of pointers for each of the storage classes.

2.18.1 Memory Layout

When memory is shared between a SPIR-V module and an API, its contents are transparent, and must be agreed on. For example, the **Offset**, **MatrixStride**, and **ArrayStride Decorations** applied to members of a struct object can partially define how the memory is laid out. In addition, the following are always true, applied recursively as needed, of the offsets within the memory buffer:

- a vector consumes contiguous memory with lower-numbered components appearing in smaller offsets than higher-numbered components, and with component 0 starting at the vector's **Offset Decoration**, if present
- in an array, lower-numbered elements appear at smaller offsets than higher-numbered elements, with element 0 starting at the **Offset Decoration** for the array, if present
- a structure has lower-numbered members appearing at smaller offsets than higher-numbered members, with member 0 starting at the **Offset Decoration** for the structure, if present
- in a matrix, lower-numbered columns appear at smaller offsets than higher-numbered columns, and lower-numbered components within the matrix's vectors appearing at smaller offsets than high-numbered components, with component 0 of column 0 starting at the **Offset Decoration**, if present (the **RowMajor** and **ColMajor Decorations** dictate what is contiguous)

2.18.2 Aliasing

Here, *aliasing* means one of:

- Two or more pointers that point into overlapping parts of the same underlying object. That is, two **intermediates**, both of which are typed pointers, that can be dereferenced (in bounds) such that both dereferences access the same memory.
- Images, buffers, or other externally allocated objects where a function might access the same underlying memory via accesses to two different objects.

How aliasing is managed depends on the **Memory Model**:

- The simple and GLSL memory models can assume that aliasing is generally not present. Specifically, the compiler is free to compile as if aliasing is not present, unless a pointer is explicitly indicated to be an alias. This is indicated by applying the **Aliased Decoration** to an *intermediate* object's *<id>*. Applying **Restrict** is allowed, but has no effect.
- The OpenCL memory models must assume that aliasing is generally present. Specifically, the compiler must compile as if aliasing is present, unless a pointer is explicitly indicated to not alias. This is done by applying the **Restrict Decoration** to an *intermediate* object's *<id>*. Applying **Aliased** is allowed, but has no effect.

It is invalid to apply both **Restrict** and **Aliased** to the same *<id>*.

2.18.3 Null pointers

A "null pointer" can be formed from an **OpConstantNull** instruction with a pointer result type. The resulting pointer value is abstract, and will not equal the pointer value formed from any declared object or access chain into a declared object. Behavior is undefined when loading or storing through an **OpConstantNull** value.

2.19 Derivatives

Derivatives appear only in the **Fragment Execution Model**. They can be implicit or explicit. Some [image instructions](#) consume implicit derivatives, while the [derivative instructions](#) compute explicit derivatives. In all cases, derivatives are well defined only if the [derivative group](#) has [uniform control flow](#).

2.20 Code Motion

Texturing instructions in the **Fragment Execution Model** that rely on an implicit derivative cannot be moved into control flow that is not known to be [uniform control flow](#) within each [derivative group](#).

2.21 Deprecation

A feature may be marked as deprecated by a version of the specification or extension to the specification. Features marked as deprecated in one version of the specification are still present in that version, but future versions may reduce their support or completely remove them. Deprecating before removing allows applications time to transition away from the deprecated feature. Once the feature is removed, all tokens used exclusively by that feature will be reserved and any use of those tokens will become invalid.

2.22 Unified Specification

This document specifies all versions of **SPIR-V**.

There are three kinds of entries in the tables of enumerated tokens:

- **Reservation:** These say [Reserved](#) in the enabling capabilities. They often contain token names only, lacking a semantic description. They are invalid **SPIR-V** for any version, serving only to reserve the tokens. They may identify enabling capabilities and extensions, in which case any listed extensions might add the tokens. See the listed extensions for additional information.
- **Conditional:** These say [Missing before](#) in the enabling capabilities. They are invalid **SPIR-V** for the missing versions. They may identify enabling capabilities and extensions, in which case any listed extensions might add the tokens for some of the missing versions. See the listed extensions for additional information. For versions not identified as missing, the tokens are valid **SPIR-V**, subject to any listed enabling capabilities.
- **Universal:** These have no mention of what version they are missing in, or of being reserved. They are valid in all versions of **SPIR-V**.

3 Binary Form

This section contains the exact form for all instructions, starting with the numerical values for all fields. See [Physical Layout](#) for the order words appear in.

3.1 Magic Number

Magic number for a SPIR-V module.

Tip

Endianness: A module is defined as a stream of words, not a stream of bytes. However, if stored as a stream of bytes (e.g., in a file), the magic number can be used to deduce what endianness to apply to convert the byte stream back to a word stream.

Magic Number
0x07230203

3.2 Source Language

The source language is for debug purposes only, with no semantics that affect the meaning of other parts of the module. Used by [OpSource](#).

Source Language	
0	Unknown
1	ESSL
2	GLSL
3	OpenCL_C
4	OpenCL_CPP
5	HLSL

3.3 Execution Model

Used by [OpEntryPoint](#).

Execution Model		Enabling Capabilities
0	Vertex Vertex shading stage.	Shader
1	TessellationControl Tessellation control (or hull) shading stage.	Tessellation
2	TessellationEvaluation Tessellation evaluation (or domain) shading stage.	Tessellation
3	Geometry Geometry shading stage.	Geometry
4	Fragment Fragment shading stage.	Shader
5	GLCompute Graphical compute shading stage.	Shader

Execution Model		Enabling Capabilities
6	Kernel Compute kernel.	Kernel

3.4 Addressing Model

Used by [OpMemoryModel](#).

Addressing Model		Enabling Capabilities
0	Logical	
1	Physical32 Indicates a 32-bit module, where the address width is equal to 32 bits.	Addresses
2	Physical64 Indicates a 64-bit module, where the address width is equal to 64 bits.	Addresses

3.5 Memory Model

Used by [OpMemoryModel](#).

Memory Model		Enabling Capabilities
0	Simple No shared memory consistency issues.	Shader
1	GLSL450 Memory model needed by later versions of GLSL and ESSL. Works across multiple versions.	Shader
2	OpenCL OpenCL memory model.	Kernel

3.6 Execution Mode

Declare the modes an [entry point](#) will execute in. Used by [OpExecutionMode](#) and [OpExecutionModeId](#).

Execution Mode		Enabling Capabilities	Extra Operands
0	Invocations Number of times to invoke the geometry stage for each input primitive received. The default is to run once for each input primitive. It is invalid to specify a value greater than the target-dependent maximum. Only valid with the Geometry Execution Model .	Geometry	Literal Number <i>Number of invocations</i>
1	SpacingEqual Requests the tessellation primitive generator to divide edges into a collection of equal-sized segments. Only valid with one of the tessellation Execution Models .	Tessellation	

	Execution Mode	Enabling Capabilities	Extra Operands
2	SpacingFractionalEven Requests the tessellation primitive generator to divide edges into an even number of equal-length segments plus two additional shorter fractional segments. Only valid with one of the tessellation Execution Models .	Tessellation	
3	SpacingFractionalOdd Requests the tessellation primitive generator to divide edges into an odd number of equal-length segments plus two additional shorter fractional segments. Only valid with one of the tessellation Execution Models .	Tessellation	
4	VertexOrderCw Requests the tessellation primitive generator to generate triangles in clockwise order. Only valid with one of the tessellation Execution Models .	Tessellation	
5	VertexOrderCcw Requests the tessellation primitive generator to generate triangles in counter-clockwise order. Only valid with one of the tessellation Execution Models .	Tessellation	
6	PixelCenterInteger Pixels appear centered on whole-number pixel offsets. E.g., the coordinate (0.5, 0.5) appears to move to (0.0, 0.0). Only valid with the Fragment Execution Model . If a Fragment entry point does not have this set, pixels appear centered at offsets of (0.5, 0.5) from whole numbers	Shader	
7	OriginUpperLeft Pixel coordinates appear to originate in the upper left, and increase toward the right and downward. Only valid with the Fragment Execution Model .	Shader	
8	OriginLowerLeft Pixel coordinates appear to originate in the lower left, and increase toward the right and upward. Only valid with the Fragment Execution Model .	Shader	
9	EarlyFragmentTests Fragment tests are to be performed before fragment shader execution. Only valid with the Fragment Execution Model .	Shader	
10	PointMode Requests the tessellation primitive generator to generate a point for each distinct vertex in the subdivided primitive, rather than to generate lines or triangles. Only valid with one of the tessellation Execution Models .	Tessellation	

Execution Mode		Enabling Capabilities	Extra Operands		
11	Xfb This stage will run in transform feedback-capturing mode and this module is responsible for describing the transform-feedback setup. See the XfbBuffer , Offset , and XfbStride Decorations .	TransformFeedback			
12	DepthReplacing This mode must be declared if this module potentially changes the fragment's depth. Only valid with the Fragment Execution Model .	Shader			
14	DepthGreater External optimizations may assume depth modifications will leave the fragment's depth as greater than or equal to the fragment's interpolated depth value (given by the z component of the FragCoord BuiltIn decorated variable). Only valid with the Fragment Execution Model .	Shader			
15	DepthLess External optimizations may assume depth modifications leave the fragment's depth less than the fragment's interpolated depth value, (given by the z component of the FragCoord BuiltIn decorated variable). Only valid with the Fragment Execution Model .	Shader			
16	DepthUnchanged External optimizations may assume this stage did not modify the fragment's depth. However, DepthReplacing mode must accurately represent depth modification. Only valid with the Fragment Execution Model .	Shader			
17	LocalSize Indicates the work-group size in the x, y, and z dimensions. Only valid with the GLCompute or Kernel Execution Models .		Literal Number <i>x size</i>	Literal Number <i>y size</i>	Literal Number <i>z size</i>
18	LocalSizeHint A hint to the compiler, which indicates the most likely to be used work-group size in the x, y, and z dimensions. Only valid with the Kernel Execution Model .	Kernel	Literal Number <i>x size</i>	Literal Number <i>y size</i>	Literal Number <i>z size</i>
19	InputPoints Stage input primitive is <i>points</i> . Only valid with the Geometry Execution Model .	Geometry			
20	InputLines Stage input primitive is <i>lines</i> . Only valid with the Geometry Execution Model .	Geometry			
21	InputLinesAdjacency Stage input primitive is <i>lines adjacency</i> . Only valid with the Geometry Execution Model .	Geometry			

Execution Mode		Enabling Capabilities	Extra Operands
22	Triangles For a geometry stage, input primitive is <i>triangles</i> . For a tessellation stage, requests the tessellation primitive generator to generate triangles. Only valid with the Geometry or one of the tessellation Execution Models .	Geometry, Tessellation	
23	InputTrianglesAdjacency Geometry stage input primitive is <i>triangles adjacency</i> . Only valid with the Geometry Execution Model .	Geometry	
24	Quads Requests the tessellation primitive generator to generate <i>quads</i> . Only valid with one of the tessellation Execution Models .	Tessellation	
25	Isolines Requests the tessellation primitive generator to generate <i>isolines</i> . Only valid with one of the tessellation Execution Models .	Tessellation	
26	OutputVertices For a geometry stage, the maximum number of vertices the shader will ever emit in a single invocation . For a tessellation-control stage, the number of vertices in the output patch produced by the tessellation control shader, which also specifies the number of times the tessellation control shader is invoked. Only valid with the Geometry or one of the tessellation Execution Models .	Geometry, Tessellation	Literal Number <i>Vertex count</i>
27	OutputPoints Stage output primitive is <i>points</i> . Only valid with the Geometry Execution Model .	Geometry	
28	OutputLineStrip Stage output primitive is <i>line strip</i> . Only valid with the Geometry Execution Model .	Geometry	
29	OutputTriangleStrip Stage output primitive is <i>triangle strip</i> . Only valid with the Geometry Execution Model .	Geometry	

Execution Mode		Enabling Capabilities	Extra Operands		
30	VecTypeHint A hint to the compiler, which indicates that most operations used in the entry point are explicitly vectorized using a particular vector type. The 16 high-order bits of <i>Vector Type</i> operand specify the <i>number of components</i> of the vector. The 16 low-order bits of <i>Vector Type</i> operand specify the <i>data type</i> of the vector. These are the legal <i>data type</i> values: 0 represents an 8-bit integer value. 1 represents a 16-bit integer value. 2 represents a 32-bit integer value. 3 represents a 64-bit integer value. 4 represents a 16-bit float value. 5 represents a 32-bit float value. 6 represents a 64-bit float value. Only valid with the Kernel Execution Model .	Kernel	Literal Number <i>Vector type</i>		
31	ContractionOff Indicates that floating-point-expressions contraction is disallowed. Only valid with the Kernel Execution Model .	Kernel			
33	Initializer Indicates that this entry point is a module initializer.	Kernel Missing before version 1.1.			
34	Finalizer Indicates that this entry point is a module finalizer.	Kernel Missing before version 1.1.			
35	SubgroupSize Indicates that this entry point requires the specified <i>Subgroup Size</i> .	SubgroupDispatch Missing before version 1.1.	Literal Number <i>Subgroup Size</i>		
36	SubgroupsPerWorkgroup Indicates that this entry point requires the specified number of <i>Subgroups Per Workgroup</i> .	SubgroupDispatch Missing before version 1.1.	Literal Number <i>Subgroups Per Workgroup</i>		
37	SubgroupsPerWorkgroupId Indicates that this entry point requires the specified number of <i>Subgroups Per Workgroup</i> . Specified as an Id.	SubgroupDispatch Missing before version 1.2.	<id> <i>Subgroups Per Workgroup</i>		
38	LocalSizeId Indicates the work-group size in the x, y, and z dimensions. Only valid with the GLCompute or Kernel Execution Models . Specified as Ids.	Missing before version 1.2.	<id> <i>x size</i>	<id> <i>y size</i>	<id> <i>z size</i>

Execution Mode		Enabling Capabilities	Extra Operands
39	LocalSizeHintId A hint to the compiler, which indicates the most likely to be used work-group size in the <i>x</i> , <i>y</i> , and <i>z</i> dimensions. Only valid with the Kernel Execution Model . Specified as an Id.	Kernel Missing before version 1.2.	<i><id></i> <i>Local Size Hint</i>
4446	PostDepthCoverage	SampleMaskPostDepthCoverage Reserved.	
5027	StencilRefReplacingEXT	StencilExportEXT Reserved.	

3.7 Storage Class

Class of storage for declared variables (does not include [intermediate](#) values). Used by:

- [OpTypePointer](#)
- [OpTypeForwardPointer](#)
- [OpVariable](#)
- [OpGenericCastToPtrExplicit](#)

Storage Class		Enabling Capabilities	Enabled by Extension
0	UniformConstant Shared externally, visible across all functions in all invocations in all work groups. Graphics uniform memory. OpenCL constant memory. Variables declared with this storage class are read-only. They may have initializers, as allowed by the client API.		
1	Input Input from pipeline. Visible across all functions in the current invocation . Variables declared with this storage class are read-only, and cannot have initializers.		
2	Uniform Shared externally, visible across all functions in all invocations in all work groups. Graphics uniform blocks and buffer blocks.	Shader	
3	Output Output to pipeline. Visible across all functions in the current invocation .	Shader	
4	Workgroup Shared across all invocations within a work group. Visible across all functions. The OpenGL "shared" storage qualifier. OpenCL local memory.		

Storage Class		Enabling Capabilities	Enabled by Extension
5	CrossWorkgroup Visible across all functions of all invocations of all work groups. OpenCL global memory.		
6	Private Visible to all functions in the current invocation . Regular global memory.	Shader	
7	Function Visible only within the declaring function of the current invocation . Regular function memory.		
8	Generic For generic pointers, which overload the Function , Workgroup , and CrossWorkgroup Storage Classes .	GenericPointer	
9	PushConstant For holding push-constant memory, visible across all functions in all invocations in all work groups. Intended to contain a small bank of values pushed from the API. Variables declared with this storage class are read-only, and cannot have initializers.	Shader	
10	AtomicCounter For holding atomic counters. Visible across all functions of the current invocation . Atomic counter-specific memory.	AtomicStorage	
11	Image For holding image memory.		
12	StorageBuffer Shared externally, readable and writable, visible across all functions in all invocations in all work groups. Graphics storage buffers (buffer blocks).	Shader Missing before version 1.3.	SPV_KHR_storage_buffer_storage_class, SPV_KHR_variable_pointers

3.8 Dim

Dimensionality of an image. Used by [OpTypeImage](#).

Dim		Enabling Capabilities
0	1D	Sampled1D
1	2D	
2	3D	
3	Cube	Shader
4	Rect	SampledRect
5	Buffer	SampledBuffer
6	SubpassData	InputAttachment

3.9 Sampler Addressing Mode

Addressing mode for creating constant samplers. Used by [OpConstantSampler](#).

Sampler Addressing Mode		Enabling Capabilities
0	None The image coordinates used to sample elements of the image refer to a location inside the image, otherwise the results are undefined.	Kernel
1	ClampToEdge Out-of-range image coordinates are clamped to the extent.	Kernel
2	Clamp Out-of-range image coordinates will return a border color.	Kernel
3	Repeat Out-of-range image coordinates are wrapped to the valid range. Can only be used with normalized coordinates.	Kernel
4	RepeatMirrored Flip the image coordinate at every integer junction. Can only be used with normalized coordinates.	Kernel

3.10 Sampler Filter Mode

Filter mode for creating constant samplers. Used by [OpConstantSampler](#).

Sampler Filter Mode		Enabling Capabilities
0	Nearest Use filter nearest mode when performing a read image operation.	Kernel
1	Linear Use filter linear mode when performing a read image operation.	Kernel

3.11 Image Format

Declarative image format. Used by [OpTypeImage](#).

Image Format		Enabling Capabilities
0	Unknown	
1	Rgba32f	Shader
2	Rgba16f	Shader
3	R32f	Shader
4	Rgba8	Shader
5	Rgba8Snorm	Shader
6	Rg32f	StorageImageExtendedFormats
7	Rg16f	StorageImageExtendedFormats
8	R11fG11fB10f	StorageImageExtendedFormats
9	R16f	StorageImageExtendedFormats

Image Format		Enabling Capabilities
10	Rgba16	StorageImageExtendedFormats
11	Rgb10A2	StorageImageExtendedFormats
12	Rg16	StorageImageExtendedFormats
13	Rg8	StorageImageExtendedFormats
14	R16	StorageImageExtendedFormats
15	R8	StorageImageExtendedFormats
16	Rgba16Snorm	StorageImageExtendedFormats
17	Rg16Snorm	StorageImageExtendedFormats
18	Rg8Snorm	StorageImageExtendedFormats
19	R16Snorm	StorageImageExtendedFormats
20	R8Snorm	StorageImageExtendedFormats
21	Rgba32i	Shader
22	Rgba16i	Shader
23	Rgba8i	Shader
24	R32i	Shader
25	Rg32i	StorageImageExtendedFormats
26	Rg16i	StorageImageExtendedFormats
27	Rg8i	StorageImageExtendedFormats
28	R16i	StorageImageExtendedFormats
29	R8i	StorageImageExtendedFormats
30	Rgba32ui	Shader
31	Rgba16ui	Shader
32	Rgba8ui	Shader
33	R32ui	Shader
34	Rgb10a2ui	StorageImageExtendedFormats
35	Rg32ui	StorageImageExtendedFormats
36	Rg16ui	StorageImageExtendedFormats
37	Rg8ui	StorageImageExtendedFormats
38	R16ui	StorageImageExtendedFormats
39	R8ui	StorageImageExtendedFormats

3.12 Image Channel Order

Image channel order returned by [OpImageQueryOrder](#).

Image Channel Order		Enabling Capabilities
0	R	Kernel
1	A	Kernel
2	RG	Kernel
3	RA	Kernel
4	RGB	Kernel
5	RGBA	Kernel
6	BGRA	Kernel
7	ARGB	Kernel
8	Intensity	Kernel
9	Luminance	Kernel
10	Rx	Kernel
11	RGx	Kernel
12	RGBx	Kernel
13	Depth	Kernel
14	DepthStencil	Kernel
15	sRGB	Kernel

Image Channel Order		Enabling Capabilities
16	sRGBx	Kernel
17	sRGBA	Kernel
18	sBGRA	Kernel
19	ABGR	Kernel

3.13 Image Channel Data Type

Image channel data type returned by [OpImageQueryFormat](#).

Image Channel Data Type		Enabling Capabilities
0	SnormInt8	Kernel
1	SnormInt16	Kernel
2	UnormInt8	Kernel
3	UnormInt16	Kernel
4	UnormShort565	Kernel
5	UnormShort555	Kernel
6	UnormInt101010	Kernel
7	SignedInt8	Kernel
8	SignedInt16	Kernel
9	SignedInt32	Kernel
10	UnsignedInt8	Kernel
11	UnsignedInt16	Kernel
12	UnsignedInt32	Kernel
13	HalfFloat	Kernel
14	Float	Kernel
15	UnormInt24	Kernel
16	UnormInt101010_2	Kernel

3.14 Image Operands

Additional operands to sampling, or getting texels from, an image. Bits that are set can indicate that another operand follows. If there are multiple following operands indicated, they are ordered: Those indicated by smaller-numbered bits appear first. At least one bit must be set (**None** is invalid).

This value is a literal mask; it can be formed by combining the bits from multiple rows in the table below.

Used by:

- [OpImageSampleImplicitLod](#)
- [OpImageSampleExplicitLod](#)
- [OpImageSampleDrefImplicitLod](#)
- [OpImageSampleDrefExplicitLod](#)
- [OpImageSampleProjImplicitLod](#)
- [OpImageSampleProjExplicitLod](#)
- [OpImageSampleProjDrefImplicitLod](#)
- [OpImageSampleProjDrefExplicitLod](#)
- [OpImageFetch](#)
- [OpImageGather](#)
- [OpImageDrefGather](#)

- [OpImageRead](#)
- [OpImageWrite](#)
- [OpImageSparseSampleImplicitLod](#)
- [OpImageSparseSampleExplicitLod](#)
- [OpImageSparseSampleDrefImplicitLod](#)
- [OpImageSparseSampleDrefExplicitLod](#)
- [OpImageSparseSampleProjImplicitLod](#)
- [OpImageSparseSampleProjExplicitLod](#)
- [OpImageSparseSampleProjDrefImplicitLod](#)
- [OpImageSparseSampleProjDrefExplicitLod](#)
- [OpImageSparseFetch](#)
- [OpImageSparseGather](#)
- [OpImageSparseDrefGather](#)
- [OpImageSparseRead](#)

Image Operands		Enabling Capabilities
0x0	None	
0x1	Bias A following operand is the bias added to the implicit level of detail. Only valid with implicit-lod instructions. It must be a floating-point type scalar. This can only be used with an OpTypeImage that has a Dim operand of 1D , 2D , 3D , or Cube , and the <i>MS</i> operand must be 0.	Shader
0x2	Lod A following operand is the explicit level-of-detail to use. Only valid with explicit-lod instructions. For sampling operations, it must be a floating-point type scalar. For fetch operations, it must be an integer type scalar. This can only be used with an OpTypeImage that has a Dim operand of 1D , 2D , 3D , or Cube , and the <i>MS</i> operand must be 0.	
0x4	Grad Two following operands are <i>dx</i> followed by <i>dy</i> . These are explicit derivatives in the <i>x</i> and <i>y</i> direction to use in computing level of detail. Each is a scalar or vector containing (<i>du/dx</i> [, <i>dv/dx</i> [, <i>dw/dx</i>]) and (<i>du/dy</i> [, <i>dv/dy</i> [, <i>dw/dy</i>]). The number of components of each must equal the number of components in <i>Coordinate</i> , minus the <i>array layer</i> component, if present. Only valid with explicit-lod instructions. They must be a scalar or vector of floating-point type . This can only be used with an OpTypeImage that has an <i>MS</i> operand of 0. It is invalid to set both the Lod and Grad bits.	

Image Operands		Enabling Capabilities
0x8	ConstOffset A following operand is added to (u, v, w) before texel lookup. It must be an <i><id></i> of an integer-based constant instruction of scalar or vector type. It is invalid for these to be outside a target-dependent allowed range. The number of components must equal the number of components in <i>Coordinate</i> , minus the <i>array layer</i> component, if present. Not valid with the Cube dimension .	
0x10	Offset A following operand is added to (u, v, w) before texel lookup. It must be a scalar or vector of integer type . It is invalid for these to be outside a target-dependent allowed range. The number of components must equal the number of components in <i>Coordinate</i> , minus the <i>array layer</i> component, if present. Not valid with the Cube dimension .	ImageGatherExtended
0x20	ConstOffsets A following operand is <i>Offsets</i> . <i>Offsets</i> must be an <i><id></i> of a constant instruction making an array of size four of vectors of two integer components. Each gathered texel is identified by adding one of these array elements to the (u, v) sampled location. It is invalid for these to be outside a target-dependent allowed range. Only valid with OpImageGather or OpImageDrefGather . Not valid with the Cube dimension .	
0x40	Sample A following operand is the sample number of the sample to use. Only valid with OpImageFetch , OpImageRead , OpImageWrite , OpImageSparseFetch , and OpImageSparseRead . It is invalid to have a Sample operand if the underlying OpTypeImage has <i>MS</i> of 0. It must be an integer type scalar.	
0x80	MinLod A following operand is the minimum level-of-detail to use when accessing the image. Only valid with Implicit instructions and Grad instructions. It must be a floating-point type scalar. This can only be used with an OpTypeImage that has a Dim operand of 1D , 2D , 3D , or Cube , and the <i>MS</i> operand must be 0.	MinLod

3.15 FP Fast Math Mode

Enables fast math operations which are otherwise unsafe.

- Only valid on [OpFAdd](#), [OpFSub](#), [OpFMul](#), [OpFDiv](#), [OpFRem](#), and [OpFMod](#) instructions.

This value is a literal mask; it can be formed by combining the bits from multiple rows in the table below.

FP Fast Math Mode		Enabling Capabilities
0x0	None	
0x1	NotNaN Assume parameters and result are not NaN.	Kernel
0x2	NotInf Assume parameters and result are not +/- Inf.	Kernel
0x4	NSZ Treat the sign of a zero parameter or result as insignificant.	Kernel
0x8	AllowRecip Allow the usage of reciprocal rather than perform a division.	Kernel
0x10	Fast Allow algebraic transformations according to real-number associative and distributive algebra. This flag implies all the others.	Kernel

3.16 FP Rounding Mode

Associate a rounding mode to a floating-point conversion instruction.

FP Rounding Mode	
0	RTE Round to nearest even.
1	RTZ Round towards zero.
2	RTP Round towards positive infinity.
3	RTN Round towards negative infinity.

3.17 Linkage Type

Associate a linkage type to functions or global variables. See [linkage](#).

Linkage Type		Enabling Capabilities
0	Export Accessible by other modules as well.	Linkage
1	Import A declaration of a global variable or a function that exists in another module.	Linkage

3.18 Access Qualifier

Defines the access permissions.

Used by [OpTypeImage](#) and [OpTypePipe](#).

Access Qualifier		Enabling Capabilities
0	ReadOnly A read-only object.	Kernel
1	WriteOnly A write-only object.	Kernel
2	ReadWrite A readable and writable object.	Kernel

3.19 Function Parameter Attribute

Adds additional information to the return type and to each parameter of a function.

Function Parameter Attribute		Enabling Capabilities
0	Zext Value should be zero extended if needed.	Kernel
1	Sext Value should be sign extended if needed.	Kernel
2	ByVal This indicates that the pointer parameter should really be passed by value to the function. Only valid for pointer parameters (not for ret value).	Kernel
3	Sret Indicates that the pointer parameter specifies the address of a structure that is the return value of the function in the source program. Only applicable to the first parameter which must be a pointer parameters.	Kernel
4	NoAlias Indicates that the memory pointed to by a pointer parameter is not accessed via pointer values which are not derived from this pointer parameter. Only valid for pointer parameters. Not valid on return values.	Kernel
5	NoCapture The callee does not make a copy of the pointer parameter into a location that is accessible after returning from the callee. Only valid for pointer parameters. Not valid on return values.	Kernel
6	NoWrite Can only read the memory pointed to by a pointer parameter. Only valid for pointer parameters. Not valid on return values.	Kernel
7	NoReadWrite Cannot dereference the memory pointed to by a pointer parameter. Only valid for pointer parameters. Not valid on return values.	Kernel

3.20 Decoration

Used by:

- [OpDecorate](#)
- [OpMemberDecorate](#)
- [OpDecorateId](#)
- [OpDecorateStringGOOGLE](#)
- [OpMemberDecorateStringGOOGLE](#)

	Decoration	Enabling Capabilities	Extra Operands
0	RelaxedPrecision Allow reduced precision operations. To be used as described in Relaxed Precision .	Shader	
1	SpecId Apply to a scalar specialization constant. Forms the API linkage for setting a specialized value. See specialization .	Shader, Kernel	Literal Number <i>Specialization Constant ID</i>
2	Block Apply to a structure type to establish it is a non-SSBO-like shader-interface block.	Shader	
3	BufferBlock Deprecated (use Block -decorated StorageBuffer Storage Class objects). Apply to a structure type to establish it is an SSBO-like shader-interface block.	Shader	
4	RowMajor Applies only to a member of a structure type. Only valid on a matrix or array whose most basic element is a matrix. Indicates that components within a row are contiguous in memory.	Matrix	
5	ColMajor Applies only to a member of a structure type. Only valid on a matrix or array whose most basic element is a matrix. Indicates that components within a column are contiguous in memory.	Matrix	
6	ArrayStride Apply to an array type to specify the stride, in bytes, of the array's elements. Can also apply to a pointer type to an array element, to specify the stride of the array that the element resides in. Must not be applied to any other type.	Shader	Literal Number <i>Array Stride</i>
7	MatrixStride Applies only to a member of a structure type. Only valid on a matrix or array whose most basic element is a matrix. Specifies the stride of rows in a RowMajor -decorated matrix, or columns in a ColMajor -decorated matrix.	Matrix	Literal Number <i>Matrix Stride</i>
8	GLSLShared Apply to a structure type to get GLSL shared memory layout.	Shader	
9	GLSLPacked Apply to a structure type to get GLSL packed memory layout.	Shader	

Decoration		Enabling Capabilities	Extra Operands
10	CPacked Apply to a structure type, to marks it as "packed", indicating that the alignment of the structure is one and that there is no padding between structure members.	Kernel	
11	BuiltIn Apply to an object or a member of a structure type. Indicates which built-in variable the entity represents. See BuiltIn for more information.		BuiltIn
13	NoPerspective Apply to an object or a member of a structure type. Indicates that linear, non-perspective correct, interpolation must be used. Only valid for the Input and Output Storage Classes .	Shader	
14	Flat Apply to an object or a member of a structure type. Indicates no interpolation will be done. The non-interpolated value will come from a vertex, as described in the API specification. Only valid for the Input and Output Storage Classes .	Shader	
15	Patch Apply to an object or a member of a structure type. Indicates a tessellation patch. Only valid for the Input and Output Storage Classes . Invalid to use on objects or types referenced by non-tessellation Execution Models .	Tessellation	
16	Centroid Apply to an object or a member of a structure type. When used with multi-sampling rasterization, allows a single interpolation location for an entire pixel. The interpolation location must lie in both the pixel and in the primitive being rasterized. Only valid for the Input and Output Storage Classes .	Shader	
17	Sample Apply to an object or a member of a structure type. When used with multi-sampling rasterization, requires per-sample interpolation. The interpolation locations must be the locations of the samples lying in both the pixel and in the primitive being rasterized. Only valid for the Input and Output Storage Classes .	SampleRateShading	
18	Invariant Apply to a variable, to indicate expressions computing its value be done invariant with respect to other modules computing the same expressions.	Shader	
19	Restrict Apply to a variable, to indicate the compiler may compile as if there is no aliasing. See the Aliasing section for more detail.		

	Decoration	Enabling Capabilities	Extra Operands
20	Aliased Apply to a variable, to indicate the compiler is to generate accesses to the variable that work correctly in the presence of aliasing. See the Aliasing section for more detail.		
21	Volatile Apply to an object, pointer type, or a member of a structure type. Can only be used for objects declared as storage images (see OpTypeImage), in the StorageBuffer Storage Class , or in the Uniform Storage Class with the BufferBlock Decoration . This indicates the memory holding the variable is volatile memory. Accesses to volatile memory cannot be eliminated, duplicated, or combined with other accesses. The variable cannot be in the Function Storage Class .		
22	Constant Indicates that a global variable is constant and will never be modified. Only allowed on global variables.	Kernel	
23	Coherent Apply to an object, pointer type, or a member of a structure type. Can only be used for objects declared as storage images (see OpTypeImage), in the StorageBuffer Storage Class , or in the Uniform Storage Class with the BufferBlock Decoration . This indicates the memory backing the object is coherent.		
24	NonWritable Apply to an object or a member of a structure type. Can only be used for objects declared as storage images (see OpTypeImage), in the StorageBuffer Storage Class , or in the Uniform Storage Class with the BufferBlock Decoration . This indicates the memory holding the variable is not writable, and that this module does not write to it.		
25	NonReadable Apply to an object or a member of a structure type. Can only be used for objects declared as storage images (see OpTypeImage), in the StorageBuffer Storage Class , or in the Uniform Storage Class with the BufferBlock Decoration . This indicates the memory holding the variable is not readable, and that this module does not read from it.		
26	Uniform Apply to an object or a member of a structure type. Asserts that the value backing the decorated <i><id></i> is dynamically uniform , hence the consumer is allowed to assume this is the case.	Shader	

	Decoration	Enabling Capabilities	Extra Operands
28	SaturatedConversion Indicates that a conversion to an integer type which is outside the representable range of <i>Result Type</i> will be clamped to the nearest representable value of <i>Result Type</i> . <i>NaN</i> will be converted to 0. This decoration can only be applied to conversion instructions to integer types, not including the OpSatConvertUToS and OpSatConvertSToU instructions.	Kernel	
29	Stream Apply to an object or a member of a structure type. Indicates the stream number to put an output on. Only valid for the Output Storage Class and the Geometry Execution Model .	GeometryStreams	Literal Number <i>Stream Number</i>
30	Location Apply to a variable or a structure-type member. Forms the main linkage for Storage Class Input and Output variables: - between the API and vertex-stage inputs, - between consecutive programmable stages, or - between fragment-stage outputs and the API. Also can tag variables or structure-type members in the UniformConstant Storage Class for linkage with the API. Only valid for the Input , Output , and UniformConstant Storage Classes .	Shader	Literal Number <i>Location</i>
31	Component Apply to an object or a member of a structure type. Indicates which component within a Location will be taken by the decorated entity. Only valid for the Input and Output Storage Classes .	Shader	Literal Number <i>Component</i>
32	Index Apply to a variable to identify a blend equation input index, used as described in the API specification. Only valid for the Output Storage Class and the Fragment Execution Model .	Shader	Literal Number <i>Index</i>
33	Binding Apply to a variable. Part of the main linkage between the API and SPIR-V modules for memory buffers, images, etc. See the API specification for more information.	Shader	Literal Number <i>Binding Point</i>
34	DescriptorSet Apply to a variable. Part of the main linkage between the API and SPIR-V modules for memory buffers, images, etc. See the API specification for more information.	Shader	Literal Number <i>Descriptor Set</i>

Decoration		Enabling Capabilities	Extra Operands	
35	Offset Apply to a structure-type member. This gives the byte offset of the member relative to the beginning of the structure. Can be used, for example, by both uniform and transform-feedback buffers. It must not cause any overlap of the structure's members, or overflow of a transform-feedback buffer's XfbStride .	Shader	Literal Number <i>Byte Offset</i>	
36	XfbBuffer Apply to an object or a member of a structure type. Indicates which transform-feedback buffer an output is written to. Only valid for the Output Storage Classes of vertex processing Execution Models .	TransformFeedback	Literal Number <i>XFB Buffer Number</i>	
37	XfbStride Apply to anything XfbBuffer is applied to. Specifies the stride, in bytes, of transform-feedback buffer vertices. If the transform-feedback buffer is capturing any double-precision components, the stride must be a multiple of 8, otherwise it must be a multiple of 4.	TransformFeedback	Literal Number <i>XFB Stride</i>	
38	FuncParamAttr Indicates a function return value or parameter attribute.	Kernel	Function Parameter Attribute <i>Function Parameter Attribute</i>	
39	FPRoundingMode Indicates a floating-point rounding mode.		FP Rounding Mode <i>Floating-Point Rounding Mode</i>	
40	FPFastMathMode Indicates a floating-point fast math flag.	Kernel	FP Fast Math Mode <i>Fast-Math Mode</i>	
41	LinkageAttributes Associate linkage attributes to values. Only valid on OpFunction or global (module scope) OpVariable . See linkage .	Linkage	Literal String Name	Linkage Type <i>Linkage Type</i>
42	NoContraction Apply to an arithmetic instruction to indicate the operation cannot be combined with another instruction to form a single operation. For example, if applied to an OpFMul , that multiply can't be combined with an addition to yield a fused multiply-add operation. Furthermore, such operations are not allowed to reassociate; e.g., $\text{add}(a + \text{add}(b+c))$ cannot be transformed to $\text{add}(\text{add}(a+b) + c)$.	Shader		
43	InputAttachmentIndex Apply to a variable to provide an input-target index (as described in the API specification). Only valid in the Fragment Execution Model and for variables of type OpTypeImage with a Dim operand of SubpassData .	InputAttachment	Literal Number <i>Attachment Index</i>	
44	Alignment Apply to a pointer. This declares a known minimum alignment the pointer has.	Kernel	Literal Number <i>Alignment</i>	

Decoration		Enabling Capabilities	Extra Operands
45	MaxByteOffset Apply to a pointer. This declares a known maximum byte offset this pointer will be incremented by from the point of the decoration. This is a guaranteed upper bound when applied to OpFunctionParameter .	Addresses Missing before version 1.1 .	Literal Number <i>Max Byte Offset</i>
46	AlignmentId Apply to a pointer. This declares a known minimum alignment the pointer has. Specified as an Id.	Kernel Missing before version 1.2 .	<i><id></i> <i>Alignment</i>
47	MaxByteOffsetId Apply to a pointer. This declares a known maximum byte offset this pointer will be incremented by from the point of the decoration. This is a guaranteed upper bound when applied to OpFunctionParameter . Specified as an Id.	Addresses Missing before version 1.2 .	<i><id></i> <i>Max Byte Offset</i>
4999	ExplicitInterpAMD	Reserved.	
5248	OverrideCoverageNV	SampleMaskOverrideCoverageNV Reserved.	
5250	PassthroughNV	GeometryShaderPassthroughNV Reserved.	
5252	ViewportRelativeNV	ShaderViewportMaskNV Reserved.	
5256	SecondaryViewportRelativeNV	ShaderStereoViewNV Reserved.	Literal Number <i>Offset</i>
5634	HlslCounterBufferGOOGLE	Reserved.SPV_GOOGLE_hlsl_functionality1	Functionality1 <i>Counter Buffer</i>
5635	HlslSemanticGOOGLE	Reserved.SPV_GOOGLE_hlsl_functionality1	Functionality1 <i>Semantic</i>

3.21 BuiltIn

Used when [Decoration](#) is **BuiltIn**. Apply to either

- the result *<id>* of the variable declaration of the built-in variable, or
- a structure-type member, if the built-in is a member of a structure.

As stated per entry below, these have additional semantics and constraints described by the client API.

BuiltIn		Enabling Capabilities
0	Position Output vertex position from a vertex processing Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader

BuiltIn		Enabling Capabilities
1	PointSize Output point size from a vertex processing Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
3	ClipDistance Array of clip distances. See Vulkan or OpenGL API specifications for more detail.	ClipDistance
4	CullDistance Array of clip distances. See Vulkan or OpenGL API specifications for more detail.	CullDistance
5	VertexId Input vertex ID to a Vertex Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
6	InstanceId Input instance ID to a Vertex Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
7	PrimitiveId Primitive ID in a Geometry Execution Model . See Vulkan or OpenGL API specifications for more detail.	Geometry, Tessellation
8	InvocationId Invocation ID, input to Geometry and TessellationControl Execution Model . See Vulkan or OpenGL API specifications for more detail.	Geometry, Tessellation
9	Layer Layer output by a Geometry Execution Model , input to a Fragment Execution Model, for multi-layer framebuffer. See Vulkan or OpenGL API specifications for more detail.	Geometry
10	ViewportIndex Viewport Index output by a Geometry stage, input to a Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	MultiViewport
11	TessLevelOuter Output patch outer levels in a TessellationControl Execution Model . See Vulkan or OpenGL API specifications for more detail.	Tessellation
12	TessLevelInner Output patch inner levels in a TessellationControl Execution Model . See Vulkan or OpenGL API specifications for more detail.	Tessellation
13	TessCoord Input vertex position in TessellationEvaluation Execution Model . See Vulkan or OpenGL API specifications for more detail.	Tessellation

BuiltIn		Enabling Capabilities
14	PatchVertices Input patch vertex count in a tessellation Execution Model . See Vulkan or OpenGL API specifications for more detail.	Tessellation
15	FragCoord Coordinates $(x, y, z, 1/w)$ of the current fragment, input to the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
16	PointCoord Coordinates within a <i>point</i> , input to the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
17	FrontFacing Face direction, input to the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
18	SampleId Input sample number to the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	SampleRateShading
19	SamplePosition Input sample position to the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	SampleRateShading
20	SampleMask Input or output sample mask to the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
22	FragDepth Output fragment depth from the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
23	HelperInvocation Input whether a helper invocation, to the Fragment Execution Model . See Vulkan or OpenGL API specifications for more detail.	Shader
24	NumWorkgroups Number of workgroups in GLCompute or Kernel Execution Models . See OpenCL, Vulkan, or OpenGL API specifications for more detail.	
25	WorkgroupSize Work-group size in GLCompute or Kernel Execution Models . See OpenCL, Vulkan, or OpenGL API specifications for more detail.	
26	WorkgroupId Work-group ID in GLCompute or Kernel Execution Models . See OpenCL, Vulkan, or OpenGL API specifications for more detail.	

	BuiltIn	Enabling Capabilities
27	LocalInvocationId Local invocation ID in GLCompute or Kernel Execution Models . See OpenCL, Vulkan, or OpenGL API specifications for more detail.	
28	GlobalInvocationId Global invocation ID in GLCompute or Kernel Execution Models . See OpenCL, Vulkan, or OpenGL API specifications for more detail.	
29	LocalInvocationIndex Local invocation index in GLCompute Execution Models . See Vulkan or OpenGL API specifications for more detail. Work-group Linear ID in Kernel Execution Models . See OpenCL API specification for more detail.	
30	WorkDim Work dimensions in Kernel Execution Models . See OpenCL API specification for more detail.	Kernel
31	GlobalSize Global size in Kernel Execution Models . See OpenCL API specification for more detail.	Kernel
32	EnqueuedWorkgroupSize Enqueued work-group size in Kernel Execution Models . See OpenCL API specification for more detail.	Kernel
33	GlobalOffset Global offset in Kernel Execution Models . See OpenCL API specification for more detail.	Kernel
34	GlobalLinearId Global linear ID in Kernel Execution Models . See OpenCL API specification for more detail.	Kernel
36	SubgroupSize Subgroup size. See OpenCL, Vulkan, or OpenGL API specifications for more detail.	Kernel, GroupNonUniform
37	SubgroupMaxSize Subgroup maximum size in Kernel Execution Models . See OpenCL API specification for more detail.	Kernel
38	NumSubgroups Number of subgroups in GLCompute or Kernel Execution Models . See OpenCL, Vulkan, or OpenGL API specifications for more detail.	Kernel, GroupNonUniform
39	NumEnqueuedSubgroups Number of enqueued subgroups in Kernel Execution Models . See OpenCL API specification for more detail.	Kernel

BuiltIn		Enabling Capabilities
40	SubgroupId Subgroup ID in GLCompute or Kernel Execution Models . See OpenCL, Vulkan, or OpenGL API specifications for more detail.	Kernel, GroupNonUniform
41	SubgroupLocalInvocationId Subgroup local invocation ID. See OpenCL, Vulkan, or OpenGL API specifications for more detail.	Kernel, GroupNonUniform
42	VertexIndex Vertex index. See Vulkan or OpenGL API specifications for more detail.	Shader
43	InstanceIndex Instance index. See Vulkan or OpenGL API specifications for more detail.	Shader
4416	SubgroupEqMask Subgroup invocations bitmask where bit index == SubgroupLocalInvocationId . See Vulkan or OpenGL API specifications for more detail.	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4417	SubgroupGeMask Subgroup invocations bitmask where bit index >= SubgroupLocalInvocationId . See Vulkan or OpenGL API specifications for more detail.	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4418	SubgroupGtMask Subgroup invocations bitmask where bit index > SubgroupLocalInvocationId . See Vulkan or OpenGL API specifications for more detail.	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4419	SubgroupLeMask Subgroup invocations bitmask where bit index <= SubgroupLocalInvocationId . See Vulkan or OpenGL API specifications for more detail.	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4420	SubgroupLtMask Subgroup invocations bitmask where bit index < SubgroupLocalInvocationId . See Vulkan or OpenGL API specifications for more detail.	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4416	SubgroupEqMaskKHR	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4417	SubgroupGeMaskKHR	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4418	SubgroupGtMaskKHR	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.

	BuiltIn	Enabling Capabilities
4419	SubgroupLeMaskKHR	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4420	SubgroupLtMaskKHR	SubgroupBallotKHR, GroupNonUniformBallot Missing before version 1.3.
4424	BaseVertex Base vertex component of vertex ID. See the Vulkan 1.1 or OpenGL 4.6 specifications for more details.	DrawParameters Missing before version 1.3.
4425	BaseInstance Base instance component of instance ID. See the Vulkan 1.1 or OpenGL 4.6 specifications for more details.	DrawParameters Missing before version 1.3.
4426	DrawIndex Contains the index of the draw currently being processed. See the Vulkan 1.1 or OpenGL 4.6 specifications for more details.	DrawParameters Missing before version 1.3.
4438	DeviceIndex Input device index of the logical device. See the Vulkan 1.1 specification for more details.	DeviceGroup Missing before version 1.3.
4440	ViewIndex Input view index of the view currently being rendered to. See the Vulkan 1.1 specification for more details.	MultiView Missing before version 1.3.
4992	BaryCoordNoPerspAMD	Reserved.
4993	BaryCoordNoPerspCentroidAMD	Reserved.
4994	BaryCoordNoPerspSampleAMD	Reserved.
4995	BaryCoordSmoothAMD	Reserved.
4996	BaryCoordSmoothCentroidAMD	Reserved.
4997	BaryCoordSmoothSampleAMD	Reserved.
4998	BaryCoordPullModelAMD	Reserved.
5014	FragStencilRefEXT	StencilExportEXT Reserved.
5253	ViewportMaskNV	ShaderViewportMaskNV Reserved.
5257	SecondaryPositionNV	ShaderStereoViewNV Reserved.
5258	SecondaryViewportMaskNV	ShaderStereoViewNV Reserved.
5261	PositionPerViewNV	PerViewAttributesNV Reserved.

BuiltIn		Enabling Capabilities
5262	ViewportMaskPerViewNV	PerViewAttributesNV
		Reserved.
5264	FullyCoveredEXT	FragmentFullyCoveredEXT
		Reserved.

3.22 Selection Control

This value is a literal mask; it can be formed by combining the bits from multiple rows in the table below.

Used by [OpSelectionMerge](#).

Selection Control	
0x0	None
0x1	Flatten Strong request, to the extent possible, to remove the control flow for this selection.
0x2	DontFlatten Strong request, to the extent possible, to keep this selection as control flow.

3.23 Loop Control

This value is a literal mask; it can be formed by combining the bits from multiple rows in the table below.

Used by [OpLoopMerge](#).

Loop Control		Enabling Capabilities
0x0	None	
0x1	Unroll Strong request, to the extent possible, to unroll or unwind this loop.	
0x2	DontUnroll Strong request, to the extent possible, to keep this loop as a loop, without unrolling.	
0x4	DependencyInfinite Guarantees that there are no dependencies between loop iterations.	Missing before version 1.1.
0x8	DependencyLength Guarantees that there are no dependencies between a number of loop iterations, specified as a subsequent literal-number operand to the instruction.	Missing before version 1.1.

3.24 Function Control

This value is a literal mask; it can be formed by combining the bits from multiple rows in the table below.

Used by [OpFunction](#).

Function Control	
0x0	None
0x1	Inline Strong request, to the extent possible, to inline the function.
0x2	DontInline Strong request, to the extent possible, to not inline the function.
0x4	Pure Compiler can assume this function has no side effect, but might read global memory or read through dereferenced function parameters. Always computes the same result for the same argument values.
0x8	Const Compiler can assume this function has no side effects, and will not access global memory or dereference function parameters. Always computes the same result for the same argument values.

3.25 Memory Semantics <id>

Must be an <id> of a 32-bit integer scalar.

Memory semantics define memory-order constraints, and on what storage classes those constraints apply to. The memory order constrains the allowed orders in which memory operations in this [invocation](#) can be made visible to another invocation. The storage classes specify to which subsets of memory these constraints are to be applied. Storage classes not selected are not being constrained.

Despite being a mask and allowing multiple bits to be combined, at most one of the first four (low-order) bits can be set. Requesting both **Acquire** and **Release** semantics is done by setting the **AcquireRelease** bit, not by setting two bits.

This value is a mask; it can be formed by combining the bits from multiple rows in the table below.

Used by:

- [OpControlBarrier](#)
- [OpMemoryBarrier](#)
- [OpAtomicLoad](#)
- [OpAtomicStore](#)
- [OpAtomicExchange](#)
- [OpAtomicCompareExchange](#)
- [OpAtomicCompareExchangeWeak](#)
- [OpAtomicIIncrement](#)
- [OpAtomicIDecrement](#)
- [OpAtomicIAdd](#)
- [OpAtomicISub](#)
- [OpAtomicSMin](#)
- [OpAtomicUMin](#)

- [OpAtomicSMax](#)
- [OpAtomicUMax](#)
- [OpAtomicAnd](#)
- [OpAtomicOr](#)
- [OpAtomicXor](#)
- [OpAtomicFlagTestAndSet](#)
- [OpAtomicFlagClear](#)
- [OpMemoryNamedBarrier](#)

Memory Semantics		Enabling Capabilities
0x0	None (Relaxed)	
0x2	Acquire All memory operations provided in program order after this memory operation will execute after this memory operation.	
0x4	Release All memory operations provided in program order before this memory operation will execute before this memory operation.	
0x8	AcquireRelease Has the properties of both Acquire and Release semantics. It is used for read-modify-write operations.	
0x10	SequentiallyConsistent All observers will see this memory access in the same order with respect to other sequentially-consistent memory accesses from this invocation .	
0x40	UniformMemory Apply the memory-ordering constraints to StorageBuffer or Uniform Storage Class memory.	Shader
0x80	SubgroupMemory Apply the memory-ordering constraints to subgroup memory.	
0x100	WorkgroupMemory Apply the memory-ordering constraints to Workgroup Storage Class memory.	
0x200	CrossWorkgroupMemory Apply the memory-ordering constraints to CrossWorkgroup Storage Class memory.	
0x400	AtomicCounterMemory Apply the memory-ordering constraints to AtomicCounter Storage Class memory.	AtomicStorage
0x800	ImageMemory Apply the memory-ordering constraints to image contents (types declared by OpTypeImage), or to accesses done through pointers to the Image Storage Class .	

3.26 Memory Access

Memory access semantics.

This value is a literal mask; it can be formed by combining the bits from multiple rows in the table below.

Used by:

- [OpLoad](#)
- [OpStore](#)
- [OpCopyMemory](#)
- [OpCopyMemorySized](#)

Memory Access	
0x0	None
0x1	Volatile This access cannot be eliminated, duplicated, or combined with other accesses.
0x2	Aligned This access has a known alignment, provided as a literal in the next operand.
0x4	Nontemporal Hints that the accessed address is not likely to be accessed again in the near future.

3.27 Scope <id>

Must be an <id> of a 32-bit integer scalar.

The execution scope or memory scope of an operation. When used as a memory scope, it specifies the distance of synchronization from the current [invocation](#). When used as an execution scope, it specifies the set of executing invocations taking part in the operation. Used by:

- [OpControlBarrier](#)
- [OpMemoryBarrier](#)
- [OpAtomicLoad](#)
- [OpAtomicStore](#)
- [OpAtomicExchange](#)
- [OpAtomicCompareExchange](#)
- [OpAtomicCompareExchangeWeak](#)
- [OpAtomicIIncrement](#)
- [OpAtomicIDecrement](#)
- [OpAtomicIAdd](#)
- [OpAtomicISub](#)
- [OpAtomicSMin](#)
- [OpAtomicUMin](#)
- [OpAtomicSMax](#)

- OpAtomicUMax
- OpAtomicAnd
- OpAtomicOr
- OpAtomicXor
- OpGroupAsyncCopy
- OpGroupWaitEvents
- OpGroupAll
- OpGroupAny
- OpGroupBroadcast
- OpGroupIAdd
- OpGroupFAdd
- OpGroupFMin
- OpGroupUMin
- OpGroupSMin
- OpGroupFMax
- OpGroupUMax
- OpGroupSMax
- OpGroupReserveReadPipePackets
- OpGroupReserveWritePipePackets
- OpGroupCommitReadPipe
- OpGroupCommitWritePipe
- OpAtomicFlagTestAndSet
- OpAtomicFlagClear
- OpMemoryNamedBarrier
- OpGroupNonUniformElect
- OpGroupNonUniformAll
- OpGroupNonUniformAny
- OpGroupNonUniformAllEqual
- OpGroupNonUniformBroadcast
- OpGroupNonUniformBroadcastFirst
- OpGroupNonUniformBallot
- OpGroupNonUniformInverseBallot
- OpGroupNonUniformBallotBitExtract
- OpGroupNonUniformBallotBitCount
- OpGroupNonUniformBallotFindLSB
- OpGroupNonUniformBallotFindMSB
- OpGroupNonUniformShuffle
- OpGroupNonUniformShuffleXor
- OpGroupNonUniformShuffleUp
- OpGroupNonUniformShuffleDown
- OpGroupNonUniformIAdd

- [OpGroupNonUniformFAdd](#)
- [OpGroupNonUniformIMul](#)
- [OpGroupNonUniformFMul](#)
- [OpGroupNonUniformSMin](#)
- [OpGroupNonUniformUMin](#)
- [OpGroupNonUniformFMin](#)
- [OpGroupNonUniformSMax](#)
- [OpGroupNonUniformUMax](#)
- [OpGroupNonUniformFMax](#)
- [OpGroupNonUniformBitwiseAnd](#)
- [OpGroupNonUniformBitwiseOr](#)
- [OpGroupNonUniformBitwiseXor](#)
- [OpGroupNonUniformLogicalAnd](#)
- [OpGroupNonUniformLogicalOr](#)
- [OpGroupNonUniformLogicalXor](#)
- [OpGroupNonUniformQuadBroadcast](#)
- [OpGroupNonUniformQuadSwap](#)
- [OpGroupIAddNonUniformAMD](#)
- [OpGroupFAddNonUniformAMD](#)
- [OpGroupFMinNonUniformAMD](#)
- [OpGroupUMinNonUniformAMD](#)
- [OpGroupSMinNonUniformAMD](#)
- [OpGroupFMaxNonUniformAMD](#)
- [OpGroupUMaxNonUniformAMD](#)
- [OpGroupSMaxNonUniformAMD](#)

Scope	
0	CrossDevice Scope crosses multiple devices.
1	Device Scope is the current device.
2	Workgroup Scope is the current workgroup.
3	Subgroup Scope is the current subgroup.
4	Invocation Scope is the current Invocation .

3.28 Group Operation

Defines the class of workgroup or subgroup operation. Used by:

- [OpGroupIAdd](#)
- [OpGroupFAdd](#)

- OpGroupFMin
- OpGroupUMin
- OpGroupSMin
- OpGroupFMax
- OpGroupUMax
- OpGroupSMax
- OpGroupNonUniformBallotBitCount
- OpGroupNonUniformIAdd
- OpGroupNonUniformFAdd
- OpGroupNonUniformIMul
- OpGroupNonUniformFMul
- OpGroupNonUniformSMin
- OpGroupNonUniformUMin
- OpGroupNonUniformFMin
- OpGroupNonUniformSMax
- OpGroupNonUniformUMax
- OpGroupNonUniformFMax
- OpGroupNonUniformBitwiseAnd
- OpGroupNonUniformBitwiseOr
- OpGroupNonUniformBitwiseXor
- OpGroupNonUniformLogicalAnd
- OpGroupNonUniformLogicalOr
- OpGroupNonUniformLogicalXor
- OpGroupIAddNonUniformAMD
- OpGroupFAddNonUniformAMD
- OpGroupFMinNonUniformAMD
- OpGroupUMinNonUniformAMD
- OpGroupSMinNonUniformAMD
- OpGroupFMaxNonUniformAMD
- OpGroupUMaxNonUniformAMD
- OpGroupSMaxNonUniformAMD

Group Operation		Enabling Capabilities
0	Reduce A reduction operation for all values of a specific value X specified by invocations within a workgroup.	Kernel, GroupNonUniformArithmetic, GroupNonUniformBallot
1	InclusiveScan A binary operation with an identity I and n (where n is the size of the workgroup) elements $[a_0, a_1, \dots, a_{n-1}]$ resulting in $[a_0, (a_0 \text{ op } a_1), \dots, (a_0 \text{ op } a_1 \text{ op } \dots \text{ op } a_{n-1})]$	Kernel, GroupNonUniformArithmetic, GroupNonUniformBallot

Group Operation		Enabling Capabilities
2	ExclusiveScan A binary operation with an identity I and n (where n is the size of the workgroup) elements $[a_0, a_1, \dots, a_{n-1}]$ resulting in $[I, a_0, (a_0 \text{ op } a_1), \dots, (a_0 \text{ op } a_1 \text{ op } \dots \text{ op } a_{n-2})]$.	Kernel, GroupNonUniformArithmetic, GroupNonUniformBallot
3	ClusteredReduce	GroupNonUniformClustered Missing before version 1.3.

3.29 Kernel Enqueue Flags

Specify when the child kernel begins execution.

Note: Implementations are not required to honor this flag. Implementations may not schedule kernel launch earlier than the point specified by this flag, however. Used by [OpEnqueueKernel](#).

Kernel Enqueue Flags		Enabling Capabilities
0	NoWait Indicates that the enqueued kernels do not need to wait for the parent kernel to finish execution before they begin execution.	Kernel
1	WaitKernel Indicates that all work-items of the parent kernel must finish executing and all immediate side effects committed before the enqueued child kernel may begin execution. Note: Immediate meaning not side effects resulting from child kernels. The side effects would include stores to global memory and pipe reads and writes.	Kernel
2	WaitWorkGroup Indicates that the enqueued kernels wait only for the workgroup that enqueued the kernels to finish before they begin execution. Note: This acts as a memory synchronization point between work-items in a work-group and child kernels enqueued by work-items in the work-group.	Kernel

3.30 Kernel Profiling Info

Specify the profiling information to be queried. Used by [OpCaptureEventProfilingInfo](#).

This value is a mask; it can be formed by combining the bits from multiple rows in the table below.

Kernel Profiling Info		Enabling Capabilities
0x0	None	
0x1	CmdExecTime Indicates that the profiling info queried is the execution time.	Kernel

3.31 Capability

Capabilities a module can declare it uses. All used capabilities must be declared, either directly or through a dependency: all capabilities that a declared capability depends on are automatically implied.

The **Depends On** column lists the dependencies for each capability. These are the ones implicitly declared. It is not necessary (but allowed) to declare a dependency for a declared capability.

See the [capabilities](#) section for more detail. Used by [OpCapability](#).

	Capability	Depends On	Enabled by Extension
0	Matrix Uses OpTypeMatrix .		
1	Shader Uses Vertex , Fragment , or GLCompute Execution Models .	Matrix	
2	Geometry Uses the Geometry Execution Model .	Shader	
3	Tessellation Uses the TessellationControl or TessellationEvaluation Execution Models .	Shader	
4	Addresses Uses physical addressing, non-logical addressing modes.		
5	Linkage Uses partially linked modules and libraries.		
6	Kernel Uses the Kernel Execution Model .		
7	Vector16 Uses OpTypeVector to declare 8 component or 16 component vectors.	Kernel	
8	Float16Buffer Allows a 16-bit OpTypeFloat instruction for the sole purpose of creating an OpTypePointer to a 16-bit float. Pointers to a 16-bit float cannot be dereferenced directly, they must only be dereferenced via an extended instruction. All other uses of 16-bit OpTypeFloat are disallowed.	Kernel	
9	Float16 Uses OpTypeFloat to declare the 16-bit floating-point type.		
10	Float64 Uses OpTypeFloat to declare the 64-bit floating-point type.		
11	Int64 Uses OpTypeInt to declare 64-bit integer types.		
12	Int64Atomics Uses atomic instructions on 64-bit integer types.	Int64	

	Capability	Depends On	Enabled by Extension
13	ImageBasic Uses OpTypeImage or OpTypeSampler in a Kernel .	Kernel	
14	ImageReadWrite Uses OpTypeImage with the ReadWrite access qualifier.	ImageBasic	
15	ImageMipmap Uses non-zero Lod Image Operands .	ImageBasic	
17	Pipes Uses OpTypePipe , OpTypeReserveId or pipe instructions.	Kernel	
18	Groups Uses group instructions.		
19	DeviceEnqueue Uses OpTypeQueue , OpTypeDeviceEvent , and device side enqueue instructions.	Kernel	
20	LiteralSampler Samplers are made from literals within the module. See OpConstantSampler .	Kernel	
21	AtomicStorage Uses the AtomicCounter Storage Class , allowing use of only the OpAtomicLoad , OpAtomicIncrement , and OpAtomicDecrement instructions.	Shader	
22	Int16 Uses OpTypeInt to declare 16-bit integer types.		
23	TessellationPointSize Tessellation stage exports point size.	Tessellation	
24	GeometryPointSize Geometry stage exports point size	Geometry	
25	ImageGatherExtended Uses texture gather with non-constant or independent offsets	Shader	
27	StorageImageMultisample Uses multi-sample images for non-sampled images.	Shader	
28	UniformBufferArrayDynamicIndexing Block -decorated arrays in uniform storage classes use dynamically uniform indexing.	Shader	
29	SampledImageArrayDynamicIndexing Arrays of sampled images use dynamically uniform indexing.	Shader	
30	StorageBufferArrayDynamicIndexing Arrays in the StorageBuffer Storage Class , or BufferBlock -decorated arrays, use dynamically uniform indexing.	Shader	
31	StorageImageArrayDynamicIndexing Arrays of non-sampled images are accessed with dynamically uniform indexing.	Shader	
32	ClipDistance Uses the ClipDistance BuiltIn .	Shader	

	Capability	Depends On	Enabled by Extension
33	CullDistance Uses the CullDistance BuiltIn .	Shader	
34	ImageCubeArray Uses the Cube Dim with the <i>Arrayed</i> operand in OpTypeImage , without a sampler .	SampledCubeArray	
35	SampleRateShading Uses per-sample rate shading.	Shader	
36	ImageRect Uses the Rect Dim without a sampler .	SampledRect	
37	SampledRect Uses the Rect Dim with a sampler .	Shader	
38	GenericPointer Uses the Generic Storage Class .	Addresses	
39	Int8 Uses OpTypeInt to declare 8-bit integer types.	Kernel	
40	InputAttachment Uses the SubpassData Dim .	Shader	
41	SparseResidency Uses OpImageSparse... instructions.	Shader	
42	MinLod Uses the MinLod Image Operand .	Shader	
43	Sampled1D Uses the 1D Dim with a sampler .		
44	Image1D Uses the 1D Dim without a sampler .	Sampled1D	
45	SampledCubeArray Uses the Cube Dim with the <i>Arrayed</i> operand in OpTypeImage , with a sampler .	Shader	
46	SampledBuffer Uses the Buffer Dim with a sampler .		
47	ImageBuffer Uses the Buffer Dim without a sampler .	SampledBuffer	
48	ImageMSArray An <i>MS</i> operand in OpTypeImage indicates multisampled, used without a sampler .	Shader	
49	StorageImageExtendedFormats One of a large set of more advanced image formats are used, namely one of those in the Image Format table listed as requiring this capability.	Shader	
50	ImageQuery The sizes, number of samples, or lod, etc. are queried.	Shader	
51	DerivativeControl Uses fine or coarse-grained derivatives, e.g., OpDPdxFine .	Shader	
52	InterpolationFunction Uses one of the InterpolateAtCentroid , InterpolateAtSample , or InterpolateAtOffset GLSL.std.450 extended instructions.	Shader	

	Capability	Depends On	Enabled by Extension
53	TransformFeedback Uses the Xfb Execution Mode .	Shader	
54	GeometryStreams Uses multiple numbered streams for geometry-stage output.	Geometry	
55	StorageImageReadWithoutFormat OpImageRead can use the Unknown Image Format .	Shader	
56	StorageImageWriteWithoutFormat OpImageWrite can use the Unknown Image Format .	Shader	
57	MultiViewport Multiple viewports are used.	Geometry	
58	SubgroupDispatch Uses subgroup dispatch instructions.	DeviceEnqueue Missing before version 1.1.	
59	NamedBarrier Uses OpTypeNamedBarrier .	Kernel Missing before version 1.1.	
60	PipeStorage Uses OpTypePipeStorage .	Pipes Missing before version 1.1.	
61	GroupNonUniform	Missing before version 1.3.	
62	GroupNonUniformVote	GroupNonUniform Missing before version 1.3.	
63	GroupNonUniformArithmetic	GroupNonUniform Missing before version 1.3.	
64	GroupNonUniformBallot	GroupNonUniform Missing before version 1.3.	
65	GroupNonUniformShuffle	GroupNonUniform Missing before version 1.3.	
66	GroupNonUniformShuffleRelative	GroupNonUniform Missing before version 1.3.	
67	GroupNonUniformClustered	GroupNonUniform Missing before version 1.3.	

	Capability	Depends On	Enabled by Extension
68	GroupNonUniformQuad	GroupNonUniform Missing before version 1.3.	
4423	SubgroupBallotKHR	Reserved.	SPV_KHR_shader_ballot
4427	DrawParameters	Shader Missing before version 1.3.	SPV_KHR_shader_draw_parameters
4431	SubgroupVoteKHR	Reserved.	SPV_KHR_subgroup_vote
4433	StorageBuffer16BitAccess Allows 16-bit OpTypeFloat and OpTypeInt for the sole purpose of creating an OpTypePointer to a 16-bit floating-point or 16-bit integer member of an object. The object must be in the StorageBuffer Storage Class , or be in the Uniform storage class and have the BufferBlock decoration . An object of a 16-bit type produced by dereferencing such a pointer may be the result of a width-only conversion instruction (OpFConvert , OpSConvert , or OpUConvert) from a 32-bit type or of an OpLoad , and may be used as an operand to a width-only conversion instruction to a 32-bit type or as the object operand of an OpStore . Other uses of 16-bit types are not enabled by this capability.	Missing before version 1.3.	SPV_KHR_16bit_storage
4433	StorageUniformBufferBlock16	Missing before version 1.3.	SPV_KHR_16bit_storage
4434	UniformAndStorageBuffer16BitAccess Allows 16-bit OpTypeFloat and OpTypeInt for the sole purpose of creating an OpTypePointer to a 16-bit floating-point or 16-bit integer member of an object. The object must be in the StorageBuffer or Uniform Storage Classes . An object of a 16-bit type produced by dereferencing such a pointer may be the result of a width-only conversion instruction from a 32-bit type or of an OpLoad , and may be used as an operand to a width-only conversion instruction to a 32-bit type or as the object operand of an OpStore . Other uses of 16-bit types are not enabled by this capability.	StorageBuffer16BitAccess,SPV_KHR_16bit_storage StorageUniform-BufferBlock16 Missing before version 1.3.	

	Capability	Depends On	Enabled by Extension
4434	StorageUniform16	StorageBuffer16BitAccess , SPV_KHR_16bit_storage StorageUniformBlock16 Missing before version 1.3.	
4435	StoragePushConstant16 Allows 16-bit OpTypeFloat and OpTypeInt for the sole purpose of creating an OpTypePointer to a 16-bit floating-point or 16-bit integer object in the PushConstant Storage Class . An object of a 16-bit type produced by dereferencing such a pointer may only be the result of a width-only conversion instruction from a 32-bit type or of an OpLoad . Other uses of 16-bit types are not enabled by this capability.	Missing before version 1.3.	SPV_KHR_16bit_storage
4436	StorageInputOutput16 Allows 16-bit OpTypeFloat and OpTypeInt for the sole purpose of creating an OpTypePointer to a 16-bit floating-point or 16-bit integer object in the Input or Output Storage Classes . An object of a 16-bit type produced by dereferencing such a pointer may only be the result of a width-only conversion instruction from a 32-bit type or of an OpLoad , and may be used as an operand to a width-only conversion instruction to a 32-bit type or as the object operand of an OpStore . Other uses of 16-bit types are not enabled by this capability.	Missing before version 1.3.	SPV_KHR_16bit_storage
4437	DeviceGroup	Missing before version 1.3.	
4439	MultiView	Shader Missing before version 1.3.	SPV_KHR_multiview
4441	VariablePointersStorageBuffer Allow variable pointers , each confined to a single Block -decorated struct in the StorageBuffer storage class.	Shader Missing before version 1.3.	SPV_KHR_variable_pointers

	Capability	Depends On	Enabled by Extension
4442	VariablePointers Allow variable pointers .	VariablePointersStorageBlock Missing before version 1.3.	SPV_KHR_variable_pointers
4445	AtomicStorageOps	Reserved.	SPV_KHR_shader_atomic_counter_ops
4447	SampleMaskPostDepthCoverage	Reserved.	SPV_KHR_post_depth_coverage
5008	Float16ImageAMD	Shader Reserved.	SPV_AMD_gpu_shader_half_float_fetch
5009	ImageGatherBiasLodAMD	Shader Reserved.	SPV_AMD_texture_gather_bias_lod
5010	FragmentMaskAMD	Shader Reserved.	SPV_AMD_shader_fragment_mask
5013	StencilExportEXT	Shader Reserved.	SPV_EXT_shader_stencil_export
5015	ImageReadWriteLodAMD	Shader Reserved.	SPV_AMD_shader_image_load_store_lod
5249	SampleMaskOverrideCoverageNV	SampleRateShading Reserved.	SPV_NV_sample_mask_override_coverage
5251	GeometryShaderPassthroughNV	Geometry Reserved.	SPV_NV_geometry_shader_passthrough
5254	ShaderViewportIndexLayerEXT	MultiViewport Reserved.	SPV_EXT_shader_viewport_index_layer
5254	ShaderViewportIndexLayerNV	MultiViewport Reserved.	SPV_NV_viewport_array2
5255	ShaderViewportMaskNV	ShaderViewportIndexLayer Reserved.	SPV_NV_viewport_array2
5259	ShaderStereoViewNV	ShaderViewportMaskNV Reserved.	SPV_NV_stereo_view_rendering
5260	PerViewAttributesNV	MultiView Reserved.	SPV_NVX_multiview_per_view_attributes
5265	FragmentFullyCoveredEXT	Shader Reserved.	SPV_EXT_fragment_fully_covered
5568	SubgroupShuffleINTEL	Reserved.	SPV_INTEL_subgroups
5569	SubgroupBufferBlockIOINTEL	Reserved.	SPV_INTEL_subgroups
5570	SubgroupImageBlockIOINTEL	Reserved.	SPV_INTEL_subgroups

3.32 Instructions

Form for each instruction:

Opcode Name Instruction description. <i>Word Count</i> is the high-order 16 bits of word 0 of the instruction, holding its total WordCount . If the instruction takes a variable number of operands, <i>Word Count</i> will also say "+ variable", after stating the minimum size of the instruction. <i>Opcode</i> is the low-order 16 bits of word 0 of the instruction, holding its opcode enumerant. <i>Results</i> , when present, are any Result <id> or <i>Result Type</i> created by the instruction. Each one is always 32 bits. <i>Operands</i> , when present, are any literals, other instruction's <i>Result <id></i> , etc., consumed by the instruction. Each one is always 32 bits.			Capability Enabling Capabilities (when needed)
Word Count	<i>Opcode</i>	<i>Results</i>	<i>Operands</i>

3.32.1 Miscellaneous Instructions

OpNop This has no semantic impact and can safely be removed from a module.	
1	0

OpUndef Make an intermediate object whose value is undefined. <i>Result Type</i> is the type of object to make. Each consumption of <i>Result <id></i> yields an arbitrary, possibly different bit pattern or abstract value resulting in possibly different concrete, abstract, or opaque values.			
3	1	<id> <i>Result Type</i>	Result <id>

OpSizeOf Computes the run-time size of the type pointed to by <i>Pointer</i> <i>Result Type</i> must be a 32-bit integer type scalar. <i>Pointer</i> must point to a concrete type.		Capability: Addresses Missing before version 1.1.
---	--	--

4	321	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Pointer</i>
---	-----	-----------------------------------	--------------------------	-------------------------------

OpFragmentMaskFetchAMD TBD				Capability: FragmentMaskAMD Reserved.	
5	5011	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Image</i>	<i><id> Coordinate</i>

OpFragmentFetchAMD TBD				Capability: FragmentMaskAMD Reserved.		
6	5012	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Image</i>	<i><id> Coordinate</i>	<i><id> Fragment Index</i>

OpDecorateStringGOOGLE			Capability:
TBD			Reserved.
3	5632	<id> Target	Decoration

OpMemberDecorateStringGOOGLE TBD				Capability: Reserved.	
4	5633	<i><id> Struct Type</i>	<i>Literal Number Member</i>	Decoration	

3.32.2 Debug Instructions

OpSourceContinued

Continue specifying the *Source* text from the previous instruction. This has no semantic impact and can safely be removed from a module.

Continued Source is a continuation of the source text in the previous *Source*.

The previous instruction must be an [OpSource](#) or an **OpSourceContinued** instruction. As is true for all literal strings, the previous instruction's string was nul terminated. That terminating 0 word from the previous instruction is not part of the source text; the first character of *Continued Source* logically immediately follows the last character of *Source* before its nul.

2 + variable	2	Literal String <i>Continued Source</i>
--------------	---	---

OpSource

Document what [source language](#) and text this module was translated from. This has no semantic impact and can safely be removed from a module.

Version is the version of the source language. This literal operand is limited to a single [word](#).

File is an [OpString](#) instruction and is the source-level file name.

Source is the text of the source-level file.

Each client API describes what form the *Version* operand takes, per source language.

3 + variable	3	Source Language	Literal Number <i>Version</i>	Optional <id> <i>File</i>	Optional Literal String <i>Source</i>
--------------	---	---------------------------------	--	---------------------------------	---

OpSourceExtension

Document an extension to the source language. This has no semantic impact and can safely be removed from a module.

Extension is a string describing a source-language extension. Its form is dependent on the how the source language describes extensions.

2 + variable	4	Literal String <i>Extension</i>
--------------	---	--

OpName

Assign a name string to another instruction's *Result <id>*. This has no semantic impact and can safely be removed from a module.

Target is the *Result <id>* to assign a name to. It can be the *Result <id>* of any other instruction; a variable, function, type, intermediate result, etc.

Name is the string to assign.

3 + variable	5	<i><id></i> <i>Target</i>	Literal String <i>Name</i>
--------------	---	------------------------------------	---

OpMemberName

Assign a name string to a member of a structure type. This has no semantic impact and can safely be removed from a module.

Type is the *<id>* from an [OpTypeStruct](#) instruction.

Member is the number of the member to assign in the structure. The first member is member 0, the next is member 1, ... This literal operand is limited to a single [word](#).

Name is the string to assign to the member.

4 + variable	6	<i><id></i> <i>Type</i>	Literal Number <i>Member</i>	Literal String <i>Name</i>
--------------	---	----------------------------------	---	---

OpString

Assign a *Result <id>* to a string for use by other debug instructions (see [OpLine](#) and [OpSource](#)). This has no semantic impact and can safely be removed from a module. (Removal also requires removal of all instructions referencing *Result <id>*.)

String is the literal string being assigned a *Result <id>*.

3 + variable	7	Result <id>	Literal String <i>String</i>
--------------	---	-----------------------------------	---

OpLine

Add source-level location information. This has no semantic impact and can safely be removed from a module.

This location information applies to the instructions physically following this instruction, up to the first occurrence of any of the following: the next end of block, the next **OpLine** instruction, or the next **OpNoLine** instruction.

File must be an **OpString** instruction and is the source-level file name.

Line is the source-level line number. This literal operand is limited to a single **word**.

Column is the source-level column number. This literal operand is limited to a single **word**.

OpLine can generally immediately precede other instructions, with the following exceptions:

- it may not be used until after the **annotation** instructions, (see the **Logical Layout** section)
- cannot be the last instruction in a block, which is defined to end with a **termination instruction**
- if a branch **merge instruction** is used, the last **OpLine** in the block must be before its merge instruction

4	8	<id> <i>File</i>	Literal Number <i>Line</i>	Literal Number <i>Column</i>
---	---	---------------------	--------------------------------------	--

OpNoLine

Discontinue any source-level location information that might be active from a previous **OpLine** instruction. This has no semantic impact and can safely be removed from a module.

This instruction can only appear after the **annotation** instructions (see the **Logical Layout** section). It cannot be the last instruction in a block, or the second-to-last instruction if the block has a **merge instruction**. There is not a requirement that there is a preceding **OpLine** instruction.

1	317
---	-----

OpModuleProcessed

Document a process that was applied to a module. This has no semantic impact and can safely be removed from a module.

Process is a string describing a process and/or tool (processor) that did the processing. Its form is dependent on the processor.

Capability:

Missing before version 1.1.

2 + variable	330	Literal String <i>Process</i>
--------------	-----	---

3.32.3 Annotation Instructions

OpDecorate

Add a [Decoration](#) to another *<id>*.

Target is the *<id>* to decorate. It can potentially be any *<id>* that is a forward reference. A set of decorations can be grouped together by having multiple decoration instructions targeting the same [OpDecorationGroup](#) instruction.

This instruction is only valid when the *Decoration* operand is a [decoration](#) that takes no **Extra Operands**, or takes **Extra Operands** that are not *<id>* operands.

3 + variable	71	<i><id></i> <i>Target</i>	Decoration	<i>Literal, Literal, ...</i> See Decoration .
--------------	----	------------------------------------	----------------------------	--

OpMemberDecorate

Add a [Decoration](#) to a member of a structure type.

Structure type is the *<id>* of a type from [OpTypeStruct](#).

Member is the number of the member to decorate in the type. The first member is member 0, the next is member 1, ...

Note: See **OpDecorate** for creating groups of decorations for consumption by **OpGroupMemberDecorate**

4 + variable	72	<i><id></i> <i>Structure Type</i>	Literal Number <i>Member</i>	Decoration	<i>Literal, Literal, ...</i> See Decoration .
--------------	----	--	---	----------------------------	--

OpDecorationGroup

A collector for [Decorations](#) from [OpDecorate](#) and [OpDecorateId](#) instructions. All such decoration instructions targeting this **OpDecorationGroup** instruction must precede it. Subsequent [OpGroupDecorate](#) and [OpGroupMemberDecorate](#) instructions that consume this instruction's *Result <id>* will apply these decorations to their targets.

2	73	Result <id>
---	----	-----------------------------------

OpGroupDecorate

Add a group of [Decorations](#) to another *<id>*.

Decoration Group is the *<id>* of an [OpDecorationGroup](#) instruction.

Targets is a list of *<id>*s to decorate with the groups of decorations. The *Targets* list must not include the *<id>* of any [OpDecorationGroup](#) instruction.

2 + variable	74	<i><id></i> <i>Decoration Group</i>	<i><id>, <id>, ...</i> <i>Targets</i>
--------------	----	--	--

OpGroupMemberDecorate

Add a group of [Decorations](#) to members of structure types.

Decoration Group is the *<id>* of an [OpDecorationGroup](#) instruction.

Targets is a list of (*<id>*, *Member*) pairs to decorate with the groups of decorations. Each *<id>* in the pair must be a target structure type, and the associated *Member* is the number of the member to decorate in the type. The first member is member 0, the next is member 1, ...

2 + variable	75	<i><id></i> <i>Decoration Group</i>	<i><id></i> , <i>literal</i> , <i><id></i> , <i>literal</i> , ... <i>Targets</i>
--------------	----	--	---

OpDecorateId

Add a [Decoration](#) to another *<id>*, using *<id>*s as **Extra Operands**.

Target is the *<id>* to decorate. It can potentially be any *<id>* that is a forward reference. A set of decorations can be grouped together by having multiple decoration instructions targeting the same [OpDecorationGroup](#) instruction.

This instruction is only valid when the *Decoration* operand is a [decoration](#) that takes **Extra Operands** that are *<id>* operands. All such *<id>* **Extra Operands** must be [constant instructions](#).

[Capability](#):

[Missing before version 1.2.](#)

3 + variable	332	<i><id></i> <i>Target</i>	Decoration	<i><id></i> , <i><id></i> , ... See Decoration .
--------------	-----	------------------------------------	----------------------------	---

3.32.4 Extension Instructions

OpExtension Declare use of an extension to SPIR-V. This allows validation of additional instructions, tokens, semantics, etc. <i>Name</i> is the extension's name string.		
2 + variable	10	Literal String <i>Name</i>

OpExtInstImport Import an extended set of instructions. It can be later referenced by the <i>Result <id></i> . <i>Name</i> is the extended instruction-set's name string. There must be an external specification defining the semantics for this extended instruction set. See Extended Instruction Sets for more information.			
3 + variable	11	Result <id>	Literal String <i>Name</i>

OpExtInst Execute an instruction in an imported set of extended instructions. <i>Result Type</i> is as defined, per <i>Instruction</i> , in the external specification for <i>Set</i> . <i>Set</i> is the result of an OpExtInstImport instruction. <i>Instruction</i> is the enumerant of the instruction to execute within <i>Set</i> . This literal operand is limited to a single word . The semantics of the instruction must be defined in the external specification for <i>Set</i> . <i>Operand 1, ...</i> are the operands to the extended instruction.						
5 + variable	12	<id> <i>Result Type</i>	Result <id>	<id> <i>Set</i>	Literal Number <i>Instruction</i>	<id>, <id> , ... <i>Operand 1,</i> <i>Operand 2,</i> ...

3.32.5 Mode-Setting Instructions

OpMemoryModel

Set addressing model and memory model for the entire module.

Addressing Model selects the module's [Addressing Model](#).

Memory Model selects the module's memory model, see [Memory Model](#).

3	14	Addressing Model	Memory Model
---	----	----------------------------------	------------------------------

OpEntryPoint

Declare an [entry point](#) and its execution model.

Execution Model is the execution model for the entry point and its static call tree. See [Execution Model](#).

Entry Point must be the *Result* *<id>* of an [OpFunction](#) instruction.

Name is a name string for the entry point. A module cannot have two **OpEntryPoint** instructions with the same [Execution Model](#) and the same *Name* string.

Interface is a list of *<id>* of global [OpVariable](#) instructions with either **Input** or **Output** for its [Storage Class](#) operand. These declare the input/output interface of the entry point. They could be a subset of the input/output declarations of the module, and a superset of those referenced by the entry point's static call tree. It is invalid for the entry point's static call tree to reference such an *<id>* if it was not listed with this instruction.

Interface *<id>* are forward references. They allow declaration of all variables forming an interface for an entry point, whether or not all the variables are actually used by the entry point.

4 + variable	15	Execution Model	<i><id></i> <i>Entry Point</i>	Literal String <i>Name</i>	<i><id></i> , <i><id></i> , ... <i>Interface</i>
--------------	----	---------------------------------	---	---	---

OpExecutionMode

Declare an execution mode for an entry point.

Entry Point must be the *Entry Point* *<id>* operand of an [OpEntryPoint](#) instruction.

Mode is the execution mode. See [Execution Mode](#).

This instruction is only valid when the *Mode* operand is an [execution mode](#) that takes no **Extra Operands**, or takes **Extra Operands** that are not *<id>* operands.

3 + variable	16	<i><id></i> <i>Entry Point</i>	Execution Mode <i>Mode</i>	<i>Literal</i> , <i>Literal</i> , ... See Execution Mode
--------------	----	---	---	---

OpCapability Declare a capability used by this module. <i>Capability</i> is the capability declared by this instruction. There are no restrictions on the order in which capabilities are declared. See the capabilities section for more detail.		
2	17	Capability <i>Capability</i>

OpExecutionModeId Declare an execution mode for an entry point, using <i><id>s</i> as Extra Operands . <i>Entry Point</i> must be the <i>Entry Point</i> <i><id></i> operand of an OpEntryPoint instruction. <i>Mode</i> is the execution mode. See Execution Mode . This instruction is only valid when the <i>Mode</i> operand is an execution mode that takes Extra Operands that are <i><id></i> operands. All such <i><id></i> Extra Operands must be constant instructions .				Capability : Missing before version 1.2.
3 + variable	331	<i><id></i> <i>Entry Point</i>	Execution Mode <i>Mode</i>	<i><id></i> , <i><id></i> , ... See Execution Mode

3.32.6 Type-Declaration Instructions

OpTypeVoid		
Declare the void type.		
2	19	Result <id>

OpTypeBool		
<p>Declare the Boolean type. Values of this type can only be either true or false. There is no physical size or bit pattern defined for these values. If they are stored (in conjunction with OpVariable), they can only be used with logical addressing operations, not physical, and only with non-externally visible shader Storage Classes: Workgroup, CrossWorkgroup, Private, and Function.</p>		
2	20	Result <id>

OpTypeInt				
<p>Declare a new integer type.</p> <p><i>Width</i> specifies how many bits wide the type is. This literal operand is limited to a single word. The bit pattern of a signed integer value is two's complement.</p> <p><i>Signedness</i> specifies whether there are signed semantics to preserve or validate. 0 indicates unsigned, or no signedness semantics 1 indicates signed semantics.</p> <p>In all cases, the type of operation of an instruction comes from the instruction's opcode, not the signedness of the operands.</p>				
4	21	Result <id>	Literal Number <i>Width</i>	Literal Number <i>Signedness</i>

OpTypeFloat			
<p>Declare a new floating-point type.</p> <p><i>Width</i> specifies how many bits wide the type is. The bit pattern of a floating-point value is as described by the IEEE 754 standard.</p>			
3	22	Result <id>	Literal Number <i>Width</i>

OpTypeVector				
<p>Declare a new vector type.</p> <p><i>Component Type</i> is the type of each component in the resulting type. It must be a scalar type.</p> <p><i>Component Count</i> is the number of components in the resulting type. It must be at least 2.</p> <p>Components are numbered consecutively, starting with 0.</p>				
4	23	Result <id>	<id> <i>Component Type</i>	Literal Number <i>Component Count</i>

OpTypeMatrix Declare a new matrix type. <i>Column Type</i> is the type of each column in the matrix. It must be vector type. <i>Column Count</i> is the number of columns in the new matrix type. It must be at least 2. Matrix columns are numbered consecutively, starting with 0. This is true independently of any Decorations describing the memory layout of a matrix (e.g., RowMajor or MatrixStride).				Capability: Matrix
4	24	Result <id>	<id> <i>Column Type</i>	Literal Number <i>Column Count</i>

OpTypeImage

Declare a new [image](#) type. Consumed, for example, by [OpTypeSampledImage](#). This type is opaque: values of this type have no defined physical size or bit pattern.

Sampled Type is the type of the components that result from sampling or reading from this image type. Must be a scalar [numerical type](#) or [OpTypeVoid](#).

Dim is the image [dimensionality](#) (Dim).

Depth is whether or not this image is a depth image. (Note that whether or not depth comparisons are actually done is a property of the sampling opcode, not of this type declaration.)

0 indicates not a depth image

1 indicates a depth image

2 means no indication as to whether this is a depth or non-depth image

Arrayed must be one of the following indicated values:

0 indicates non-arrayed content

1 indicates arrayed content

MS must be one of the following indicated values:

0 indicates single-sampled content

1 indicates multisampled content

Sampled indicates whether or not this image will be accessed in combination with a [sampler](#), and must be one of the following values:

0 indicates this is only known at run time, not at compile time

1 indicates will be used with sampler

2 indicates will be used without a sampler (a storage image)

Image Format is the [Image Format](#), which can be **Unknown**, depending on the client API.

If *Dim* is **SubpassData**, *Sampled* must be 2, *Image Format* must be **Unknown**, and the [Execution Model](#) must be **Fragment**.

Access Qualifier is an image [Access Qualifier](#).

9 + variable	25	Result <id>	<id> <i>Sampled Type</i>	Dim	Literal Number <i>Depth</i>	Literal Number <i>Arrayed</i>	Literal Number <i>MS</i>	Literal Number <i>Sampled</i>	Image Format	Optional Access Quali- fier
-----------------	----	--	---	---------------------	--	--	---	--	----------------------------------	--

OpTypeSampler

Declare the [sampler](#) type. Consumed by [OpSampledImage](#). This type is opaque: values of this type have no defined physical size or bit pattern.

2	26	Result <id>
---	----	---

OpTypeSampledImage

Declare a [sampled image](#) type, the *Result Type* of [OpSampledImage](#), or an externally combined sampler and image. This type is opaque: values of this type have no defined physical size or bit pattern.

Image Type must be an [OpTypeImage](#). It is the type of the image in the combined sampler and image type.

3	27	Result <id>	<id> <i>Image Type</i>
---	----	-------------	---------------------------

OpTypeArray

Declare a new array type: a dynamically-indexable ordered aggregate of elements all having the same type.

Element Type is the type of each element in the array.

Length is the number of elements in the array. It must be at least 1. *Length* must come from a [constant instruction](#) of an [integer-type](#) scalar whose value is at least 1.

Array elements are number consecutively, starting with 0.

4	28	Result <id>	<id> <i>Element Type</i>	<id> <i>Length</i>
---	----	-------------	-----------------------------	-----------------------

OpTypeRuntimeArray

Declare a new run-time array type. Its length is not known at compile time.

Element Type is the type of each element in the array. It must be a [concrete](#) type.

See [OpArrayLength](#) for getting the *Length* of an array of this type.

[Objects](#) of this type can only be created with [OpVariable](#) using the **StorageBuffer** or **Uniform Storage Classes**.

[Capability:](#)
Shader

3	29	Result <id>	<id> <i>Element Type</i>
---	----	-------------	-----------------------------

OpTypeStruct

Declare a new structure type: an aggregate of zero or more potentially heterogeneous members.

Member N type is the type of member *N* of the structure. The first member is member 0, the next is member 1, ...

If an operand is not yet defined, it must be defined by an [OpTypePointer](#), where the type pointed to is an **OpTypeStruct**.

2 + variable	30	Result <id>	<id>, <id>, ... <i>Member 0 type,</i> <i>member 1 type,</i> ...
--------------	----	-------------	--

OpTypeOpaque			Capability: Kernel
Declare a structure type with no body specified.			
3 + variable	31	Result <id>	Literal String The name of the opaque type.

OpTypePointer				
Declare a new pointer type.				
<p><i>Storage Class</i> is the Storage Class of the memory holding the object pointed to. If there was a forward reference to this type from an OpTypeForwardPointer, the <i>Storage Class</i> of that instruction must equal the <i>Storage Class</i> of this instruction.</p> <p><i>Type</i> is the type of the object pointed to.</p>				
4	32	Result <id>	Storage Class	<id> <i>Type</i>

OpTypeFunction				
Declare a new function type.				
<p>OpFunction will use this to declare the return type and parameter types of a function. OpFunction is the only valid use of OpTypeFunction.</p> <p><i>Return Type</i> is the type of the return value of functions of this type. It must be a concrete or abstract type, or a pointer to such a type. If the function has no return value, <i>Return Type</i> must be OpTypeVoid.</p> <p><i>Parameter N Type</i> is the type <id> of the type of parameter <i>N</i>.</p>				
3 + variable	33	Result <id>	<id> <i>Return Type</i>	<id>, <id>, ... <i>Parameter 0 Type</i> , <i>Parameter 1 Type</i> , ...

OpTypeEvent		Capability: Kernel
Declare an OpenCL event type.		
2	34	Result <id>

OpTypeDeviceEvent		Capability: DeviceEnqueue
Declare an OpenCL device-side event type.		
2	35	Result <id>

OpTypeReserveId		Capability: Pipes
Declare an OpenCL reservation id type.		
2	36	Result <id>

OpTypeQueue		Capability: DeviceEnqueue
Declare an OpenCL queue type.		
2	37	Result <id>

OpTypePipe		Capability: Pipes
Declare an OpenCL pipe type.		
<i>Qualifier</i> is the pipe access qualifier.		
3	38	Result <id> Access Qualifier <i>Qualifier</i>

OpTypeForwardPointer			Capability: Addresses
Declare the Storage Class for a forward reference to a pointer.			
<i>Pointer Type</i> is a forward reference to the result of an OpTypePointer . The type of object the pointer points to is declared by the OpTypePointer instruction, not this instruction. Subsequent OpTypeStruct instructions can use <i>Pointer Type</i> as an operand.			
<i>Storage Class</i> is the Storage Class of the memory holding the object pointed to.			
3	39	<i><id></i> <i>Pointer Type</i>	Storage Class

OpTypePipeStorage		Capability: PipeStorage
Declare the OpenCL pipe-storage type.		Missing before version 1.1.
2	322	Result <id>

OpTypeNamedBarrier		Capability: NamedBarrier
Declare the named-barrier type.		Missing before version 1.1.
2	327	Result <id>

3.32.7 Constant-Creation Instructions

OpConstantTrue Declare a true Boolean-type scalar constant. <i>Result Type</i> must be the scalar Boolean type.			
3	41	<i><id></i> <i>Result Type</i>	Result <i><id></i>

OpConstantFalse Declare a false Boolean-type scalar constant. <i>Result Type</i> must be the scalar Boolean type.			
3	42	<i><id></i> <i>Result Type</i>	Result <i><id></i>

OpConstant Declare a new integer-type or floating-point-type scalar constant. <i>Result Type</i> must be a scalar integer type or floating-point type. <i>Value</i> is the bit pattern for the constant. Types 32 bits wide or smaller take one word. Larger types take multiple words, with low-order words appearing first.				
3 + variable	43	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i>Literal, Literal, ...</i> <i>Value</i>

OpConstantComposite Declare a new composite constant. <i>Result Type</i> must be a composite type, whose top-level members/elements/components/columns have the same type as the types of the <i>Constituents</i> . The ordering must be the same between the top-level types in <i>Result Type</i> and the <i>Constituents</i> . <i>Constituents</i> will become members of a structure, or elements of an array, or components of a vector, or columns of a matrix. There must be exactly one <i>Constituent</i> for each top-level member/element/component/column of the result. The <i>Constituents</i> must appear in the order needed by the definition of the <i>Result Type</i> . The <i>Constituents</i> must all be <i><id></i> s of other constant declarations or an OpUndef .				
3 + variable	44	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id>, <id>, ...</i> <i>Constituents</i>

OpConstantSampler Declare a new sampler constant. <i>Result Type</i> must be OpTypeSampler . <i>Sampler Addressing Mode</i> is the addressing mode; a literal from Sampler Addressing Mode . <i>Param</i> is one of: 0: Non Normalized 1: Normalized <i>Sampler Filter Mode</i> is the filter mode; a literal from Sampler Filter Mode .					Capability: LiteralSampler	
6	45	<id> <i>Result Type</i>	Result <id>	Sampler Addressing Mode	Literal Number <i>Param</i>	Sampler Filter Mode

OpConstantNull Declare a new <i>null</i> constant value. The <i>null</i> value is type dependent, defined as follows: - Scalar Boolean: false - Scalar integer: 0 - Scalar floating point: +0.0 (all bits 0) - All other scalars: Abstract - Composites: Members are set recursively to the null constant according to the null value of their constituent types. <i>Result Type</i> must be one of the following types: - Scalar or vector Boolean type - Scalar or vector integer type - Scalar or vector floating-point type - Pointer type - Event type - Device side event type - Reservation id type - Queue type - Composite type						
3	46	<id> <i>Result Type</i>	Result <id>			

OpSpecConstantTrue

Declare a [Boolean-type](#) scalar specialization constant with a default value of **true**.

This instruction can be specialized to become either an [OpConstantTrue](#) or [OpConstantFalse](#) instruction.

Result Type must be the scalar [Boolean type](#).

See [Specialization](#).

3	48	<i><id></i> <i>Result Type</i>	Result <id>
---	----	---	-----------------------------------

OpSpecConstantFalse

Declare a [Boolean-type](#) scalar specialization constant with a default value of **false**.

This instruction can be specialized to become either an [OpConstantTrue](#) or [OpConstantFalse](#) instruction.

Result Type must be the scalar [Boolean type](#).

See [Specialization](#).

3	49	<i><id></i> <i>Result Type</i>	Result <id>
---	----	---	-----------------------------------

OpSpecConstant

Declare a new [integer-type](#) or [floating-point-type](#) scalar specialization constant.

Result Type must be a scalar [integer type](#) or [floating-point type](#).

Value is the bit pattern for the default value of the constant. Types 32 bits wide or smaller take one word. Larger types take multiple words, with low-order words appearing first.

This instruction can be specialized to become an [OpConstant](#) instruction.

See [Specialization](#).

3 + variable	50	<i><id></i> <i>Result Type</i>	Result <id>	<i>Literal, Literal, ...</i> <i>Value</i>
--------------	----	---	-----------------------------------	--

OpSpecConstantComposite

Declare a new [composite](#) specialization constant.

Result Type must be a [composite](#) type, whose top-level members/elements/components/columns have the same type as the types of the *Constituents*. The ordering must be the same between the top-level types in *Result Type* and the *Constituents*.

Constituents will become members of a structure, or elements of an array, or components of a vector, or columns of a matrix. There must be exactly one *Constituent* for each top-level member/element/component/column of the result. The *Constituents* must appear in the order needed by the definition of the type of the result. The *Constituents* must be the *<id>* of other specialization constant or constant declarations.

This instruction will be specialized to an [OpConstantComposite](#) instruction.

See [Specialization](#).

3 + variable	51	<i><id></i> <i>Result Type</i>	Result <id>	<i><id>, <id>, ...</i> <i>Constituents</i>
--------------	----	---	-----------------------------------	---

OpSpecConstantOp

Declare a new specialization constant that results from doing an operation.

Result Type must be the type required by the *Result Type* of *Opcode*.

Opcode must be one of the following opcodes. This literal operand is limited to a single [word](#).

OpSConvert, OpFConvert
OpSNegate, OpNot
OpIAdd, OpISub
OpIMul, OpUDiv, OpSDiv, OpUMod, OpSRem, OpSMod
OpShiftRightLogical, OpShiftRightArithmetic, OpShiftLeftLogical
OpBitwiseOr, OpBitwiseXor, OpBitwiseAnd
OpVectorShuffle, OpCompositeExtract, OpCompositeInsert
OpLogicalOr, OpLogicalAnd, OpLogicalNot,
OpLogicalEqual, OpLogicalNotEqual
OpSelect
OpIEqual, OpINotEqual
OpULessThan, OpSLessThan
OpUGreaterThan, OpSGreaterThan
OpULEssThanEqual, OpSLEssThanEqual
OpUGreaterThanEqual, OpSGreaterThanEqual

If the **Shader** capability was declared, the following opcode is also valid:

OpQuantizeToF16

If the **Kernel** capability was declared, the following opcodes are also valid:

OpConvertFToS, OpConvertSToF
OpConvertFToU, OpConvertUToF
OpUConvert
OpConvertPtrToU, OpConvertUToPtr
OpGenericCastToPtr, OpPtrCastToGeneric
OpBitcast
OpFNegate
OpFAdd, OpFSub
OpFMul, OpFDiv
OpFRem, OpFMod
OpAccessChain, OpInBoundsAccessChain
OpPtrAccessChain, OpInBoundsPtrAccessChain

Operands are the operands required by *opcode*, and satisfy the semantics of *opcode*. In addition, all *Operands* must be either:

- the *<id>*s of other [constant instructions](#), or
- **OpUndef**, when allowed by *opcode*, or
- for the **AccessChain** named opcodes, their *Base* is allowed to be a global (module scope) [OpVariable](#) instruction.

See [Specialization](#).

4 + variable	52	<i><id></i> <i>Result Type</i>	Result <id>	Literal Number <i>Opcode</i>	<i><id>, <id>, ...</i> <i>Operands</i>
--------------	----	---	-----------------------------------	---	---

3.32.8 Memory Instructions

OpVariable

Allocate an object in memory, resulting in a pointer to it, which can be used with [OpLoad](#) and [OpStore](#).

Result Type must be an [OpTypePointer](#). Its *Type* operand is the type of object in memory. Its *Storage Class* operand must be the same as the *Storage Class* operand of the result type.

Storage Class is the [Storage Class](#) of the memory holding the object. It cannot be **Generic**.

Initializer is optional. If *Initializer* is present, it will be the initial value of the variable's memory content. *Initializer* must be an *<id>* from a [constant instruction](#) or a global (module scope) [OpVariable](#) instruction. *Initializer* must have the same type as the type pointed to by *Result Type*.

4 + variable	59	<i><id></i> <i>Result Type</i>	Result <id>	Storage Class	Optional <i><id></i> <i>Initializer</i>
--------------	----	---	-----------------------------------	-------------------------------	---

OpImageTexelPointer

Form a pointer to a texel of an image. Use of such a pointer is limited to atomic operations.

Result Type must be an [OpTypePointer](#) whose *Storage Class* operand is **Image**. Its *Type* operand must be a scalar [numerical type](#) or [OpTypeVoid](#).

Image must have a type of [OpTypePointer](#) with *Type* [OpTypeImage](#). The *Sampled Type* of the type of *Image* must be the same as the *Type* pointed to by *Result Type*. The *Dim* operand of *Type* cannot be **SubpassData**.

Coordinate and *Sample* specify which texel and sample within the image to form a pointer to.

Coordinate must be a scalar or vector of [integer type](#). It must have the number of components specified below, given the following *Arrayed* and *Dim* operands of the type of the [OpTypeImage](#).

If *Arrayed* is 0:

1D: scalar

2D: 2 components

3D: 3 components

Cube: 3 components

Rect: 2 components

Buffer: scalar

If *Arrayed* is 1:

1D: 2 components

2D: 3 components

Cube: 3 components; the face and layer combine into the 3rd component, *layer_face*, such that face is *layer_face* % 6 and layer is floor(*layer_face* / 6)

Sample must be an [integer type](#) scalar. It specifies which sample to select at the given coordinate. It must be a valid *<id>* for the value 0 if the [OpTypeImage](#) has *MS* of 0.

6	60	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Image</i>	<i><id></i> <i>Coordinate</i>	<i><id></i> <i>Sample</i>
---	----	---	-----------------------------------	-----------------------------------	--	------------------------------------

OpLoad

Load through a pointer.

Result Type is the type of the loaded object.

Pointer is the pointer to load through. Its type must be an [OpTypePointer](#) whose *Type* operand is the same as *Result Type*.

Memory Access must be a [Memory Access](#) literal. If not present, it is the same as specifying **None**.

4 + variable	61	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Pointer</i>	Optional Memory Access
--------------	----	---	-----------------------------------	-------------------------------------	---

OpStore

Store through a pointer.

Pointer is the pointer to store through. Its type must be an [OpTypePointer](#) whose *Type* operand is the same as the type of *Object*.

Object is the object to store.

Memory Access must be a [Memory Access](#) literal. If not present, it is the same as specifying **None**.

3 + variable	62	<i><id></i> <i>Pointer</i>	<i><id></i> <i>Object</i>	Optional Memory Access
--------------	----	-------------------------------------	------------------------------------	---

OpCopyMemory

Copy from the memory pointed to by *Source* to the memory pointed to by *Target*. Both operands must be non-void pointers of the same type. Matching Storage Class is not required. The amount of memory copied is the size of the type pointed to.

Memory Access must be a [Memory Access](#) literal. If not present, it is the same as specifying **None**.

3 + variable	63	<i><id></i> <i>Target</i>	<i><id></i> <i>Source</i>	Optional Memory Access
--------------	----	------------------------------------	------------------------------------	---

OpCopyMemorySized Copy from the memory pointed to by <i>Source</i> to the memory pointed to by <i>Target</i> . <i>Size</i> is the number of bytes to copy. It must have a scalar integer type . If it is a constant instruction , the constant value cannot be 0. It is invalid for both the constant's type to have <i>Signedness</i> of 1 and to have the sign bit set. Otherwise, as a run-time value, <i>Size</i> is treated as unsigned, and if its value is 0, no memory access will be made. <i>Memory Access</i> must be a Memory Access literal. If not present, it is the same as specifying None .					Capability: Addresses
4 + variable	64	<id> <i>Target</i>	<id> <i>Source</i>	<id> <i>Size</i>	Optional Memory Access

OpAccessChain Create a pointer into a composite object that can be used with OpLoad and OpStore . <i>Result Type</i> must be an OpTypePointer . Its <i>Type</i> operand must be the type reached by walking the <i>Base</i> 's type hierarchy down to the last provided index in <i>Indexes</i> , and its <i>Storage Class</i> operand must be the same as the Storage Class of <i>Base</i> . <i>Base</i> must be a pointer, pointing to the base of a composite object. <i>Indexes</i> walk the type hierarchy to the desired depth, potentially down to scalar granularity. The first index in <i>Indexes</i> will select the top-level member/element/component/element of the base composite. All composite constituents use zero-based numbering, as described by their OpType... instruction. The second index will apply similarly to that result, and so on. Once any non-composite type is reached, there must be no remaining (unused) indexes. Each of the <i>Indexes</i> must: <ul style="list-style-type: none"> - be a scalar integer type, - be an OpConstant when indexing into a structure. 					
4 + variable	65	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id>, <id>, ... <i>Indexes</i>

OpInBoundsAccessChain Has the same semantics as OpAccessChain , with the addition that the resulting pointer is known to point within the base object.					
4 + variable	66	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id>, <id>, ... <i>Indexes</i>

OpPtrAccessChain Has the same semantics as OpAccessChain , with the addition of the <i>Element</i> operand. <i>Element</i> is used to do the initial dereference of <i>Base</i> : <i>Base</i> is treated as the address of the first element of an array, and the <i>Element</i> element's address is computed to be the base for the <i>Indexes</i> , as per OpAccessChain . The type of <i>Base</i> after being dereferenced with <i>Element</i> is still the same as the original type of <i>Base</i> . When the type of <i>Base</i> is decorated with ArrayStride , this array is dereferenced as an array whose stride is the <i>Base</i> -type's <i>Array Stride</i> . Note: If <i>Base</i> is originally typed to be a pointer an array, and the desired operation is to select an element of that array, OpAccessChain should be directly used, as its first <i>Index</i> will select the array element.					Capability: Addresses, VariablePointers, VariablePointersStorageBuffer	
5 + variable	67	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Element</i>	<id>, <id>, ... <i>Indexes</i>

OpArrayLength Length of a run-time array. <i>Result Type</i> must be an OpTypeInt with 32-bit <i>Width</i> and 0 <i>Signedness</i> . <i>Structure</i> must be a pointer to an OpTypeStruct whose last member is a run-time array. <i>Array member</i> is the index of the last member of the structure that <i>Structure</i> points to. That member's type must be from OpTypeRuntimeArray .					Capability: Shader	
5	68	<id> <i>Result Type</i>	Result <id>	<id> <i>Structure</i>	Literal Number <i>Array member</i>	

OpGenericPtrMemSemantics				Capability: Kernel
Result is a valid Memory Semantics which includes mask bits set for the Storage Class for the specific (non-Generic) Storage Class of <i>Pointer</i> .				
<i>Pointer</i> must point to Generic Storage Class .				
<i>Result Type</i> must be an OpTypeInt with 32-bit <i>Width</i> and 0 <i>Signedness</i> .				
4	69	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>

OpInBoundsPtrAccessChain Has the same semantics as OpPtrAccessChain , with the addition that the resulting pointer is known to point within the base object.					Capability: Addresses	
5 + variable	70	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Element</i>	<id>, <id>, ... <i>Indexes</i>

3.32.9 Function Instructions

OpFunction					
Add a function. This instruction must be immediately followed by one OpFunctionParameter instruction per each formal parameter of this function. This function’s body or declaration will terminate with the next OpFunctionEnd instruction.					
The <i>Result <id></i> cannot be used generally by other instructions. It can only be used by OpFunctionCall , OpEntryPoint , and decoration instructions.					
<i>Result Type</i> must be the same as the <i>Return Type</i> declared in <i>Function Type</i> .					
<i>Function Type</i> is the result of an OpTypeFunction , which declares the types of the return value and parameters of the function.					
5	54	<id> <i>Result Type</i>	Result <id>	Function Control	<id> <i>Function Type</i>

OpFunctionParameter			
Declare a formal parameter of the current function.			
<i>Result Type</i> is the type of the parameter.			
This instruction must immediately follow an OpFunction or OpFunctionParameter instruction. The order of contiguous OpFunctionParameter instructions is the same order arguments will be listed in an OpFunctionCall instruction to this function. It is also the same order in which <i>Parameter Type</i> operands are listed in the OpTypeFunction of the <i>Function Type</i> operand for this function’s OpFunction instruction.			
3	55	<id> <i>Result Type</i>	Result <id>

OpFunctionEnd	
Last instruction of a function.	
1	56

OpFunctionCall

Call a function.

Result Type is the type of the return value of the function. It must be the same as the *Return Type* operand of the *Function Type* operand of the *Function* operand.

Function is an [OpFunction](#) instruction. This could be a forward reference.

Argument N is the object to copy to parameter *N* of *Function*.

Note: A forward call is possible because there is no missing type information: *Result Type* must match the *Return Type* of the function, and the calling argument types must match the formal parameter types.

4 + variable	57	<id> <i>Result Type</i>	Result <id>	<id> <i>Function</i>	<id>, <id>, ... <i>Argument 0</i> , <i>Argument 1</i> , ...
--------------	----	----------------------------	-----------------------------------	-------------------------	--

3.32.10 Image Instructions

OpSampledImage

Create a **sampled image**, containing both a **sampler** and an **image**.

Result Type must be the **OpTypeSampledImage** type.

Image is an object whose type is an **OpTypeImage**, whose *Sampled* operand is 0 or 1, and whose **Dim** operand is not **SubpassData**.

Sampler must be an object whose type is **OpTypeSampler**.

5	86	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	<id> <i>Sampler</i>
---	----	----------------------------	--------------------	----------------------	------------------------

OpImageSampleImplicitLod

Sample an image with an implicit level of detail.

Result Type must be a vector of four components of **floating-point type** or **integer type**. Its components must be the same as *Sampled Type* of the underlying **OpTypeImage** (unless that underlying *Sampled Type* is **OpTypeVoid**).

Sampled Image must be an object whose type is **OpTypeSampledImage**.

Coordinate must be a scalar or vector of **floating-point type**. It contains (u , v) ... [z , $array\ layer$]) as needed by the definition of *Sampled Image*. It may be a vector larger than needed, but all unused components will appear after all used components.

Image Operands encodes what operands follow, as per **Image Operands**.

This instruction is only valid in the **Fragment Execution Model**. In addition, it consumes an implicit derivative that can be affected by code motion.

Capability:
Shader

5 + variable	87	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	Optional Image Operands	Optional <id>, <id>, ...
--------------	----	----------------------------	--------------------	------------------------------	---------------------------	-----------------------------------	-----------------------------

OpImageSampleExplicitLod

Sample an image using an explicit level of detail.

Result Type must be a vector of four components of [floating-point type](#) or [integer type](#). Its components must be the same as *Sampled Type* of the underlying [OpTypeImage](#) (unless that underlying *Sampled Type* is **OpTypeVoid**).

Sampled Image must be an object whose type is [OpTypeSampledImage](#).

Coordinate must be a scalar or vector of [floating-point type](#) or [integer type](#). It contains (u , v) ... [$array\ layer$]) as needed by the definition of *Sampled Image*. Unless the **Kernel capability** is being used, it must be floating point. It may be a vector larger than needed, but all unused components will appear after all used components.

Image Operands encodes what operands follow, as per [Image Operands](#). At least one operand setting the level of detail must be present.

7 + variable	88	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	Image Operands	<id>	Optional <id>, <id>, ...
-----------------	----	--------------------------------	--	----------------------------------	---------------------------	------------------------------------	------	--------------------------------

OpImageSampleDrefImplicitLod

Sample an image doing depth-comparison with an implicit level of detail.

Result Type must be a scalar of [integer type](#) or [floating-point type](#). It must be the same as *Sampled Type* of the underlying [OpTypeImage](#).

Sampled Image must be an object whose type is [OpTypeSampledImage](#).

Coordinate must be a scalar or vector of [floating-point type](#). It contains (u , v) ... [$array\ layer$]) as needed by the definition of *Sampled Image*. It may be a vector larger than needed, but all unused components will appear after all used components.

D_{ref} is the depth-comparison reference value.

Image Operands encodes what operands follow, as per [Image Operands](#).

This instruction is only valid in the **Fragment Execution Model**. In addition, it consumes an implicit derivative that can be affected by code motion.

[Capability:](#)
Shader

6 + variable	89	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> D_{ref}	Optional Image Operands	Optional <id>, <id>, ...
-----------------	----	--------------------------------	--	----------------------------------	---------------------------	-------------------	--	--------------------------------

OpImageSampleDrefExplicitLod Sample an image doing depth-comparison using an explicit level of detail. <i>Result Type</i> must be a scalar of integer type or floating-point type . It must be the same as <i>Sampled Type</i> of the underlying OpTypeImage . <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains (u , v) ... [$array\ layer$]) as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. D_{ref} is the depth-comparison reference value. <i>Image Operands</i> encodes what operands follow, as per Image Operands . At least one operand setting the level of detail must be present.								Capability: Shader	
8 + variable	90	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> D_{ref}	Image Operands	<id>	Optional <id>, <id>, ...

OpImageSampleProjImplicitLod Sample an image with with a project coordinate and an implicit level of detail. <i>Result Type</i> must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . The <i>Dim</i> operand of the underlying OpTypeImage must be 1D , 2D , 3D , or Rect , and the <i>Arrayed</i> and <i>MS</i> operands must be 0. <i>Coordinate</i> is a floating-point vector containing (u [, v] [, w], q), as needed by the definition of <i>Sampled Image</i> , with the q component consumed for the projective division. That is, the actual sample coordinate will be (u/q [, v/q] [, w/q]), as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. <i>Image Operands</i> encodes what operands follow, as per Image Operands . This instruction is only valid in the Fragment Execution Model . In addition, it consumes an implicit derivative that can be affected by code motion.						Capability: Shader	
5 + variable	91	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Sampled Image</i>	<i><id></i> <i>Coordinate</i>	Optional Image Operands	Optional <i><id></i> , <i><id></i> , ...

OpImageSampleProjExplicitLod Sample an image with a project coordinate using an explicit level of detail. <i>Result Type</i> must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . The <i>Dim</i> operand of the underlying OpTypeImage must be 1D , 2D , 3D , or Rect , and the <i>Arrayed</i> and <i>MS</i> operands must be 0. <i>Coordinate</i> is a floating-point vector containing (<i>u</i> [, <i>v</i>] [, <i>w</i>], <i>q</i>), as needed by the definition of <i>Sampled Image</i> , with the <i>q</i> component consumed for the projective division. That is, the actual sample coordinate will be (<i>u</i> / <i>q</i> [, <i>v</i> / <i>q</i>] [, <i>w</i> / <i>q</i>]), as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. <i>Image Operands</i> encodes what operands follow, as per Image Operands . At least one operand setting the level of detail must be present.							Capability: Shader	
7 + variable	92	< <i>id</i> > <i>Result Type</i>	Result <id>	< <i>id</i> > <i>Sampled Image</i>	< <i>id</i> > <i>Coordinate</i>	Image Operands	< <i>id</i> >	Optional < <i>id</i> >, ... < <i>id</i> >, ...

OpImageSampleProjDrefImplicitLod Sample an image with a project coordinate, doing depth-comparison, with an implicit level of detail. <i>Result Type</i> must be a scalar of integer type or floating-point type . It must be the same as <i>Sampled Type</i> of the underlying OpTypeImage . <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . The Dim operand of the underlying OpTypeImage must be 1D , 2D , 3D , or Rect , and the <i>Arrayed</i> and <i>MS</i> operands must be 0. <i>Coordinate</i> is a floating-point vector containing $(u \text{ [, } v \text{ [, } w \text{] , } q)$, as needed by the definition of <i>Sampled Image</i> , with the q component consumed for the projective division. That is, the actual sample coordinate will be $(u/q \text{ [, } v/q \text{ [, } w/q \text{]})$, as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. D_{ref} / q is the depth-comparison reference value. <i>Image Operands</i> encodes what operands follow, as per Image Operands . This instruction is only valid in the Fragment Execution Model . In addition, it consumes an implicit derivative that can be affected by code motion.							Capability: Shader	
6 + variable	93	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> D_{ref}	Optional Image Operands	Optional <id>, ... <id>, ...

OpImageSampleProjDrefExplicitLod Sample an image with a project coordinate, doing depth-comparison, using an explicit level of detail. <i>Result Type</i> must be a scalar of integer type or floating-point type . It must be the same as <i>Sampled Type</i> of the underlying OpTypeImage . <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . The <i>Dim</i> operand of the underlying OpTypeImage must be 1D , 2D , 3D , or Rect , and the <i>Arrayed</i> and <i>MS</i> operands must be 0. <i>Coordinate</i> is a floating-point vector containing (u [, v] [, w], q), as needed by the definition of <i>Sampled Image</i> , with the q component consumed for the projective division. That is, the actual sample coordinate will be (u/q [, v/q] [, w/q]), as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. D_{ref}/q is the depth-comparison reference value. <i>Image Operands</i> encodes what operands follow, as per Image Operands . At least one operand setting the level of detail must be present.								Capability: Shader	
8 + variable	94	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> D_{ref}	Image Operands	<id>	Optional <id>, <id>, ...

OpImageFetch

Fetch a single texel from a sampled image.

Result Type must be a vector of four components of [floating-point type](#) or [integer type](#). Its components must be the same as *Sampled Type* of the underlying [OpTypeImage](#) (unless that underlying *Sampled Type* is **OpTypeVoid**).

Image must be an object whose type is [OpTypeImage](#). Its *Dim* operand cannot be **Cube**, and its *Sampled* operand must be 1.

Coordinate is an integer scalar or vector containing (u [, v] ... [, *array layer*]) as needed by the definition of *Sampled Image*.

Image Operands encodes what operands follow, as per [Image Operands](#).

5 + variable	95	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	<id> <i>Coordinate</i>	Optional Image Operands	Optional <id>, <id>, ...
--------------	----	----------------------------	-----------------------------	----------------------	---------------------------	--	-----------------------------

OpImageGather Gathers the requested component from four texels. <i>Result Type</i> must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). It has one component per gathered texel. <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . Its OpTypeImage must have a Dim of 2D , Cube , or Rect . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of <i>Sampled Image</i> . <i>Component</i> is the component number that will be gathered from all four texels. It must be 0, 1, 2 or 3. <i>Image Operands</i> encodes what operands follow, as per Image Operands .							Capability: Shader	
6 + variable	96	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> <i>Component</i>	Optional Image Operands	Optional <id>, <id>, ...

OpImageDrefGather Gathers the requested depth-comparison from four texels. <i>Result Type</i> must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). It has one component per gathered texel. <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . Its OpTypeImage must have a Dim of 2D , Cube , or Rect . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of <i>Sampled Image</i> . <i>D_{ref}</i> is the depth-comparison reference value. <i>Image Operands</i> encodes what operands follow, as per Image Operands .							Capability: Shader	
6 + variable	97	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> <i>D_{ref}</i>	Optional Image Operands	Optional <id>, <id>, ...

OpImageRead

Read a texel from an [image](#) without a [sampler](#).

Result Type must be a scalar or vector of [floating-point type](#) or [integer type](#). Its component type must be the same as *Sampled Type* of the [OpTypeImage](#) (unless that *Sampled Type* is **OpTypeVoid**).

Image must be an object whose type is [OpTypeImage](#) with a *Sampled* operand of 0 or 2. If the *Sampled* operand is 2, then some [dimensions](#) require a [capability](#); e.g., one of **Image1D**, **ImageRect**, **ImageBuffer**, **ImageCubeArray**, or **ImageMSArray**.

Coordinate is an integer scalar or vector containing non-normalized texel coordinates ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of *Image*. If the coordinates are outside the image, the memory location that is accessed is undefined.

When the *Image Dim* operand is **SubpassData**, *Coordinate* is relative to the current fragment location. That is, the integer value (rounded down) of the current fragment's window-relative (x, y) coordinate is added to (u, v) .

When the *Image Dim* operand is not **SubpassData**, the [Image Format](#) must not be **Unknown**, unless the **StorageImageReadWithoutFormat Capability** was declared.

Image Operands encodes what operands follow, as per [Image Operands](#).

5 + variable	98	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	<id> <i>Coordinate</i>	Optional Image Operands	Optional <id>, <id>, ...
--------------	----	----------------------------	-----------------------------------	----------------------	---------------------------	--	-----------------------------

OpImageWrite

Write a texel to an [image](#) without a [sampler](#).

Image must be an object whose type is [OpTypeImage](#) with a *Sampled* operand of 0 or 2. If the *Sampled* operand is 2, then some [dimensions](#) require a [capability](#); e.g., one of **Image1D**, **ImageRect**, **ImageBuffer**, **ImageCubeArray**, or **ImageMSArray**. Its *Dim* operand cannot be **SubpassData**.

Coordinate is an integer scalar or vector containing non-normalized texel coordinates ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of *Image*. If the coordinates are outside the image, the memory location that is accessed is undefined.

Texel is the data to write. Its component type must be the same as *Sampled Type* of the [OpTypeImage](#) (unless that *Sampled Type* is **OpTypeVoid**).

The [Image Format](#) must not be **Unknown**, unless the **StorageImageWriteWithoutFormat Capability** was declared.

Image Operands encodes what operands follow, as per [Image Operands](#).

4 + variable	99	<id> <i>Image</i>	<id> <i>Coordinate</i>	<id> <i>Texel</i>	Optional Image Operands	Optional <id>, <id>, ...
--------------	----	----------------------	---------------------------	----------------------	--	-----------------------------

OpImage Extract the image from a sampled image. <i>Result Type</i> must be OpTypeImage . <i>Sampled Image</i> must have type OpTypeSampledImage whose <i>Image Type</i> is the same as <i>Result Type</i> .				
4	100	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>

OpImageQueryFormat Query the image format of an image created with an Unknown Image Format . <i>Result Type</i> must be a scalar integer type . The resulting value is an enumerant from Image Channel Data Type . <i>Image</i> must be an object whose type is OpTypeImage .			Capability: Kernel	
4	101	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>

OpImageQueryOrder Query the channel order of an image created with an Unknown Image Format . <i>Result Type</i> must be a scalar integer type . The resulting value is an enumerant from Image Channel Order . <i>Image</i> must be an object whose type is OpTypeImage .			Capability: Kernel	
4	102	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>

OpImageQuerySizeLod Query the dimensions of <i>Image</i> for mipmap level for <i>Level of Detail</i> . <i>Result Type</i> must be an integer type scalar or vector. The number of components must be 1 for 1D Dim , 2 for 2D , and Cube Dimensionalities , 3 for 3D Dim , plus 1 more if the image type is arrayed. This vector is filled in with (<i>width</i> [, <i>height</i>] [, <i>depth</i>] [, <i>elements</i>]) where <i>elements</i> is the number of layers in an image array, or the number of cubes in a cube-map array. <i>Image</i> must be an object whose type is OpTypeImage . Its <i>Dim</i> operand must be one of 1D , 2D , 3D , or Cube , and its <i>MS</i> must be 0. See OpImageQuerySize for querying image types without level of detail. <i>Level of Detail</i> is used to compute which mipmap level to query, as described in the API specification.					Capability: Kernel, ImageQuery
5	103	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	<id> <i>Level of Detail</i>

OpImageQuerySize Query the dimensions of <i>Image</i> , with no level of detail. <i>Result Type</i> must be an integer type scalar or vector. The number of components must be 1 for Buffer Dim , 2 for 2D and Rect Dimensionalities , 3 for 3D Dim , plus 1 more if the image type is arrayed. This vector is filled in with (<i>width</i> [, <i>height</i>] [, <i>elements</i>]) where <i>elements</i> is the number of layers in an image array. <i>Image</i> must be an object whose type is OpTypeImage . Its <i>Dim</i> operand must be one of Rect or Buffer , or if its <i>MS</i> is 1, it can be 2D , or, if its <i>Sampled Type</i> is 0 or 2, it can be 2D or 3D . It cannot be an image with level of detail; there is no implicit level-of-detail consumed by this instruction. See OpImageQuerySizeLod for querying images having level of detail.					Capability: Kernel, ImageQuery
4	104	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	

OpImageQueryLod Query the mipmap level and the level of detail for a hypothetical sampling of <i>Image</i> at <i>Coordinate</i> using an implicit level of detail. <i>Result Type</i> must be a two-component floating-point type vector. The first component of the result will contain the mipmap array layer. The second component of the result will contain the implicit level of detail relative to the base level. <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . Its Dim operand must be one of 1D , 2D , 3D , or Cube . <i>Coordinate</i> must be a scalar or vector of floating-point type or integer type . It contains (<i>u</i> [, <i>v</i>] . . .) as needed by the definition of <i>Sampled Image</i> , not including any array layer index. Unless the Kernel capability is being used, it must be floating point. If called on an incomplete image, the results are undefined. This instruction is only valid in the Fragment Execution Model . In addition, it consumes an implicit derivative that can be affected by code motion.					Capability: ImageQuery
5	105	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>

OpImageQueryLevels Query the number of mipmap levels accessible through <i>Image</i> . <i>Result Type</i> must be a scalar integer type . The result is the number of mipmap levels, as defined by the API specification. <i>Image</i> must be an object whose type is OpTypeImage . Its Dim operand must be one of 1D , 2D , 3D , or Cube .					Capability: Kernel, ImageQuery
4	106	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	

OpImageQuerySamples Query the number of samples available per texel fetch in a multisample image. <i>Result Type</i> must be a scalar integer type . The result is the number of samples. <i>Image</i> must be an object whose type is OpTypeImage . Its Dim operand must be one of 2D and <i>MS</i> of 1.					Capability: Kernel, ImageQuery
4	107	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	

OpImageSparseSampleImplicitLod Sample a sparse image with an implicit level of detail. <i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. <i>Image Operands</i> encodes what operands follow, as per Image Operands . This instruction is only valid in the Fragment Execution Model . In addition, it consumes an implicit derivative that can be affected by code motion.						Capability: SparseResidency	
5 + variable	305	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Sampled Image</i>	<i><id></i> <i>Coordinate</i>	Optional Image Operands	Optional <i><id></i> , <i><id></i> , ...

OpImageSparseSampleExplicitLod							Capability: SparseResidency
Sample a sparse image using an explicit level of detail.							
<i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid).							
<i>Sampled Image</i> must be an object whose type is OpTypeSampledImage .							
<i>Coordinate</i> must be a scalar or vector of floating-point type or integer type . It contains (<i>u</i> [, <i>v</i>] ... [, <i>array layer</i>]) as needed by the definition of <i>Sampled Image</i> . Unless the Kernel capability is being used, it must be floating point. It may be a vector larger than needed, but all unused components will appear after all used components.							
<i>Image Operands</i> encodes what operands follow, as per Image Operands . At least one operand setting the level of detail must be present.							
7 + variable	306	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	Image Operands	<id> Optional <id>, <id>, ...

OpImageSparseSampleDrefImplicitLod Sample a sparse image doing depth-comparison with an implicit level of detail. <i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a scalar of integer type or floating-point type . It must be the same as <i>Sampled Type</i> of the underlying OpTypeImage . <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains (u , v) ... [z , $array\ layer$]) as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. D_{ref} is the depth-comparison reference value. <i>Image Operands</i> encodes what operands follow, as per Image Operands . This instruction is only valid in the Fragment Execution Model . In addition, it consumes an implicit derivative that can be affected by code motion.							Capability: SparseResidency	
6 + variable	307	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> D_{ref}	Optional Image Operands	Optional <id>, ... <id>, ...

OpImageSparseSampleDrefExplicitLod Sample a sparse image doing depth-comparison using an explicit level of detail. <i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a scalar of integer type or floating-point type . It must be the same as <i>Sampled Type</i> of the underlying OpTypeImage . <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains (u , v) ... [$array\ layer$]) as needed by the definition of <i>Sampled Image</i> . It may be a vector larger than needed, but all unused components will appear after all used components. <i>D_{ref}</i> is the depth-comparison reference value. <i>Image Operands</i> encodes what operands follow, as per Image Operands . At least one operand setting the level of detail must be present.								Capability: SparseResidency	
8 + variable	308	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> <i>D_{ref}</i>	Image Operands	<id>	Optional <id>, <id>, ...

OpImageSparseSampleProjImplicitLod						Capability: SparseResidency	
Sample a sparse image with a projective coordinate and an implicit level of detail.						Reserved.	
5 + variable	309	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	Optional Image Operands	Optional <id>, <id>, ...

OpImageSparseSampleProjExplicitLod Sample a sparse image with a projective coordinate using an explicit level of detail.							Capability: SparseResidency Reserved.
7 + variable	310	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	Image Operands	<id> Optional <id>, <id>, ...

OpImageSparseSampleProjDrefImplicitLod							Capability: SparseResidency	
Sample a sparse image with a projective coordinate, doing depth-comparison, with an implicit level of detail.							Reserved.	
6 + variable	311	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> <i>D_{ref}</i>	Optional Image Operands	Optional <id>, <id>, ...

OpImageSparseSampleProjDrefExplicitLod								Capability: SparseResidency	
Sample a sparse image with a projective coordinate, doing depth-comparison, using an explicit level of detail.								Reserved.	
8 + variable	312	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> <i>D_{ref}</i>	Image Operands	<id>	Optional <id>, <id>, ...

OpImageSparseFetch Fetch a single texel from a sampled sparse image. <i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). <i>Image</i> must be an object whose type is OpTypeImage . Its Dim operand cannot be Cube . <i>Coordinate</i> is an integer scalar or vector containing ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of <i>Sampled Image</i> . <i>Image Operands</i> encodes what operands follow, as per Image Operands .						Capability: SparseResidency	
5 + variable	313	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	<id> <i>Coordinate</i>	Optional Image Operands	Optional <id>, <id>, ...

OpImageSparseGather Gathers the requested component from four texels of a sparse image. <i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). It has one component per gathered texel. <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . Its OpTypeImage must have a Dim of 2D , Cube , or Rect . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains (<i>u</i> [, <i>v</i>] ... [, <i>array layer</i>]) as needed by the definition of <i>Sampled Image</i> . <i>Component</i> is the component number that will be gathered from all four texels. It must be 0, 1, 2 or 3. <i>Image Operands</i> encodes what operands follow, as per Image Operands .							Capability: SparseResidency	
6 + variable	314	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> <i>Component</i>	Optional Image Operands	Optional <id>, ...

OpImageSparseDrefGather Gathers the requested depth-comparison from four texels of a sparse image. <i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a vector of four components of floating-point type or integer type . Its components must be the same as <i>Sampled Type</i> of the underlying OpTypeImage (unless that underlying <i>Sampled Type</i> is OpTypeVoid). It has one component per gathered texel. <i>Sampled Image</i> must be an object whose type is OpTypeSampledImage . Its OpTypeImage must have a <i>Dim</i> of 2D , Cube , or Rect . <i>Coordinate</i> must be a scalar or vector of floating-point type . It contains ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of <i>Sampled Image</i> . <i>D_{ref}</i> is the depth-comparison reference value. <i>Image Operands</i> encodes what operands follow, as per Image Operands .							Capability: SparseResidency	
6 + variable	315	<id> <i>Result Type</i>	Result <id>	<id> <i>Sampled Image</i>	<id> <i>Coordinate</i>	<id> <i>D_{ref}</i>	Optional Image Operands	Optional <id>, <id>, ...

OpImageSparseTexelsResident Translates a <i>Resident Code</i> into a Boolean. Result is false if any of the texels were in uncommitted texture memory, and true otherwise. <i>Result Type</i> must be a Boolean type scalar. <i>Resident Code</i> is a value from an OpImageSparse... instruction that returns a resident code.					Capability: SparseResidency			
4	316	<id> <i>Result Type</i>	Result <id>		<id> <i>Resident Code</i>			

OpImageSparseRead Read a texel from a sparse image without a sampler . <i>Result Type</i> must be an OpTypeStruct with two members. The first member's type must be an integer type scalar. It will hold a <i>Residency Code</i> that can be passed to OpImageSparseTexelsResident . The second member must be a scalar or vector of floating-point type or integer type . Its component type must be the same as <i>Sampled Type</i> of the OpTypeImage (unless that <i>Sampled Type</i> is OpTypeVoid). <i>Image</i> must be an object whose type is OpTypeImage with a <i>Sampled</i> operand of 2. <i>Coordinate</i> is an integer scalar or vector containing non-normalized texel coordinates ($u[, v] \dots [, \text{array layer}]$) as needed by the definition of <i>Image</i> . If the coordinates are outside the image, the memory location that is accessed is undefined. The <i>Image Dim</i> operand must not be SubpassData . The Image Format must not be Unknown unless the StorageImageReadWithoutFormat Capability was declared. <i>Image Operands</i> encodes what operands follow, as per Image Operands .						Capability: SparseResidency	
5 + variable	320	<id> <i>Result Type</i>	Result <id>	<id> <i>Image</i>	<id> <i>Coordinate</i>	Optional Image Operands	Optional <id>, <id>, ...

3.32.11 Conversion Instructions

OpConvertFToU

Convert (value preserving) from floating point to unsigned integer, with round toward 0.0.

Result Type must be a scalar or vector of [integer type](#), whose *Signedness* operand is 0.

Float Value must be a scalar or vector of [floating-point type](#). It must have the same number of components as *Result Type*.

Results are computed per component.

4	109	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> <i>Float Value</i>
---	-----	---	--------------------------	---

OpConvertFToS

Convert (value preserving) from floating point to signed integer, with round toward 0.0.

Result Type must be a scalar or vector of [integer type](#).

Float Value must be a scalar or vector of [floating-point type](#). It must have the same number of components as *Result Type*.

Results are computed per component.

4	110	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> <i>Float Value</i>
---	-----	---	--------------------------	---

OpConvertSToF

Convert (value preserving) from signed integer to floating point.

Result Type must be a scalar or vector of [floating-point type](#).

Signed Value must be a scalar or vector of [integer type](#). It must have the same number of components as *Result Type*.

Results are computed per component.

4	111	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> <i>Signed Value</i>
---	-----	---	--------------------------	--

OpConvertUToF

Convert (value preserving) from unsigned integer to floating point.

Result Type must be a scalar or vector of [floating-point type](#).

Unsigned Value must be a scalar or vector of [integer type](#). It must have the same number of components as *Result Type*.

Results are computed per component.

4	112	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Unsigned Value</i>
---	-----	---	-----------------------------------	--

OpUConvert

Convert (value preserving) unsigned width. This is either a truncate or a zero extend.

Result Type must be a scalar of [integer type](#), whose *Signedness* operand is 0.

Unsigned Value must be a scalar or vector of [integer type](#). It must have the same number of components as *Result Type*. The component width cannot equal the component width in *Result Type*.

Results are computed per component.

4	113	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Unsigned Value</i>
---	-----	---	-----------------------------------	--

OpSConvert

Convert (value preserving) signed width. This is either a truncate or a sign extend.

Result Type must be a scalar or vector of [integer type](#).

Signed Value must be a scalar or vector of [integer type](#). It must have the same number of components as *Result Type*. The component width cannot equal the component width in *Result Type*.

Results are computed per component.

4	114	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Signed Value</i>
---	-----	---	-----------------------------------	--

OpFConvert

Convert (value preserving) floating-point width.

Result Type must be a scalar or vector of [floating-point type](#).

Float Value must be a scalar or vector of [floating-point type](#). It must have the same number of components as *Result Type*. The component width cannot equal the component width in *Result Type*.

Results are computed per component.

4	115	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Float Value</i>
---	-----	---	-----------------------------------	---

OpQuantizeToF16 Quantize a floating-point value to what is expressible by a 16-bit floating-point value. <i>Result Type</i> must be a scalar or vector of floating-point type . The component width must be 32 bits. <i>Value</i> is the value to quantize. The type of <i>Value</i> must be the same as <i>Result Type</i> . If <i>Value</i> is an infinity, the result is the same infinity. If <i>Value</i> is a NaN, the result is a NaN, but not necessarily the same NaN. If <i>Value</i> is positive with a magnitude too large to represent as a 16-bit floating-point value, the result is positive infinity. If <i>Value</i> is negative with a magnitude too large to represent as a 16-bit floating-point value, the result is negative infinity. If the magnitude of <i>Value</i> is too small to represent as a normalized 16-bit floating-point value, the result may be either +0 or -0. The RelaxedPrecision Decoration has no effect on this instruction. Results are computed per component.				Capability: Shader
4	116	<id> <i>Result Type</i>	Result <id>	<id> <i>Value</i>

OpConvertPtrToU Convert a pointer to an unsigned integer type. A <i>Result Type</i> width larger than the width of <i>Pointer</i> will zero extend. A <i>Result Type</i> smaller than the width of <i>Pointer</i> will truncate. For same-width source and result, this is the same as OpBitcast . <i>Result Type</i> must be a scalar or vector of integer type , whose <i>Signedness</i> operand is 0.				Capability: Addresses
4	117	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>

OpSatConvertSToU Convert a signed integer to unsigned integer. Converted values outside the representable range of <i>Result Type</i> are clamped to the nearest representable value of <i>Result Type</i> . <i>Result Type</i> must be a scalar or vector of integer type . <i>Signed Value</i> must be a scalar or vector of integer type . It must have the same number of components as <i>Result Type</i> . Results are computed per component.				Capability: Kernel
4	118	<id> <i>Result Type</i>	Result <id>	<id> <i>Signed Value</i>

OpSatConvertUToS Convert an unsigned integer to signed integer. Converted values outside the representable range of <i>Result Type</i> are clamped to the nearest representable value of <i>Result Type</i> . <i>Result Type</i> must be a scalar or vector of integer type . <i>Unsigned Value</i> must be a scalar or vector of integer type . It must have the same number of components as <i>Result Type</i> . Results are computed per component.				Capability: Kernel
4	119	<id> <i>Result Type</i>	Result <id>	<id> <i>Unsigned Value</i>

OpConvertUToPtr Convert an integer to pointer. A <i>Result Type</i> width smaller than the width of <i>Integer Value</i> pointer will truncate. A <i>Result Type</i> width larger than the width of <i>Integer Value</i> pointer will zero extend. <i>Result Type</i> must be an OpTypePointer . For same-width source and result, this is the same as OpBitcast .				Capability: Addresses
4	120	<id> <i>Result Type</i>	Result <id>	<id> <i>Integer Value</i>

OpPtrCastToGeneric Convert a pointer's Storage Class to Generic . <i>Result Type</i> must be an OpTypePointer . Its Storage Class must be Generic . <i>Pointer</i> must point to the Workgroup , CrossWorkgroup , or Function Storage Class . <i>Result Type</i> and <i>Pointer</i> must point to the same type.				Capability: Kernel
4	121	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>

OpGenericCastToPtr Convert a pointer's Storage Class to a non- Generic class. <i>Result Type</i> must be an OpTypePointer . Its Storage Class must be Workgroup , CrossWorkgroup , or Function . <i>Pointer</i> must point to the Generic Storage Class . <i>Result Type</i> and <i>Pointer</i> must point to the same type.				Capability: Kernel
4	122	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>

OpGenericCastToPtrExplicit Attempts to explicitly convert <i>Pointer</i> to <i>Storage</i> storage-class pointer value. <i>Result Type</i> must be an OpTypePointer . Its Storage Class must be <i>Storage</i> . <i>Pointer</i> must have a type of OpTypePointer whose <i>Type</i> is the same as the <i>Type</i> of <i>Result Type</i> . <i>Pointer</i> must point to the Generic Storage Class . If the cast fails, the instruction result is an OpConstantNull pointer in the <i>Storage Storage Class</i> . <i>Storage</i> must be one of the following literal values from Storage Class : Workgroup , CrossWorkgroup , or Function .					Capability: Kernel
5	123	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Storage Class <i>Storage</i>

OpBitcast Bit pattern-preserving type conversion. <i>Result Type</i> must be an OpTypePointer , or a scalar or vector of numerical-type . <i>Operand</i> must have a type of OpTypePointer , or a scalar or vector of numerical-type . It must be a different type than <i>Result Type</i> . If <i>Result Type</i> is a pointer, <i>Operand</i> must be a pointer or integer scalar. If <i>Operand</i> is a pointer, <i>Result Type</i> must be a pointer or integer scalar. If <i>Result Type</i> has the same number of components as <i>Operand</i> , they must also have the same component width, and results are computed per component. If <i>Result Type</i> has a different number of components than <i>Operand</i> , the total number of bits in <i>Result Type</i> must equal the total number of bits in <i>Operand</i> . Let <i>L</i> be the type, either <i>Result Type</i> or <i>Operand</i> 's type, that has the larger number of components. Let <i>S</i> be the other type, with the smaller number of components. The number of components in <i>L</i> must be an integer multiple of the number of components in <i>S</i> . The first component (that is, the only or lowest-numbered component) of <i>S</i> maps to the first components of <i>L</i> , and so on, up to the last component of <i>S</i> mapping to the last components of <i>L</i> . Within this mapping, any single component of <i>S</i> (mapping to multiple components of <i>L</i>) maps its lower-ordered bits to the lower-numbered components of <i>L</i> .					
4	124	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand</i>	

3.32.12 Composite Instructions

OpVectorExtractDynamic

Extract a single, dynamically selected, component of a vector.

Result Type must be a [scalar](#) type.

Vector must have a type [OpTypeVector](#) whose *Component Type* is *Result Type*.

Index must be a scalar [integer](#) 0-based index of which component of *Vector* to extract.

The value read is undefined if *Index*'s value is less than zero or greater than or equal to the number of components in *Vector*.

5	77	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector</i>	<id> <i>Index</i>
---	----	----------------------------	-----------------------------------	-----------------------	----------------------

OpVectorInsertDynamic

Make a copy of a vector, with a single, variably selected, component modified.

Result Type must be an [OpTypeVector](#).

Vector must have the same type as *Result Type* and is the vector that the non-written components will be copied from.

Component is the value that will be supplied for the component selected by *Index*. It must have the same type as the type of components in *Result Type*.

Index must be a scalar [integer](#) 0-based index of which component to modify.

What is written is undefined if *Index*'s value is less than zero or greater than or equal to the number of components in *Vector*.

6	78	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector</i>	<id> <i>Component</i>	<id> <i>Index</i>
---	----	----------------------------	-----------------------------------	-----------------------	--------------------------	----------------------

OpVectorShuffle

Select arbitrary components from two vectors to make a new vector.

Result Type must be an [OpTypeVector](#). The number of components in *Result Type* must be the same as the number of *Component* operands.

Vector 1 and *Vector 2* must both have vector types, with the same *Component Type* as *Result Type*. They do not have to have the same number of components as *Result Type* or with each other. They are logically concatenated, forming a single vector with *Vector 1*'s components appearing before *Vector 2*'s. The components of this logical vector are logically numbered with a single consecutive set of numbers from 0 to $N - 1$, where N is the total number of components.

Components are these logical numbers (see above), selecting which of the logically numbered components form the result. They can select the components in any order and can repeat components. The first component of the result is selected by the first *Component* operand, the second component of the result is selected by the second *Component* operand, etc. A *Component literal* may also be FFFFFFFF, which means the corresponding result component has no source and is undefined. All *Component literals* must either be FFFFFFFF or in $[0, N - 1]$ ([inclusive](#)).

Note: A vector “swizzle” can be done by using the vector for both *Vector* operands, or using an [OpUndef](#) for one of the *Vector* operands.

5 + variable	79	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector 1</i>	<id> <i>Vector 2</i>	<i>Literal, Literal,</i> ... <i>Components</i>
--------------	----	----------------------------	-----------------------------------	-------------------------	-------------------------	--

OpCompositeConstruct

Construct a new [composite](#) object from a set of constituent objects that will fully form it.

Result Type must be a [composite](#) type, whose top-level members/elements/components/columns have the same type as the types of the operands, with one exception. The exception is that for constructing a vector, the operands may also be vectors with the same component type as the *Result Type* component type. When constructing a vector, the total number of components in all the operands must equal the number of components in *Result Type*.

Constituents will become members of a structure, or elements of an array, or components of a vector, or columns of a matrix. There must be exactly one *Constituent* for each top-level member/element/component/column of the result, with one exception. The exception is that for constructing a vector, a contiguous subset of the scalars consumed can be represented by a vector operand instead. The *Constituents* must appear in the order needed by the definition of the type of the result. When constructing a vector, there must be at least two *Constituent* operands.

3 + variable	80	<id> <i>Result Type</i>	Result <id>	<id>, <id>, ... <i>Constituents</i>
--------------	----	----------------------------	-----------------------------------	--

OpCompositeExtract

Extract a part of a [composite](#) object.

Result Type must be the type of object selected by the last provided index. The instruction result is the extracted object.

Composite is the composite to extract from.

Indexes walk the type hierarchy, potentially down to component granularity, to select the part to extract. All indexes must be in bounds. All composite constituents use zero-based numbering, as described by their **OpType...** instruction.

4 + variable	81	<id> <i>Result Type</i>	Result <id>	<id> <i>Composite</i>	<i>Literal, Literal, ... Indexes</i>
--------------	----	----------------------------	-----------------------------------	--------------------------	--

OpCompositeInsert

Make a copy of a [composite](#) object, while modifying one part of it.

Result Type must be the same type as *Composite*.

Object is the object to use as the modified part.

Composite is the composite to copy all but the modified part from.

Indexes walk the type hierarchy of *Composite* to the desired depth, potentially down to component granularity, to select the part to modify. All indexes must be in bounds. All composite constituents use zero-based numbering, as described by their **OpType...** instruction. The type of the part selected to modify must match the type of *Object*.

5 + variable	82	<id> <i>Result Type</i>	Result <id>	<id> <i>Object</i>	<id> <i>Composite</i>	<i>Literal, Literal, ... Indexes</i>
--------------	----	----------------------------	-----------------------------------	-----------------------	--------------------------	--

OpCopyObject

Make a copy of *Operand*. There are no dereferences involved.

Result Type must match *Operand* type. There are no other restrictions on the types.

4	83	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand</i>
---	----	----------------------------	-----------------------------------	------------------------

OpTranspose Transpose a matrix. <i>Result Type</i> must be an OpTypeMatrix . <i>Matrix</i> must be an object of type OpTypeMatrix . The number of columns and the column size of <i>Matrix</i> must be the reverse of those in <i>Result Type</i> . The types of the scalar components in <i>Matrix</i> and <i>Result Type</i> must be the same. <i>Matrix</i> must have of type of OpTypeMatrix .			Capability: Matrix	
4	84	<id> <i>Result Type</i>	Result <id>	<id> <i>Matrix</i>

3.32.13 Arithmetic Instructions

OpSNegate

Signed-integer subtract of *Operand* from zero.

Result Type must be a scalar or vector of [integer type](#).

Operand's type must be a scalar or vector of [integer type](#). It must have the same number of components as *Result Type*. The component width must equal the component width in *Result Type*.

Results are computed per component.

4	126	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand</i>
---	-----	----------------------------	-------------	------------------------

OpFNegate

Floating-point subtract of *Operand* from zero.

Result Type must be a scalar or vector of [floating-point type](#).

The type of *Operand* must be the same as *Result Type*.

Results are computed per component.

4	127	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand</i>
---	-----	----------------------------	-------------	------------------------

OpIAdd

Integer addition of *Operand 1* and *Operand 2*.

Result Type must be a scalar or vector of [integer type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

Results are computed per component.

5	128	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFAdd

Floating-point addition of *Operand 1* and *Operand 2*.

Result Type must be a scalar or vector of [floating-point type](#).

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component.

5	129	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpISub

Integer subtraction of *Operand 2* from *Operand 1*.

Result Type must be a scalar or vector of [integer type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

Results are computed per component.

5	130	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFSub

Floating-point subtraction of *Operand 2* from *Operand 1*.

Result Type must be a scalar or vector of [floating-point type](#).

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component.

5	131	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpIMul

Integer multiplication of *Operand 1* and *Operand 2*.

Result Type must be a scalar or vector of [integer type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

Results are computed per component.

5	132	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFMul

Floating-point multiplication of *Operand 1* and *Operand 2*.

Result Type must be a scalar or vector of [floating-point type](#).

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component.

5	133	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpUDiv

Unsigned-integer division of *Operand 1* divided by *Operand 2*.

Result Type must be a scalar or vector of [integer type](#), whose *Signedness* operand is 0.

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	134	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpSDiv

Signed-integer division of *Operand 1* divided by *Operand 2*.

Result Type must be a scalar or vector of [integer type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	135	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFDiv

Floating-point division of *Operand 1* divided by *Operand 2*.

Result Type must be a scalar or vector of [floating-point type](#).

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	136	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpUMod

Unsigned modulo operation of *Operand 1* modulo *Operand 2*.

Result Type must be a scalar or vector of [integer type](#), whose *Signedness* operand is 0.

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	137	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpSRem

Signed remainder operation of *Operand 1* divided by *Operand 2*. The sign of a non-0 result comes from *Operand 1*.

Result Type must be a scalar or vector of [integer type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	138	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpSMod

Signed modulo operation of *Operand 1* modulo *Operand 2*. The sign of a non-0 result comes from *Operand 2*.

Result Type must be a scalar or vector of [integer type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	139	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFRem

Floating-point remainder operation of *Operand 1* divided by *Operand 2*. The sign of a non-0 result comes from *Operand 1*.

Result Type must be a scalar or vector of [floating-point type](#).

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	140	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFMod

Floating-point remainder operation of *Operand 1* divided by *Operand 2*. The sign of a non-0 result comes from *Operand 2*.

Result Type must be a scalar or vector of [floating-point type](#).

The types of *Operand 1* and *Operand 2* both must be the same as *Result Type*.

Results are computed per component. The resulting value is undefined if *Operand 2* is 0.

5	141	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpVectorTimesScalar Scale a floating-point vector. <i>Result Type</i> must be a vector of floating-point type . The type of <i>Vector</i> must be the same as <i>Result Type</i> . Each component of <i>Vector</i> is multiplied by <i>Scalar</i> . <i>Scalar</i> must have the same type as the <i>Component Type</i> in <i>Result Type</i> .					
5	142	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector</i>	<id> <i>Scalar</i>

OpMatrixTimesScalar Scale a floating-point matrix. <i>Result Type</i> must be an OpTypeMatrix whose <i>Column Type</i> is a vector of floating-point type . The type of <i>Matrix</i> must be the same as <i>Result Type</i> . Each component in each column in <i>Matrix</i> is multiplied by <i>Scalar</i> . <i>Scalar</i> must have the same type as the <i>Component Type</i> in <i>Result Type</i> .					Capability: Matrix
5	143	<id> <i>Result Type</i>	Result <id>	<id> <i>Matrix</i>	<id> <i>Scalar</i>

OpVectorTimesMatrix Linear-algebraic <i>Vector X Matrix</i> . <i>Result Type</i> must be a vector of floating-point type . <i>Vector</i> must be a vector with the same <i>Component Type</i> as the <i>Component Type</i> in <i>Result Type</i> . Its number of components must equal the number of components in each column in <i>Matrix</i> . <i>Matrix</i> must be a matrix with the same <i>Component Type</i> as the <i>Component Type</i> in <i>Result Type</i> . Its number of columns must equal the number of components in <i>Result Type</i> .					Capability: Matrix
5	144	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector</i>	<id> <i>Matrix</i>

OpMatrixTimesVector Linear-algebraic <i>Vector X Matrix</i> . <i>Result Type</i> must be a vector of floating-point type . <i>Matrix</i> must be an OpTypeMatrix whose <i>Column Type</i> is <i>Result Type</i> . <i>Vector</i> must be a vector with the same <i>Component Type</i> as the <i>Component Type</i> in <i>Result Type</i> . Its number of components must equal the number of columns in <i>Matrix</i> .					Capability: Matrix
5	145	<id> <i>Result Type</i>	Result <id>	<id> <i>Matrix</i>	<id> <i>Vector</i>

OpMatrixTimesMatrix Linear-algebraic multiply of <i>LeftMatrix X RightMatrix</i> . <i>Result Type</i> must be an OpTypeMatrix whose <i>Column Type</i> is a vector of floating-point type . <i>LeftMatrix</i> must be a matrix whose <i>Column Type</i> is the same as the <i>Column Type</i> in <i>Result Type</i> . <i>RightMatrix</i> must be a matrix with the same <i>Component Type</i> as the <i>Component Type</i> in <i>Result Type</i> . Its number of columns must equal the number of columns in <i>Result Type</i> . Its columns must have the same number of components as the number of columns in <i>LeftMatrix</i> .					Capability: Matrix
5	146	<id> <i>Result Type</i>	Result <id>	<id> <i>LeftMatrix</i>	<id> <i>RightMatrix</i>

OpOuterProduct Linear-algebraic outer product of <i>Vector 1</i> and <i>Vector 2</i> . <i>Result Type</i> must be an OpTypeMatrix whose <i>Column Type</i> is a vector of floating-point type . <i>Vector 1</i> must have the same type as the <i>Column Type</i> in <i>Result Type</i> . <i>Vector 2</i> must be a vector with the same <i>Component Type</i> as the <i>Component Type</i> in <i>Result Type</i> . Its number of components must equal the number of columns in <i>Result Type</i> .					Capability: Matrix
5	147	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector 1</i>	<id> <i>Vector 2</i>

OpDot Dot product of <i>Vector 1</i> and <i>Vector 2</i> . <i>Result Type</i> must be a floating-point type scalar. <i>Vector 1</i> and <i>Vector 2</i> must be vectors of the same type, and their component type must be <i>Result Type</i> .					
5	148	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector 1</i>	<id> <i>Vector 2</i>

OpIAddCarry

Result is the unsigned integer addition of *Operand 1* and *Operand 2*, including its carry.

Result Type must be from [OpTypeStruct](#). The struct must have two members, and the two members must be the same type. The member type must be a scalar or vector of [integer type](#), whose *Signedness* operand is 0.

Operand 1 and *Operand 2* must have the same type as the members of *Result Type*. These are consumed as unsigned integers.

Results are computed per component.

Member 0 of the result gets the low-order bits (full component width) of the addition.

Member 1 of the result gets the high-order (carry) bit of the result of the addition. That is, it gets the value 1 if the addition overflowed the component width, and 0 otherwise.

5	149	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-----------------------------------	--------------------------	--------------------------

OpISubBorrow

Result is the unsigned integer subtraction of *Operand 2* from *Operand 1*, and what it needed to borrow.

Result Type must be from [OpTypeStruct](#). The struct must have two members, and the two members must be the same type. The member type must be a scalar or vector of [integer type](#), whose *Signedness* operand is 0.

Operand 1 and *Operand 2* must have the same type as the members of *Result Type*. These are consumed as unsigned integers.

Results are computed per component.

Member 0 of the result gets the low-order bits (full component width) of the subtraction. That is, if *Operand 1* is larger than *Operand 2*, member 0 gets the full value of the subtraction; if *Operand 2* is larger than *Operand 1*, member 0 gets $2^w + \text{Operand 1} - \text{Operand 2}$, where w is the component width.

Member 1 of the result gets 0 if $\text{Operand 1} \geq \text{Operand 2}$, and gets 1 otherwise.

5	150	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-----------------------------------	--------------------------	--------------------------

OpUMulExtended

Result is the full value of the unsigned integer multiplication of *Operand 1* and *Operand 2*.

Result Type must be from [OpTypeStruct](#). The struct must have two members, and the two members must be the same type. The member type must be a scalar or vector of [integer type](#), whose *Signedness* operand is 0.

Operand 1 and *Operand 2* must have the same type as the members of *Result Type*. These are consumed as unsigned integers.

Results are computed per component.

Member 0 of the result gets the low-order bits of the multiplication.

Member 1 of the result gets the high-order bits of the multiplication.

5	151	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Operand 1</i>	<i><id></i> <i>Operand 2</i>
---	-----	---	-----------------------------------	---------------------------------------	---------------------------------------

OpSMulExtended

Result is the full value of the signed integer multiplication of *Operand 1* and *Operand 2*.

Result Type must be from [OpTypeStruct](#). The struct must have two members, and the two members must be the same type. The member type must be a scalar or vector of [integer type](#).

Operand 1 and *Operand 2* must have the same type as the members of *Result Type*. These are consumed as signed integers.

Results are computed per component.

Member 0 of the result gets the low-order bits of the multiplication.

Member 1 of the result gets the high-order bits of the multiplication.

5	152	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Operand 1</i>	<i><id></i> <i>Operand 2</i>
---	-----	---	-----------------------------------	---------------------------------------	---------------------------------------

3.32.14 Bit Instructions

OpShiftRightLogical

Shift the bits in *Base* right by the number of bits specified in *Shift*. The most-significant bits will be zero filled.

Result Type must be a scalar or vector of [integer type](#).

The type of each *Base* and *Shift* must be a scalar or vector of [integer type](#). *Base* and *Shift* must have the same number of components. The number of components and bit width of the type of *Base* must be the same as in *Result Type*.

Shift is consumed as an unsigned integer. The result is undefined if *Shift* is greater than the bit width of the components of *Base*.

Results are computed per component.

5	194	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Shift</i>
---	-----	----------------------------	-------------	---------------------	----------------------

OpShiftRightArithmetic

Shift the bits in *Base* right by the number of bits specified in *Shift*. The most-significant bits will be filled with the sign bit from *Base*.

Result Type must be a scalar or vector of [integer type](#).

The type of each *Base* and *Shift* must be a scalar or vector of [integer type](#). *Base* and *Shift* must have the same number of components. The number of components and bit width of the type of *Base* must be the same as in *Result Type*.

Shift is treated as unsigned. The result is undefined if *Shift* is greater than the bit width of the components of *Base*.

Results are computed per component.

5	195	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Shift</i>
---	-----	----------------------------	-------------	---------------------	----------------------

OpShiftLeftLogical

Shift the bits in *Base* left by the number of bits specified in *Shift*. The least-significant bits will be zero filled.

Result Type must be a scalar or vector of [integer type](#).

The type of each *Base* and *Shift* must be a scalar or vector of [integer type](#). *Base* and *Shift* must have the same number of components. The number of components and bit width of the type of *Base* must be the same as in *Result Type*.

Shift is treated as unsigned. The result is undefined if *Shift* is greater than the bit width of the components of *Base*.

The number of components and bit width of *Result Type* must match those *Base* type. All types must be integer types.

Results are computed per component.

5	196	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Shift</i>
---	-----	----------------------------	-------------	---------------------	----------------------

OpBitwiseOr

Result is 1 if either *Operand 1* or *Operand 2* is 1. Result is 0 if both *Operand 1* and *Operand 2* are 0.

Results are computed per component, and within each component, per bit.

Result Type must be a scalar or vector of [integer type](#). The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

5	197	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpBitwiseXor

Result is 1 if exactly one of *Operand 1* or *Operand 2* is 1. Result is 0 if *Operand 1* and *Operand 2* have the same value.

Results are computed per component, and within each component, per bit.

Result Type must be a scalar or vector of [integer type](#). The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

5	198	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpBitwiseAnd

Result is 1 if both *Operand 1* and *Operand 2* are 1. Result is 0 if either *Operand 1* or *Operand 2* are 0.

Results are computed per component, and within each component, per bit.

Result Type must be a scalar or vector of [integer type](#). The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same number of components as *Result Type*. They must have the same component width as *Result Type*.

5	199	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpNot

Complement the bits of *Operand*.

Results are computed per component, and within each component, per bit.

Result Type must be a scalar or vector of [integer type](#).

Operand's type must be a scalar or vector of [integer type](#). It must have the same number of components as *Result Type*. The component width must equal the component width in *Result Type*.

4	200	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand</i>
---	-----	----------------------------	-------------	------------------------

OpBitFieldInsert Make a copy of an object, with a modified bit field that comes from another object. Results are computed per component. <i>Result Type</i> must be a scalar or vector of integer type . The type of <i>Base</i> and <i>Insert</i> must be the same as <i>Result Type</i> . Any result bits numbered outside [<i>Offset</i> , <i>Offset</i> + <i>Count</i> - 1] (inclusive) will come from the corresponding bits in <i>Base</i> . Any result bits numbered in [<i>Offset</i> , <i>Offset</i> + <i>Count</i> - 1] come, in order, from the bits numbered [0, <i>Count</i> - 1] of <i>Insert</i> . <i>Count</i> must be an integer type scalar. <i>Count</i> is the number of bits taken from <i>Insert</i> . It will be consumed as an unsigned value. <i>Count</i> can be 0, in which case the result will be <i>Base</i> . <i>Offset</i> must be an integer type scalar. <i>Offset</i> is the lowest-order bit of the bit field. It will be consumed as an unsigned value. The resulting value is undefined if <i>Count</i> or <i>Offset</i> or their sum is greater than the number of bits in the result.							
Capability: Shader							
7	201	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Insert</i>	<id> <i>Offset</i>	<id> <i>Count</i>

OpBitFieldSExtract Extract a bit field from an object, with sign extension. Results are computed per component. <i>Result Type</i> must be a scalar or vector of <i>integer type</i> . The type of <i>Base</i> must be the same as <i>Result Type</i> . If <i>Count</i> is greater than 0: The bits of <i>Base</i> numbered in [<i>Offset</i> , <i>Offset</i> + <i>Count</i> - 1] (<i>inclusive</i>) become the bits numbered [0, <i>Count</i> - 1] of the result. The remaining bits of the result will all be the same as bit <i>Offset</i> + <i>Count</i> - 1 of <i>Base</i> . <i>Count</i> must be an <i>integer type</i> scalar. <i>Count</i> is the number of bits extracted from <i>Base</i> . It will be consumed as an unsigned value. <i>Count</i> can be 0, in which case the result will be 0. <i>Offset</i> must be an <i>integer type</i> scalar. <i>Offset</i> is the lowest-order bit of the bit field to extract from <i>Base</i> . It will be consumed as an unsigned value. The resulting value is undefined if <i>Count</i> or <i>Offset</i> or their sum is greater than the number of bits in the result.				Capability: Shader		
6	202	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Offset</i>	<id> <i>Count</i>

OpBitFieldUExtract Extract a bit field from an object, without sign extension. The semantics are the same as with <i>OpBitFieldSExtract</i> with the exception that there is no sign extension. The remaining bits of the result will all be 0.				Capability: Shader		
6	203	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>	<id> <i>Offset</i>	<id> <i>Count</i>

OpBitReverse Reverse the bits in an object. Results are computed per component. <i>Result Type</i> must be a scalar or vector of <i>integer type</i> . The type of <i>Base</i> must be the same as <i>Result Type</i> . The bit-number <i>n</i> of the result will be taken from bit-number <i>Width</i> - 1 - <i>n</i> of <i>Base</i> , where <i>Width</i> is the <i>OpTypeInt</i> operand of the <i>Result Type</i> .				Capability: Shader		
4	204	<id> <i>Result Type</i>	Result <id>	<id> <i>Base</i>		

OpBitCount

Count the number of set bits in an object.

Results are computed per component.

Result Type must be a scalar or vector of [integer type](#). The components must be wide enough to hold the unsigned *Width* of *Base* as an unsigned value. That is, no sign bit is needed or counted when checking for a wide enough result width.

Base must be a scalar or vector of [integer type](#). It must have the same number of components as *Result Type*.

The result is the unsigned value that is the number of bits in *Base* that are 1.

4	205	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Base</i>
---	-----	---	-----------------------------------	----------------------------------

3.32.15 Relational and Logical Instructions

OpAny

Result is **true** if any component of *Vector* is **true**, otherwise result is **false**.

Result Type must be a **Boolean type** scalar.

Vector must be a vector of **Boolean type**.

4	154	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector</i>
---	-----	----------------------------	-------------	-----------------------

OpAll

Result is **true** if all components of *Vector* are **true**, otherwise result is **false**.

Result Type must be a **Boolean type** scalar.

Vector must be a vector of **Boolean type**.

4	155	<id> <i>Result Type</i>	Result <id>	<id> <i>Vector</i>
---	-----	----------------------------	-------------	-----------------------

OpIsNan

Result is **true** if *x* is an IEEE NaN, otherwise result is **false**.

Result Type must be a scalar or vector of **Boolean type**.

x must be a scalar or vector of **floating-point type**. It must have the same number of components as *Result Type*.

Results are computed per component.

4	156	<id> <i>Result Type</i>	Result <id>	<id> <i>x</i>
---	-----	----------------------------	-------------	------------------

OpIsInf

Result is **true** if *x* is an IEEE Inf, otherwise result is **false**

Result Type must be a scalar or vector of **Boolean type**.

x must be a scalar or vector of **floating-point type**. It must have the same number of components as *Result Type*.

Results are computed per component.

4	157	<id> <i>Result Type</i>	Result <id>	<id> <i>x</i>
---	-----	----------------------------	-------------	------------------

OpIsFinite Result is true if x is an IEEE finite number, otherwise result is false . <i>Result Type</i> must be a scalar or vector of Boolean type . x must be a scalar or vector of floating-point type . It must have the same number of components as <i>Result Type</i> . Results are computed per component.				Capability: Kernel
4	158	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> x

OpIsNormal Result is true if x is an IEEE normal number, otherwise result is false . <i>Result Type</i> must be a scalar or vector of Boolean type . x must be a scalar or vector of floating-point type . It must have the same number of components as <i>Result Type</i> . Results are computed per component.				Capability: Kernel
4	159	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> x

OpSignBitSet Result is true if x has its sign bit set, otherwise result is false . <i>Result Type</i> must be a scalar or vector of Boolean type . x must be a scalar or vector of floating-point type . It must have the same number of components as <i>Result Type</i> . Results are computed per component.				Capability: Kernel
4	160	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> x

OpLessOrGreater Result is true if $x < y$ or $x > y$, where IEEE comparisons are used, otherwise result is false . <i>Result Type</i> must be a scalar or vector of Boolean type . x must be a scalar or vector of floating-point type . It must have the same number of components as <i>Result Type</i> . y must have the same type as x . Results are computed per component.					Capability: Kernel
5	161	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> x	<i><id></i> y

OpOrdered Result is true if both $x == x$ and $y == y$ are true , where IEEE comparison is used, otherwise result is false . <i>Result Type</i> must be a scalar or vector of Boolean type . x must be a scalar or vector of floating-point type . It must have the same number of components as <i>Result Type</i> . y must have the same type as x . Results are computed per component.					Capability: Kernel
5	162	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> x	<i><id></i> y

OpUnordered Result is true if either x or y is an IEEE NaN, otherwise result is false . <i>Result Type</i> must be a scalar or vector of Boolean type . x must be a scalar or vector of floating-point type . It must have the same number of components as <i>Result Type</i> . y must have the same type as x . Results are computed per component.					Capability: Kernel
5	163	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> x	<i><id></i> y

OpLogicalEqual

Result is **true** if *Operand 1* and *Operand 2* have the same value. Result is **false** if *Operand 1* and *Operand 2* have different values.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* must be the same as *Result Type*.

The type of *Operand 2* must be the same as *Result Type*.

Results are computed per component.

5	164	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpLogicalNotEqual

Result is **true** if *Operand 1* and *Operand 2* have different values. Result is **false** if *Operand 1* and *Operand 2* have the same value.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* must be the same as *Result Type*.

The type of *Operand 2* must be the same as *Result Type*.

Results are computed per component.

5	165	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpLogicalOr

Result is **true** if either *Operand 1* or *Operand 2* is **true**. Result is **false** if both *Operand 1* and *Operand 2* are **false**.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* must be the same as *Result Type*.

The type of *Operand 2* must be the same as *Result Type*.

Results are computed per component.

5	166	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpLogicalAnd

Result is **true** if both *Operand 1* and *Operand 2* are **true**. Result is **false** if either *Operand 1* or *Operand 2* are **false**.

Result Type must be a scalar or vector of **Boolean type**.

The type of *Operand 1* must be the same as *Result Type*.

The type of *Operand 2* must be the same as *Result Type*.

Results are computed per component.

5	167	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpLogicalNot

Result is **true** if *Operand* is **false**. Result is **false** if *Operand* is **true**.

Result Type must be a scalar or vector of **Boolean type**.

The type of *Operand* must be the same as *Result Type*.

Results are computed per component.

4	168	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand</i>
---	-----	----------------------------	-------------	------------------------

OpSelect

Select components from two objects.

Result Type must be a pointer, scalar, or vector.

The type of *Object 1* must be the same as *Result Type*. *Object 1* is selected as the result if *Condition* is **true**.

The type of *Object 2* must be the same as *Result Type*. *Object 2* is selected as the result if *Condition* is **false**.

Condition must be a scalar or vector of **Boolean type**. It must have the same number of components as *Result Type*.

Results are computed per component.

6	169	<id> <i>Result Type</i>	Result <id>	<id> <i>Condition</i>	<id> <i>Object 1</i>	<id> <i>Object 2</i>
---	-----	----------------------------	-------------	--------------------------	-------------------------	-------------------------

OpIEqual

Integer comparison for equality.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	170	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpINotEqual

Integer comparison for inequality.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	171	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpUGreaterThan

Unsigned-integer comparison if *Operand 1* is greater than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	172	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpSGreaterThan

Signed-integer comparison if *Operand 1* is greater than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	173	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpUGreaterThanEqual

Unsigned-integer comparison if *Operand 1* is greater than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	174	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpSGreaterThanEqual

Signed-integer comparison if *Operand 1* is greater than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	175	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpULessThan

Unsigned-integer comparison if *Operand 1* is less than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	176	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpSLessThan

Signed-integer comparison if *Operand 1* is less than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	177	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpULessThanEqual

Unsigned-integer comparison if *Operand 1* is less than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	178	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpSLessThanEqual

Signed-integer comparison if *Operand 1* is less than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [integer type](#). They must have the same component width, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	179	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFOrdEqual

Floating-point comparison for being ordered and equal.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	180	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFUnordEqual

Floating-point comparison for being unordered or equal.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	181	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFOrdNotEqual

Floating-point comparison for being ordered and not equal.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	182	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFUnordNotEqual

Floating-point comparison for being unordered or not equal.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	183	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFOrdLessThan

Floating-point comparison if operands are ordered and *Operand 1* is less than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	184	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFUnordLessThan

Floating-point comparison if operands are unordered or *Operand 1* is less than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	185	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFOrdGreaterThan

Floating-point comparison if operands are ordered and *Operand 1* is greater than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	186	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFUnordGreaterThan

Floating-point comparison if operands are unordered or *Operand 1* is greater than *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	187	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFOrdLessThanEqual

Floating-point comparison if operands are ordered and *Operand 1* is less than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	188	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFUnordLessThanEqual

Floating-point comparison if operands are unordered or *Operand 1* is less than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	189	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFOrdGreaterThanEqual

Floating-point comparison if operands are ordered and *Operand 1* is greater than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	190	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

OpFUnordGreaterThanEqual

Floating-point comparison if operands are unordered or *Operand 1* is greater than or equal to *Operand 2*.

Result Type must be a scalar or vector of [Boolean type](#).

The type of *Operand 1* and *Operand 2* must be a scalar or vector of [floating-point type](#). They must have the same type, and they must have the same number of components as *Result Type*.

Results are computed per component.

5	191	<id> <i>Result Type</i>	Result <id>	<id> <i>Operand 1</i>	<id> <i>Operand 2</i>
---	-----	----------------------------	-------------	--------------------------	--------------------------

3.32.16 Derivative Instructions

OpDPdx Same result as either OpDPdxFine or OpDPdxCoarse on <i>P</i> . Selection of which one is based on external factors. <i>Result Type</i> must be a scalar or vector of floating-point type . The type of <i>P</i> must be the same as <i>Result Type</i> . <i>P</i> is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .				Capability: Shader
4	207	<id> <i>Result Type</i>	Result <id>	<id> <i>P</i>

OpDPdy Same result as either OpDPdyFine or OpDPdyCoarse on <i>P</i> . Selection of which one is based on external factors. <i>Result Type</i> must be a scalar or vector of floating-point type . The type of <i>P</i> must be the same as <i>Result Type</i> . <i>P</i> is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .				Capability: Shader
4	208	<id> <i>Result Type</i>	Result <id>	<id> <i>P</i>

OpFwidth Result is the same as computing the sum of the absolute values of OpDPdx and OpDPdy on <i>P</i> . <i>Result Type</i> must be a scalar or vector of floating-point type . The type of <i>P</i> must be the same as <i>Result Type</i> . <i>P</i> is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .				Capability: Shader
4	209	<id> <i>Result Type</i>	Result <id>	<id> <i>P</i>

OpDPdxFine Result is the partial derivative of P with respect to the window x coordinate. Will use local differencing based on the value of P for the current fragment and its immediate neighbor(s). <i>Result Type</i> must be a scalar or vector of floating-point type . The type of P must be the same as <i>Result Type</i> . P is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .					Capability: DerivativeControl
4	210	<id> <i>Result Type</i>	Result <id>	<id> P	

OpDPdyFine Result is the partial derivative of P with respect to the window y coordinate. Will use local differencing based on the value of P for the current fragment and its immediate neighbor(s). <i>Result Type</i> must be a scalar or vector of floating-point type . The type of P must be the same as <i>Result Type</i> . P is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .					Capability: DerivativeControl
4	211	<id> <i>Result Type</i>	Result <id>	<id> P	

OpFwidthFine Result is the same as computing the sum of the absolute values of OpDPdxFine and OpDPdyFine on P . <i>Result Type</i> must be a scalar or vector of floating-point type . The type of P must be the same as <i>Result Type</i> . P is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .					Capability: DerivativeControl
4	212	<id> <i>Result Type</i>	Result <id>	<id> P	

OpDPdxCoarse Result is the partial derivative of P with respect to the window x coordinate. Will use local differencing based on the value of P for the current fragment's neighbors, and will possibly, but not necessarily, include the value of P for the current fragment. That is, over a given area, the implementation can compute x derivatives in fewer unique locations than would be allowed for OpDPdxFine . <i>Result Type</i> must be a scalar or vector of floating-point type . The type of P must be the same as <i>Result Type</i> . P is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .					Capability: DerivativeControl
4	213	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> P	

OpDPdyCoarse Result is the partial derivative of P with respect to the window y coordinate. Will use local differencing based on the value of P for the current fragment's neighbors, and will possibly, but not necessarily, include the value of P for the current fragment. That is, over a given area, the implementation can compute y derivatives in fewer unique locations than would be allowed for OpDPdyFine . <i>Result Type</i> must be a scalar or vector of floating-point type . The type of P must be the same as <i>Result Type</i> . P is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .					Capability: DerivativeControl
4	214	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> P	

OpFwidthCoarse Result is the same as computing the sum of the absolute values of OpDPdxCoarse and OpDPdyCoarse on P . <i>Result Type</i> must be a scalar or vector of floating-point type . The type of P must be the same as <i>Result Type</i> . P is the value to take the derivative of. This instruction is only valid in the Fragment Execution Model .					Capability: DerivativeControl
4	215	<i><id></i> <i>Result Type</i>	Result <i><id></i>	<i><id></i> P	

3.32.17 Control-Flow Instructions

OpPhi

The SSA phi function.

The result is selected based on control flow: If control reached the current block from *Parent i*, *Result Id* gets the value that *Variable i* had at the end of *Parent i*.

Result Type can be any type.

Operands are a sequence of pairs: (*Variable 1*, *Parent 1* block), (*Variable 2*, *Parent 2* block), ... Each *Parent i* block is the label of an immediate predecessor in the CFG of the current block. There must be exactly one *Parent i* for each parent block of the current block in the CFG. All *Variables* must have a type matching *Result Type*.

Within a block, this instruction must appear before all non-**OpPhi** instructions (except for **OpLine**, which can be mixed with **OpPhi**).

3 + variable	245	<id> <i>Result Type</i>	Result <id>	<id>, <id>, ... <i>Variable, Parent, ...</i>
--------------	-----	----------------------------	--------------------------	---

OpLoopMerge

Declare a structured loop.

This instruction must immediately precede either an **OpBranch** or **OpBranchConditional** instruction. That is, it must be the second-to-last instruction in its block.

Merge Block is the label of the merge block for this structured loop.

Continue Target is the label of a block targeted for processing a loop "continue".

Loop Control Parameters appear in **Loop Control**-table order for any *Loop Control* setting that requires such a parameter.

See **Structured Control Flow** for more detail.

4 + variable	246	<id> <i>Merge Block</i>	<id> <i>Continue Target</i>	Loop Control	<i>Literal, Literal, ...</i> <i>Loop Control</i> <i>Parameters</i>
--------------	-----	----------------------------	--------------------------------	---------------------	--

OpSelectionMerge

Declare a structured selection.

This instruction must immediately precede either an **OpBranchConditional** or **OpSwitch** instruction. That is, it must be the second-to-last instruction in its block.

Merge Block is the label of the merge block for this structured selection.

See **Structured Control Flow** for more detail.

3	247	<id> <i>Merge Block</i>	Selection Control
---	-----	----------------------------	--------------------------

OpLabel

The block label instruction: Any reference to a block is through the *Result <id>* of its label.

Must be the first instruction of any block, and appears only as the first instruction of a block.

2	248	Result <id>
---	-----	-------------

OpBranch

Unconditional branch to *Target Label*.

Target Label must be the *Result <id>* of an **OpLabel** instruction in the current function.

This instruction must be the last instruction in a block.

2	249	<id> Target Label
---	-----	----------------------

OpBranchConditional

If *Condition* is **true**, branch to *True Label*, otherwise branch to *False Label*.

Condition must be a **Boolean type** scalar.

True Label must be an **OpLabel** in the current function.

False Label must be an **OpLabel** in the current function.

Branch weights are unsigned 32-bit integer literals. There must be either no *Branch Weights* or exactly two branch weights. If present, the first is the weight for branching to *True Label*, and the second is the weight for branching to *False Label*. The implied probability that a branch is taken is its weight divided by the sum of the two *Branch weights*. At least one weight must be non-zero. A weight of zero does not imply a branch is dead or permit its removal; branch weights are only hints. The two weights must not overflow a 32-bit unsigned integer when added together.

This instruction must be the last instruction in a block.

4 + variable	250	<id> Condition	<id> True Label	<id> False Label	Literal, Literal, ... Branch weights
--------------	-----	-------------------	--------------------	---------------------	---

OpSwitch

Multi-way branch to one of the operand label *<id>*.

Selector must have a type of [OpTypeInt](#). *Selector* will be compared for equality to the *Target* literals.

Default must be the *<id>* of a label. If *Selector* does not equal any of the *Target* literals, control flow will branch to the *Default* label *<id>*.

Target must be alternating scalar integer *literals* and the *<id>* of a label. If *Selector* equals a *literal*, control flow will branch to the following *label <id>*. It is invalid for any two *literal* to be equal to each other. If *Selector* does not equal any *literal*, control flow will branch to the *Default* label *<id>*. Each *literal* is interpreted with the type of *Selector*: The bit width of *Selector*'s type will be the width of each *literal*'s type. If this width is not a multiple of 32-bits, the literals must be sign extended when the [OpTypeInt Signedness](#) is set to 1. (See [Literal Number](#).)

This instruction must be the last instruction in a block.

3 + variable	251	<i><id></i> <i>Selector</i>	<i><id></i> <i>Default</i>	<i>literal, label <id></i> , <i>literal, label <id></i> , ... <i>Target</i>
--------------	-----	--------------------------------------	-------------------------------------	--

OpKill

Fragment-shader discard.

Ceases all further processing in any [invocation](#) that executes it: Only instructions these invocations executed before **OpKill** will have observable side effects. If this instruction is executed in non-[uniform control flow](#), all subsequent control flow is non-uniform (for invocations that continue to execute).

This instruction must be the last instruction in a block.

This instruction is only valid in the **Fragment Execution Model**.

[Capability](#):
Shader

1	252
---	-----

OpReturn

Return with no value from a function with void return type.

This instruction must be the last instruction in a block.

1	253
---	-----

OpReturnValue

Return a value from a function.

Value is the value returned, by copy, and must match the *Return Type* operand of the **OpTypeFunction** type of the **OpFunction** body this return instruction is in.

This instruction must be the last instruction in a block.

2	254	<id> <i>Value</i>
---	-----	----------------------

OpUnreachable

Declares that this block is not reachable in the CFG.

This instruction must be the last instruction in a block.

1	255
---	-----

OpLifetimeStart

Declare that an object was not defined before this instruction.

Pointer is a pointer to the object whose lifetime is starting. Its type must be an **OpTypePointer** with **Storage Class Function**.

Size must be 0 if *Pointer* is a pointer to a non-void type or the **Addresses capability** is not being used. If *Size* is non-zero, it is the number of bytes of memory whose lifetime is starting. Its type must be an **integer type** scalar. It is treated as unsigned; if its type has *Signedness* of 1, its sign bit cannot be set.

Capability:
Kernel

3	256	<id> <i>Pointer</i>	Literal Number <i>Size</i>
---	-----	------------------------	--------------------------------------

OpLifetimeStop

Declare that an object is dead after this instruction.

Pointer is a pointer to the object whose lifetime is ending. Its type must be an **OpTypePointer** with **Storage Class Function**.

Size must be 0 if *Pointer* is a pointer to a non-void type or the **Addresses capability** is not being used. If *Size* is non-zero, it is the number of bytes of memory whose lifetime is ending. Its type must be an **integer type** scalar. It is treated as unsigned; if its type has *Signedness* of 1, its sign bit cannot be set.

Capability:
Kernel

3	257	<id> <i>Pointer</i>	Literal Number <i>Size</i>
---	-----	------------------------	--------------------------------------

3.32.18 Atomic Instructions

OpAtomicLoad

Atomically load through *Pointer* using the given *Semantics*. All subparts of the value that is loaded will be read atomically with respect to all other atomic accesses to it within *Scope*.

Result Type must be a scalar of [integer type](#) or [floating-point type](#).

Pointer is the pointer to the memory to read. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

6	227	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	--

OpAtomicStore

Atomically store through *Pointer* using the given *Semantics*. All subparts of *Value* will be written atomically with respect to all other atomic accesses to it within *Scope*.

Pointer is the pointer to the memory to write. The type it points to must be a scalar of [integer type](#) or [floating-point type](#).

Value is the value to write. The type of *Value* and the type pointed to by *Pointer* must be the same type.

5	228	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	------------------------	----------------------------	--	----------------------

OpAtomicExchange

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* from copying *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be a scalar of [integer type](#) or [floating-point type](#).

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	229	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	--	----------------------

OpAtomicCompareExchange

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by selecting *Value* if *Original Value* equals *Comparator* or selecting *Original Value* otherwise, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an [integer type](#) scalar.

Use *Equal* for the memory semantics of this instruction when *Value* and *Original Value* compare equal.

Use *Unequal* for the memory semantics of this instruction when *Value* and *Original Value* compare unequal. *Unequal* cannot be set to **Release** or **Acquire and Release**. In addition, *Unequal* cannot be set to a stronger memory-order than *Equal*.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*. This type must also match the type of *Comparator*.

9	230	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Equal</i>	Memory Semantics <id> <i>Unequal</i>	<id> <i>Value</i>	<id> <i>Comparator</i>
---	-----	--------------------------------	--	------------------------	---	--	--	----------------------	---------------------------

OpAtomicCompareExchangeWeak Deprecated (use OpAtomicCompareExchange). Has the same semantics as OpAtomicCompareExchange.								Capability: Kernel	
9	231	<id> Result Type	Result <id>	<id> Pointer	Scope <id> Scope	Memory Semantics <id> Equal	Memory Semantics <id> Unequal	<id> Value	<id> Comparator

OpAtomicIncrement

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* through integer addition of 1 to *Original Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an **integer type** scalar. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

6	232	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	--

OpAtomicDecrement

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* through integer subtraction of 1 from *Original Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an **integer type** scalar. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

6	233	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	--

OpAtomicIAdd

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by integer addition of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an **integer type** scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	234	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	--	----------------------

OpAtomicSub

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by integer subtraction of *Value* from *Original Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an [integer type](#) scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	235	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	---	----------------------

OpAtomicSMin

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by finding the smallest signed integer of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an [integer type](#) scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	236	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	---	----------------------

OpAtomicUMin

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by finding the smallest unsigned integer of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an **integer type** scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	237	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	---	----------------------

OpAtomicSMax

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by finding the largest signed integer of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an **integer type** scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	238	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	---	----------------------

OpAtomicUMax

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by finding the largest unsigned integer of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an [integer type](#) scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	239	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-----------------------------------	------------------------	--	--	----------------------

OpAtomicAnd

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by the bitwise AND of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an [integer type](#) scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	240	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-----------------------------------	------------------------	--	--	----------------------

OpAtomicOr

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by the bitwise OR of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an [integer type](#) scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	241	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	---	----------------------

OpAtomicXor

Perform the following steps atomically with respect to any other atomic accesses within *Scope* to the same location:

- 1) load through *Pointer* to get an *Original Value*,
- 2) get a *New Value* by the bitwise exclusive OR of *Original Value* and *Value*, and
- 3) store the *New Value* back through *Pointer*.

The instruction's result is the *Original Value*.

Result Type must be an [integer type](#) scalar.

The type of *Value* must be the same as *Result Type*. The type of the value pointed to by *Pointer* must be the same as *Result Type*.

7	242	<id> <i>Result Type</i>	Result <id>	<id> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	<id> <i>Value</i>
---	-----	----------------------------	-------------	------------------------	----------------------------	---	----------------------

OpAtomicFlagTestAndSet Atomically sets the flag value pointed to by <i>Pointer</i> to the set state. <i>Pointer</i> must be a pointer to a 32-bit integer type representing an atomic flag. The instruction's result is true if the flag was in the set state or false if the flag was in the clear state immediately before the operation. <i>Result Type</i> must be a Boolean type . Results are undefined if an atomic flag is modified by an instruction other than OpAtomicFlagTestAndSet or OpAtomicFlagClear					Capability: Kernel	
6	318	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Pointer</i>	Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>

OpAtomicFlagClear Atomically sets the flag value pointed to by <i>Pointer</i> to the clear state. <i>Pointer</i> must be a pointer to a 32-bit integer type representing an atomic flag. Memory Semantics cannot be Acquire or AcquireRelease Results are undefined if an atomic flag is modified by an instruction other than OpAtomicFlagTestAndSet or OpAtomicFlagClear					Capability: Kernel	
4	319	<i><id></i> <i>Pointer</i>		Scope <id> <i>Scope</i>	Memory Semantics <id> <i>Semantics</i>	

3.32.19 Primitive Instructions

OpEmitVertex Emits the current values of all output variables to the current output primitive. After execution, the values of all output variables are undefined. This instruction can only be used when only one stream is present.		Capability: Geometry
1		218

OpEndPrimitive Finish the current primitive and start a new one. No vertex is emitted. This instruction can only be used when only one stream is present.		Capability: Geometry
1		219

OpEmitStreamVertex Emits the current values of all output variables to the current output primitive. After execution, the values of all output variables are undefined. <i>Stream</i> must be an <i><id></i> of a constant instruction with a scalar integer type. That constant is the output-primitive stream number. This instruction can only be used when multiple streams are present.		Capability: GeometryStreams
2	220	<i><id></i> <i>Stream</i>

OpEndStreamPrimitive Finish the current primitive and start a new one. No vertex is emitted. <i>Stream</i> must be an <i><id></i> of a constant instruction with a scalar integer type. That constant is the output-primitive stream number. This instruction can only be used when multiple streams are present.		Capability: GeometryStreams
2	221	<i><id></i> <i>Stream</i>

3.32.20 Barrier Instructions

OpControlBarrier

Wait for other invocations of this module to reach the current point of execution.

All [invocations](#) of this module within *Execution* scope must reach this point of execution before any invocation will proceed beyond it.

This instruction is only guaranteed to work correctly if placed strictly within [uniform control flow](#) within *Execution*. This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely.

If *Semantics* is not **None**, this instruction also serves as an [OpMemoryBarrier](#) instruction, and must also perform and adhere to the description and semantics of an **OpMemoryBarrier** instruction with the same *Memory* and *Semantics* operands. This allows atomically specifying both a control barrier and a memory barrier (that is, without needing two instructions). If *Semantics* is **None**, *Memory* is ignored.

Before version 1.3, it is only valid to use this instruction with **TessellationControl**, **GLCompute**, or **Kernel execution models**. There is no such restriction starting with version 1.3.

When used with the **TessellationControl execution model**, it also implicitly synchronizes the **Output Storage Class**: Writes to **Output** variables performed by any invocation executed prior to a **OpControlBarrier** will be visible to any other invocation after return from that **OpControlBarrier**.

4	224	Scope <id> <i>Execution</i>	Scope <id> <i>Memory</i>	Memory Semantics <id> <i>Semantics</i>
---	-----	--	---	---

OpMemoryBarrier

Control the order that memory accesses are observed.

Ensures that memory accesses issued before this instruction will be observed before memory accesses issued after this instruction. This control is ensured only for memory accesses issued by this [invocation](#) and observed by another invocation executing within *Memory* scope.

Semantics declares what kind of memory is being controlled and what kind of control to apply.

To execute both a memory barrier and a control barrier, see [OpControlBarrier](#).

3	225	Scope <id> <i>Memory</i>	Memory Semantics <id> <i>Semantics</i>
---	-----	---	---

OpNamedBarrierInitialize

Declare a new named-barrier object.

Result Type must be the type [OpTypeNamedBarrier](#).

Subgroup Count must be a 32-bit [integer type](#) scalar representing the number of subgroups that must reach the current point of execution.

Capability:
NamedBarrier

[Missing before version 1.1.](#)

4	328	<id> <i>Result Type</i>	Result <id>	<id> <i>Subgroup Count</i>
---	-----	--	-----------------------------------	---

OpMemoryNamedBarrier Wait for other invocations of this module to reach the current point of execution. <i>Named Barrier</i> must be the type OpTypeNamedBarrier . If <i>Semantics</i> is not None , this instruction also serves as an OpMemoryBarrier instruction, and must also perform and adhere to the description and semantics of an OpMemoryBarrier instruction with the same <i>Memory</i> and <i>Semantics</i> operands. This allows atomically specifying both a control barrier and a memory barrier (that is, without needing two instructions). If <i>Semantics</i> None , <i>Memory</i> is ignored.				
Capability: NamedBarrier Missing before version 1.1.				
4	329	<i><id></i> <i>Named Barrier</i>	Scope <id> <i>Memory</i>	Memory Semantics <id> <i>Semantics</i>

3.32.21 Group Instructions

OpGroupAsyncCopy Perform an asynchronous group copy of <i>Num Elements</i> elements from <i>Source</i> to <i>Destination</i> . The asynchronous copy is performed by all work-items in a group. This instruction returns an event object that can be used by OpGroupWaitEvents to wait for the async copy to finish. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be an OpTypeEvent object. <i>Destination</i> must be a pointer to a scalar or vector of floating-point type or integer type . <i>Destination</i> pointer Storage Class must be Workgroup or CrossWorkgroup . The type of <i>Source</i> must be the same as <i>Destination</i> . When <i>Destination</i> pointer Storage Class is Workgroup , the <i>Source</i> pointer Storage Class must be CrossWorkgroup . In this case <i>Stride</i> defines the stride in elements when reading from <i>Source</i> pointer. When <i>Destination</i> pointer Storage Class is CrossWorkgroup , the <i>Source</i> pointer Storage Class must be Workgroup . In this case <i>Stride</i> defines the stride in elements when writing each element to <i>Destination</i> pointer. <i>Stride</i> and <i>NumElements</i> must be a 32-bit integer type scalar when the addressing model is <i>Physical32</i> and 64 bit integer type scalar when the <i>Addressing Model</i> is <i>Physical64</i> . <i>Event</i> must have a type of OpTypeEvent . <i>Event</i> can be used to associate the copy with a previous copy allowing an event to be shared by multiple copies. Otherwise <i>Event</i> should be an OpConstantNull . If <i>Event</i> argument is not OpConstantNull , the event object supplied in event argument will be returned.								Capability: Kernel	
9	259	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Destination</i>	<id> <i>Source</i>	<id> <i>Num Elements</i>	<id> <i>Stride</i>	<id> <i>Event</i>

OpGroupWaitEvents Wait for events generated by OpGroupAsyncCopy operations to complete. <i>Events List</i> points to <i>Num Events</i> event objects, which will be released after the wait is performed. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Num Events</i> must be a 32-bit integer type scalar. <i>Events List</i> must be a pointer to OpTypeEvent .					Capability: Kernel
4	260	Scope <id> <i>Execution</i>	<id> <i>Num Events</i>	<id> <i>Events List</i>	

OpGroupAll Evaluates a predicate for all invocations in the group, resulting in true if predicate evaluates to true for all invocations in the group, otherwise the result is false . All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be a Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Predicate</i> must be a Boolean type .					Capability: Groups
5	261	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Predicate</i>

OpGroupAny Evaluates a predicate for all invocations in the group, resulting in true if predicate evaluates to true for any invocation in the group, otherwise the result is false . All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be a Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Predicate</i> must be a Boolean type .					Capability: Groups
5	262	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Predicate</i>

OpGroupBroadcast				Capability: Groups		
<p>Return the <i>Value</i> of the invocation identified by the local id <i>LocalId</i> to all invocations in the group.</p> <p>All invocations of this module within <i>Execution</i> must reach this point of execution.</p> <p>This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i>. This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely.</p> <p><i>Result Type</i> must be a 32-bit or 64-bit integer type or a 16, 32 or 64 float type scalar.</p> <p><i>Execution</i> must be Workgroup or Subgroup Scope.</p> <p>The type of <i>Value</i> must be the same as <i>Result Type</i>.</p> <p><i>LocalId</i> must be an integer datatype. It can be a scalar, or a vector with 2 components or a vector with 3 components. <i>LocalId</i> must be the same for all invocations in the group.</p>						
6	263	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>LocalId</i>

<div>OpGroupIAdd</div> <div>An integer add group operation specified for all values of X specified by invocations in the group.</div> <div>All invocations of this module within <i>Execution</i> must reach this point of execution.</div> <div>This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i>. This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely.</div> <div><i>Result Type</i> must be a 32-bit or 64-bit integer type scalar.</div> <div><i>Execution</i> must be Workgroup or Subgroup Scope.</div> <div>The identity I for <i>Operation</i> is 0.</div> <div>The type of X must be the same as <i>Result Type</i>.</div>					<div>Capability:</div> <div>Groups</div>	
6	264	<div><id></div> <div>Result Type</div>	<div>Result <id></div>	<div>Scope <id></div> <div>Execution</div>	<div>Group Operation</div> <div>Operation</div>	<div><id></div> <div>X</div>

OpGroupFAdd A floating-point add group operation specified for all values of <i>X</i> specified by invocations in the group. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be a 16-bit, 32-bit, or 64-bit floating-point type scalar. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. The type of <i>X</i> must be the same as <i>Result Type</i> .				Capability: Groups		
6	265	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>X</i>

<div>OpGroupFMin</div> <div>A floating-point minimum group operation specified for all values of <i>X</i> specified by invocations in the group.</div> <div>All invocations of this module within <i>Execution</i> must reach this point of execution.</div> <div>This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i>. This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely.</div> <div><i>Result Type</i> must be a 16-bit, 32-bit, or 64-bit floating-point type scalar.</div> <div><i>Execution</i> must be Workgroup or Subgroup Scope.</div> <div>The identity <i>I</i> for <i>Operation</i> is +INF.</div> <div>The type of <i>X</i> must be the same as <i>Result Type</i>.</div>					<div>Capability:</div> <div>Groups</div>	
6	266	<div><id></div> <div>Result Type</div>	<div>Result <id></div>	<div>Scope <id></div> <div>Execution</div>	<div>Group Operation</div> <div>Operation</div>	<div><id></div> <div>X</div>

OpGroupUMin An unsigned integer minimum group operation specified for all values of <i>X</i> specified by invocations in the group. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be a 32-bit or 64-bit integer type scalar. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is <code>UINT_MAX</code> when <i>X</i> is 32 bits wide and <code>ULONG_MAX</code> when <i>X</i> is 64 bits wide. The type of <i>X</i> must be the same as <i>Result Type</i> .					Capability: Groups	
6	267	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>X</i>

<div>OpGroupSMin</div> <div>A signed integer minimum group operation specified for all values of <i>X</i> specified by invocations in the group.</div> <div>All invocations of this module within <i>Execution</i> must reach this point of execution.</div> <div>This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i>. This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely.</div> <div><i>Result Type</i> must be a 32-bit or 64-bit integer type scalar.</div> <div><i>Execution</i> must be Workgroup or Subgroup Scope.</div> <div>The identity <i>I</i> for <i>Operation</i> is INT_MAX when <i>X</i> is 32 bits wide and LONG_MAX when <i>X</i> is 64 bits wide.</div> <div>The type of <i>X</i> must be the same as <i>Result Type</i>.</div>					<div>Capability:</div> <div>Groups</div>	
6	268	<div><id></div> <div>Result Type</div>	<div>Result <id></div>	<div>Scope <id></div> <div>Execution</div>	<div>Group Operation</div> <div>Operation</div>	<div><id></div> <div>X</div>

OpGroupFMax A floating-point maximum group operation specified for all values of <i>X</i> specified by invocations in the group. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be a 16-bit, 32-bit, or 64-bit floating-point type scalar. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is -INF. The type of <i>X</i> must be the same as <i>Result Type</i> .				Capability: Groups		
6	269	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>X</i>

OpGroupUMax An unsigned integer maximum group operation specified for all values of <i>X</i> specified by invocations in the group. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be a 32-bit or 64-bit integer type scalar. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. The type of <i>X</i> must be the same as <i>Result Type</i> .				Capability: Groups		
6	270	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>X</i>

OpGroupSMax A signed integer maximum group operation specified for all values of <i>X</i> specified by invocations in the group. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>X</i> and <i>Result Type</i> must be a 32-bit or 64-bit OpTypeInt data type. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is INT_MIN when <i>X</i> is 32 bits wide and LONG_MIN when <i>X</i> is 64 bits wide. The type of <i>X</i> must be the same as <i>Result Type</i> .				Capability: Groups		
6	271	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>X</i>

OpSubgroupBallotKHR See extension SPV_KHR_shader_ballot				Capability: SubgroupBallotKHR		
4	4421	<id> <i>Result Type</i>	Result <id>	<id> <i>Predicate</i>		

OpSubgroupFirstInvocationKHR				Capability: SubgroupBallotKHR
See extension SPV_KHR_shader_ballot				
4	4422	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Value</i>

OpSubgroupAllKHR				Capability: SubgroupVoteKHR
TBD				Reserved.
4	4428	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Predicate</i>

OpSubgroupAnyKHR				Capability: SubgroupVoteKHR
TBD				Reserved.
4	4429	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Predicate</i>

OpSubgroupAllEqualKHR				Capability: SubgroupVoteKHR
TBD				Reserved.
4	4430	<i><id></i> <i>Result Type</i>	Result <id>	<i><id></i> <i>Predicate</i>

OpSubgroupReadInvocationKHR					Capability: SubgroupBallotKHR
See extension SPV_KHR_shader_ballot					Reserved.
5	4432	<id> <i>Result Type</i>	Result <id>	<id> <i>Value</i>	<id> <i>Index</i>

OpGroupIAddNonUniformAMD					Capability: Groups	
TBD					Reserved.	
6	5000	<id> Result Type	Result <id>	Scope <id> Execution	Group Operation Operation	<id> X

OpGroupFAddNonUniformAMD				Capability: Groups
TBD				Reserved.

6	5001	<i><id> Result Type</i>	<i>Result <id></i>	<i>Scope <id> Execution</i>	<i>Group Operation Operation</i>	<i><id> X</i>
---	------	-----------------------------------	--------------------------	---------------------------------------	--	-------------------------

OpGroupFMinNonUniformAMD					Capability: Groups	
TBD					Reserved.	
6	5002	<id> Result Type	Result <id>	Scope <id> Execution	Group Operation Operation	<id> X

OpGroupUMinNonUniformAMD					Capability: Groups	
TBD					Reserved.	
6	5003	<id> Result Type	Result <id>	Scope <id> Execution	Group Operation Operation	<id> X

OpGroupSMinNonUniformAMD					Capability: Groups	
TBD					Reserved.	
6	5004	<id> Result Type	Result <id>	Scope <id> Execution	Group Operation Operation	<id> X

OpGroupFMaxNonUniformAMD					Capability: Groups	
TBD					Reserved.	
6	5005	<id> Result Type	Result <id>	Scope <id> Execution	Group Operation Operation	<id> X

OpGroupUMaxNonUniformAMD					Capability: Groups	
TBD					Reserved.	
6	5006	<id> Result Type	Result <id>	Scope <id> Execution	Group Operation Operation	<id> X

OpGroupSMaxNonUniformAMD TBD					Capability: Groups Reserved.
--	--	--	--	--	--

6	5007	<i><id> Result Type</i>	<i>Result <id></i>	<i>Scope <id> Execution</i>	<i>Group Operation Operation</i>	<i><id> X</i>
---	------	-----------------------------------	--------------------------	---------------------------------------	--	-------------------------

OpSubgroupShuffleINTEL TBD					Capability: SubgroupShuffleINTEL Reserved.
5	5571	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Data</i>	<i><id> InvocationId</i>

OpSubgroupShuffleDownINTEL TBD					Capability: SubgroupShuffleINTEL Reserved.
6	5572	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Current</i>	<i><id> Next</i> <i><id> Delta</i>

OpSubgroupShuffleUpINTEL TBD					Capability: SubgroupShuffleINTEL Reserved.
6	5573	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Previous</i>	<i><id> Current</i> <i><id> Delta</i>

OpSubgroupShuffleXorINTEL TBD					Capability: SubgroupShuffleINTEL Reserved.
5	5574	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Data</i>	<i><id> Value</i>

OpSubgroupBlockReadINTEL TBD					Capability: SubgroupBufferBlockIOINTEL Reserved.
4	5575	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Ptr</i>	

OpSubgroupBlockWriteINTEL TBD					Capability: SubgroupBufferBlockIOINTEL Reserved.
3	5576	<i><id> Ptr</i>		<i><id> Data</i>	

OpSubgroupImageBlockReadINTEL					Capability:
TBD					SubgroupImageBlockIOINTEL
					Reserved.
5	5577	<id> Result Type	Result <id>	<id> Image	<id> Coordinate

OpSubgroupImageBlockWriteINTEL				Capability:
TBD				SubgroupImageBlockIOINTEL
				Reserved.
4	5578	<id> Image	<id> Coordinate	<id> Data

3.32.22 Device-Side Enqueue Instructions

OpEnqueueMarker Enqueue a marker command to the queue object specified by <i>Queue</i> . The marker command waits for a list of events to complete, or if the list is empty it waits for all previously enqueued commands in <i>Queue</i> to complete before the marker completes. <i>Result Type</i> must be a 32-bit integer type scalar. A successful enqueue results in the value 0. A failed enqueue results in a non-0 value. <i>Queue</i> must be of the type OpTypeQueue . <i>Num Events</i> specifies the number of event objects in the wait list pointed to by <i>Wait Events</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Wait Events</i> specifies the list of wait event objects and must be a pointer to OpTypeDeviceEvent . <i>Ret Event</i> is a pointer to a device event which gets implicitly retained by this instruction. It must have a type of OpTypePointer to OpTypeDeviceEvent . If <i>Ret Event</i> is set to null this instruction becomes a no-op.						Capability: DeviceEnqueue	
7	291	<id> <i>Result Type</i>	Result <id>	<id> <i>Queue</i>	<id> <i>Num Events</i>	<id> <i>Wait Events</i>	<id> <i>Ret Event</i>

OpEnqueueKernel Enqueue the function specified by <i>Invoke</i> and the NDRange specified by <i>ND Range</i> for execution to the queue object specified by <i>Queue</i> . <i>Result Type</i> must be a 32-bit integer type scalar. A successful enqueue results in the value 0. A failed enqueue results in a non-0 value. <i>Queue</i> must be of the type OpTypeQueue . <i>Flags</i> must be an integer type scalar. The content of <i>Flags</i> is interpreted as Kernel Enqueue Flags mask. The type of <i>ND Range</i> must be an OpTypeStruct whose members are as described by the <i>Result Type</i> of OpBuildNDRange . <i>Num Events</i> specifies the number of event objects in the wait list pointed to by <i>Wait Events</i> and must be 32-bit integer type scalar, which is treated as an unsigned integer. <i>Wait Events</i> specifies the list of wait event objects and must be a pointer to OpTypeDeviceEvent . <i>Ret Event</i> must be a pointer to OpTypeDeviceEvent which gets implicitly retained by this instruction. <i>Invoke</i> must be an OpFunction whose OpTypeFunction operand has: <ul style="list-style-type: none"> - <i>Result Type</i> must be OpTypeVoid. - The first parameter must have a type of OpTypePointer to an 8-bit OpTypeInt. - An optional list of parameters, each of which must have a type of OpTypePointer to the Workgroup Storage Class. <i>Param</i> is the first parameter of the function specified by <i>Invoke</i> and must be a pointer to an 8-bit integer type scalar. <i>Param Size</i> is the size in bytes of the memory pointed to by <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Param Align</i> is the alignment of <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. Each <i>Local Size</i> operand corresponds (in order) to one OpTypePointer to Workgroup Storage Class parameter to the <i>Invoke</i> function, and specifies the number of bytes of Workgroup storage used to back the pointer during the execution of the <i>Invoke</i> function.											Capability: DeviceEnqueue			
13 + vari- able	292	<id> <i>Result Type</i>	Result <id>	<id> <i>Queue</i>	<id> <i>Flags</i>	<id> <i>ND Range</i>	<id> <i>Num Events</i>	<id> <i>Wait Events</i>	<id> <i>Ret Event</i>	<id> <i>Invoke</i>	<id> <i>Param</i>	<id> <i>Param Size</i>	<id> <i>Param Align</i>	<id>, <id>, ... <i>Local Size</i>

OpGetKernelNDRangeSubGroupCount Returns the number of subgroups in each workgroup of the dispatch (except for the last in cases where the global size does not divide cleanly into work-groups) given the combination of the passed NDRange descriptor specified by <i>ND Range</i> and the function specified by <i>Invoke</i> . <i>Result Type</i> must be a 32-bit integer type scalar. The type of <i>ND Range</i> must be an OpTypeStruct whose members are as described by the <i>Result Type</i> of OpBuildNDRange . <i>Invoke</i> must be an OpFunction whose OpTypeFunction operand has: <ul style="list-style-type: none"> - <i>Result Type</i> must be OpTypeVoid. - The first parameter must have a type of OpTypePointer to an 8-bit OpTypeInt. - An optional list of parameters, each of which must have a type of OpTypePointer to the Workgroup Storage Class. <i>Param</i> is the first parameter of the function specified by <i>Invoke</i> and must be a pointer to an 8-bit integer type scalar. <i>Param Size</i> is the size in bytes of the memory pointed to by <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Param Align</i> is the alignment of <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer.							Capability: DeviceEnqueue	
8	293	<id> <i>Result Type</i>	Result <id>	<id> <i>ND Range</i>	<id> <i>Invoke</i>	<id> <i>Param</i>	<id> <i>Param Size</i>	<id> <i>Param Align</i>

OpGetKernelNDRangeMaxSubGroupSize Returns the maximum sub-group size for the function specified by <i>Invoke</i> and the NDRange specified by <i>ND Range</i> . <i>Result Type</i> must be a 32-bit integer type scalar. The type of <i>ND Range</i> must be an OpTypeStruct whose members are as described by the <i>Result Type</i> of OpBuildNDRange . <i>Invoke</i> must be an OpFunction whose OpTypeFunction operand has: <ul style="list-style-type: none"> - <i>Result Type</i> must be OpTypeVoid. - The first parameter must have a type of OpTypePointer to an 8-bit OpTypeInt. - An optional list of parameters, each of which must have a type of OpTypePointer to the Workgroup Storage Class. <i>Param</i> is the first parameter of the function specified by <i>Invoke</i> and must be a pointer to an 8-bit integer type scalar. <i>Param Size</i> is the size in bytes of the memory pointed to by <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Param Align</i> is the alignment of <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer.							Capability: DeviceEnqueue	
8	294	<id> <i>Result Type</i>	Result <id>	<id> <i>ND Range</i>	<id> <i>Invoke</i>	<id> <i>Param</i>	<id> <i>Param Size</i>	<id> <i>Param Align</i>

OpGetKernelWorkGroupSize Returns the maximum work-group size that can be used to execute the function specified by <i>Invoke</i> on the device. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Invoke</i> must be an OpFunction whose OpTypeFunction operand has: <ul style="list-style-type: none"> - <i>Result Type</i> must be OpTypeVoid. - The first parameter must have a type of OpTypePointer to an 8-bit OpTypeInt. - An optional list of parameters, each of which must have a type of OpTypePointer to the Workgroup Storage Class. <i>Param</i> is the first parameter of the function specified by <i>Invoke</i> and must be a pointer to an 8-bit integer type scalar. <i>Param Size</i> is the size in bytes of the memory pointed to by <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Param Align</i> is the alignment of <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer.							Capability: DeviceEnqueue	
7	295	<id> <i>Result Type</i>	Result <id>	<id> <i>Invoke</i>	<id> <i>Param</i>	<id> <i>Param Size</i>	<id> <i>Param Align</i>	

OpGetKernelPreferredWorkGroupSizeMultiple Returns the preferred multiple of work-group size for the function specified by <i>Invoke</i> . This is a performance hint. Specifying a work-group size that is not a multiple of the value returned by this query as the value of the local work size will not fail to enqueue <i>Invoke</i> for execution unless the work-group size specified is larger than the device maximum. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Invoke</i> must be an OpFunction whose OpTypeFunction operand has: - <i>Result Type</i> must be OpTypeVoid . - The first parameter must have a type of OpTypePointer to an 8-bit OpTypeInt . - An optional list of parameters, each of which must have a type of OpTypePointer to the Workgroup Storage Class . <i>Param</i> is the first parameter of the function specified by <i>Invoke</i> and must be a pointer to an 8-bit integer type scalar. <i>Param Size</i> is the size in bytes of the memory pointed to by <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Param Align</i> is the alignment of <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer.					Capability: DeviceEnqueue		
7	296	<id> <i>Result Type</i>	Result <id>	<id> <i>Invoke</i>	<id> <i>Param</i>	<id> <i>Param Size</i>	<id> <i>Param Align</i>

OpRetainEvent Increments the reference count of the event object specified by <i>Event</i> . <i>Event</i> must be an event that was produced by OpEnqueueKernel , OpEnqueueMarker or OpCreateUserEvent .			Capability: DeviceEnqueue				
2	297		<id> <i>Event</i>				

OpReleaseEvent Decrements the reference count of the event object specified by <i>Event</i> . The event object is deleted once the event reference count is zero, the specific command identified by this event has completed (or terminated) and there are no commands in any device command queue that require a wait for this event to complete. <i>Event</i> must be an event that was produced by OpEnqueueKernel , OpEnqueueMarker or OpCreateUserEvent .		Capability: DeviceEnqueue	
2	298	<id> <i>Event</i>	

OpCreateUserEvent Create a user event. The execution status of the created event is set to a value of 2 (CL_SUBMITTED). <i>Result Type</i> must be OpTypeDeviceEvent .		Capability: DeviceEnqueue	
3	299	<id> <i>Result Type</i>	Result <id>

OpIsValidEvent Returns true if the event specified by <i>Event</i> is a valid event, otherwise result is false . <i>Result Type</i> must be a Boolean type . <i>Event</i> must have a type of OpTypeDeviceEvent			Capability: DeviceEnqueue	
4	300	<id> <i>Result Type</i>	Result <id>	<id> <i>Event</i>

OpSetUserEventStatus Sets the execution status of a user event specified by <i>Event</i> . <i>Status</i> can be either 0 (CL_COMPLETE) to indicate that this kernel and all its child kernels finished execution successfully, or a negative integer value indicating an error. <i>Event</i> must have a type of OpTypeDeviceEvent that was produced by OpCreateUserEvent . <i>Status</i> must have a type of 32-bit OpTypeInt treated as a signed integer.			Capability: DeviceEnqueue	
3	301	<id> <i>Event</i>	<id> <i>Status</i>	

OpCaptureEventProfilingInfo Captures the profiling information specified by <i>Profiling Info</i> for the command associated with the event specified by <i>Event</i> in the memory pointed to by <i>Value</i> . The profiling information will be available in the memory pointed to by <i>Value</i> once the command identified by <i>Event</i> has completed. <i>Event</i> must have a type of OpTypeDeviceEvent that was produced by OpEnqueueKernel or OpEnqueueMarker . <i>Profiling Info</i> must be an integer type scalar. The content of <i>Profiling Info</i> is interpreted as Kernel Profiling Info mask. <i>Value</i> must be a pointer to a scalar 8-bit integer type in the CrossWorkgroup Storage Class . When <i>Profiling Info</i> is CmdExecTime , <i>Value</i> must point to 128-bit memory range. The first 64 bits contain the elapsed time CL_PROFILING_COMMAND_END - CL_PROFILING_COMMAND_START for the command identified by <i>Event</i> in nanoseconds. The second 64 bits contain the elapsed time CL_PROFILING_COMMAND_COMPLETE - CL_PROFILING_COMMAND_START for the command identified by <i>Event</i> in nanoseconds. Note: The behavior of this instruction is undefined when called multiple times for the same event.				
Capability: DeviceEnqueue				
4	302	<id> <i>Event</i>	<id> <i>Profiling Info</i>	<id> <i>Value</i>

OpGetDefaultQueue Returns the default device queue. If a default device queue has not been created, a null queue object is returned. <i>Result Type</i> must be an OpTypeQueue .			Capability: DeviceEnqueue
3	303	<id> <i>Result Type</i>	Result <id>

OpBuildNDRange Given the global work size specified by <i>GlobalWorkSize</i> , local work size specified by <i>LocalWorkSize</i> and global work offset specified by <i>GlobalWorkOffset</i> , builds a 1D, 2D or 3D ND-range descriptor structure and returns it. <i>Result Type</i> must be an OpTypeStruct with the following ordered list of members, starting from the first to last: 1) 32-bit integer type scalar, that specifies the number of dimensions used to specify the global work-items and work-items in the work-group. 2) OpTypeArray with 3 elements, where each element is 32-bit integer type scalar when the addressing model is Physical32 and 64-bit integer type scalar when the addressing model is Physical64 . This member is an array of per-dimension unsigned values that describe the offset used to calculate the global ID of a work-item. 3) OpTypeArray with 3 elements, where each element is 32-bit integer type scalar when the addressing model is Physical32 and 64-bit integer type scalar when the addressing model is Physical64 . This member is an array of per-dimension unsigned values that describe the number of global work-items in the dimensions that will execute the kernel function. 4) OpTypeArray with 3 elements, where each element is 32-bit integer type scalar when the addressing model is Physical32 and 64-bit integer type scalar when the addressing model is Physical64 . This member is an array of per-dimension unsigned values that describe the number of work-items that make up a work-group. <i>GlobalWorkSize</i> must be a scalar or an array with 2 or 3 components. Where the type of each element in the array is 32-bit integer type scalar when the addressing model is Physical32 or 64-bit integer type scalar when the addressing model is Physical64 . The type of <i>LocalWorkSize</i> must be the same as <i>GlobalWorkSize</i> . The type of <i>GlobalWorkOffset</i> must be the same as <i>GlobalWorkSize</i> .				Capability: DeviceEnqueue		
6	304	<id> <i>Result Type</i>	Result <id>	<id> <i>GlobalWorkSize</i>	<id> <i>LocalWorkSize</i>	<id> <i>GlobalWorkOffset</i>

OpGetKernelLocalSizeForSubgroupCount Returns the 1D local size to enqueue <i>Invoke</i> with <i>Subgroup Count</i> subgroups per workgroup. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Subgroup Count</i> must be a 32-bit integer type scalar. <i>Invoke</i> must be an OpFunction whose OpTypeFunction operand has: <ul style="list-style-type: none"> - <i>Result Type</i> must be OpTypeVoid. - The first parameter must have a type of OpTypePointer to an 8-bit OpTypeInt. - An optional list of parameters, each of which must have a type of OpTypePointer to the Workgroup Storage Class. <i>Param</i> is the first parameter of the function specified by <i>Invoke</i> and must be a pointer to an 8-bit integer type scalar. <i>Param Size</i> is the size in bytes of the memory pointed to by <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Param Align</i> is the alignment of <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer.							Capability: SubgroupDispatch Missing before version 1.1.	
8	325	<id> <i>Result Type</i>	Result <id>	<id> <i>Subgroup Count</i>	<id> <i>Invoke</i>	<id> <i>Param</i>	<id> <i>Param Size</i>	<id> <i>Param Align</i>

OpGetKernelMaxNumSubgroups Returns the maximum number of subgroups that can be used to execute <i>Invoke</i> on the device. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Invoke</i> must be an OpFunction whose OpTypeFunction operand has: <ul style="list-style-type: none"> - <i>Result Type</i> must be OpTypeVoid. - The first parameter must have a type of OpTypePointer to an 8-bit OpTypeInt. - An optional list of parameters, each of which must have a type of OpTypePointer to the Workgroup Storage Class. <i>Param</i> is the first parameter of the function specified by <i>Invoke</i> and must be a pointer to an 8-bit integer type scalar. <i>Param Size</i> is the size in bytes of the memory pointed to by <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer. <i>Param Align</i> is the alignment of <i>Param</i> and must be a 32-bit integer type scalar, which is treated as an unsigned integer.							Capability: SubgroupDispatch Missing before version 1.1.	
7	326	<id> <i>Result Type</i>	Result <id>	<id> <i>Invoke</i>	<id> <i>Param</i>	<id> <i>Param Size</i>	<id> <i>Param Align</i>	

3.32.23 Pipe Instructions

OpReadPipe Read a packet from the pipe object specified by <i>Pipe</i> into <i>Pointer</i> . Result is 0 if the operation is successful and a negative value if the pipe is empty. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Pipe</i> must have a type of OpTypePipe with ReadOnly access qualifier. <i>Pointer</i> must have a type of OpTypePointer with the same data type as <i>Pipe</i> and a Generic Storage Class . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.					Capability: Pipes		
7	274	<id> <i>Result Type</i>	Result <id>	<id> <i>Pipe</i>	<id> <i>Pointer</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpWritePipe Write a packet from <i>Pointer</i> to the pipe object specified by <i>Pipe</i> . Result is 0 if the operation is successful and a negative value if the pipe is full. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Pipe</i> must have a type of OpTypePipe with WriteOnly access qualifier. <i>Pointer</i> must have a type of OpTypePointer with the same data type as <i>Pipe</i> and a Generic Storage Class. <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - 1 <= <i>Packet Alignment</i> <= <i>Packet Size</i> . - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.						Capability: Pipes	
7	275	<id> Result Type	Result <id>	<id> Pipe	<id> Pointer	<id> Packet Size	<id> Packet Alignment

OpReservedReadPipe Read a packet from the reserved area specified by <i>Reserve Id</i> and <i>Index</i> of the pipe object specified by <i>Pipe</i> into <i>Pointer</i> . The reserved pipe entries are referred to by indices that go from 0 ... <i>Num Packets</i> - 1. Result is 0 if the operation is successful and a negative value otherwise. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Pipe</i> must have a type of OpTypePipe with ReadOnly access qualifier. <i>Reserve Id</i> must have a type of OpTypeReserveId. <i>Index</i> must be a 32-bit integer type scalar, which is treated as an unsigned value. <i>Pointer</i> must have a type of OpTypePointer with the same data type as <i>Pipe</i> and a Generic Storage Class . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - 1 <= <i>Packet Alignment</i> <= <i>Packet Size</i> . - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.								Capability: Pipes	
9	276	<id> Result Type	Result <id>	<id> Pipe	<id> Reserve Id	<id> Index	<id> Pointer	<id> Packet Size	<id> Packet Alignment

OpReservedWritePipe Write a packet from <i>Pointer</i> into the reserved area specified by <i>Reserve Id</i> and <i>Index</i> of the pipe object specified by <i>Pipe</i> . The reserved pipe entries are referred to by indices that go from 0 ... <i>Num Packets</i> - 1. Result is 0 if the operation is successful and a negative value otherwise. <i>Result Type</i> must be a 32-bit integer type scalar. <i>Pipe</i> must have a type of OpTypePipe with WriteOnly access qualifier. <i>Reserve Id</i> must have a type of OpTypeReserveId. <i>Index</i> must be a 32-bit integer type scalar, which is treated as an unsigned value. <i>Pointer</i> must have a type of OpTypePointer with the same data type as <i>Pipe</i> and a Generic Storage Class . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - 1 <= <i>Packet Alignment</i> <= <i>Packet Size</i> . - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.								Capability: Pipes	
9	277	<id> Result Type	Result <id>	<id> Pipe	<id> Reserve Id	<id> Index	<id> Pointer	<id> Packet Size	<id> Packet Alignment

OpReserveReadPipePackets Reserve <i>Num Packets</i> entries for reading from the pipe object specified by <i>Pipe</i> . Result is a valid reservation ID if the reservation is successful. <i>Result Type</i> must be an OpTypeReserveId . <i>Pipe</i> must have a type of OpTypePipe with ReadOnly access qualifier. <i>Num Packets</i> must be a 32-bit integer type scalar, which is treated as an unsigned value. <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.						Capability: Pipes	
7	278	<id> <i>Result Type</i>	Result <id>	<id> <i>Pipe</i>	<id> <i>Num Packets</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpReserveWritePipePackets Reserve <i>num_packets</i> entries for writing to the pipe object specified by <i>Pipe</i> . Result is a valid reservation ID if the reservation is successful. <i>Pipe</i> must have a type of OpTypePipe with WriteOnly access qualifier. <i>Num Packets</i> must be a 32-bit OpTypeInt which is treated as an unsigned value. <i>Result Type</i> must be an OpTypeReserveId . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.						Capability: Pipes	
--	--	--	--	--	--	---	--

7	279	<i><id> Result Type</i>	<i>Result <id></i>	<i><id> Pipe</i>	<i><id> Num Packets</i>	<i><id> Packet Size</i>	<i><id> Packet Alignment</i>
---	-----	-----------------------------------	--------------------------	----------------------------	-----------------------------------	-----------------------------------	--

OpCommitReadPipe Indicates that all reads to <i>Num Packets</i> associated with the reservation specified by <i>Reserve Id</i> and the pipe object specified by <i>Pipe</i> are completed. <i>Pipe</i> must have a type of OpTypePipe with ReadOnly access qualifier. <i>Reserve Id</i> must have a type of OpTypeReserveId . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.					Capability: Pipes
5	280	<id> <i>Pipe</i>	<id> <i>Reserve Id</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpCommitWritePipe Indicates that all writes to <i>Num Packets</i> associated with the reservation specified by <i>Reserve Id</i> and the pipe object specified by <i>Pipe</i> are completed. <i>Pipe</i> must have a type of OpTypePipe with WriteOnly access qualifier. <i>Reserve Id</i> must have a type of OpTypeReserveId . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.					Capability: Pipes
5	281	<id> <i>Pipe</i>	<id> <i>Reserve Id</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpIsValidReserveId Return true if <i>Reserve Id</i> is a valid reservation id and false otherwise. <i>Result Type</i> must be a Boolean type . <i>Reserve Id</i> must have a type of OpTypeReserveId .				Capability: Pipes
4	282	<id> <i>Result Type</i>	Result <id>	<id> <i>Reserve Id</i>

OpGetNumPipePackets Result is the number of available entries in the pipe object specified by <i>Pipe</i> . The number of available entries in a pipe is a dynamic value. The value returned should be considered immediately stale. <i>Result Type</i> must be a 32-bit integer type scalar, which should be treated as an unsigned value. <i>Pipe</i> must have a type of OpTypePipe with ReadOnly or WriteOnly access qualifier . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> . For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.				Capability: Pipes		
6	283	<id> <i>Result Type</i>	Result <id>	<id> <i>Pipe</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpGetMaxPipePackets Result is the maximum number of packets specified when the pipe object specified by <i>Pipe</i> was created. <i>Result Type</i> must be a 32-bit integer type scalar, which should be treated as an unsigned value. <i>Pipe</i> must have a type of OpTypePipe with ReadOnly or WriteOnly access qualifier . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> . For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.				Capability: Pipes		
--	--	--	--	------------------------------------	--	--

6	284	<id> <i>Result Type</i>	Result <id>	<id> <i>Pipe</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>
---	-----	----------------------------	-------------	---------------------	----------------------------	---------------------------------

OpGroupReserveReadPipePackets Reserve <i>Num Packets</i> entries for reading from the pipe object specified by <i>Pipe</i> at group level. Result is a valid reservation id if the reservation is successful. The reserved pipe entries are referred to by indices that go from 0 . . . <i>Num Packets</i> - 1. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be an OpTypeReserveId . <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Pipe</i> must have a type of OpTypePipe with ReadOnly access qualifier. <i>Num Packets</i> must be a 32-bit integer type scalar, which is treated as an unsigned value. <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - 1 <= <i>Packet Alignment</i> <= <i>Packet Size</i> . - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.							Capability: Pipes	
8	285	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Pipe</i>	<id> <i>Num Packets</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpGroupReserveWritePipePackets Reserve <i>Num Packets</i> entries for writing to the pipe object specified by <i>Pipe</i> at group level. Result is a valid reservation ID if the reservation is successful. The reserved pipe entries are referred to by indices that go from 0 . . . <i>Num Packets</i> - 1. All invocations of this module within <i>Execution</i> must reach this point of execution. This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i> . This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely. <i>Result Type</i> must be an OpTypeReserveId . <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Pipe</i> must have a type of OpTypePipe with WriteOnly access qualifier . <i>Num Packets</i> must be a 32-bit integer type scalar, which is treated as an unsigned value. <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.							Capability: Pipes	
8	286	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Pipe</i>	<id> <i>Num Packets</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpGroupCommitReadPipe <p>A group level indication that all reads to <i>Num Packets</i> associated with the reservation specified by <i>Reserve Id</i> to the pipe object specified by <i>Pipe</i> are completed.</p> <p>All invocations of this module within <i>Execution</i> must reach this point of execution.</p> <p>This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i>. This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely.</p> <p><i>Execution</i> must be Workgroup or Subgroup Scope.</p> <p><i>Pipe</i> must have a type of OpTypePipe with ReadOnly access qualifier.</p> <p><i>Reserve Id</i> must have a type of OpTypeReserveId.</p> <p><i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe.</p> <p><i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe.</p> <p><i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following:</p> <ul style="list-style-type: none"> - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> <p>For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i>. For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.</p>				Capability: Pipes		
6	287	Scope <id> <i>Execution</i>	<id> <i>Pipe</i>	<id> <i>Reserve Id</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpGroupCommitWritePipe <p>A group level indication that all writes to <i>Num Packets</i> associated with the reservation specified by <i>Reserve Id</i> to the pipe object specified by <i>Pipe</i> are completed.</p> <p>All invocations of this module within <i>Execution</i> must reach this point of execution.</p> <p>This instruction is only guaranteed to work correctly if placed strictly within uniform control flow within <i>Execution</i>. This ensures that if any invocation executes it, all invocations will execute it. If placed elsewhere, an invocation may stall indefinitely.</p> <p><i>Execution</i> must be Workgroup or Subgroup Scope.</p> <p><i>Pipe</i> must have a type of OpTypePipe with WriteOnly access qualifier.</p> <p><i>Reserve Id</i> must have a type of OpTypeReserveId.</p> <p><i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe.</p> <p><i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe.</p> <p><i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following:</p> <ul style="list-style-type: none"> - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> <p>For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i>. For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types.</p>				Capability: Pipes		
6	288	Scope <id> <i>Execution</i>	<id> <i>Pipe</i>	<id> <i>Reserve Id</i>	<id> <i>Packet Size</i>	<id> <i>Packet Alignment</i>

OpConstantPipeStorage Creates a pipe-storage object. <i>Result Type</i> must be OpTypePipeStorage . <i>Packet Size</i> must be a 32-bit integer type scalar that represents the size in bytes of each packet in the pipe. <i>Packet Alignment</i> must be a 32-bit integer type scalar that presents the alignment in bytes of each packet in the pipe. <i>Packet Size</i> and <i>Packet Alignment</i> must satisfy the following: - $1 \leq \text{Packet Alignment} \leq \text{Packet Size}$. - <i>Packet Alignment</i> must evenly divide <i>Packet Size</i> . For concrete types, <i>Packet Alignment</i> should equal <i>Packet Size</i> . For aggregate types, <i>Packet Alignment</i> should be the size of the largest primitive type in the hierarchy of types. <i>Capacity</i> is the minimum number of <i>Packet Size</i> blocks the resulting OpTypePipeStorage can hold.				Capability: PipeStorage Missing before version 1.1.		
6	323	<id> <i>Result Type</i>	Result <id>	Literal Number <i>Packet Size</i>	Literal Number <i>Packet Alignment</i>	Literal Number <i>Capacity</i>

OpCreatePipeFromPipeStorage Creates a pipe object from a pipe-storage object. <i>Result Type</i> must be OpTypePipe . <i>Pipe Storage</i> must be a pipe-storage object created from OpConstantPipeStorage . <i>Qualifier</i> is the pipe access qualifier.				Capability: PipeStorage Missing before version 1.1.		
4	324	<id> <i>Result Type</i>	Result <id>	<id> <i>Pipe Storage</i>		

3.32.24 Non-Uniform Instructions

OpGroupNonUniformElect Result is true only in the active invocation with the lowest id in the group, otherwise result is false. <i>Result Type</i> must be a Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope .				Capability: GroupNonUniform Missing before version 1.3.
4	333	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>

OpGroupNonUniformAll					Capability: GroupNonUniformVote
Evaluates a predicate for all active invocations in the group, resulting in true if predicate evaluates to true for all active invocations in the group, otherwise the result is false .					Missing before version 1.3.
<i>Result Type</i> must be a Boolean type .					
<i>Execution</i> must be Workgroup or Subgroup Scope .					
<i>Predicate</i> must be a Boolean type .					
5	334	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Predicate</i>

OpGroupNonUniformAny					Capability: GroupNonUniformVote
Evaluates a predicate for all active invocations in the group, resulting in true if predicate evaluates to true for any active invocation in the group, otherwise the result is false .					Missing before version 1.3.
<i>Result Type</i> must be a Boolean type .					
<i>Execution</i> must be Workgroup or Subgroup Scope .					
<i>Predicate</i> must be a Boolean type .					
5	335	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Predicate</i>

OpGroupNonUniformAllEqual					Capability: GroupNonUniformVote
Evaluates a value for all active invocations in the group, resulting in true if value is equal for all active invocations in the group, otherwise the result is false .					Missing before version 1.3.
<i>Result Type</i> must be a Boolean type .					
<i>Execution</i> must be Workgroup or Subgroup Scope .					
<i>Value</i> must be a scalar or vector of floating-point type , integer type , or Boolean type .					
5	336	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>

OpGroupNonUniformBroadcast				Capability: GroupNonUniformBallot Missing before version 1.3.		
Return the <i>Value</i> of the invocation identified by the id <i>Id</i> to all active invocations in the group.						
<i>Result Type</i> must be a scalar or vector of floating-point type , integer type , or Boolean type .						
<i>Execution</i> must be Workgroup or Subgroup Scope .						
The type of <i>Value</i> must be the same as <i>Result Type</i> .						
<i>Id</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0.						
<i>Id</i> must come from a constant instruction .						
The resulting value is undefined if <i>Id</i> is an inactive invocation, or is greater than or equal to the size of the group.						
6	337	< <i>id</i> > <i>Result Type</i>	Result <<i>id</i>>	Scope <<i>id</i>> <i>Execution</i>	< <i>id</i> > <i>Value</i>	< <i>id</i> > <i>Id</i>

OpGroupNonUniformBroadcastFirst Return the <i>Value</i> of the invocation from the active invocation with the lowest id in the group to all active invocations in the group. <i>Result Type</i> must be a scalar or vector of floating-point type , integer type , or Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . The type of <i>Value</i> must be the same as <i>Result Type</i> .					Capability: GroupNonUniformBallot Missing before version 1.3.
5	338	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>

OpGroupNonUniformBallot Returns a bitfield value combining the <i>Predicate</i> value from all invocations in the group that execute the same dynamic instance of this instruction. The bit is set to one if the corresponding invocation is active and the <i>Predicate</i> for that invocation evaluated to true; otherwise, it is set to zero. <i>Result Type</i> must be a vector of four components of <i>integer type</i> scalar, whose <i>Signedness</i> operand is 0. <i>Result</i> is a set of bitfields where the first invocation is represented in the lowest bit of the first vector component and the last (up to the size of the group) is the higher bit number of the last bitmask needed to represent all bits of the group invocations. <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Predicate</i> must be a <i>Boolean type</i> .					
5	339	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Predicate</i>

Capability:
GroupNonUniformBallot

Missing before
version 1.3.

OpGroupNonUniformInverseBallot Evaluates a value for all active invocations in the group, resulting in true if the bit in <i>Value</i> for the corresponding invocation is set to one, otherwise the result is false . <i>Result Type</i> must be a <i>Boolean type</i> . <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Value</i> must be a vector of four components of <i>integer type</i> scalar, whose <i>Signedness</i> operand is 0. <i>Value</i> must be the same for all invocations that execute the same dynamic instance of this instruction. <i>Value</i> is a set of bitfields where the first invocation is represented in the lowest bit of the first vector component and the last (up to the size of the group) is the higher bit number of the last bitmask needed to represent all bits of the group invocations.					
5	340	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>

Capability:
GroupNonUniformBallot

Missing before
version 1.3.

OpGroupNonUniformBallotBitExtract Evaluates a value for all active invocations in the group, resulting in true if the bit in <i>Value</i> that corresponds to <i>Index</i> is set to one, otherwise the result is false . <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Value</i> must be a vector of four components of integer type scalar, whose <i>Signedness</i> operand is 0. <i>Value</i> is a set of bitfields where the first invocation is represented in the lowest bit of the first vector component and the last (up to the size of the group) is the higher bit number of the last bitmask needed to represent all bits of the group invocations. <i>Index</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. The resulting value is undefined if <i>Index</i> is an inactive invocation, or is greater than or equal to the size of the group.				Capability: GroupNonUniformBallot Missing before version 1.3.		
6	341	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>Index</i>

OpGroupNonUniformBallotBitCount A group operation that returns the number of bits that are set to 1 in <i>Value</i> , only considering the bits in <i>Value</i> required to represent all bits of the group's invocations. <i>Result Type</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. <i>Value</i> must be a vector of four components of integer type scalar, whose <i>Signedness</i> operand is 0. <i>Value</i> is a set of bitfields where the first invocation is represented in the lowest bit of the first vector component and the last (up to the size of the group) is the higher bit number of the last bitmask needed to represent all bits of the group invocations.				Capability: GroupNonUniformBallot Missing before version 1.3.		
6	342	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>Value</i>

OpGroupNonUniformBallotFindLSB Find the least significant bit set to 1 in <i>Value</i> , considering only the bits in <i>Value</i> required to represent all bits of the group's invocations. If none of the considered bits is set to 1, the result is undefined. <i>Result Type</i> must be a scalar of <i>integer type</i> , whose <i>Signedness</i> operand is 0. <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Value</i> must be a vector of four components of <i>integer type</i> scalar, whose <i>Signedness</i> operand is 0. <i>Value</i> is a set of bitfields where the first invocation is represented in the lowest bit of the first vector component and the last (up to the size of the group) is the higher bit number of the last bitmask needed to represent all bits of the group invocations.					Capability: GroupNonUniformBallot Missing before version 1.3.
5	343	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>

OpGroupNonUniformBallotFindMSB Find the most significant bit set to 1 in <i>Value</i> , considering only the bits in <i>Value</i> required to represent all bits of the group's invocations. If none of the considered bits is set to 1, the result is undefined. <i>Result Type</i> must be a scalar of <i>integer type</i> , whose <i>Signedness</i> operand is 0. <i>Execution</i> must be Workgroup or Subgroup Scope . <i>Value</i> must be a vector of four components of <i>integer type</i> scalar, whose <i>Signedness</i> operand is 0. <i>Value</i> is a set of bitfields where the first invocation is represented in the lowest bit of the first vector component and the last (up to the size of the group) is the higher bit number of the last bitmask needed to represent all bits of the group invocations.					Capability: GroupNonUniformBallot Missing before version 1.3.
5	344	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>

OpGroupNonUniformShuffle Return the <i>Value</i> of the invocation identified by the id <i>Id</i> . <i>Result Type</i> must be a scalar or vector of floating-point type , integer type , or Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>Id</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. The resulting value is undefined if <i>Id</i> is an inactive invocation, or is greater than or equal to the size of the group.					Capability: GroupNonUniformShuffle Missing before version 1.3.	
6	345	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>Id</i>

OpGroupNonUniformShuffleXor Return the <i>Value</i> of the invocation identified by the current invocation's id within the group xor'ed with <i>Mask</i> . <i>Result Type</i> must be a scalar or vector of floating-point type , integer type , or Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>Mask</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. The resulting value is undefined if current invocation's id within the group xor'ed with <i>Mask</i> is an inactive invocation, or is greater than or equal to the size of the group. <i>Mask</i> must evaluate to a power of 2.					Capability: GroupNonUniformShuffle Missing before version 1.3.	
6	346	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>Mask</i>

OpGroupNonUniformShuffleUp Return the <i>Value</i> of the <i>invocation</i> identified by the current invocation's id within the group - <i>Delta</i> . <i>Result Type</i> must be a scalar or vector of <i>floating-point type</i> , <i>integer type</i> , or <i>Boolean type</i> . <i>Execution</i> must be Workgroup or Subgroup Scope . The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>Delta</i> must be a scalar of <i>integer type</i> , whose <i>Signedness</i> operand is 0. The resulting value is undefined if current invocation's id within the group - <i>Delta</i> is an inactive invocation, or is greater than or equal to the size of the group.				Capability: GroupNonUniformShuffleRelative Missing before version 1.3.		
6	347	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>Delta</i>

OpGroupNonUniformShuffleDown Return the <i>Value</i> of the <i>invocation</i> identified by the current invocation's id within the group + <i>Delta</i> . <i>Result Type</i> must be a scalar or vector of <i>floating-point type</i> , <i>integer type</i> , or <i>Boolean type</i> . <i>Execution</i> must be Workgroup or Subgroup Scope . The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>Delta</i> must be a scalar of <i>integer type</i> , whose <i>Signedness</i> operand is 0. The resulting value is undefined if current invocation's id within the group + <i>Delta</i> is an inactive invocation, or is greater than or equal to the size of the group.				Capability: GroupNonUniformShuffleRelative Missing before version 1.3.		
6	348	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>Delta</i>

OpGroupNonUniformIAdd An integer add group operation of all <i>Value</i> operands contributed active by invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	349	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformFAdd A floating point add group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of floating-point type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	350	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformIMul An integer multiply group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 1. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	351	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformFMul A floating point multiply group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of floating-point type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 1. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	352	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformSMin A signed integer minimum group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is INT_MAX. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	353	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformUMin An unsigned integer minimum group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type , whose <i>Signedness</i> operand is 0. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is UINT_MAX. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	354	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformFMin A floating point minimum group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of floating-point type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is +INF. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	355	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformSMax A signed integer maximum group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is INT_MIN. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	356	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformUMax An unsigned integer maximum group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type , whose <i>Signedness</i> operand is 0. <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	357	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformFMax A floating point maximum group operation of all <i>Value</i> operands contributed by active invocations in by group. <i>Result Type</i> must be a scalar or vector of floating-point type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is -INF. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic , GroupNonUniformClustered Missing before version 1.3.	
6 + variable	358	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformBitwiseAnd A bitwise and group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is ~0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	359	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformBitwiseOr A bitwise or group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	360	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<id> <i>Value</i>	Optional <id> <i>ClusterSize</i>

OpGroupNonUniformBitwiseXor A bitwise xor group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of integer type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	361	<i><id></i> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<i><id></i> <i>Value</i>	Optional <i><id></i> <i>ClusterSize</i>

OpGroupNonUniformLogicalAnd A logical and group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is ~0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	362	<i><id></i> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation <i>Operation</i>	<i><id></i> <i>Value</i>	Optional <i><id></i> <i>ClusterSize</i>

OpGroupNonUniformLogicalOr A logical or group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	363	<i><id></i> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<i><id></i> <i>Value</i>	Optional <i><id></i> <i>ClusterSize</i>

OpGroupNonUniformLogicalXor A logical xor group operation of all <i>Value</i> operands contributed by active invocations in the group. <i>Result Type</i> must be a scalar or vector of Boolean type . <i>Execution</i> must be Workgroup or Subgroup Scope . The identity <i>I</i> for <i>Operation</i> is 0. If <i>Operation</i> is ClusteredReduce , <i>ClusterSize</i> must be specified. The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>ClusterSize</i> is the size of cluster to use. <i>ClusterSize</i> must be a scalar of integer type , whose <i>Signedness</i> operand is 0. <i>ClusterSize</i> must come from a constant instruction . <i>ClusterSize</i> must be at least 1, and must be a power of 2. If <i>ClusterSize</i> is greater than the declared SubGroupSize , executing this instruction results in undefined behavior.						Capability: GroupNonUniformArithmetic, GroupNonUniformClustered Missing before version 1.3.	
6 + variable	364	<i><id></i> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	Group Operation Operation	<i><id></i> <i>Value</i>	Optional <i><id></i> <i>ClusterSize</i>

OpGroupNonUniformQuadBroadcast Return the <i>Value</i> of the <i>invocation</i> within the quad whose SubgroupLocalInvocationId % 4 is equal to <i>Id</i> . <i>Result Type</i> must be a scalar or vector of <i>floating-point type</i> , <i>integer type</i> , or <i>Boolean type</i> . <i>Execution</i> must be Workgroup or Subgroup Scope . The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>Id</i> must be a scalar of <i>integer type</i> , whose <i>Signedness</i> operand is 0. <i>Id</i> must come from a <i>constant instruction</i> . If the value of <i>Id</i> is greater or equal to 4, an undefined result is returned.				Capability: GroupNonUniformQuad Missing before version 1.3.		
6	365	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>Index</i>

OpGroupNonUniformQuadSwap Swap the <i>Value</i> of the <i>invocation</i> within the quad with another invocation in the quad using <i>Direction</i> . <i>Result Type</i> must be a scalar or vector of <i>floating-point type</i> , <i>integer type</i> , or <i>Boolean type</i> . <i>Execution</i> must be Workgroup or Subgroup Scope . The type of <i>Value</i> must be the same as <i>Result Type</i> . <i>Direction</i> is the kind of swap to perform. <i>Direction</i> must be a scalar of <i>integer type</i> , whose <i>Signedness</i> operand is 0. <i>Direction</i> must come from a <i>constant instruction</i> . The value of <i>Direction</i> is evaluated such that: 0 indicates a horizontal swap within the quad. 1 indicates a vertical swap within the quad. 2 indicates a diagonal swap within the quad.				Capability: GroupNonUniformQuad Missing before version 1.3.		
6	366	<id> <i>Result Type</i>	Result <id>	Scope <id> <i>Execution</i>	<id> <i>Value</i>	<id> <i>Direction</i>

A Changes

A.1 Changes from Version 0.99, Revision 31

- Added the **PushConstant Storage Class**.
- Added **OpIAddCarry**, **OpISubBorrow**, **OpUMulExtended**, and **OpSMulExtended**.
- Added **OpInBoundsPtrAccessChain**.
- Added the **Decoration NoContraction** to prevent combining multiple operations into a single operation (bug 14396).
- Added sparse texturing (14486):
 - Added **OpImageSparse...** for accessing images that might not be resident.
 - Added **MinLod** functionality for accessing images with a minimum level of detail.
- Added back the **Alignment Decoration**, for the **Kernel** capability (14505).
- Added a **NonTemporal Memory Access** (14566).
- **Structured control flow** changes:
 - Changed structured loops to have a structured continue *Continue Target* in **OpLoopMerge** (14422).
 - Added rules for how "fall through" works with **OpSwitch** (13579).
 - Added definitions for what is "inside" a structured control-flow construct (14422).
- Added **SubpassData Dim** to support input targets written by a previous subpass as an output target (14304). This is also a **Decoration** and a **Capability**, and can be used by some image ops to read the input target.
- Added **OpTypeForwardPointer** to establish the Storage Class of a forward reference to a pointer type (13822).
- Improved Debuggability
 - Changed **OpLine** to not have a target *<id>*, but instead be placed immediately preceding the instruction(s) it is annotating (13905).
 - Added **OpNoLine** to terminate the affect of **OpLine** (13905).
 - Changed **OpSource** to include the source code:
 - * Allow multiple occurrences.
 - * Be mixed in with the **OpString** instructions.
 - * Optionally consume an **OpString** result to say which file it is annotating.
 - * Optionally include the source text corresponding to that **OpString**.
 - * Included adding **OpSourceContinued** for source text that is too long for a single instruction.
- Added a large number of **Capabilities** for subsetting functionality (14520, 14453), including 8-bit integer support for OpenCL kernels.
- Added **VertexIndex** and **InstanceIndex BuiltIn Decorations** (14255).
- Added **GenericPointer** capability that allows the ability to use the **Generic Storage Class** (14287).
- Added **IndependentForwardProgress Execution Mode** (14271).
- Added **OpAtomicFlagClear** and **OpAtomicFlagTestAndSet** instructions (14315).
- Changed **OpEntryPoint** to take a list of **Input** and **Output** *<id>* for declaring the entry point's interface.
- Fixed internal bugs
 - 14411 Added missing documentation for mad_sat OpenCL extended instructions (enums existed, just the documentation was missing)
 - 14241 Removed shader capability requirement from **OpImageQueryLevels** and **OpImageQuerySamples**.
 - 14241 Removed unneeded **OpImageQueryDim** instruction.

- 14241 Filled in *TBD* section for `OpAtomicCompareExchangeWeak`
- 14366 All `OpSampledImage` must appear before uses of sampled images (and still in the first block of the entry point).
- 14450 `DeviceEnqueue` capability is required for `OpTypeQueue` and `OpTypeDeviceEvent`
- 14363 `OpTypePipe` is opaque - moved packet size and alignment to opcodes
- 14367 `Float16Buffer` capability clarified
- 14241 Clarified how `OpSampledImage` can be used
- 14402 Clarified `OpTypeImage` encodings for OpenCL extended instructions
- 14569 Removed mention of non-existent `OpFunctionDecl`
- 14372 Clarified usage of `OpGenericPtrMemSemantics`
- 13801 Clarified the **SpecId Decoration** is just for constants
- 14447 Changed literal values of `Memory Semantic` enums to match OpenCL/C++11 atomics, and made the `Memory Semantic None` and `Relaxed` be aliases
- 14637 Removed subgroup scope from `OpGroupAsyncCopy` and `OpGroupWaitEvents`

A.2 Changes from Version 0.99, Revision 32

- Added `UnormInt101010_2` to the `Image Channel Data Type` table.
- Added place holder for C++11 atomic *Consume* Memory Semantics along with an explicit `AcquireRelease` memory semantic.
- Fixed internal bugs:
 - 14690 `OpSwitch` *literal* width (and hence number of operands) is determined by the type of *Selector*, and be rigorous about how sub-32-bit literals are stored.
 - 14485 The client API owns the semantics of built-ins that only have "pass through" semantics WRT SPIR-V.
- Fixed public bugs:
 - 1387 Don't describe result type of `OpImageWrite`.

A.3 Changes from Version 1.00, Revision 1

- Adjusted `Capabilities`:
 - Split geometry-stream functionality into its own **GeometryStreams** capability (14873).
 - Have **InputAttachmentIndex** to depend on **InputAttachment** instead of **Shader** (14797).
 - Merge **AdvancedFormats** and **StorageImageExtendedFormats** into just **StorageImageExtendedFormats** (14824).
 - Require **StorageImageReadWithoutFormat** and **StorageImageWriteWithoutFormat** to read and write storage images with an **Unknown Image Format**.
 - Removed the **ImageSRGBWrite** capability.
- Clarifications
 - **RelaxedPrecision Decoration** can be applied to **OpFunction** (14662).
- Fixed internal bugs:
 - 14797 The literal argument was missing for the **InputAttachmentIndex Decoration**.
 - 14547 Remove the **FragColor BuiltIn**, so that no implicit broadcast is implied.
 - 13292 Make statements about "Volatile" be more consistent with the memory model specification (non-functional change).

- 14948 Remove image-"Query" overloading on image/sampled-image type and "fetch" on non-sampled images, by adding the [OpImage](#) instruction to get the image from a sampled image.
 - 14949 Make consistent placement between **OpSource** and **OpSourceExtension** in the [logical layout](#) of a module.
 - 14865 Merge **WorkgroupLinearId** with **LocalInvocationId** [BuiltIn Decorations](#).
 - 14806 Include 3D images for [OpImageQuerySize](#).
 - 14325 Removed the **Smooth Decoration**.
 - 12771 Make the version word formatted as: "0 | Major Number | Minor Number | 0" in the [physical layout](#).
 - 15035 Allow [OpTypeImage](#) to use a *Depth* operand of 2 for not indicating a depth or non-depth image.
 - 15009 Split the **OpenCL Source Language** into two: **OpenCL_C** and **OpenCL_CPP**.
 - 14683 [OpSampledImage](#) instructions can only be the consuming block, for scalars, and directly consumed by an image lookup or query instruction.
 - 14325 mutual exclusion validation rules of [Execution Modes](#) and [Decorations](#)
 - 15112 add definitions for [invocation](#), [dynamically uniform](#), and [uniform control flow](#).
- Renames
 - **InputTargetIndex** [Decoration](#) → **InputAttachmentIndex**
 - **InputTarget** [Capability](#) → **InputAttachment**
 - **InputTarget** [Dim](#) → **SubpassData**
 - **WorkgroupLocal** [Storage Class](#) → **Workgroup**
 - **WorkgroupGlobal** [Storage Class](#) → **CrossWorkgroup**
 - **PrivateGlobal** [Storage Class](#) → **Private**
 - **OpAsyncGroupCopy** → [OpGroupAsyncCopy](#)
 - **OpWaitGroupEvents** → [OpGroupWaitEvents](#)
 - **InputTriangles** [Execution Mode](#) → **Triangles**
 - **InputQuads** [Execution Mode](#) → **Quads**
 - **InputIsolines** [Execution Mode](#) → **Isolines**

A.4 Changes from Version 1.00, Revision 2

- Updated example at the end of Section 1 to conform to the KHR_vulkan_glsl extension and treat **OpTypeBool** as an abstract type.
- Adjusted [Capabilities](#):
 - **MatrixStride** depends on **Matrix** (15234).
 - **Sample**, **SampleId**, **SamplePosition**, and **SampleMask** depend on **SampleRateShading** (15234).
 - **ClipDistance** and **CullDistance** [BuiltIns](#) depend on, respectively, **ClipDistance** and **CullDistance** (1407, 15234).
 - **ViewportIndex** depends on **MultiViewport** (15234).
 - **AtomicCounterMemory** should be the **AtomicStorage** (15234).
 - **Float16** has no dependencies (15234).
 - **Offset** [Decoration](#) should only be for **Shader** (15268).
 - **Generic** [Storage Class](#) is supposed to need the **GenericPointer** [Capability](#) (14287).
 - Remove capability restriction on the **BuiltIn** [Decoration](#) (15248).
- Fixed internal bugs:
 - 15203 Updated description of **SampleMask** [BuiltIn](#) to include "Input or output. . .", not just "Input. . ."
 - 15225 Include no re-association as a constraint required by the **NoContraction** [Decoration](#).
 - 15210 Clarify [OpPhi](#) semantics that operand values only come from parent blocks.

- 15239 Add [OpImageSparseRead](#), which was missing (supposed to be 12 sparse-image instructions, but only 11 got incorporated, this adds the 12th).
- 15299 Move [OpUndef](#) back to the Miscellaneous section.
- 15321 [OpTypeImage](#) does not have a *Depth* restriction when used with **SubpassData**.
- 14948 Fix the **Lod Image Operands** to allow both integer and floating-point values.
- 15275 Clarify specific storage classes allowed for atomic operations under universal validation rules "Atomic access rules".
- 15501 Restrict **Patch Decoration** to one of the tessellation execution models.
- 15472 Reserved use of [OpImageSparseSampleProjImplicitLod](#), [OpImageSparseSampleProjExplicitLod](#), [OpImageSparseSampleProjDrefImplicitLod](#), and [OpImageSparseSampleProjDrefExplicitLod](#).
- 15459 Clarify what makes different aggregate types in "Types and Variables".
- 15426 Don't require [OpQuantizeToF16](#) to preserve NaN patterns.
- 15418 Don't set both **Acquire** and **Release** bits in [Memory Semantics](#).
- 15404 [OpFunction Result](#) *<id>* can only be used by **OpFunctionCall**, **OpEntryPoint**, and decoration instructions.
- 15437 Restrict element type for [OpTypeRuntimeArray](#) by adding a definition of **concrete** types.
- 15403 Clarify [OpTypeFunction](#) can only be consumed by [OpFunction](#) and functions can only return concrete and abstract types.
- Improved accuracy of the opcode word count in each instruction regarding which operands are optional. For sampling operations with explicit LOD, this included not marking the required LOD operands as optional.
- Clarified that when **NonWritable**, **NonReadable**, **Volatile**, and **Coherent Decorations** are applied to the **Uniform** storage class, the **BufferBlock** decoration must be present.
- Fixed external bugs:
 - 1413 (see internal 15275)
 - 1417 Added definitions for block, [dominate](#), [post dominate](#), CFG, and [back edge](#). Removed use of "dominator tree".

A.5 Changes from Version 1.00, Revision 3

- Added definition of [derivative group](#), and use it to say when derivatives are well defined.

A.6 Changes from Version 1.00, Revision 4

- Expanded the list of instructions that may use or return a pointer in the **Logical addressing model**.
- Added missing ABGR [Image Channel Order](#)

A.7 Changes from Version 1.00, Revision 5

- Khronos SPIR-V issue #27: Removed **Shader** dependency from **SampledBuffer** and **Sampled1D Capabilities**.
- Khronos SPIR-V issue #56: Clarify that the meaning of "read-only" in the [Storage Classes](#) includes not allowing initializers.
- Khronos SPIR-V issue #57: Clarify "modulo" means "remainder" in [OpFMod](#)'s description.
- Khronos SPIR-V issue #60: [OpControlBarrier](#) synchronizes **Output** variables when used in tessellation-control shader.
- Public SPIRV-Headers issue #1: Remove the **Shader** capability requirement from the **Input Storage Class**.
- Public SPIRV-Headers issue #10: Don't say the $(u [, v] [, w], q)$ has four components, as it can be closed up when the optional ones are missing. Seen in the [projective image](#) instructions.
- Public SPIRV-Headers issues #12 and #13 and Khronos SPIR-V issue #65: Allow [OpVariable](#) as an initializer for another **OpVariable** instruction or the *Base* of an [OpSpecConstantOp](#) with an **AccessChain** opcode.
- Public SPIRV-Headers issues #14: add **Max** enumerants of 0x7FFFFFFF to each of the non-mask enums in the C-based header files.

A.8 Changes from Version 1.00, Revision 6

- Khronos SPIR-V issue #63: Be clear that **OpUndef** can be used in sequence 9 (and is preferred to be) of the [Logical Layout](#) and can be part of partially-defined [OpConstantComposite](#).
- Khronos SPIR-V issue #70: Don't explicitly require operand truncation for integer operations when operating at [RelaxedPrecision](#).
- Khronos SPIR-V issue #76: Include **OpINEqual** in the list of allowed instructions for [OpSpecConstantOp](#).
- Khronos SPIR-V issue #79: Remove implication that [OpImageQueryLod](#) should have a component for the array index.
- Public SPIRV-Headers issue #17: [Decorations](#) **Noperspective**, **Flat**, **Patch**, **Centroid**, and **Sample** can apply to a top-level member that is itself a structure, so don't disallow it through restrictions to numeric types.

A.9 Changes from Version 1.00, Revision 7

- Khronos SPIR-V issue #69: [OpImageSparseFetch](#) editorial change in summary: include that it is sampled image.
- Khronos SPIR-V issue #74: [OpImageQueryLod](#) requires a sampler.
- Khronos SPIR-V issue #82: Clarification to the **Float16Buffer Capability**.
- Khronos SPIR-V issue #89: Editorial improvements to [OpMemberDecorate](#) and [OpDecorationGroup](#).

A.10 Changes from Version 1.00, Revision 8

- Add SPV_KHR_subgroup_vote tokens.
- Typo: Change "without a sampler" to "with a sampler" for the description of the [SampledBuffer](#) Capability.
- Khronos SPIR-V issue #61: Clarification of packet size and alignment on all instructions that use the [Pipes](#) Capability.
- Khronos SPIR-V issue #99: Use "invalid" language to replace any "compile-time error" language.
- Khronos SPIR-V issue #55: Distinguish between [branch instructions](#) and [termination instructions](#).
- Khronos SPIR-V issue #94: Add missing [OpSubgroupReadInvocationKHR](#) enumerant.
- Khronos SPIR-V issue #114: Header blocks [strictly dominate](#) their merge blocks.
- Khronos SPIR-V issue #119: [OpSpecConstantOp](#) allows **OpUndef** where allowed by its *opcode*.

A.11 Changes from Version 1.00, Revision 9

- Khronos Vulkan issue #652: Remove statements about matrix offsets and padding. These are described correctly in the Vulkan API specifications.
- Khronos SPIR-V issue #113: Remove the "By Default" statements in [FP Rounding Mode](#). These should be properly documented in client API execution environment specifications.
- Add extension enumerants for
 - SPV_KHR_16bit_storage
 - SPV_KHR_device_group
 - SPV_KHR_multiview
 - SPV_NV_sample_mask_override_coverage
 - SPV_NV_geometry_shader_passthrough
 - SPV_NV_viewport_array2
 - SPV_NV_stereo_view_rendering
 - SPV_NVX_multiview_per_view_attributes

A.12 Changes from Version 1.00, Revision 10

- Add **HLSL** [source language](#).
- Add **StorageBuffer** [storage class](#).
- Add **StorageBuffer16BitAccess**, **UniformAndStorageBuffer16BitAccess**, **VariablePointersStorageBuffer**, and **VariablePointers** [capabilities](#).
- Khronos SPIR-V issue #163: Be more clear that **OpTypeStruct** allows zero members. Also affects **ArrayStride** and **Offset** decoration [validation rules](#).
- Khronos SPIR-V issue #159: List allowed **AtomicCounter** instructions with the **AtomicStorage** [capability](#) rather than the validation rules.
- Khronos SPIR-V issue #36: Describe more clearly the type of *ND Range* in **OpGetKernelNDRangeSubGroupCount**, **OpGetKernelNDRangeMaxSubGroupSize**, and **OpEnqueueKernel**.
- Khronos SPIR-V issue #128: Be clear the **OpDot** operates only on vectors.
- Khronos SPIR-V issue #80: Loop headers must dominate their continue target. See [Structured Control Flow](#).
- Khronos SPIR-V issue #150 allow **UniformConstant** [storage-class](#) variables to have initializers, depending on the client API.

A.13 Changes from Version 1.00, Revision 11

- Public issue #2: Disallow the **Cube** dimension from use with the **Offset**, **ConstOffset**, and **ConstOffset** [image operands](#).
- Public issue #48: **OpConvertPtrToU** only returns a scalar, not a vector.
- Khronos SPIR-V issue #130: Be more clear which masks are literal and which are not.
- Khronos SPIR-V issue #154: Clarify only one of the listed [Capabilities](#) needs to be declared to use a feature that lists multiple capabilities. The non-declared capabilities need not be supported by the underlying implementation.
- Khronos SPIR-V issue #174: **OpImageDrefGather** and **OpImageSparseDrefGather** return vectors, not scalars.
- Khronos SPIR-V issue #182: The **SampleMask** [built in](#) does not depend on **SampleRateShading**, only **Shader**.
- Khronos SPIR-V issue #183: **OpQuantizeToF16** with too-small magnitude can result in either +0 or -0.
- Khronos SPIR-V issue #203: **OpImageTexelPointer** has 3 components for cube arrays, not 4.
- Khronos SPIR-V issue #217: Clearer language for **OpArrayLength**.
- Khronos SPIR-V issue #213: **Image Operand LoD** is not used by query operations.
- Khronos SPIR-V issue #223: **OpPhi** has exactly one parent operand per parent block.
- Khronos SPIR-V issue #212: In the [Validation Rules](#), make clear a pointer can be an operand in an extended instruction set.
- Add extension enumerants for
 - SPV_AMD_shader_ballot
 - SPV_KHR_post_depth_coverage
 - SPV_AMD_shader_explicit_vertex_parameter
 - SPV_EXT_shader_stencil_export
 - SPV_INTEL_subgroups

A.14 Changes from Version 1.00

- Moved version number to SPIR-V 1.1
- New functionality:
 - Bug 14202 named barriers:
 - * Added the **NamedBarrier Capability**.
 - * Added the instructions: **OpTypeNamedBarrier**, **OpNamedBarrierInitialize**, and **OpMemoryNamedBarrier**.
 - Bug 14201 subgroup dispatch:
 - * Added the **SubgroupDispatch Capability**.
 - * Added the instructions: **OpGetKernelLocalSizeForSubgroupCount** and **OpGetKernelMaxNumSubgroups**.
 - * Added **SubgroupSize** and **SubgroupsPerWorkgroup Execution Modes**.
 - Bug 14441 program-scope pipes:
 - * Added the **PipeStorage Capability**.
 - * Added Instructions: **OpTypePipeStorage**, **OpConstantPipeStorage**, and **OpCreatePipeFromPipeStorage**.
 - Bug 15434 Added the **OpSizeOf** instruction.
 - Bug 15024 support for OpenCL-C++ ivdep loop attribute:
 - * Added **DependencyInfinite** and **DependencyLength Loop Controls**.
 - * Updated **OpLoopMerge** to support these.
 - Bug 14022 Added **Initializer** and **Finalizer** and **Execution Modes**.
 - Bug 15539 Added the **MaxByteOffset Decoration**.
 - Bug 15073 Added the **Kernel Capability** to the **SpecId Decoration**.
 - Bug 14828 Added the **OpModuleProcessed** instruction.
- Fixed internal bugs:
 - Bug 15481 Clarification on alignment and size operands for pipe operands

A.15 Changes from Version 1.1, Revision 1

- Incorporated bug fixes from Revision 6 of Version 1.00 (see section 4.7. Changes from Version 1.00, Revision 5).

A.16 Changes from Version 1.1, Revision 2

- Incorporated bug fixes from Revision 7 of Version 1.00 (see section 4.8. Changes from Version 1.00, Revision 6).

A.17 Changes from Version 1.1, Revision 3

- Incorporated bug fixes from Revision 8 of Version 1.00 (see section 4.9. Changes from Version 1.00, Revision 7).

A.18 Changes from Version 1.1, Revision 4

- Incorporated bug fixes from Revision 9 of Version 1.00 (see section 4.10. Changes from Version 1.00, Revision 8).

A.19 Changes from Version 1.1, Revision 5

- Incorporated changes from Revision 10 of Version 1.00 (see section 4.11. Changes from Version 1.00, Revision 9).

A.20 Changes from Version 1.1, Revision 6

- Incorporated changes from Revision 11 of Version 1.00 (see section 4.12. Changes from Version 1.00, Revision 10).

A.21 Changes from Version 1.1, Revision 7

- Incorporated changes from Revision 12 of Version 1.00 (see section 4.13. Changes from Version 1.00, Revision 11).
- State where all [OpModuleProcessed](#) belong, in [the logical layout](#).

A.22 Changes from Version 1.1

- Moved version number to SPIR-V 1.2
- New functionality:
 - Added [OpExecutionModelId](#) to allow using an *<id>* to set the [execution modes](#) [SubgroupsPerWorkgroupId](#), [LocalSizeId](#), and [LocalSizeHintId](#).
 - Added [OpDecorateId](#) to allow using an *<id>* to set the [decorations](#) [AlignmentId](#) and [MaxByteOffsetId](#).

A.23 Changes from Version 1.2, Revision 1

- Incorporated changes from Revision 12 of Version 1.00 (see section 4.13. Changes from Version 1.00, Revision 11).
- Incorporated changes from Revision 8 of Version 1.1 (see section 4.21. Changes from Version 1.1, Revision 7).

A.24 Changes from Version 1.2, Revision 2

- Combine the 1.0, 1.1, and 1.2 specifications, making a [unified specification](#). The previous 1.0, 1.1, and 1.2 specifications are replaced with this one unified specification.

A.25 Changes from Version 1.2, Revision 3

Fixed Khronos-internal issues:

- #249: Improve description of [OpTranspose](#).
- #251: Undefined values in [OpUndef](#) include abstract and opaque values.
- #258: Deprecate [OpAtomicCompareExchangeWeak](#) in favor of [OpAtomicCompareExchange](#).
- #241: Use "invalid" instead of "compile-time" error for [ConstOffsets](#).
- #248: [OpImageSparseRead](#) is not for [SubpassData](#).
- #257: Allow [OpImageSparseFetch](#) and [OpImageSparseRead](#) with the [Sample image operands](#).
- #229: Some sensible constraints on branch hints for [OpBranchConditional](#).
- #236: [OpVariable](#)'s storage class must match storage class of the pointer type.
- #216: Can [decorate pointer types](#) with [Coherent](#) and [Volatile](#).
- #247: Don't say [Scope <id>](#) is a mask; it is not.
- #254: Remove [validation](#) rules about the types atomic instructions can operate on. These rules belong instead to the client API.
- #265: [OpGroupDecorate](#) cannot target an [OpDecorationGroup](#).

A.26 Changes from Version 1.2

- Moved version number to SPIR-V 1.3
- New functionality:
 - Added subgroup operations:
 - * the [OpGroupNonUniform](#) instructions and [capabilities](#).
 - * **Subgroup**-mask [built-in decorations](#).
 - Khronos SPIR-V issue #125, #138, #196: Removed capabilities from the [rounding modes](#).
 - Khronos SPIR-V issue #110: Removed the execution-model restrictions from [OpControlBarrier](#).
- Incorporated the following extensions:
 - SPV_KHR_shader_draw_parameters
 - SPV_KHR_16bit_storage
 - SPV_KHR_device_group
 - SPV_KHR_multiview
 - SPV_KHR_storage_buffer_storage_class
 - SPV_KHR_variable_pointers
- Reserved symbols for
 - SPV_GOOGLE_decorate_string
 - SPV_GOOGLE_hlsl_functionality1
 - SPV_AMD_gpu_shader_half_float_fetch
- Added [deprecation model](#).