

Class 5: Data visualization with ggplot

Winnie (A16673200)

Table of contents

A more complicated scatter plot	5
Exploring the gapminder dataset	9

Today we will have our first play with the **ggplot2** package - one of the most popular graphics packages on the planet.

There are many plotting systems in R. These include so-called “*base*” plotting/graphics.

```
plot(cars)
```



Base plot is generally rather short code and somewhat dull plots - but it is always there for you and is fast for big datasets.

If I want to use **ggplot2** it takes some more work.

```
# ggplot(cars)
```


I need to install the package first to my computer. To do this I can use the function `install.packages("ggplot2")`

Every time I want to use a package I need to load it up with a 'library()' call.

```
library(ggplot2)
```

Now I finally can use ggplot

```
ggplot(cars)
```



Every ggplot has at least 3 things:


- **data** (the data.frame with the data you want to plot)
- **aes** (the aesthetic mapping of the data to the plot)
- **geom** (how do you want the plot to look, points, lines, etc.)

```
head(cars)
```

	speed	dist
1	4	2
2	4	10
3	7	4
4	7	22
5	8	16
6	9	10


First point plot of cars

```
ggplot(cars) +  
  aes(x=speed, y=dist) +  
  geom_point()
```



```
ggplot(cars) +  
  aes(x=speed, y=dist) +  
  geom_point() +  
  geom_smooth()
```


```
`geom_smooth()` using method = 'loess' and formula = 'y ~ x'
```



I want a linear model and no standard error bounds shown on my plot. I also want a nicer axis labels a title etc.

```
bp <- ggplot(cars) +  
  aes(x=speed, y=dist) +  
  geom_point()  
  
bp + geom_smooth(se=FALSE, method="lm") +  
  labs(title="Stopping Distance of Old Cars",  
        x="Speed (MPH)",  
        y="Distance (ft)",  
        caption="From the cars dataset") +  
  theme_bw()
```

```
`geom_smooth()` using formula = 'y ~ x'
```



From the cars dataset

A more complicated scatter plot

Here we make a plot of gene expression data:

```
url <- "https://bioboot.github.io/bimm143_S20/class-material/up_down_expression.txt"
genes <- read.delim(url)
head(genes)
```

	Gene	Condition1	Condition2	State
1	A4GNT	-3.6808610	-3.4401355	unchanging
2	AAAS	4.5479580	4.3864126	unchanging
3	AASDH	3.7190695	3.4787276	unchanging
4	AATF	5.0784720	5.0151916	unchanging
5	AATK	0.4711421	0.5598642	unchanging
6	AB015752.4	-3.6808610	-3.5921390	unchanging

Q. Use the `nrow()` function to find out how many genes are in this dataset. What is your answer?

```
nrow(genes)
```

```
[1] 5196
```

Q. Use the `colnames()` function and the `ncol()` function on the `genes` data frame to find out what the column names are (we will need these later) and how many columns there are. How many columns did you find?

```
colnames(genes)
```

```
[1] "Gene"          "Condition1" "Condition2" "State"
```

```
ncol(genes)
```

```
[1] 4
```

Q. Use the `table()` function on the `State` column of this `data.frame` to find out how many 'up' regulated genes there are. What is your answer?

```
table(genes$State)
```

down	unchanging	up
72	4997	127

Q. Using your values above and 2 significant figures. What fraction of total genes is up-regulated in this dataset?

```
round(sum(genes$State == "up")/nrow(genes)*100, 2)
```

```
[1] 2.44
```

```
n.gene <- nrow(genes)
n.up <- sum(genes$State == "up")

up.precent <- n.up/n.gene * 100
round(up.precent, 2)
```


```
[1] 2.44
```

```
head(genes, 2)
```


	Gene	Condition1	Condition2	State
1	A4GNT	-3.680861	-3.440135	unchanging
2	AAAS	4.547958	4.386413	unchanging

```
library(ggplot2)
```

```
ggplot(genes) +  
  aes(x=Condition1, y=Condition2, col=State) +  
  geom_point()
```




```
p <- ggplot(genes) +  
  aes(x=Condition1, y=Condition2, col=State) +  
  geom_point()  
p
```



Change the colors

```
p + labs(title="Gene Expression Changes Upon Drug Treatment",
         x="Control (no drug)",
         y="Drug Treatment") +
  scale_color_manual(values=c("purple","green","pink"))
```

Exploring the gapminder dataset

Here we will load up the gapminder dataset to get practice with different aes

```
url <- "https://raw.githubusercontent.com/jennybc/gapminder/master/inst/extdata/gapminder.  
gapminder <- read.delim(url)
```

Q. How many entries rows are in this dataset?

```
nrow(gapminder)
```

```
[1] 1704
```

Q. How many columns are in this dataset?

```
ncol(gapminder)
```

```
[1] 6
```

```
head(gapminder)
```

	country	continent	year	lifeExp	pop	gdpPercap
1	Afghanistan	Asia	1952	28.801	8425333	779.4453
2	Afghanistan	Asia	1957	30.332	9240934	820.8530
3	Afghanistan	Asia	1962	31.997	10267083	853.1007
4	Afghanistan	Asia	1967	34.020	11537966	836.1971
5	Afghanistan	Asia	1972	36.088	13079460	739.9811
6	Afghanistan	Asia	1977	38.438	14880372	786.1134

```
table(gapminder$year)
```

1952	1957	1962	1967	1972	1977	1982	1987	1992	1997	2002	2007
142	142	142	142	142	142	142	142	142	142	142	142

Q. How many continents?

```
table(gapminder$continent)
```

Africa	Americas	Asia	Europe	Oceania
624	300	396	360	24

I could use the `unique()` function...

```
unique(gapminder$continent)
```

```
[1] "Asia"      "Europe"    "Africa"    "Americas" "Oceania"
```

```
length(unique(gapminder$continent))
```


```
[1] 5
```

Q. How many countries are there in this dataset?


```
length(unique(gapminder$country))
```

```
[1] 142
```

```
ggplot(gapminder) +
  aes(x=gdpPercap, y=lifeExp) +
  geom_point(alpha=0.2)
```



```
ggplot(gapminder) +
  aes(x=gdpPercap, y=lifeExp, col=continent, size=pop) +
  geom_point(alpha=0.5)
```



```
library(dplyr)
```

Attaching package: 'dplyr'

The following objects are masked from 'package:stats':

filter, lag

The following objects are masked from 'package:base':

intersect, setdiff, setequal, union


I need to install dplyr

```
# install.packages("dplyr") ## un-comment to install if needed
library(dplyr)

gapminder_2007 <- gapminder %>% filter(year==2007)
```


Plot of 2007 gapminder

```
ggplot(gapminder_2007) +  
  aes(x=gdpPerCap, y=lifeExp) +  
  geom_point(alpha=0.5)
```



More aes

```
ggplot(gapminder_2007) +  
  aes(x=gdpPerCap, y=lifeExp, color=continent, size=pop) +  
  geom_point(alpha=0.5)
```



```
ggplot(gapminder) +
  aes(x = gdpPercap, y = lifeExp) +
  geom_point() +
  facet_wrap(~continent)
```

