

Page K-55

(KN 65/65A Continued)

SHIELD GROUND	21
STANDBY OVERIDE	12
SUPPRESSION	

Notes

- 1. For optional KA43.
- 2. Internally selected, 14 or 28 volts.
- 3. Jumper unless KN74 or equivalent used.

For familiarization only. Consult the manufacturers current data.

Page K-54

DME

KING KN 65/65A

Circuit Pin:	# Notes
- 15 VDC CONTROLLED 1	1
- MOTOR SUPPLY9)
+ 3.6 VDC4	
+ MOTOR SUPPLY8	,
+15 VDC CONTROLLED1	0
50 KHZ3	
A+ IN + 13.75 VDC 1	Note 2
A+ IN + 13.75 VDC2	Note 2
A+ IN +27.5 VDC 2	3 Note 2
A+ IN +27.5 VDC 2	
AUDIO GROUND6	}
AUDIO HI5	,
CONTROL COMMON 2	2
DME ANALOG RANGE2	27
DME ANALOG SPEED 2	28
DME CHANNEL CHANG7	•
DME FLAG OUTPUT 2	9 Note 3
GROUND1	8 Note 1
K0 3	2
K1 3	3
K2 3	34
K3 3	3 5
M01	4
M1 1	5
M21	6
M31	7
MOTOR COMMON 2	25
POWER GROUND 1	9
POWER GROUND2	20
REFERENCE GROUND2	26
RNAV FLAG INPUT3	Note 3
(Continued)	

For familiarization only. Consult the manufacturers current data.