
KING KMA 20

Connector



Circuit Pin #	Note
	Note:
31	Note 2
A/C HEADPHONES	
A/C MIC KEY IN	
A/C POWER4	
A/C SPKR 4 OHM	
ADF AUDIO	
AIRCRAFT GROUND	
AMBER LIGHT OUT21	Note:
BLUE LIGHT OUT20	Note:
COM 1 MIC AUDIO27	
COM 1 MIC KEY25	
COM 1 PHONE AUDIO14	
COM 1 SPKR6	
COM 2 MIC AUDIO28	
COM 2 MIC KEY26	
COM 2 PHONE AUDIO15	
COM 2 SPKR7	
HF MCI KEY24	

HF MIC AUDIO	.12	
INST LIGHT DIMMER	.2	Note 4
INST LIGHT DIMMER	.3	Note 4
MARKER ANTENNA CONDUCTOR	.17	
MARKER ANTENNA SHIELD	.18	
MIC AUDIO IN	.11	
NAV 1 AUDIO		
NAV 2 AUDIO	.29	
PA 4 OHM	.22	
RAMP HAIL 8 OHM		
SPKR LOAD RETURN	.8.	Note 5
UNSWITCHED AUDIO INPUT		Note 6
WHITE LIGHT OUT	19	Note 3

Notes

- 1. Models 00,03,06,08,09 not used. Models 01,02,04,05,07,10,11 HF Audio.
- Model 12, Radio Tel Audio.
 Models 00,01,03,04,06,07,12,13,15,16, DME Audio. Models 02,05,11, ADF2 Audio. Models 08,09,10, not used.
- 3. For -16 model, 19 MKR Audio input, 20 and 21 not used.
- 4. For 14 volts, 2 to ground, 3 to Dimmer. For 28 volts, 3 open, 2 to Dimmer.
- 5. Below S/N 11233, Ext Ramp Hail Spkr Load.
- 6. MOD 3 only.

For familiarization only. Consult the manufacturers current data.