

Current faculty question architecture

Use a JSON package with banks, repairQuestions, bridgeQuestions, objectiveLabels, embeddedQuestionAssets and questionAssetMetadata. Download the working package rather than copying incomplete fragments from this document.

<https://masteryquests.org/downloads/resources/faculty-question-package-example.json>

A complete ordinary question

```
{
  "id": "demo-13",
  "q": "Practice 13: What is 13 + 2?",
  "options": [
    "15",
    "14",
    "16",
    "13"
  ],
  "a": 0,
  "tag": "numeracy",
  "type": "calculation",
  "objective": "NUM1",
  "difficulty": "medium",
  "primarySkill": "addition",
  "repairSkill": "addition",
  "feedback": "Add two to 13 to get 15. This starter demonstrates the workflow; replace it with your course content."
}
```

Place this object in banks.medium. All questions require id or questionId, q, four nonempty string options, a from 0–3 or aHash, tag, type, objective, primarySkill, repairSkill and feedback. Main/boss difficulty must match its pool. Repair and bridge can omit difficulty. Numeric ID ranges, objectiveLabel and bossEligible are not required.

Images and adaptive routes

For an image question add image: "sample-bars.svg" and, for Trial by Graph, graphRequired: true. In questionAssetMetadata["sample-bars.svg"], supply imageAlt and graphDescription. The downloadable example also embeds the SVG as a base64 image data URL under embeddedQuestionAssets, so no image folder is required. Per-question alt fields alone do not supply the maintained graph dialog metadata.

Main repairSkill values must match repair and bridge primarySkill values. Keep all IDs unique. Type is any nonempty string label; custom labels are allowed. Current aliases include questionType, outcomeIds[0] or conceptId, skillId, repairSkillId and canonicalDifficulty. BossStage, when provided, is 1, 2, 3, opening, middle or final.

Validate the complete package at <https://masteryquests.org/tools/question-bank-validator/> and use the manual guide for pool counts, settings, telemetry and the release checklist. The free template is local-only; remote anonymous telemetry is OFF by default.