

tf.contrib.timeseries.WholeDatasetInputFn

Contents

Class `WholeDatasetInputFn`

Methods

`__init__`

`__call__`

`create_batch`

Class `WholeDatasetInputFn`

Defined in `tensorflow/contrib/timeseries/python/timeseries/input_pipeline.py`.

Supports passing a full time series to a model for evaluation/inference.

Note that this `TimeSeriesInputFn` is not designed for high throughput, and should not be used for training. It allows for sequential evaluation on a full dataset (with sequential in-sample predictions), which then feeds naturally into `predict_continuation_input_fn` for making out-of-sample predictions. While this is useful for plotting and interactive use, `RandomWindowInputFn` is better suited to training and quantitative evaluation.

Methods

`__init__`

```
__init__(time_series_reader)
```

Initialize the `TimeSeriesInputFn`.

Args:

- `time_series_reader`: A `TimeSeriesReader` object.

`__call__`

```
__call__()
```

`create_batch`

```
create_batch()
```

A suitable `input_fn` for an `Estimator`'s `evaluate()`.

Returns:

A dictionary mapping feature names to `Tensors`, each shape prefixed by `[1, data set size]` (i.e. a batch size of 1).

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)