

tf.contrib.learn.read_keyed_batch_features_shared_queue

```
read_keyed_batch_features_shared_queue(  
    file_pattern,  
    batch_size,  
    features,  
    reader,  
    randomize_input=True,  
    num_epochs=None,  
    queue_capacity=10000,  
    reader_num_threads=1,  
    feature_queue_capacity=100,  
    num_queue_runners=2,  
    parse_fn=None,  
    name=None  
)
```

Defined in [tensorflow/contrib/learn/python/learn/learn_io/graph_io.py](#).

Adds operations to read, queue, batch and parse **Example** protos.

Given file pattern (or list of files), will setup a shared queue for file names, setup a worker queue that gets filenames from the shared queue, read **Example** proto using provided **reader**, use batch queue to create batches of examples of size **batch_size** and parse example given **features** specification.

All queue runners are added to the queue runners collection, and may be started via **start_queue_runners**.

All ops are added to the default graph.

Args:

- file_pattern**: List of files or patterns of file paths containing **Example** records. See **tf.gfile.Glob** for pattern rules.
- batch_size**: An int or scalar **Tensor** specifying the batch size to use.
- features**: A **dict** mapping feature keys to **FixedLenFeature** or **VarLenFeature** values.
- reader**: A function or class that returns an object with **read** method, (filename tensor) -> (example tensor).
- randomize_input**: Whether the input should be randomized.
- num_epochs**: Integer specifying the number of times to read through the dataset. If **None**, cycles through the dataset forever. NOTE - If specified, creates a variable that must be initialized, so call **tf.local_variables_initializer()** and run the op in a session.
- queue_capacity**: Capacity for input queue.
- reader_num_threads**: The number of threads to read examples.
- feature_queue_capacity**: Capacity of the parsed features queue.
- num_queue_runners**: Number of threads to enqueue the parsed example queue. Using multiple threads to enqueue the parsed example queue helps maintain a full queue when the subsequent computations overall are cheaper than parsing.
- parse_fn**: Parsing function, takes **Example** Tensor returns parsed representation. If **None**, no parsing is done.
- name**: Name of resulting op.

Returns:

Returns tuple of: - `Tensor` of string keys. - A dict of `Tensor` or `SparseTensor` objects for each in `features` .

Raises:

- `ValueError` : for invalid inputs.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

- Blog
- GitHub
- Twitter

Support

- Issue Tracker
- Release Notes
- Stack Overflow

English

Terms | Privacy