TopogrElow

TensorFlow API r1.4

tf.nn.weighted_cross_entropy_with_logits

```
weighted_cross_entropy_with_logits(
   targets,
   logits,
   pos_weight,
   name=None
)
```

Defined in tensorflow/python/ops/nn_impl.py.

See the guide: Neural Network > Classification

Computes a weighted cross entropy.

This is like **sigmoid_cross_entropy_with_logits()** except that **pos_weight**, allows one to trade off recall and precision by up- or down-weighting the cost of a positive error relative to a negative error.

The usual cross-entropy cost is defined as:

```
targets * -log(sigmoid(logits)) +
   (1 - targets) * -log(1 - sigmoid(logits))
```

The argument **pos_weight** is used as a multiplier for the positive targets:

```
targets * -log(sigmoid(logits)) * pos_weight +
  (1 - targets) * -log(1 - sigmoid(logits))
```

For brevity, let x = logits, z = targets, $q = pos_weight$. The loss is:

```
\begin{array}{l} \text{qz} \ * \ -\text{log}(\text{sigmoid}(x)) \ + \ (1 \ - \ z) \ * \ -\text{log}(1 \ - \ \text{sigmoid}(x)) \\ = \ \text{qz} \ * \ -\text{log}(1 \ / \ (1 \ + \ \text{exp}(-x))) \ + \ (1 \ - \ z) \ * \ -\text{log}(\text{exp}(-x) \ / \ (1 \ + \ \text{exp}(-x))) \\ = \ \text{qz} \ * \ \text{log}(1 \ + \ \text{exp}(-x)) \ + \ (1 \ - \ z) \ * \ (x \ + \ \text{log}(1 \ + \ \text{exp}(-x))) \\ = \ (1 \ - \ z) \ * \ x \ + \ (\text{qz} \ + \ 1 \ - \ z) \ * \ \text{log}(1 \ + \ \text{exp}(-x)) \\ = \ (1 \ - \ z) \ * \ x \ + \ (1 \ + \ (\text{q} \ - \ 1) \ * \ z) \ * \ \text{log}(1 \ + \ \text{exp}(-x)) \end{array}
```

Setting 1 = (1 + (q - 1) * z), to ensure stability and avoid overflow, the implementation uses

```
(1 - z) * x + 1 * (log(1 + exp(-abs(x))) + max(-x, 0))
```

logits and targets must have the same type and shape.

Args:

- targets: A Tensor of the same type and shape as logits.
- logits: A Tensor of type float32 or float64.
- pos_weight: A coefficient to use on the positive examples.
- name: A name for the operation (optional).

Returns:

A Tensor of the same shape as logits with the componentwise weighted logistic losses.

Raises:

• ValueError: If logits and targets do not have the same shape.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

