TencorFlow

TensorFlow API r1.4

tf.transpose

```
transpose(
    a,
    perm=None,
    name='transpose'
)
```

Defined in tensorflow/python/ops/array_ops.py.

See the guides: Math > Matrix Math Functions, Tensor Transformations > Slicing and Joining

Transposes a. Permutes the dimensions according to perm.

The returned tensor's dimension i will correspond to the input dimension **perm[i]**. If **perm** is not given, it is set to (n-1...0), where n is the rank of the input tensor. Hence by default, this operation performs a regular matrix transpose on 2-D input Tensors.

For example:

```
x = tf.constant([[1, 2, 3], [4, 5, 6]])
tf.transpose(x) # [[1, 4]]
                # [2, 5]
                # [3, 6]]
# Equivalently
tf.transpose(x, perm=[1, 0]) # [[1, 4]
                             # [2, 5]
                             # [3, 6]]
\# 'perm' is more useful for n-dimensional tensors, for n > 2
x = tf.constant([[[1, 2, 3],
                 [4, 5, 6]],
                [[7, 8, 9],
                 [10, 11, 12]]])
# Take the transpose of the matrices in dimension-0
tf.transpose(x, perm=[0, 2, 1]) # [[[1, 4],
                                # [2, 5],
                                  [3, 6]],
                                #
                                # [[7, 10],
                                # [8, 11],
                                    [9, 12]]]
```

Args:

- a: A Tensor.
- perm: A permutation of the dimensions of a.
- name: A name for the operation (optional).

Returns:

A transposed **Tensor** .

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

