TencorFlow

```
TensorFlow API r1.4
```

tf.scatter_sub

```
scatter_sub(
    ref,
    indices,
    updates,
    use_locking=False,
    name=None
)
```

Defined in tensorflow/python/ops/gen_state_ops.py.

See the guide: Variables > Sparse Variable Updates

Subtracts sparse updates to a variable reference.

```
# Scalar indices
ref[indices, ...] -= updates[...]


# Vector indices (for each i)
ref[indices[i], ...] -= updates[i, ...]

# High rank indices (for each i, ..., j)
ref[indices[i, ..., j], ...] -= updates[i, ..., j, ...]
```

This operation outputs **ref** after the update is done. This makes it easier to chain operations that need to use the reset value.

Duplicate entries are handled correctly: if multiple indices reference the same location, their (negated) contributions add.

Requires updates.shape = indices.shape + ref.shape[1:].



Args:

- ref: A mutable Tensor. Must be one of the following types: float32, float64, int64, int32, uint8, uint16, int16, int8, complex64, complex128, qint8, quint8, qint32, half. Should be from a Variable node.
- indices: A **Tensor**. Must be one of the following types: int32, int64. A tensor of indices into the first dimension of ref.

- updates: A Tensor. Must have the same type as ref. A tensor of updated values to subtract from ref.
- use_locking: An optional **bool**. Defaults to **False**. If True, the subtraction will be protected by a lock; otherwise the behavior is undefined, but may exhibit less contention.
- name: A name for the operation (optional).

Returns:

Same as ref. Returned as a convenience for operations that want to use the updated values after the update is done.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

