TancarFlow

TensorFlow API r1.4

tf.contrib.signal.overlap_and_add

```
overlap_and_add(
    signal,
    frame_step,
    name=None
)
```

Defined in tensorflow/contrib/signal/python/ops/reconstruction_ops.py.

See the guide: Signal Processing (contrib) > Reconstructing framed sequences and applying a tapering window

Reconstructs a signal from a framed representation.

Adds potentially overlapping frames of a signal with shape [..., frames, frame_length], offsetting subsequent frames by frame_step. The resulting tensor has shape [..., output_size] where

```
output_size = (frames - 1) * frame_step + frame_length
```

Args:

- signal: A [..., frames, frame_length] Tensor. All dimensions may be unknown, and rank must be at least 2.
- frame_step: An integer or scalar Tensor denoting overlap offsets. Must be less than or equal to frame_length.
- name: An optional name for the operation.

Returns:

A Tensor with shape [..., output_size] containing the overlap-added frames of signal's inner-most two dimensions.

Raises:

• ValueError: If signal's rank is less than 2, frame_step is not a scalar integer or frame_step is greater than frame_length.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

Issue Tracker
Release Notes
Stack Overflow

English
Terms | Privacy