

tf.LMDBReader

Contents

Class LMDBReader

Properties

reader_ref

supports_serialize

Class **LMDBReader**Inherits From: [ReaderBase](#)Defined in [tensorflow/python/ops/io_ops.py](#).

A Reader that outputs the records from a LMDB file.

See ReaderBase for supported methods.

Properties

reader_ref

Op that implements the reader.

supports_serialize

Whether the Reader implementation can serialize its state.

Methods

__init__

```
__init__(  
    name=None,  
    options=None  
)
```

Create a LMDBReader.

Args:

- **name**: A name for the operation (optional).
- **options**: A LMDBRecordOptions object (optional).

num_records_produced

```
num_records_produced(name=None)
```

Returns the number of records this reader has produced.

This is the same as the number of Read executions that have succeeded.

Args:

- `name` : A name for the operation (optional).

Returns:

An int64 Tensor.

num_work_units_completed

```
num_work_units_completed(name=None)
```

Returns the number of work units this reader has finished processing.

Args:

- `name` : A name for the operation (optional).

Returns:

An int64 Tensor.

read

```
read(  
    queue,  
    name=None  
)
```

Returns the next record (key, value) pair produced by a reader.

Will dequeue a work unit from queue if necessary (e.g. when the Reader needs to start reading from a new file since it has finished with the previous file).

Args:

- `queue` : A Queue or a mutable string Tensor representing a handle to a Queue, with string work items.
- `name` : A name for the operation (optional).

Returns:

A tuple of Tensors (key, value). `key` : A string scalar Tensor. `value` : A string scalar Tensor.

read_up_to

```
read_up_to(  
    queue,  
    num_records,  
    name=None  
)
```

Returns up to num_records (key, value) pairs produced by a reader.

Will dequeue a work unit from queue if necessary (e.g., when the Reader needs to start reading from a new file since it has finished with the previous file). It may return less than num_records even before the last batch.

Args:

- `queue` : A Queue or a mutable string Tensor representing a handle to a Queue, with string work items.
- `num_records` : Number of records to read.
- `name` : A name for the operation (optional).

Returns:

A tuple of Tensors (keys, values). `keys` : A 1-D string Tensor. `values` : A 1-D string Tensor.

reset

```
reset(name=None)
```

Restore a reader to its initial clean state.

Args:

- `name` : A name for the operation (optional).

Returns:

The created Operation.

restore_state

```
restore_state(  
    state,  
    name=None  
)
```

Restore a reader to a previously saved state.

Not all Readers support being restored, so this can produce an Unimplemented error.

Args:

- `state` : A string Tensor. Result of a SerializeState of a Reader with matching type.
- `name` : A name for the operation (optional).

Returns:

The created Operation.

serialize_state

```
serialize_state(name=None)
```

Produce a string tensor that encodes the state of a reader.

Not all Readers support being serialized, so this can produce an Unimplemented error.

Args:

- `name`: A name for the operation (optional).

Returns:

A string Tensor.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)