

tf.GraphKeys

Contents

Class GraphKeys

Class Members

ACTIVATIONS

ASSET_FILEPATHS

Class **GraphKeys**

Defined in `tensorflow/python/framework/ops.py`.

See the guide: [Building Graphs > Graph collections](#)

Standard names to use for graph collections.

The standard library uses various well-known names to collect and retrieve values associated with a graph. For example, the `tf.Optimizer` subclasses default to optimizing the variables collected under `tf.GraphKeys.TRAINABLE_VARIABLES` if none is specified, but it is also possible to pass an explicit list of variables.

The following standard keys are defined:

- **GLOBAL_VARIABLES**: the default collection of `Variable` objects, shared across distributed environment (model variables are subset of these). See [tf.global_variables](#) for more details. Commonly, all **TRAINABLE_VARIABLES** variables will be in **MODEL_VARIABLES**, and all **MODEL_VARIABLES** variables will be in **GLOBAL_VARIABLES**.
- **LOCAL_VARIABLES**: the subset of `Variable` objects that are local to each machine. Usually used for temporarily variables, like counters. Note: use `tf.contrib.framework.local_variable` to add to this collection.
- **MODEL_VARIABLES**: the subset of `Variable` objects that are used in the model for inference (feed forward). Note: use `tf.contrib.framework.model_variable` to add to this collection.
- **TRAINABLE_VARIABLES**: the subset of `Variable` objects that will be trained by an optimizer. See [tf.trainable_variables](#) for more details.
- **SUMMARIES**: the summary `Tensor` objects that have been created in the graph. See [tf.summary.merge_all](#) for more details.
- **QUEUE_RUNNERS**: the `QueueRunner` objects that are used to produce input for a computation. See [tf.train.start_queue_runners](#) for more details.
- **MOVING_AVERAGE_VARIABLES**: the subset of `Variable` objects that will also keep moving averages. See [tf.moving_average_variables](#) for more details.
- **REGULARIZATION_LOSSES**: regularization losses collected during graph construction.

The following standard keys are *defined*, but their collections are **not** automatically populated as many of the others are:

- **WEIGHTS**
- **BIASES**
- **ACTIVATIONS**

Class Members

ACTIVATIONS

ASSET_FILEPATHS

BIASES

CONCATENATED_VARIABLES

COND_CONTEXT

EVAL_STEP

GLOBAL_STEP

GLOBAL_VARIABLES

INIT_OP

LOCAL_INIT_OP

LOCAL_RESOURCES

LOCAL_VARIABLES

LOSSES

MODEL_VARIABLES

MOVING_AVERAGE_VARIABLES

QUEUE_RUNNERS

READY_FOR_LOCAL_INIT_OP

READY_OP

REGULARIZATION_LOSSES

RESOURCES

SAVEABLE_OBJECTS

SAVERS

SUMMARIES

SUMMARY_OP

TABLE_INITIALIZERS

TRAINABLE_RESOURCE_VARIABLES

TRAINABLE_VARIABLES

TRAIN_OP

UPDATE_OPS

VARIABLES

WEIGHTS

WHILE_CONTEXT

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

Issue Tracker

Release Notes

Stack Overflow

English

Terms | **Privacy**