#### TancarFlow

TensorFlow API r1.4

# tf.keras.optimizers.Adadelta

```
Contents
Class Adadelta
Methods
__init__
from_config
```

# Class Adadelta

Inherits From: Optimizer

Defined in tensorflow/python/keras/\_impl/keras/optimizers.py.

Adadelta optimizer.

It is recommended to leave the parameters of this optimizer at their default values.

# Arguments:

- 1r: float >= 0. Learning rate. It is recommended to leave it at the default value.
- rho: float >= 0.
- epsilon: float >= 0. Fuzz factor.
- decay: float >= 0. Learning rate decay over each update.

References: - Adadelta - an adaptive learning rate method

# Methods

#### \_\_init\_\_

# from\_config

```
from_config(
   cls,
   config
)
```

# get\_config

```
get_config()
```

#### get\_gradients

```
get_gradients(
   loss,
   params
)
```

### get\_updates

```
get_updates(
    loss,
    params
)
```

# get\_weights

```
get_weights()
```

Returns the current value of the weights of the optimizer.

Returns:

A list of numpy arrays.

### set\_weights

```
set_weights(weights)
```

Sets the weights of the optimizer, from Numpy arrays.

Should only be called after computing the gradients (otherwise the optimizer has no weights).

#### Arguments:

• weights: a list of Numpy arrays. The number of arrays and their shape must match number of the dimensions of the weights of the optimizer (i.e. it should match the output of **get\_weights**).

#### Raises:

ValueError: in case of incompatible weight shapes.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected	
Blog	
GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms   Privacy	