

tf.layers.InputSpec

Contents

Class InputSpec

Aliases:

Methods

`__init__`Class **InputSpec**

Aliases:

- Class `tf.keras.layers.InputSpec`
- Class `tf.layers.InputSpec`

Defined in `tensorflow/python/layers/base.py`.

Specifies the ndim, dtype and shape of every input to a layer.

Every layer should expose (if appropriate) an `input_spec` attribute: a list of instances of InputSpec (one per input tensor).

A None entry in a shape is compatible with any dimension, a None shape is compatible with any shape.

Arguments:

- `dtype`: Expected DataType of the input.
- `shape`: Shape tuple, expected shape of the input (may include None for unchecked axes).
- `ndim`: Integer, expected rank of the input.
- `max_ndim`: Integer, maximum rank of the input.
- `min_ndim`: Integer, minimum rank of the input.
- `axes`: Dictionary mapping integer axes to a specific dimension value.

Methods

`__init__`

```
__init__(
    dtype=None,
    shape=None,
    ndim=None,
    max_ndim=None,
    min_ndim=None,
    axes=None
)
```

the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)