

tf.contrib.learn.evaluate

```
evaluate(  
    graph,  
    output_dir,  
    checkpoint_path,  
    eval_dict,  
    update_op=None,  
    global_step_tensor=None,  
    supervisor_master='',  
    log_every_steps=10,  
    feed_fn=None,  
    max_steps=None  
)
```

Defined in [tensorflow/contrib/learn/python/learn/graph_actions.py](#).

See the guide: [Learn \(contrib\) > Graph actions](#)

Evaluate a model loaded from a checkpoint. (deprecated)

THIS FUNCTION IS DEPRECATED. It will be removed after 2017-02-15. Instructions for updating: graph_actions.py will be deleted. Use tf.train.* utilities instead. You can use learn/estimators/estimator.py as an example.

Given **graph**, a directory to write summaries to (**output_dir**), a checkpoint to restore variables from, and a **dict** of **Tensor**s to evaluate, run an eval loop for **max_steps** steps, or until an exception (generally, an end-of-input signal from a reader operation) is raised from running **eval_dict**.

In each step of evaluation, all tensors in the **eval_dict** are evaluated, and every **log_every_steps** steps, they are logged. At the very end of evaluation, a summary is evaluated (finding the summary ops using **Supervisor**'s logic) and written to **output_dir**.

Args:

- **graph**: A **Graph** to train. It is expected that this graph is not in use elsewhere.
- **output_dir**: A string containing the directory to write a summary to.
- **checkpoint_path**: A string containing the path to a checkpoint to restore. Can be **None** if the graph doesn't require loading any variables.
- **eval_dict**: A **dict** mapping string names to tensors to evaluate. It is evaluated in every logging step. The result of the final evaluation is returned. If **update_op** is **None**, then it's evaluated in every step. If **max_steps** is **None**, this should depend on a reader that will raise an end-of-input exception when the inputs are exhausted.
- **update_op**: A **Tensor** which is run in every step.
- **global_step_tensor**: A **Variable** containing the global step. If **None**, one is extracted from the graph using the same logic as in **Supervisor**. Used to place eval summaries on training curves.
- **supervisor_master**: The master string to use when preparing the session.
- **log_every_steps**: Integer. Output logs every **log_every_steps** evaluation steps. The logs contain the **eval_dict** and timing information.
- **feed_fn**: A function that is called every iteration to produce a **feed_dict** passed to **session.run** calls. Optional.

- `max_steps` : Integer. Evaluate `eval_dict` this many times.

Returns:

A tuple `(eval_results, global_step)` : `eval_results` : A `dict` mapping `string` to numeric values (`int`, `float`) that are the result of running `eval_dict` in the last step. `None` if no eval steps were run. `global_step` : The global step this evaluation corresponds to.

Raises:

- `ValueError` : if `output_dir` is empty.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)