

tf.image.encode_jpeg

```
encode_jpeg(  
    image,  
    format='',  
    quality=95,  
    progressive=False,  
    optimize_size=False,  
    chroma_downsampling=True,  
    density_unit='in',  
    x_density=300,  
    y_density=300,  
    xmp_metadata='',  
    name=None  
)
```

Defined in `tensorflow/python/ops/gen_image_ops.py`.

See the guide: [Images > Encoding and Decoding](#)

JPEG-encode an image.

`image` is a 3-D uint8 Tensor of shape `[height, width, channels]`.

The attr `format` can be used to override the color format of the encoded output. Values can be:

- `''`: Use a default format based on the number of channels in the image.
- `grayscale`: Output a grayscale JPEG image. The `channels` dimension of `image` must be 1.
- `rgb`: Output an RGB JPEG image. The `channels` dimension of `image` must be 3.

If `format` is not specified or is the empty string, a default format is picked in function of the number of channels in `image`:

- 1: Output a grayscale image.
- 3: Output an RGB image.

Args:

- `image`: A `Tensor` of type `uint8`. 3-D with shape `[height, width, channels]`.
- `format`: An optional `string` from: `""`, `"grayscale"`, `"rgb"`. Defaults to `""`. Per pixel image format.
- `quality`: An optional `int`. Defaults to `95`. Quality of the compression from 0 to 100 (higher is better and slower).
- `progressive`: An optional `bool`. Defaults to `False`. If True, create a JPEG that loads progressively (coarse to fine).
- `optimize_size`: An optional `bool`. Defaults to `False`. If True, spend CPU/RAM to reduce size with no quality change.
- `chroma_downsampling`: An optional `bool`. Defaults to `True`. See http://en.wikipedia.org/wiki/Chroma_subsampling.
- `density_unit`: An optional `string` from: `"in"`, `"cm"`. Defaults to `"in"`. Unit used to specify `x_density` and `y_density`: pixels per inch (`'in'`) or centimeter (`'cm'`).
- `x_density`: An optional `int`. Defaults to `300`. Horizontal pixels per density unit.
- `y_density`: An optional `int`. Defaults to `300`. Vertical pixels per density unit.

- `xmp_metadata` : An optional `string`. Defaults to `""`. If not empty, embed this XMP metadata in the image header.
- `name` : A name for the operation (optional).

Returns:

A `Tensor` of type `string`. 0-D. JPEG-encoded image.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)