#### TopoorFlow

TensorFlow API r1.4

# tf.nn.conv3d\_transpose

```
conv3d_transpose(
    value,
    filter,
    output_shape,
    strides,
    padding='SAME',
    data_format='NDHWC',
    name=None
)
```

Defined in tensorflow/python/ops/nn\_ops.py.

See the guide: Neural Network > Convolution

The transpose of conv3d.

This operation is sometimes called "deconvolution" after Deconvolutional Networks, but is actually the transpose (gradient) of **conv3d** rather than an actual deconvolution.

# Args:

- value: A 5-D Tensor of type float and shape [batch, depth, height, width, in\_channels].
- filter: A 5-D Tensor with the same type as value and shape [depth, height, width, output\_channels, in\_channels]. filter's in\_channels dimension must match that of value.
- output\_shape: A 1-D **Tensor** representing the output shape of the deconvolution op.
- strides: A list of ints. The stride of the sliding window for each dimension of the input tensor.
- padding: A string, either 'VALID' or 'SAME'. The padding algorithm. See the comment here
- data\_format: A string, either 'NDHWC' or 'NCDHW' specifying the layout of the input and output tensors. Defaults to 'NDHWC'.
- name: Optional name for the returned tensor.

## Returns:

A Tensor with the same type as value.

### Raises:

ValueError: If input/output depth does not match filter's shape, or if padding is other than 'VALID' or 'SAME'.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Stay Connected	
Blog	
GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms   Privacy	