TencorFlow

```
TensorFlow API r1.4
```

tf.name_scope

```
Contents
Class name_scope
Aliases:
Methods
__init__
__enter__
__exit__
```

Class name_scope

Aliases:

- Class tf.keras.backend.name_scope
- Class tf.name_scope

Defined in tensorflow/python/framework/ops.py.

See the guide: Building Graphs > Utility functions

A context manager for use when defining a Python op.

This context manager validates that the given values are from the same graph, makes that graph the default graph, and pushes a name scope in that graph (see tf.Graph.name_scope for more details on that).

For example, to define a new Python op called my_op:

```
def my_op(a, b, c, name=None):
    with tf.name_scope(name, "MyOp", [a, b, c]) as scope:
    a = tf.convert_to_tensor(a, name="a")
    b = tf.convert_to_tensor(b, name="b")
    c = tf.convert_to_tensor(c, name="c")
    # Define some computation that uses `a`, `b`, and `c`.
    return foo_op(..., name=scope)
```

Methods

__init__

```
__init__(
   name,
   default_name=None,
   values=None
)
```

Initialize the context manager.

Args:

- name: The name argument that is passed to the op function.
- default_name: The default name to use if the name argument is None.
- values: The list of Tensor arguments that are passed to the op function.

__enter__

```
__enter__()
```

Start the scope block.

Returns:

The scope name.

Raises:

• ValueError: if neither name nor default_name is provided but values are.

__exit__

```
__exit__(
   type_arg,
   value_arg,
   traceback_arg
)
```

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

