

tf.train.update_checkpoint_state

```
update_checkpoint_state(  
    save_dir,  
    model_checkpoint_path,  
    all_model_checkpoint_paths=None,  
    latest_filename=None  
)
```

Defined in [tensorflow/python/training/saver.py](#).

See the guide: [Variables > Saving and Restoring Variables](#)

Updates the content of the 'checkpoint' file.

This updates the checkpoint file containing a CheckpointState proto.

Args:

- `save_dir`: Directory where the model was saved.
- `model_checkpoint_path`: The checkpoint file.
- `all_model_checkpoint_paths`: List of strings. Paths to all not-yet-deleted checkpoints, sorted from oldest to newest. If this is a non-empty list, the last element must be equal to `model_checkpoint_path`. These paths are also saved in the CheckpointState proto.
- `latest_filename`: Optional name of the checkpoint file. Default to 'checkpoint'.

Raises:

- `RuntimeError`: If any of the model checkpoint paths conflict with the file containing CheckpointState.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)