TancarFlow

TensorFlow API r1.4

tf.keras.backend.spatial_3d_padding

```
spatial_3d_padding(
    x,
    padding=((1, 1), (1, 1), (1, 1)),
    data_format=None
)
```

Defined in tensorflow/python/keras/_impl/keras/backend.py.

Pads 5D tensor with zeros along the depth, height, width dimensions.

Pads these dimensions with respectively "padding[0]", "padding[1]" and "padding[2]" zeros left and right.

For 'channels_last' data_format, the 2nd, 3rd and 4th dimension will be padded. For 'channels_first' data_format, the 3rd, 4th and 5th dimension will be padded.

Arguments:

- x: Tensor or variable.
- padding: Tuple of 3 tuples, padding pattern.
- data_format: One of channels_last or channels_first.

Returns:

A padded 5D tensor.

Raises:

ValueError: if data_format is neither channels_last or channels_first.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

Issue Tracker

Release Notes

Stack Overflow

English
Terms | Privacy