

tf.RegisterGradient

Contents

Class RegisterGradient

Methods

`__init__`

`__call__`

Class RegisterGradient

Defined in `tensorflow/python/framework/ops.py`.

See the guide: [Building Graphs > Defining new operations](#)

A decorator for registering the gradient function for an op type.

This decorator is only used when defining a new op type. For an op with `m` inputs and `n` outputs, the gradient function is a function that takes the original `Operation` and `n Tensor` objects (representing the gradients with respect to each output of the op), and returns `m Tensor` objects (representing the partial gradients with respect to each input of the op).

For example, assuming that operations of type `"Sub"` take two inputs `x` and `y`, and return a single output `x - y`, the following gradient function would be registered:

```
@tf.RegisterGradient("Sub")
def _sub_grad(unused_op, grad):
    return grad, tf.negative(grad)
```

The decorator argument `op_type` is the string type of an operation. This corresponds to the `OpDef.name` field for the proto that defines the operation.

Methods

`__init__`

```
__init__(op_type)
```

Creates a new decorator with `op_type` as the Operation type.

Args:

- `op_type`: The string type of an operation. This corresponds to the `OpDef.name` field for the proto that defines the operation.

`__call__`

```
__call__(f)
```

Registers the function `f` as gradient function for `op_type`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)